

CTC Laboratories, Inc. (FCC Designation Number: CN1208)

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 http://www.sz-ctc.org.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2APN5-ECAM

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Applicant	Shenzhen Sonoff Technologies Co.,Ltd.			
Address	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China			
Product Name:	Wi-Fi Smart Security Camera			
Trade Mark:	Sonoff			
Model/Type Reference:	E-CAM			
Listed Model(s):	/			
Model Differences:	/			
Frequency Band (Operating)	BLE: 2402~2480MHz 2.4G WiFi: 2412-2462MHz 5G WiFi: 5150MHz~5250MHz, 5725MHz~5850MHz			
Device Category	□ Portable (<5mm separation) □ Mobile (>20cm separation) □ Fixed (>20cm separation) □ Others			
Exposure Classification	ification Occupational/Controlled exposure (S=5mW/cm²) General Population/Uncontrolled exposure (S=1mW/cm²)			
□ Single antenna □ Multiple antennas □ TX diversity □ RX diversity □ TX/RX diversity				
BLE ANT2: 3.47dBi 2.4G WiFi: ANT1: 3.98dBi, ANT2: 3.47dBi, Directional Gain: 6.74dBi 5G WiFi: ANT1 U-NII-1: 4.47dBi, ANT2 U-NII-1: 4.94dBi, Directional Gain: 7.72dB ANT1 U-NII-3: 4.60dBi, ANT2 U-NII-3: 4.08dBi, Directional Gain: 7.35dB				
Evaluation Applied SAR Evaluation				



Report No.: CTC20240774E10



Limits for Maximum Permissible Exposure (MPE)

Frequency Range Electric Field Strength (V/m)		Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)		
(A) Limits for Occupational/Controlled Exposure						
300-1500			F/300	<6		
1500-100000	1500-100000		5	<6		
(B) Limits for General Population/Uncontrolled Exposure						
300-1500			F/1500	<30		
1500-100000			1	<30		

Calculation Method

Friis transmission formula: Pd=(Pout*G)/(4*Pi*R²)

Where:

Pd= Power density in mW/cm²

P_{out}= output power to antenna in mW

G= gain of antenna in linear scale

Pi= 3.1416

R= distance between observation point and center of the radiator in cm

Pd limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report No.: CTC20240774E10



Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Dower	Tune Up Tolerance (dB)	Power	Power Density at 20cm (mW/cm ²)	(mW/cm ²)	Result
BLE	2402	3.47	5.44	±1	6.50	0.0020	1	Pass
802.11g	2462	3.47	21.27	±1	22.00	0.0701	1	Pass
802.11a	5785	4.60	17.47	±1	18.50	0.0406	1	Pass

The BLE and WiFi can transmit simultaneously.

Mode	Frequency (MHz)		Total Power density at 20cm (mW/cm²)		Result
BLE	2402	0.0020	0.0721	1	Pass
802.11g	2462	0.0701	- 0.0721 1		F d 5 5

Note:

- 1. Calculate in the worst-case mode.
- 2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
- 3. For a more detailed features description, please refer to the RF Test Report.

*******THE	END**************
INE	END

CTC Laboratories, Inc. Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China

Http://www.sz-ctc.org.cn

Tel.: (86)755-27521059