

CTC Laboratories, Inc. (FCC Designation Number: CN1208)

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China Tel: +86-755-27521059 Fax: +86-755-27521011 http://www.sz-ctc.org.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2APN5POWCT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Applicant	Shenzhen Sonoff Technologies Co.,Ltd.
Address	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China
Product Name:	Smart Power Meter
Trade Mark:	Sonoff
Model/Type Reference:	POWCT-D
Listed Model(s):	POWCT
Model Differences:	All these models are identical in the same PCB, layout, electrical circuit. Model: POWCT-D, the product includes 2 current transformers and 2 transformer interfaces. Model: POWCT, the product has only 1 current transformer and 1 transformer interface.
Frequency Band (Operating)	BLE: 2402~2480MHz WiFi: 2412-2462MHz
Device Category	 Portable (<5mm separation) Mobile (>20cm separation) Fixed (>20cm separation) Others
Exposure Classification	 ☐Occupational/Controlled exposure (S=5mW/cm²) ☑General Population/Uncontrolled exposure (S=1mW/cm²)
Antenna Diversity	 Single antenna Multiple antennas □Tx diversity □Rx diversity □Tx/Rx diversity
Antenna Gain (Max)	2.15dBi
Evaluation Applied	MPE Evaluation



Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)					
(A) Limits for Occupational/Controlled Exposure									
300-1500			F/300	<6					
1500-100000			5	<6					
(B) Lim	(B) Limits for General Population/Uncontrolled Exposure								
300-1500			F/1500	<30					
1500-100000			1	<30					

Limits for Maximum Permissible Exposure (MPE)

Calculation Method

Friis transmission formula: $Pd=(P_{out}*G)/(4*Pi*R^2)$ Where: Pd= Power density in mW/cm² Pout= output power to antenna in mW G= gain of antenna in linear scale Pi= 3.1416 R= distance between observation point and center of the radiator in cm

Pd limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Power	Power Density at 20cm (mW/cm ²)	(mw/cm ⁻)	Result
BLE	2402	2.15	0.63	±1	1.00	0.0003	1	PASS
802.11b	2412	2.15	20.35	±1	21.00	0.0250	1	PASS

The BLE and WiFi can transmit simultaneously.

Mode	Frequency (MHz)	Antenna Gain (dBi)	Power Density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm2)	Limit (mW/cm²)	Result
BLE	2402	2.15	0.0003	0.0253	1	PASS
802.11b	2412	2.15	0.0250	0.0200		

0

Note:

1. Calculate in the worst-case mode.

2. Max. Tune Up Power is declared by manufacturer, and used to calculate.

3. For a more detailed features description, please refer to the RF Test Report.

CTC Laboratories, Inc.

