

# FCC SAR Test Report

Report No. : SA191217W002  
Applicant : Gosuncn Technology Group Co., Ltd.  
Address : 6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China.  
Product : Wearable  
FCC ID : 2APNR-GT105  
Brand : GOSUNCN  
Model No. : GT105  
Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2013  
KDB 447498 D01 v06  
Sample Received Date : Dec.17, 2019  
Date of Testing : Dec. 18, 2019 ~ Dec. 23, 2019

**CERTIFICATION:** The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By : Wiky Zhang  
Wiky Zhang / Engineer

Approved By : Luke Lu  
Luke Lu / Manager



This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

# Table of Contents

Release Control Record .....	3
1. Description of Equipment Under Test .....	4
2. Maximum Output Power.....	5
2.1 Maximum Conducted Power .....	5
2.2 Measured Conducted Power Result.....	6
3. SAR Test Exclusion Evaluations.....	13
4. Information on the Testing Laboratories.....	14

## Release Control Record

Report No.	Reason for Change	Date Issued
SA190123W002	Initial release	Apr. 04, 2019
SA191217W002	Based on the original product changing product name, SW version, changing LTE B12 to LTE B13, delete LTE B5 and remove 3G feature by software. In this report LTE B2&4&13&66 is full measured for conducted power and evaluated for SAR test exclusion, other test data is copied from the original test report SA190123W002.	Jan. 09, 2020

# 1. Description of Equipment Under Test

<b>EUT Type</b>	Wearable
<b>FCC ID</b>	2APNR-GT105
<b>Brand Name</b>	GOSUNCN
<b>Model Name</b>	GT105
<b>HW Version</b>	SD2000.H02
<b>SW Version</b>	EN_K2000VLV1.0.0B01
<b>Tx Frequency Bands (Unit: MHz)</b>	LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 13 : 779.5 ~ 784.5 (5M), 782 (10M) LTE Band 66 : 1710.7 ~ 1779.3 (1.4M), 1711.5 ~ 1778.5 (3M), 1712.5 ~ 1777.5 (5M), 1715 ~ 1775 (10M), 1717.5 ~ 1772.5 (15M), 1720 ~ 1770 (20M) BT_LE : 2402 ~ 2480
<b>Uplink Modulations</b>	LTE : QPSK, 16QAM(LTE B13 and LTE B4 10M/15M/20M not support 16QAM) BT_LE : GFSK
<b>Maximum Tune-up Conducted Power (Unit: dBm)</b>	Please refer to section 4.6.1 of this report.
<b>Antenna Type</b>	BT_LE: PIFA Antenna WWAN: Fixed Internal Antenna
<b>EUT Stage</b>	Identical Prototype

**Note:**

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
2. According to the manufacturer's product equivalent declaration , the change not affect the original RF parameters;

**List of Accessory:**

<b>Battery</b>	<b>Brand Name</b>	GOSUNCN
	<b>Model Name</b>	422831
	<b>Power Rating</b>	3.8Vdc, 413mAh
	<b>Type</b>	Li-ion

## 2. Maximum Output Power

### 2.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	LTE 2	LTE 4	LTE 66
QPSK / 16QAM	23.0 / 22.0	23.0 / 22.0	23.0 / 22.0

Mode	LTE 13
QPSK	23.5

Mode	2.4G Bluetooth
LE	1.3

## 2.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	20.42	20.32	20.49	0	20.20	20.12	20.27	1
	1	2	20.37	20.29	20.48	0	20.09	20.01	20.16	1
	1	5	20.33	20.25	20.42	0	19.99	19.91	20.06	1
	3	0	20.41	20.31	20.48	0	19.56	19.48	19.63	1
	3	1	20.36	20.28	20.47	0	19.49	19.41	19.56	1
	3	3	20.32	20.24	20.41	0	19.45	19.37	19.52	1
	6	0	20.18	20.10	20.25	1	19.41	19.33	19.48	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	20.45	20.35	20.52	0	20.23	20.15	20.30	1
	1	7	20.40	20.32	20.51	0	20.12	20.04	20.19	1
	1	14	20.36	20.28	20.45	0	20.02	19.94	20.09	1
	8	0	20.32	20.24	20.39	1	19.59	19.51	19.66	2
	8	3	20.25	20.17	20.32	1	19.52	19.44	19.59	2
	8	7	20.24	20.16	20.31	1	19.48	19.40	19.55	2
	15	0	20.21	20.13	20.28	1	19.44	19.36	19.51	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	20.48	20.38	20.55	0	20.26	20.18	20.33	1
	1	12	20.43	20.35	20.54	0	20.15	20.07	20.22	1
	1	24	20.39	20.31	20.48	0	20.05	19.97	20.12	1
	12	0	20.35	20.27	20.42	1	19.62	19.54	19.69	2
	12	6	20.28	20.20	20.35	1	19.55	19.47	19.62	2
	12	13	20.27	20.19	20.34	1	19.51	19.43	19.58	2
	25	0	20.24	20.16	20.31	1	19.47	19.39	19.54	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
2 / 10M	1	0	20.50	20.40	20.57	0	20.28	20.20	20.35	1
	1	24	20.45	20.37	20.56	0	20.17	20.09	20.24	1
	1	49	20.41	20.33	20.50	0	20.07	19.99	20.14	1
	25	0	20.37	20.29	20.44	1	-	-	-	-
	25	12	20.30	20.22	20.37	1	-	-	-	-
	25	25	20.29	20.21	20.36	1	-	-	-	-
	50	0	20.26	20.18	20.33	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18675	Mid CH 18900	High CH 19125		Low CH 18675	Mid CH 18900	High CH 19125	
			1857.5 MHz	1880.0 MHz	1902.5 MHz		1857.5 MHz	1880.0 MHz	1902.5 MHz	
2 / 15M	1	0	20.53	20.43	20.60	0	20.31	20.23	20.38	1
	1	37	20.48	20.40	20.59	0	20.20	20.12	20.27	1
	1	74	20.44	20.36	20.53	0	20.10	20.02	20.17	1
	36	0	20.40	20.32	20.47	1	-	-	-	-
	36	19	20.33	20.25	20.40	1	-	-	-	-
	36	39	20.32	20.24	20.39	1	-	-	-	-
	75	0	20.29	20.21	20.36	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 18700	Mid CH 18900	High CH 19100		Low CH 18700	Mid CH 18900	High CH 19100	
			1860.0 MHz	1880.0 MHz	1900.0 MHz		1860.0 MHz	1880.0 MHz	1900.0 MHz	
2 / 20M	1	0	20.58	20.48	<b>20.65</b>	0	20.36	20.28	20.43	1
	1	50	20.53	20.45	20.64	0	20.25	20.17	20.32	1
	1	99	20.49	20.41	20.58	0	20.15	20.07	20.22	1
	50	0	20.45	20.37	20.52	1	-	-	-	-
	50	25	20.38	20.30	20.45	1	-	-	-	-
	50	50	20.37	20.29	20.44	1	-	-	-	-
	100	0	20.34	20.26	20.41	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 20393		Low CH 19957	Mid CH 20175	High CH 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	21.94	21.96	21.99	0	20.67	20.78	20.97	1
	1	2	21.92	21.94	21.98	0	20.62	20.73	20.87	1
	1	5	21.74	21.85	21.95	0	20.60	20.71	20.88	1
	3	0	21.92	21.94	21.97	0	19.74	19.85	20.02	1
	3	1	21.90	21.92	21.96	0	19.64	19.75	19.92	1
	3	3	21.72	21.83	21.93	0	19.59	19.70	19.87	1
	6	0	20.89	21.00	21.14	1	19.64	19.75	19.92	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	21.95	21.97	22.00	0	20.68	20.79	20.98	1
	1	7	21.93	21.95	21.99	0	20.63	20.74	20.88	1
	1	14	21.75	21.86	21.96	0	20.61	20.72	20.89	1
	8	0	20.97	21.08	21.21	1	19.75	19.86	20.03	2
	8	3	20.93	21.04	21.18	1	19.65	19.76	19.93	2
	8	7	20.89	21.00	21.16	1	19.60	19.71	19.88	2
	15	0	20.90	21.01	21.15	1	19.65	19.76	19.93	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	21.98	22.00	22.03	0	20.71	20.82	21.01	1
	1	12	21.96	21.98	22.02	0	20.66	20.77	20.91	1
	1	24	21.78	21.89	21.99	0	20.64	20.75	20.92	1
	12	0	21.00	21.11	21.24	1	19.78	19.89	20.06	2
	12	6	20.96	21.07	21.21	1	19.68	19.79	19.96	2
	12	13	20.92	21.03	21.19	1	19.63	19.74	19.91	2
	25	0	20.93	21.04	21.18	1	19.68	19.79	19.96	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	22.02	22.04	22.07	0	-	-	-	-
	1	24	22.00	22.02	22.06	0	-	-	-	-
	1	49	21.82	21.93	22.03	0	-	-	-	-
	25	0	21.04	21.15	21.28	1	-	-	-	-
	25	12	21.00	21.11	21.25	1	-	-	-	-
	25	25	20.96	21.07	21.23	1	-	-	-	-
	50	0	20.97	21.08	21.22	1	-	-	-	-



LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	22.08	22.10	22.13	0	-	-	-	-
	1	37	22.06	22.08	22.12	0	-	-	-	-
	1	74	21.88	21.99	22.09	0	-	-	-	-
	36	0	21.10	21.21	21.34	1	-	-	-	-
	36	19	21.06	21.17	21.31	1	-	-	-	-
	36	39	21.02	21.13	21.29	1	-	-	-	-
	75	0	21.03	21.14	21.28	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	22.11	22.13	<b>22.16</b>	0	-	-	-	-
	1	50	22.09	22.11	22.15	0	-	-	-	-
	1	99	21.91	22.02	22.12	0	-	-	-	-
	50	0	21.13	21.24	21.37	1	-	-	-	-
	50	25	21.09	21.20	21.34	1	-	-	-	-
	50	50	21.05	21.16	21.32	1	-	-	-	-
	100	0	21.06	21.17	21.31	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)
			Low CH 23205	Mid CH 23230	High CH 23255	
			779.5 MHz	782.0 MHz	784.5 MHz	
13 / 5M	1	0	22.46	22.51	22.49	0
	1	12	22.68	22.73	22.71	0
	1	24	22.86	22.91	22.89	0
	12	0	21.74	21.79	21.77	1
	12	6	21.90	21.95	21.93	1
	12	13	21.91	21.96	21.94	1
	25	0	21.87	21.92	21.90	1

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)
			-	Mid CH 23230	-	
			-	782.0 MHz	-	
13 / 10M	1	0	-	22.52	-	0
	1	24	-	22.75	-	0
	1	49	-	<b>22.92</b>	-	0
	25	0	-	21.88	-	1
	25	12	-	21.79	-	1
	25	25	-	21.89	-	1
	50	0	-	21.85	-	1

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 131979	Mid CH 132322	High CH 132665		Low CH 131979	Mid CH 132322	High CH 132665	
			1710.7 MHz	1745.0 MHz	1779.3 MHz		1710.7 MHz	1745.0 MHz	1779.3 MHz	
66 / 1.4M	1	0	20.86	20.92	20.87	0	20.60	20.66	20.61	1
	1	2	21.29	21.35	21.30	0	20.59	20.65	20.60	1
	1	5	20.82	20.88	20.83	0	20.56	20.62	20.57	1
	3	0	20.85	20.91	20.86	0	19.92	19.98	19.93	1
	3	1	21.28	21.34	21.29	0	20.16	20.22	20.17	1
	3	3	20.81	20.87	20.82	0	20.07	20.13	20.08	1
	6	0	21.01	21.07	21.02	1	20.04	20.10	20.05	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 131987	Mid CH 132322	High CH 132657		Low CH 131987	Mid CH 132322	High CH 132657	
			1711.5 MHz	1745.0 MHz	1778.5 MHz		1711.5 MHz	1745.0 MHz	1778.5 MHz	
66 / 3M	1	0	20.89	20.95	20.90	0	20.63	20.69	20.64	1
	1	7	21.32	21.38	21.33	0	20.62	20.68	20.63	1
	1	14	20.85	20.91	20.86	0	20.59	20.65	20.60	1
	8	0	21.02	21.08	21.03	1	19.95	20.01	19.96	2
	8	3	21.15	21.21	21.16	1	20.19	20.25	20.20	2
	8	7	21.05	21.11	21.06	1	20.10	20.16	20.11	2
	15	0	21.04	21.10	21.05	1	20.07	20.13	20.08	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 131997	Mid CH 132322	High CH 132647		Low CH 131997	Mid CH 132322	High CH 132647	
			1712.5 MHz	1745.0 MHz	1777.5 MHz		1712.5 MHz	1745.0 MHz	1777.5 MHz	
66 / 5M	1	0	20.92	20.98	20.93	0	20.66	20.72	20.67	1
	1	12	21.35	21.41	21.36	0	20.65	20.71	20.66	1
	1	24	20.88	20.94	20.89	0	20.62	20.68	20.63	1
	12	0	21.05	21.11	21.06	1	19.98	20.04	19.99	2
	12	6	21.18	21.24	21.19	1	20.22	20.28	20.23	2
	12	13	21.08	21.14	21.09	1	20.13	20.19	20.14	2
	25	0	21.07	21.13	21.08	1	20.10	20.16	20.11	2

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 132022	Mid CH 132322	High CH 132622		Low CH 132022	Mid CH 132322	High CH 132622	
			1715.0 MHz	1745.0 MHz	1775.0 MHz		1715.0 MHz	1745.0 MHz	1775.0 MHz	
66 / 10M	1	0	20.94	21.00	20.95	0	20.68	20.74	20.69	1
	1	24	21.37	21.43	21.38	0	20.67	20.73	20.68	1
	1	49	20.90	20.96	20.91	0	20.64	20.70	20.65	1
	25	0	21.07	21.13	21.08	1	-	-	-	-
	25	12	21.20	21.26	21.21	1	-	-	-	-
	25	25	21.10	21.16	21.11	1	-	-	-	-
	50	0	21.09	21.15	21.10	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 132047	Mid CH 132322	High CH 132597		Low CH 132047	Mid CH 132322	High CH 132597	
			1717.5 MHz	1745.0 MHz	1772.5 MHz		1717.5 MHz	1745.0 MHz	1772.5 MHz	
66 / 15M	1	0	20.97	21.03	20.98	0	20.71	20.77	20.72	1
	1	37	21.40	21.46	21.41	0	20.70	20.76	20.71	1
	1	74	20.93	20.99	20.94	0	20.67	20.73	20.68	1
	36	0	21.10	21.16	21.11	1	-	-	-	-
	36	19	21.23	21.29	21.24	1	-	-	-	-
	36	39	21.13	21.19	21.14	1	-	-	-	-
	75	0	21.12	21.18	21.13	1	-	-	-	-

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low CH 132072	Mid CH 132322	High CH 132572		Low CH 132072	Mid CH 132322	High CH 132572	
			1720.0 MHz	1745.0 MHz	1770.0 MHz		1720.0 MHz	1745.0 MHz	1770.0 MHz	
66 / 20M	1	0	21.02	21.08	21.03	0	20.76	20.82	20.77	1
	1	50	21.45	<b>21.51</b>	21.46	0	20.75	20.81	20.76	1
	1	99	20.98	21.04	20.99	0	20.72	20.78	20.73	1
	50	0	21.15	21.21	21.16	1	-	-	-	-
	50	25	21.28	21.34	21.29	1	-	-	-	-
	50	50	21.18	21.24	21.19	1	-	-	-	-
	100	0	21.17	21.23	21.18	1	-	-	-	-

<Bluetooth>

Mode	Bluetooth LE		
Channel / Frequency (MHz)	0 (2402)	19 (2440)	39 (2480)
Average Power	-3.13	-4.33	-4.04

### 3. SAR Test Exclusion Evaluations

According to the document <GT105 principles of work>, this is a device that works intermittently, the maximum transmitting time is 1s and the minimum transmission interval time is 20s.

Consider 20s as the minimum period for the worst condition to calculate, as below

$$Duty\ Cycle = \frac{max\ TX\ time}{Period} * 100\% = \frac{1}{20} * 100\% = 5\%$$

Per KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

$$\frac{Max.\ Tune\ up\ Power_{(mW)}}{Min.\ Test\ Separation\ Distance_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0\ for\ SAR-1g, \leq 7.5\ for\ SAR-10g$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Wireless Interface	LTE Band 4	LTE Band 2	LTE Band 13	LTE Band 66	BT
Calculated Frequency	1754MHz	1909MHz	787MHz	1780MHz	2480MHz
Maximum Tune-up power (dBm)	23.00	23.00	23.50	23.00	1.3
Maximum Tune-up power (mW)	200.0	200.0	224.0	200.0	1.0
Duty Cycle	0.05	0.05	0.05	0.05	0.83
Maximum rated power(mW)	10.00	10.00	11.20	10.00	0.83
Separation distance(mm)	5.0				
Calculated Result	2.7	2.8	2.0	2.7	0.3
Testing required?	No	No	No	No	No

**Note:**

1. The Calculated Result<3.0, Per KDB 447498 D01, the SAR test is excluded;
2. This device no support simultaneous transmissions, because Wifi is RX only, no TX function, and when BT is in the linked state, the WWAN module is closed;

Test Engineer : Wiky Zhang

## **4. Information on the Testing Laboratories**

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Add: No. B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industry Park, Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-8869-6566

Fax: 86-755-8869-6577

**Email:** [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**Web Site:** [www.bureauveritas.com](http://www.bureauveritas.com)

The road map of all our labs can be found in our web site also.

**---END**