


Inverted F Antenna Specification

Summary

ITEM	ANT SPEC					
Model Name	2.4G ANT					
Center Frequency	Horizontal			Vertical		
	2400MHz	2450MHz	2500MHz	2400MHz	2450MHz	2500MHz
	-1.26	-0.76	-0.58	-0.42	-0.33	0.07
MAX. Gain	0.07 dBi					
Polarization	Horizontal and Vertical					
Azimuth Beam Pattern	Omni-directional					
Impedance	50 Ohm					
Antenna Length	38.20mm					
Antenna Type	PCB ANT					
Manufacture	Shenzhen Jundaxin Electronics Co., Ltd					
Address	2nd Floor, Building C2, Wan'an Road, Ma'anshan Community, Shajing Street, Bao'an District, Shenzhen					

Antenna Photo & Length (mm)



Horizontal: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -40 Scale: 5/div



Frequency (MHz)	Gain(dBi)		
	Max	Min	Avg
2400	-1.26174	-30.0801	-7.18716
2450	-0.765802	-36.5604	-7.48023
2500	-0.585582	-22.0315	-6.59127

Vertical: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -30 Scale: 5/div



Frequency (MHz)	Gain(dBi)		
	Max	Min	Avg
2400	-0.4229	-22.1424	-12.4294
2450	-0.3355	-24.5837	-10.4702
2500	0.07660	-29.5214	-9.20432

ANT Test Labs: Attestation of Global Compliance Co., Ltd.