

# Longhorn Intelligent Tech Co.,Ltd

## RF TEST REPORT

**Report Type:**

FCC Part 15.225 RF report

**Model:**

ECA-NH1606S-\*\*\*#, ECA-NH3206S-\*\*\*#,  
ECA-NH4006S-\*\*\*#, ECA-NH4806S-\*\*\*#

**REPORT NUMBER:**

231200949SHA-001

**ISSUE DATE:**

May 14, 2024

**DOCUMENT CONTROL NUMBER:**

TTRF15.225\_V1 © 2018 Intertek



**Applicant:** Longhorn Intelligent Tech Co.,Ltd  
Longhorn Hi-Tech Estate, Gongyeyuan Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

**Manufacturer:** Longhorn Intelligent Tech Co.,Ltd  
Longhorn Hi-Tech Estate, Gongyeyuan Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

**Factory:** Longhorn Intelligent Tech Co.,Ltd  
Floor 2-3, Emerging Industrial Park Factory Building, No. 72, Longhai Third Road, Xiqu, Dayawan District, Huizhou, Guangdong, China

**FCC ID:** 2APP2-LHEHA

### SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 15 (2023):** Radio Frequency Devices (Subpart C)

**ANSI C63.10 (2020):** American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

**PREPARED BY:**

**REVIEWED BY:**



Project Engineer  
Sky Yang

Reviewer  
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT**

**Content**

**REVISION HISTORY..... 4**

**MEASUREMENT RESULT SUMMARY ..... 5**

**1 GENERAL INFORMATION ..... 6**

1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) ..... 6

1.2 TECHNICAL SPECIFICATION ..... 6

1.3 DESCRIPTION OF TEST FACILITY ..... 7

**2 TEST SPECIFICATIONS..... 8**

2.1 STANDARDS OR SPECIFICATION ..... 8

2.2 MODE OF OPERATION DURING THE TEST..... 8

2.3 TEST SOFTWARE LIST ..... 8

2.4 TEST PERIPHERALS LIST ..... 8

2.5 TEST ENVIRONMENT CONDITION:..... 8

2.6 INSTRUMENT LIST ..... 9

2.7 MEASUREMENT UNCERTAINTY ..... 10

**3 FUNDAMENTAL EMISSION ..... 11**

3.1 LIMIT ..... 11

3.2 MEASUREMENT PROCEDURE ..... 11

3.3 TEST CONFIGURATION ..... 12

3.4 TEST RESULTS OF FUNDAMENTAL EMISSIONS ..... 13

**4 SPURIOUS EMISSION ..... 14**

4.1 LIMIT ..... 14

4.2 MEASUREMENT PROCEDURE ..... 14

4.3 TEST RESULTS OF RADIATED EMISSIONS ..... 16

**5 FREQUENCY STABILITY (TEMPERATURE VARIATION) ..... 20**

5.1 TEST LIMIT ..... 20

5.2 TEST CONFIGURATION ..... 20

5.3 TEST PROCEDURE AND TEST SETUP ..... 21

5.4 TEST PROTOCOL ..... 21

**6 FREQUENCY STABILITY (VOLTAGE VARIATION) ..... 22**

6.1 TEST LIMIT ..... 22

6.2 TEST CONFIGURATION ..... 22

6.3 TEST PROCEDURE AND TEST SETUP ..... 22

6.4 TEST PROTOCOL ..... 23

**7 CONDUCTED EMISSIONS ..... 24**

7.1 LIMIT ..... 24

7.2 TEST CONFIGURATION ..... 24

7.3 MEASUREMENT PROCEDURE ..... 25

7.4 TEST RESULTS OF CONDUCTED EMISSIONS..... 26

**8 20DB BANDWIDTH ..... 28**

8.1 LIMIT..... 28

8.2 TEST CONFIGURATION ..... 28

8.3 TEST PROCEDURE AND TEST SET UP ..... 29

8.4 TEST PROTOCOL ..... 30

**9 ANTENNA REQUIREMENT ..... 31**

## Revision History

Report No.	Version	Description	Issued Date
231200949SHA-001	Rev. 01	Initial issue of report	May 14, 2024

### Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Fundamental emission	15.225(a) (b) (c)	Pass
Spurious emission	15.225(d)	Pass
Frequency stability	15.225(e)	Pass
Conducted emissions	15.207	Pass
99% and 20dB Bandwidth	15.215(c)	Pass
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

**TEST REPORT**

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	EV Charger
Type/Model:	ECA-NH1606S-***#, ECA-NH3206S-***#, ECA-NH4006S-***#, ECA-NH4806S-***# The first two symbol "***" denotes communication function like RS485, can be AA to ZZ; The third symbol "#" denotes power input wire type, can be 0 to 9; The fourth symbol "#" denotes front shell color, can be 0 to 9
Description of EUT:	The EUT is electric vehicle AC charger with RFID function and Bluetooth, WIFI, LTE function. The wireless module FCC ID is XMR202008EC25AFXD, 2AFOS-WT32C3-SX and 2ANDL-CBU. All models are electrically identical except the rated output power. We choose the ECA-NH1606S-AA17 and ECA-NH4806S-AA17(full function) to test as representative and list the worst results in this report.
Rating:	ECA-NH1606S-***#: 120/208/240VAC, 60Hz, 16A Max ECA-NH3206S-***#: 208/240VAC, 60Hz, 32A Max ECA-NH4006S-***#: 208/240VAC, 60Hz, 40A Max ECA-NH4806S-***#: 208/240VAC, 60Hz, 48A Max
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	-
Hardware Version:	-
Serial numbers:	0231031-24-001
Sample received date:	October 31, 2023
Date of test:	November 1, 2023 ~ May 14, 2024

### 1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

**TEST REPORT****1.3 Description of Test Facility**

<b>Name:</b>	Intertek Testing Services Shanghai
<b>Address:</b>	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
<b>Telephone:</b>	86 21 61278200
<b>Telefax:</b>	86 21 54262353

<b>The test facility is recognized, certified, or accredited by these organizations:</b>	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

**TEST REPORT**

**2 TEST SPECIFICATIONS**

**2.1 Standards or specification**

47CFR Part 15 (2023)  
ANSI C63.10 (2020)

**2.2 Mode of operation during the test**

While testing, the internal modulation and continuously transmission was applied.

**2.3 Test software list**

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

**2.4 Test peripherals list**

Item No	Description	Band and Model	S/No

**2.5 Test environment condition:**

Test items	Temperature	Humidity
Radiated emission	26°C	53% RH
Power line conducted emission	27°C	53% RH



## 2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESR7	EC 6194	2025-02-27
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2024-11-19
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2025-01-11
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2024-08-22
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2024-09-12
<input checked="" type="checkbox"/>	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2024-07-16
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2024-07-08
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030B	EC 6078	2024-06-15
<input checked="" type="checkbox"/>	Climate chamber	GWS	MT3065	EC 6021	2025-03-06
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Thermo-Hygrograph	Testo	175h1	EC 6640	2024-08-28
<input checked="" type="checkbox"/>	Thermo-Hygrograph	Testo	175h1	EC6642	2024-08-28

## 2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Expanded Uncertainty (k=2)
Conducted emission at mains ports	9kHz ~ 150kHz	3.52 dB
	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	3.06 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB

### 3 Fundamental Emission

Test result: Pass

#### 3.1 Limit

Frequencies (MHz)	Limit at 30m (dBuV/m)	Limit at 3m (dBuV/m)
13.110 – 13.410	40.50	80.50
13.410 – 13.553	50.50	90.50
13.553 – 13.567	84.00	124.00
13.567 – 13.710	50.50	90.50
13.710 – 14.010	40.50	80.50


#### 3.2 Measurement Procedure

- a) The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to PK Detect Function and Specified Bandwidth with Maximum Hold Mode.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

### 3.3 Test Configuration



TEST REPORT

3.4 Test Results of Fundamental Emissions



Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin	Detector
X	13.56	62.7	124.00	61.3	PK
Y	13.56	66.5	124.00	57.5	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m.

Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;

Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;

Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

## 4 Spurious Emission

Test result: Pass

### 4.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

### 4.2 Measurement Procedure

#### For Radiated emission below 30MHz:

- f) The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- g) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- h) Both X and Y axes of the antenna are set to make the measurement.
- i) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- j) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### NOTE:

- 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

#### For Radiated emission above 30MHz:

- a) The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.



**TEST REPORT**

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. All modes of operation were evaluated and the worst-case emissions were reported

### 4.3 Test Results of Radiated Emissions





**TEST REPORT**

**Test data below 30MHz:**


Frequency	Limit (dBuV/m)	Level (dBuV/m)	Delta	Detector	Polarity
501.000kHz	73.6	58.0	15.6	PK	X
618.000kHz	71.8	55.7	16.1	PK	X
775.500kHz	69.8	51.5	18.3	PK	X
1.698MHz	63.0	34.8	28.2	PK	X
7.436MHz	69.5	42.5	27.0	PK	X
10.172MHz	69.5	46.6	22.9	PK	X
496.500kHz	73.7	60.7	13.0	PK	Y
640.500kHz	71.5	58.1	13.4	PK	Y
771.000kHz	69.9	53.0	16.9	PK	Y
1.127MHz	66.6	38.8	27.8	PK	Y
7.535MHz	69.5	41.1	28.4	PK	Y
10.181MHz	69.5	32.0	37.5	PK	Y

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Level = Original Receiver Reading + Correct Factor  
 3. Delta = Limit - Level


Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
 Limit = 40.00dBuV/m.  
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;  
 Level = 10dBuV + 0.20dB/m = 10.20dBuV/m;  
 Delta = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

## TEST REPORT

H



V



**TEST REPORT**

**Test data from 30MHz to 1000MHz:**

Antenna Polarization	Frequency	Limit (dBuV/m)	Level (dBuV/m)	Delta	Detector
H	119.046MHz	43.5	26.0	17.5	PK
H	148.049MHz	43.5	28.4	15.1	PK
H	325.462MHz	46.0	30.1	15.9	PK
H	352.525MHz	46.0	31.9	14.1	PK
H	379.685MHz	46.0	38.1	7.9	PK
H	406.845MHz	46.0	34.7	11.3	PK
V	114.972MHz	43.5	29.0	14.5	PK
V	122.344MHz	43.5	33.3	10.2	PK
V	149.601MHz	43.5	28.3	15.2	PK
V	352.525MHz	46.0	31.5	14.5	PK
V	379.685MHz	46.0	32.2	13.8	PK
V	406.845MHz	46.0	30.6	15.4	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Level = Original Receiver Reading + Correct Factor  
 3. Delta = Limit - Level

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
 Limit = 40.00dBuV/m.  
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;  
 Level = 10dBuV + 0.20dB/m = 10.20dBuV/m;  
 Delta = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.


## 5 Frequency Stability (Temperature Variation)

Test result: PASS

### 5.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage.

### 5.2 Test Configuration



**TEST REPORT**

**5.3 Test procedure and test setup**

Test Procedure as per ANSI 63.10 clause 6.8.1.

**5.4 Test protocol**

The test was performed under 120VAC, 208VAC and 240VAC, the worst results was listed below.

Voltage (V)	Temp (°C)	Freq measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
240	-30	13.5595	13.56	-0.004	±.01
	-20	13.5597		-0.002	
	-10	13.5596		-0.003	
	0	13.5602		0.001	
	10	13.5600		0	
	20	13.5600		0	
	30	13.5603		0.002	
	40	13.5594		0.003	
	50	13.5598		0.001	


## 6 Frequency Stability (Voltage Variation)

Test result: PASS

### 6.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 6.2 Test Configuration



### 6.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.2.

**TEST REPORT**

**6.4 Test protocol**

Temp (°C)	Voltage (V)	Freq Measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
20	102	13.5598	13.56	-0.001	±0.01
	120	13.5601		0.0007	
	138	13.5604		0.003	
	177	13.5597		-0.002	
	208	13.5603		0.002	
	240	13.5600		0	
	276	13.5601		0.0007	

## 7 Conducted emissions


Test result: Pass

### 7.1 Limit

Frequency of Emission (MHz)	Conducted Emissions Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### 7.2 Test Configuration





**TEST REPORT****7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50  $\Omega$  LISN port (to which the EUT is connected), where permitted, terminated into a 50  $\Omega$  measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50  $\Omega$  measuring port is terminated by a measuring instrument having 50  $\Omega$  input impedance. All other ports are terminated in 50  $\Omega$  loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.


**TEST REPORT**

**7.4 Test Results of Conducted Emissions**


The test was performed under 120VAC, 208VAC and 240VAC, the worst results(240VAC) was listed below.

**Test Curve:**

L1 Line



L2 Line



**TEST REPORT**

Test Data:

No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Detector	Phase
1	487.500kHz	56.2	31.0	25.2	QP	L1
2	586.500kHz	56.0	33.6	22.4	QP	L1
3	9.411MHz	60.0	32.5	27.5	QP	L1
4	11.576MHz	60.0	18.4	41.6	QP	L1
5	14.082MHz	60.0	34.7	25.3	QP	L1
6	15.464MHz	60.0	22.3	37.7	QP	L1
7	487.500kHz	56.2	32.6	23.6	QP	L2
8	582.000kHz	56.0	34.2	21.8	QP	L2
9	9.357MHz	60.0	34.9	25.1	QP	L2
10	11.999MHz	60.0	25.0	35.0	QP	L2
11	13.421MHz	60.0	48.0	12.0	QP	L2
12	14.969MHz	60.0	18.6	41.4	QP	L2
13	469.500kHz	46.5	20.1	26.4	CAV	L1
14	591.000kHz	46.0	24.4	21.6	CAV	L1
15	9.371MHz	50.0	21.0	29.0	CAV	L1
16	14.082MHz	50.0	8.6	41.4	CAV	L1
17	27.123MHz	50.0	32.9	17.1	CAV	L1
18	469.500kHz	46.5	21.9	24.6	CAV	L2
19	591.000kHz	46.0	25.7	20.3	CAV	L2
20	8.475MHz	50.0	19.8	30.2	CAV	L2
21	9.434MHz	50.0	25.2	24.8	CAV	L2
22	13.349MHz	50.0	13.9	36.1	CAV	L2
23	27.123MHz	50.0	34.4	15.6	CAV	L2

- Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.*
- 2. Level = Original Receiver Reading + Correct Factor*
- 3. Delta = Limit - Level*
- 4. If the PK Level is lower than AV limit, the AV test can be elided.*
- 5. the emissions of 13.56MHz are the product's RF signal.*


## 8 20dB Bandwidth

Test result: Pass

### 8.1 Limit

The 20dB bandwidth should be fallen in the allocated operating frequency range.  
No limit for 99% bandwidth.

### 8.2 Test configuration



### **8.3 Test procedure and test set up**

The measurement was applied in a 3m semi-anechoic chamber.

The center of the loop antenna shall be 1 m above the horizontal metal ground plane.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set RBW = 1 % to 5 % of the OBW
3. Set VBW  $\geq 3 \cdot$  RBW
4. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
5. Use the 99 % power bandwidth function of the instrument (if available).
6. the 20dB bandwidth is also measured with the same setting.

## 8.4 Test protocol

	Lower point (MHz)	Higher point (MHz)	Bandwidth (kHz)	Allocated bandwidth (MHz)
20dB Bandwidth	13.560162	13.560699	0.537	13.553 ~ 13.567
Occupied bandwidth	13.559160	13.561679	2.519	13.553 ~ 13.567



**TEST REPORT**

**9 Antenna requirement**

**Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

\*\*\*\*\* END \*\*\*\*\*