

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Smart WIFI LED Flood Light
<b>Model Number</b>	AT1852, AT1853, SMW028F4R03FT001, SMW028F4R03FT001A
<b>FCC ID</b>	2APP3AT1852
<b>Antenna gain (Max)</b>	1.3dBi
<b>Operation Frequency</b>	BT:2.402-2.480GHz WLAN: 2.412GHz ~ 2.462GHz
<b>Input Rating</b>	AC 120V, 50/60Hz
<b>Max. output power</b>	BT:1.97dBm WLAN: 802.11b: 15.58dBm 802.11g: 12.89dBm 802.11n(HT20): 11.57dBm 802.11n(HT40): 10.12dBm

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1416$

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## 11.2 Measurement Result

Antenna gain: 1.3 dBi

BT:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
GFSK	2402	1.97	2±1	3	1.349	0.000535	1
GFSK	2440	1.75	2±1	3	1.349	0.000535	1
GFSK	2480	0.87	1±1	2	1.349	0.000425	1

WIFI:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	1	15±1	16	39.811	1.3	1.349	0.010684	1
	6	15±1	16	39.811	1.3	1.349	0.010684	1
	11	15±1	16	39.811	1.3	1.349	0.010684	1
802.11g	1	13±1	14	25.119	1.3	1.349	0.006741	1
	6	12±1	13	19.953	1.3	1.349	0.005355	1
	11	12±1	13	19.953	1.3	1.349	0.005355	1
802.11n (HT20)	1	12±1	13	19.953	1.3	1.349	0.005355	1
	6	11±1	12	15.849	1.3	1.349	0.004253	1
	11	11±1	12	15.849	1.3	1.349	0.004253	1
802.11n (HT40)	3	10±1	11	12.589	1.3	1.349	0.003379	1
	6	10±1	11	12.589	1.3	1.349	0.003379	1
	9	9±1	10	10.000	1.3	1.349	0.002684	1

Signature:



Alan He

Date: 2021-01-17