| | HNOLOGY | | | | | | | |
|----------------------------------|---|--|---------|----|--|--|--|--|
| | TEST REP | ORT | | | | | | |
| FCC ID : | 2APP6AM-718 | | | | | | | |
| Test Report No:: | TCT230906E031 | CT230906E031 | | | | | | |
| Date of issue: | Sep. 14, 2023 | | | | | | | |
| Testing laboratory: : | SHENZHEN TONGCE TI | ESTING LAB | | | | | | |
| Testing location/ address: | Fuhai Subdistrict, Bao'an | 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China | | | | | | |
| Applicant's name: : | Aroma Music Co., Ltd. | | | | | | | |
| Address: | 203, No. 93 Qianjin 2nd Road, Area 81, Hexi Neighbourhood, Xixiang Town, Baoan District, Shenzhen City, Guangdong, 518000 China | | | | | | | |
| Manufacturer's name: | Aroma Technology Co., L | _imited | S. | | | | | |
| Address: | Building A, Aroma Park, Guwu Village, Danshui Town, Huiyang District, Huizhou, Guangdong 516200 China | | | | | | | |
| Standard(s): | KDB 447498 D01 General RF Exposure Guidance v06 | | | | | | | |
| Product Name:: | RECHARGEABLE VOCA | RECHARGEABLE VOCAL METRONOME/BLUETOOTH AMP. | | | | | | |
| Trade Mark: | N/A | (\mathcal{C}) | (3) | | | | | |
| Model/Type reference : | AM-718 | | | | | | | |
| Rating(s): | Rechargeable Li-ion Batte | ery DC 3.7V | | | | | | |
| Date of receipt of test item | Sep. 06, 2023 | S. | | S. | | | | |
| Date (s) of performance of test: | Sep. 06, 2023 - Sep. 14, 2023 | | | | | | | |
| Tested by (+signature) : | Yannie ZHONG | Yannie. | TONECET | | | | | |
| Check by (+signature) : | Beryl ZHAO | Barge | TOT | | | | | |
| Approved by (+signature): | Tomsin | Toms | Pers By | | | | | |


General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Report No.: TCT230906E031

Table of Contents

| 1. | General Product Information | | | 3 |
|----|-------------------------------------|-------------|------------|---|
| | 1.1. EUT description | <u> </u> | <u>)</u> | |
| | 1.2. Model(s) list | | | 3 |
| 2. | General Information | | | 4 |
| | 2.1. Test environment and mode | | | 4 |
| | 2.2. Description of Support Units | | | |
| 3. | Facilities and Accreditations | | <u>)</u> | |
| | 3.1. Facilities | | | 5 |
| | 3.2. Location | | | 5 |
| 4. | Test Results and Measurement Data . | <u>(</u> G) | <u>(G)</u> | 6 |



Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



1. General Product Information

1.1. EUT description

| Product Name: | RECHARGEABLE VOCAL METRONOME/BLUETOOTH AMP. | | | | |
|-----------------------|---|--|--|--|--|
| Model/Type reference: | AM-718 | | | | |
| Sample Number: | TCT230906E030-0101 | | | | |
| Operation Frequency: | 2402MHz~2480MHz | | | | |
| Modulation Type: | GFSK, π/4-DQPSK | | | | |
| Antenna Type: | PCB Antenna | | | | |
| Antenna Gain: | -0.58dBi | | | | |
| Rating(s): | Rechargeable Li-ion Battery DC 3.7V | | | | |

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.



Report No.: TCT230906E031

2. General Information

2.1. Test environment and mode

| ltem | Normal condition | | | | |
|--------------------------|---|-----------|--|----|--|
| Temperature | | +25°C | | | |
| Voltage | | DC 3.7V | | | |
| Humidity | .) | 56% | | | |
| Atmospheric Pressure: | (c) | 1008 mbar | | (C | |
| Test Mode: | | | | | |
| Transmitting mode: | Keep the EUT in continuous transmitting by select channel | | | | |
| | | | | | |

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No. | Serial No. | FCC ID | Trade Name | | |
|-----------|-----------|------------|--------|------------|--|--|
| / | 1 | | 1 | 1 | | |
| | KU) | | | 20 | | |

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Report No.: TCT230906E031



3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC Registration No.: 10668A-1
- SHENZHEN TONGCE TESTING LAB
- CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China TEL: +86-755-27673339



4. Test Results and Measurement Data

According to KDB 447498 D01 General RF Exposure Guidance v06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f}(GHz)] \le 3.0$ for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation When the minimum test separation distance is < 5 mm, a distance of 5 mm
- according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison
- BDR+EDR:

TCT通测检测 TESTING CENTRE TECHNOLOGY

| Channel | Frequency (GHz) | Max. Power (dBm) | Tune up Power (dBm) | Max. Tune up Power (dBm) | Max. Tune up Power (mW) | Test distance (mm) | Result | exclusion thresholds for 1-g SAR | |
|---------|--------------------|------------------------|------------------------------|--------------------------------------|-------------------------------------|--------------------------|--------|---|--|
| CH 78 | 2.480 | 1.43 | 1±1 | 2 | 1.58 | 5 | 0.50 | 3.0 | |

Result: Base on the calculation value, No SAR measurement is required.

*****END OF REPORT*****