

FCC RF EXPOSURE REPORT

FCC ID: 2APPZ-I31S

Project No. : 1712C118A
Equipment : SIP DoorPhone
Model : i31S
Series Models : i23S, i18S
Applicant : Fanvil Technology Co.,LTD.
Address : 4F,Block A,Bldg#1,GaoXinQi Hi-TechPark Phase-II,67th
District,Bao'An Shenzhen China

According: : FCC Guidelines for Human Exposure IEEE
C95.1 & KDB447498 D01

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Certificate #5123.02

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type
1	N/A	N/A	LOOP

GENERAL CONCLUSION:

Maximum measured transmitter power:

Outpu Power (dBm)	Outpu Power (mW)	Limit(mW)
-33.84	0.0004	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100MHz-6GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 0.0004mW, less than 10mW at 20cm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report