


# TEST REPORT

Applicant Name : Fanvil Technology Co., LTD.  
Address : 10/F Block A, Dualshine Global Science Innovation Honglang  
North 2nd Road, Bao'an District, Shenzhen, 518101, China  
Report Number : SZNS220120-03042E-RF-00  
FCC ID: 2APPZ-I51W

## Test Standard (s)

FCC PART 15.247

## Sample Description

Product Type: Indoor Station  
Model No.: i51W  
Multiple Model(s) No.: N/A  
Trade Mark:   
Date Received: 2022/01/20  
Date of Test: 2022/02/16~2022/03/22  
Report Date: 2022/03/29

Test Result:	Pass*
--------------	-------

\* In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:



Ting Lü  
EMC Engineer

## Approved By:



Robert Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*" .

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "\*\*". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY.....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
EUT EXERCISE SOFTWARE .....	6
DUTY CYCLE .....	7
SUPPORT EQUIPMENT LIST AND DETAILS .....	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP .....	10
<b>SUMMARY OF TEST RESULTS</b> .....	<b>13</b>
<b>TEST EQUIPMENT LIST</b> .....	<b>14</b>
<b>FCC §15.247 (I) &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b> .....	<b>16</b>
<b>FCC §15.203 - ANTENNA REQUIREMENT</b> .....	<b>17</b>
APPLICABLE STANDARD .....	17
ANTENNA CONNECTOR CONSTRUCTION .....	17
<b>FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS</b> .....	<b>18</b>
APPLICABLE STANDARD .....	18
EUT SETUP .....	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE .....	18
TRANSF FACTOR & MARGIN CALCULATION.....	19
TEST DATA .....	19
<b>FCC §15.209, §15.205 &amp; §15.247(D) - SPURIOUS EMISSIONS</b> .....	<b>24</b>
APPLICABLE STANDARD .....	24
EUT SETUP .....	24
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	25
TEST PROCEDURE .....	25
FACTOR & MARGIN CALCULATION .....	25
TEST DATA .....	25
<b>FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH &amp; OCCUPIED BANDWIDTH</b> .....	<b>38</b>
APPLICABLE STANDARD .....	38
TEST PROCEDURE .....	38
TEST DATA .....	38
<b>FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER</b> .....	<b>52</b>
APPLICABLE STANDARD .....	52
TEST PROCEDURE .....	52
TEST DATA .....	52
<b>FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b> .....	<b>54</b>
APPLICABLE STANDARD .....	54

---

TEST PROCEDURE .....	54
TEST DATA .....	54
<b>FCC §15.247(E) - POWER SPECTRAL DENSITY.....</b>	<b>59</b>
APPLICABLE STANDARD .....	59
TEST PROCEDURE .....	59
TEST DATA .....	59

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Frequency Range	Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	Wi-Fi: 802.11b: 17.04dBm, 802.11g: 20.44dBm, 802.11n-HT20: 19.93dBm, 802.11n-HT40: 19.37dBm
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification*	Internal Antenna: 3.6dBi(provided by the applicant)
Voltage Range	DC 12V from adapter or battery, DC 48V from POE
Sample serial number	SZNS220120-03042E-RF-S1 for Conducted and Radiated Emissions SZNS220120-03042E-RF-S2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		$0.082 \times 10^{-7}$
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 2.4GHz Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.  
802.11n-HT40 mode was tested with Channel 3, 6 and 9.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software


“CMD-Telnet”\* software was used to test and power level as below:

Mode	Date rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	-12	-12	-12
802.11g	6Mbps	-10	-10	-10
802.11n-HT20	MCS0	-12	-12	-12
802.11n-HT40	MCS0	-10	-10	-10

The software and power level was provided by the applicant.


### Duty cycle

#### 802.11b mode




Date: 16.FEB.2022 16:05:48

#### 802.11g mode




Date: 16.FEB.2022 16:05:06

### 802.11n-HT20 Mode



Date: 16.FEB.2022 16:02:55

### 802.11n-HT40 Mode



Date: 16.FEB.2022 16:03:32



Mode	T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)	1/T (kHz)
802.11b	4.329	4.401	98.36	0.23
802.11g	0.720	0.807	89.22	1.39
802.11n-HT20	0.665	0.696	95.55	1.50
802.11n-HT40	0.333	0.368	90.49	3.00

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Unknown	Adapter	RD1202000-C55-29MG	20200608
Yealink	POE	YLPOE30	204501292
CHUANXI	Battery	6-QW-60	CCA 500A
ATC	Test Load	Unknown	Unknown


### External I/O Cable

Cable Description	Length (m)	From Port	To
Un-Shielding Detachable DC Cable	1.0	EUT	Adapter
Un-Shielding Detachable DC Cable	1.0	EUT	Battery
Un-Shielding Detachable DC Cable	0.2	EUT	Test Load
Un-Shielding Detachable RJ45 Cable	5.0	EUT/POE	Network
Un-Shielding Detachable AC Cable	1.5	POE	LISN
Un-Shielding Detachable RJ45 Cable	1.0/5.0	POE	EUT


### Block Diagram of Test Setup

For conducted emission

Powered by Adapter:




Powered by POE




For Radiated Emissions (below 1GHz):


Powered by DC source (Battery):




Powered by Adapter:



Powered by POE:



For Radiated emission (above 1GHz):



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
WEINSCHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2021/12/13	2022/12/12
Unknown	RF Cable	Unknown	Unknown	Each time	

\* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Result

#### Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	3.6	2.29	21.0	125.89	20	0.057	1

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant



## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
  - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 3.6dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

## Test Data

### Environmental Conditions

<b>Temperature:</b>	23 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Caro Hu on 2022-03-10.*

*EUT operation mode: Transmitting*

**Wi-Fi: (Worst case is 802.11g mode, low Channel)**

**Powered by Adapter:**


**AC 120V/60 Hz, Line**



Site : Shielding Room  
 Condition: Line  
 Mode : 2.4G WIFI  
 Model : i51W  
 Power : AC 120V 60Hz  
 Note : Adapter

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.172	9.80	21.63	31.43	54.88	-23.45	Average
2	0.172	9.80	29.51	39.31	64.88	-25.57	QP
3	0.215	9.80	21.14	30.94	53.01	-22.07	Average
4	0.215	9.80	27.09	36.89	63.01	-26.12	QP
5	0.360	9.80	30.13	39.93	48.72	-8.79	Average
6	0.360	9.80	35.29	45.09	58.72	-13.63	QP
7	1.062	9.81	16.39	26.20	46.00	-19.80	Average
8	1.062	9.81	19.71	29.52	56.00	-26.48	QP
9	3.656	9.84	14.34	24.18	46.00	-21.82	Average
10	3.656	9.84	20.88	30.72	56.00	-25.28	QP
11	5.333	9.85	9.26	19.11	50.00	-30.89	Average
12	5.333	9.85	15.15	25.00	60.00	-35.00	QP

AC 120V/60 Hz, Neutral




Site : Shielding Room  
 Condition: Neutral  
 Mode : 2.4G WIFI  
 Model : i51W  
 Power : AC 120V 60Hz  
 Note : Adapter

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.151	9.80	22.02	31.82	55.94	-24.12	Average
2	0.151	9.80	29.81	39.61	65.94	-26.33	QP
3	0.217	9.80	21.49	31.29	52.93	-21.64	Average
4	0.217	9.80	27.20	37.00	62.93	-25.93	QP
5	0.362	9.80	29.59	39.39	48.67	-9.28	Average
6	0.362	9.80	34.94	44.74	58.67	-13.93	QP
7	0.543	9.81	18.41	28.22	46.00	-17.78	Average
8	0.543	9.81	25.23	35.04	56.00	-20.96	QP
9	3.445	9.83	15.80	25.63	46.00	-20.37	Average
10	3.445	9.83	21.65	31.48	56.00	-24.52	QP
11	5.680	9.92	11.77	21.69	50.00	-28.31	Average
12	5.680	9.92	16.57	26.49	60.00	-33.51	QP

**Powered by POE**


**AC 120V/60 Hz, Line**



Site : Shielding Room  
 Condition: Line  
 Mode : 2.4G WIFI  
 Model : i51W  
 Power : AC 120V 60Hz  
 Note : POE

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.151	9.80	27.42	37.22	55.92	-18.70	Average
2	0.151	9.80	38.48	48.28	65.92	-17.64	QP
3	0.243	9.80	16.64	26.44	52.01	-25.57	Average
4	0.243	9.80	26.97	36.77	62.01	-25.24	QP
5	0.342	9.80	19.47	29.27	49.16	-19.89	Average
6	0.342	9.80	25.48	35.28	59.16	-23.88	QP
7	0.614	9.81	8.26	18.07	46.00	-27.93	Average
8	0.614	9.81	13.54	23.35	56.00	-32.65	QP
9	2.213	9.82	7.41	17.23	46.00	-28.77	Average
10	2.213	9.82	9.47	19.29	56.00	-36.71	QP
11	13.569	9.94	-0.96	8.98	50.00	-41.02	Average
12	13.569	9.94	2.42	12.36	60.00	-47.64	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room  
 Condition: Neutral  
 Mode : 2.4G WIFI  
 Model : i51W  
 Power : AC 120V 60Hz  
 Note : POE

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.157	9.80	26.52	36.32	55.64	-19.32	Average
2	0.157	9.80	36.82	46.62	65.64	-19.02	QP
3	0.216	9.80	18.09	27.89	52.95	-25.06	Average
4	0.216	9.80	29.68	39.48	62.95	-23.47	QP
5	0.342	9.80	19.68	29.48	49.15	-19.67	Average
6	0.342	9.80	26.47	36.27	59.15	-22.88	QP
7	1.820	9.82	10.74	20.56	46.00	-25.44	Average
8	1.820	9.82	17.85	27.67	56.00	-28.33	QP
9	3.549	9.84	12.04	21.88	46.00	-24.12	Average
10	3.549	9.84	21.14	30.98	56.00	-25.02	QP
11	18.946	10.09	10.64	20.73	50.00	-29.27	Average
12	18.946	10.09	15.12	25.21	60.00	-34.79	QP


## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

#### Below 1 GHz:



#### Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.



## EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz <sup>Note 1</sup>	/	Average
	1MHz	> 1/T <sup>Note 2</sup>	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

## Test Data

### Environmental Conditions

<b>Temperature:</b>	24 °C
<b>Relative Humidity:</b>	60 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Chao Mo on 2022-03-22.


EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case of X-axis orientation was recorded)

**30MHz-1GHz: (Worst case is 802.11g mode, low Channel)**

*Note: when the test result of peak was below the limit of QP more than 6dB, just the peak value was recorded.*

**Powered by Adapter:**


**Horizontal**



Site : chamber  
 Condition: 3m Horizontal  
 Job No. : SZNS220120-03042E-RF  
 Test Mode: Transmitting  
 Note : Adapter

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	56.767	-10.08	30.97	20.89	40.00	-19.11	Peak
2	137.481	-15.28	40.46	25.18	43.50	-18.32	Peak
3	244.446	-10.61	46.36	35.75	46.00	-10.25	Peak
4	307.831	-8.96	48.30	39.34	46.00	-6.66	QP
5	366.341	-7.49	46.46	38.97	46.00	-7.03	Peak
6	874.097	1.14	32.96	34.10	46.00	-11.90	Peak

**Vertical**




Site : chamber  
 Condition: 3m VERTICAL  
 Job No. : SZNS220120-03042E-RF  
 Test Mode: Transmitting  
 Note : Adapter

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	44.704	-9.93	38.74	28.81	40.00	-11.19	Peak
2	51.571	-9.96	34.90	24.94	40.00	-15.06	Peak
3	103.397	-11.69	30.36	18.67	43.50	-24.83	Peak
4	138.206	-15.36	34.48	19.12	43.50	-24.38	Peak
5	183.120	-12.40	38.00	25.60	43.50	-17.90	Peak
6	313.002	-8.79	36.82	28.03	46.00	-17.97	Peak

**Powered by POE:**


**Horizontal**



Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No. : SZNS220120-03042E-RF  
 Test Mode: Transmitting  
 Note : POE

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.076	-10.28	35.02	24.74	40.00	-15.26	Peak
2	128.450	-14.75	45.06	30.31	43.50	-13.19	Peak
3	256.184	-10.60	47.50	36.90	46.00	-9.10	QP
4	271.325	-10.14	47.00	36.86	46.00	-9.14	QP
5	379.249	-7.17	43.20	36.03	46.00	-9.97	Peak
6	768.075	-0.28	33.74	33.46	46.00	-12.54	Peak

**Vertical**




Site : chamber  
 Condition: 3m VERTICAL  
 Job No. : SZNS220120-03042E-RF  
 Test Mode: Transmitting  
 Note : POE

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	68.721	-14.17	44.50	30.33	40.00	-9.67	QP
2	89.551	-14.14	44.82	30.68	43.50	-12.82	Peak
3	124.079	-14.22	44.59	30.37	43.50	-13.13	Peak
4	200.249	-11.42	40.58	29.16	43.50	-14.34	Peak
5	238.310	-10.92	39.27	28.35	46.00	-17.65	Peak
6	453.117	-5.56	36.24	30.68	46.00	-15.32	Peak

Powered by DC source (Battery):


Horizontal



Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No. : SZNS220120-03042E-RF  
 Test Mode: Transmitting  
 Note : Battery

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	119.331	-13.41	36.33	22.92	43.50	-20.58	Peak
2	202.366	-11.61	39.05	27.44	43.50	-16.06	Peak
3	238.310	-10.92	47.28	36.36	46.00	-9.64	Peak
4	272.039	-10.10	48.53	38.43	46.00	-7.57	Peak
5	293.599	-9.28	48.67	39.39	46.00	-6.61	Peak
6	411.644	-6.30	40.13	33.83	46.00	-12.17	Peak

Vertical



Site : chamber  
 Condition: 3m VERTICAL  
 Job No. : SZNS220120-03042E-RF  
 Test Mode: Transmitting  
 Note : Battery

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.613	-10.25	43.50	33.25	40.00	-6.75	Peak
2	116.847	-12.95	34.91	21.96	43.50	-21.54	Peak
3	162.112	-14.29	38.78	24.49	43.50	-19.01	Peak
4	238.728	-10.93	39.13	28.20	46.00	-17.80	Peak
5	288.622	-9.35	38.53	29.18	46.00	-16.82	Peak
6	405.377	-6.70	36.93	30.23	46.00	-15.77	Peak

## 1-25 GHz: (worst case is powered by DC source (battery))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	68.03	PK	171	1	H	-7.24	60.79	74	-13.21
2310	54.48	AV	171	1	H	-7.24	47.24	54	-6.76
2310	70.61	PK	230	1.4	V	-7.24	63.37	74	-10.63
2310	55.45	AV	230	1.4	V	-7.24	48.21	54	-5.79
2390	68.50	PK	247	2.1	H	-7.22	61.28	74	-12.72
2390	54.20	AV	247	2.1	H	-7.22	46.98	54	-7.02
2390	72.94	PK	268	1.9	V	-7.22	65.72	74	-8.28
2390	55.14	AV	268	1.9	V	-7.22	47.92	54	-6.08
4824	61.11	PK	226	2.2	H	-3.52	57.59	74	-16.41
4824	54.51	AV	226	2.2	H	-3.52	50.99	54	-3.01
4824	60.95	PK	186	2	V	-3.52	57.43	74	-16.57
4824	54.13	AV	186	2	V	-3.52	50.61	54	-3.39
802.11B, Middle Channel									
4874	59.94	PK	155	1.6	H	-3.42	56.52	74	-17.48
4874	53.60	AV	155	1.6	H	-3.42	50.18	54	-3.82
4874	60.74	PK	158	2.4	V	-3.42	57.32	74	-16.68
4874	53.86	AV	158	2.4	V	-3.42	50.44	54	-3.56
11B, High Channel									
2483.5	68.84	PK	327	1.4	H	-7.20	61.64	74	-12.36
2483.5	54.73	AV	327	1.4	H	-7.20	47.53	54	-6.47
2483.5	69.87	PK	127	2.4	V	-7.20	62.67	74	-11.33
2483.5	54.96	AV	127	2.4	V	-7.20	47.76	54	-6.24
2500	69.01	PK	176	2.5	H	-7.18	61.83	74	-12.17
2500	55.29	AV	176	2.5	H	-7.18	48.11	54	-5.89
2500	69.06	PK	10	1.9	V	-7.18	61.88	74	-12.12
2500	55.42	AV	10	1.9	V	-7.18	48.24	54	-5.76
4924	59.29	PK	51	2.3	H	-3.16	56.13	74	-17.87
4924	53.40	AV	51	2.3	H	-3.16	50.24	54	-3.76
4924	60.68	PK	290	1.6	V	-3.16	57.52	74	-16.48
4924	53.33	AV	290	1.6	V	-3.16	50.17	54	-3.83



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11G, Low Channel									
2310	68.67	PK	7	2.3	H	-7.24	61.43	74	-12.57
2310	54.00	AV	7	2.3	H	-7.24	46.76	54	-7.24
2310	69.45	PK	28	1.4	V	-7.24	62.21	74	-11.79
2310	55.67	AV	28	1.4	V	-7.24	48.43	54	-5.57
2390	68.50	PK	34	1.6	H	-7.22	61.28	74	-12.72
2390	53.67	AV	34	1.6	H	-7.22	46.45	54	-7.55
2390	71.41	PK	81	1.8	V	-7.22	64.19	74	-9.81
2390	55.52	AV	81	1.8	V	-7.22	48.30	54	-5.70
4824	56.89	PK	222	1.3	H	-3.52	53.37	74	-20.63
4824	57.74	PK	287	1.3	V	-3.52	54.22	74	-19.78
4824	41.68	AV	287	1.3	V	-3.52	38.16	54	-15.84
802.11G, Middle Channel									
4874	56.17	PK	37	2.2	H	-3.42	52.75	74	-21.25
4874	57.49	PK	227	1.7	V	-3.42	54.07	74	-19.93
4874	40.28	AV	227	1.7	V	-3.42	36.86	54	-17.14
802.11G, High Channel									
2483.5	68.49	PK	266	2.2	H	-7.20	61.29	74	-12.71
2483.5	54.82	AV	266	2.2	H	-7.20	47.62	54	-6.38
2483.5	70.37	PK	32	2.4	V	-7.20	63.17	74	-10.83
2483.5	55.11	AV	32	2.4	V	-7.20	47.91	54	-6.09
2500	69.22	PK	20	1.6	H	-7.18	62.04	74	-11.96
2500	54.82	AV	20	1.6	H	-7.18	47.64	54	-6.36
2500	69.60	PK	262	1.2	V	-7.18	62.42	74	-11.58
2500	54.33	AV	262	1.2	V	-7.18	47.15	54	-6.85
4924	56.22	PK	153	2.1	H	-3.16	53.06	74	-20.94
4924	57.52	PK	225	1.4	V	-3.16	54.36	74	-19.64
4924	40.28	AV	225	1.4	V	-3.16	37.12	54	-16.88

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11N20, Low Channel									
2310	67.81	PK	294	1.7	H	-7.24	60.57	74	-13.43
2310	54.11	AV	294	1.7	H	-7.24	46.87	54	-7.13
2310	68.18	PK	52	1.9	V	-7.24	60.94	74	-13.06
2310	54.96	AV	52	1.9	V	-7.24	47.72	54	-6.28
2390	68.22	PK	359	2.4	H	-7.22	61.00	74	-13.00
2390	53.75	AV	359	2.4	H	-7.22	46.53	54	-7.47
2390	73.33	PK	347	2.2	V	-7.22	66.11	74	-7.89
2390	54.73	AV	347	2.2	V	-7.22	47.51	54	-6.49
4824	54.92	PK	312	1.3	H	-3.52	51.40	74	-22.60
4824	56.59	PK	329	2	V	-3.52	53.07	74	-20.93
802.11N20, Middle Channel									
4874	57.20	PK	1	1.4	H	-3.42	53.78	74	-20.22
4874	56.85	PK	28	1.9	V	-3.42	53.43	74	-20.57
802.11N20, High Channel									
2483.5	69.05	PK	199	1.4	H	-7.20	61.85	74	-12.15
2483.5	54.24	AV	199	1.4	H	-7.20	47.04	54	-6.96
2483.5	69.23	PK	250	1.7	V	-7.20	62.03	74	-11.97
2483.5	54.44	AV	250	1.7	V	-7.20	47.24	54	-6.76
2500	69.15	PK	317	1.3	H	-7.18	61.97	74	-12.03
2500	54.82	AV	317	1.3	H	-7.18	47.64	54	-6.36
2500	69.50	PK	123	1.1	V	-7.18	62.32	74	-11.68
2500	55.00	AV	123	1.1	V	-7.18	47.82	54	-6.18
4924	55.09	PK	170	2.3	H	-3.16	51.93	74	-22.07
4924	56.61	PK	35	2.4	V	-3.16	53.45	74	-20.55

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11N40, Low Channel									
2310	68.83	PK	221	1.9	H	-7.24	61.59	74	-12.41
2310	54.32	AV	221	1.9	H	-7.24	47.08	54	-6.92
2310	74.80	PK	137	2.2	V	-7.24	67.56	74	-6.44
2310	56.90	AV	137	2.2	V	-7.24	49.66	54	-4.34
2390	70.05	PK	34	1.2	H	-7.22	62.83	74	-11.17
2390	53.99	AV	34	1.2	H	-7.22	46.77	54	-7.23
2390	74.84	PK	77	1.5	V	-7.22	67.62	74	-6.38
2390	56.58	AV	77	1.5	V	-7.22	49.36	54	-4.64
4844	53.36	PK	45	1.3	H	-3.54	49.82	74	-24.18
4844	54.81	PK	57	1.3	V	-3.54	51.27	74	-22.73
802.11N40, Middle Channel									
4874	55.13	PK	74	1.8	H	-3.42	51.71	74	-22.29
4874	53.91	PK	328	1.8	V	-3.42	50.49	74	-23.51
802.11N40, High Channel									
2483.5	70.54	PK	41	1.4	H	-7.20	63.34	74	-10.66
2483.5	54.20	AV	41	1.4	H	-7.20	47	54	-7.00
2483.5	68.75	PK	268	1.9	V	-7.20	61.55	74	-12.45
2483.5	54.39	AV	268	1.9	V	-7.20	47.19	54	-6.81
2500	68.97	PK	102	2.1	H	-7.18	61.79	74	-12.21
2500	54.82	AV	102	2.1	H	-7.18	47.64	54	-6.36
2500	69.06	PK	139	1.5	V	-7.18	61.88	74	-12.12
2500	54.96	AV	139	1.5	V	-7.18	47.78	54	-6.22
4904	55.10	PK	212	1.7	H	-3.26	51.84	74	-22.16
4904	54.57	PK	110	1.7	V	-3.26	51.31	74	-22.69

**Note:**

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit


The other spurious emission which is 20dB below to the limit or in noise floor level was not recorded.

When the test result of peak was less than the limit of average, just peak values were recorded.


1-18 GHz:

Pre-scan Plots:

802.11 b Low Channel  
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 b Low Channel  
Horizontal



Vertical




## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Data

#### Environmental Conditions

<b>Temperature:</b>	23.8 °C
<b>Relative Humidity:</b>	59.8 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Key Pei on 2022-02-16.*

*EUT operation mode: Transmitting*


Please refer to the following table and plots.

*EUT operation mode: Transmitting*

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode				
Low	2412	9.551	13.111	≥500
Middle	2437	9.551	13.111	≥500
High	2462	9.551	13.025	≥500
802.11g mode				
Low	2412	16.281	16.498	≥500
Middle	2437	16.324	16.498	≥500
High	2462	16.324	16.454	≥500
802.11n-HT20 mode				
Low	2412	16.932	17.496	≥500
Middle	2437	16.975	17.496	≥500
High	2462	16.975	17.540	≥500
802.11n-HT40 mode				
Low	2422	35.514	35.948	≥500
Middle	2437	35.514	35.861	≥500
High	2452	35.514	35.861	≥500


6 dB Emission Bandwidth

802.11b Low Channel



Date: 16.FEB.2022 15:31:34


802.11b Middle Channel



Date: 16.FEB.2022 15:30:43




### 802.11b High Channel




Date: 16.FEB.2022 15:29:58

### 802.11g Low Channel




Date: 16.FEB.2022 15:26:43

### 802.11g Middle Channel




Date: 16.FEB.2022 15:27:31

### 802.11g High Channel




Date: 16.FEB.2022 15:28:24

### 802.11n-HT20 Low Channel




Date: 16.FEB.2022 15:25:36

### 802.11n-HT20 Middle Channel




Date: 16.FEB.2022 15:24:33

### 802.11n-HT20 High Channel




Date: 16.FEB.2022 15:23:42

### 802.11n-HT40 Low Channel




Date: 16.FEB.2022 15:20:28

### 802.11n-HT40 Middle Channel



Date: 16.FEB.2022 15:21:20


### 802.11n-HT40 High Channel



Date: 16.FEB.2022 15:22:05


99% Emission Bandwidth

802.11b Low Channel




Date: 16.FEB.2022 15:49:01

802.11b Middle Channel




Date: 16.FEB.2022 15:49:21

### 802.11b High Channel




Date: 16.FEB.2022 15:49:38

### 802.11g Low Channel




Date: 16.FEB.2022 15:48:40

### 802.11g Middle Channel



Date: 16.FEB.2022 15:48:19


### 802.11g High Channel



Date: 16.FEB.2022 15:47:54




### 802.11n-HT20 Low Channel




Date: 16.FEB.2022 15:46:44

### 802.11n-HT20 Middle Channel




Date: 16.FEB.2022 15:47:07

### 802.11n-HT20 High Channel




Date: 16.FEB.2022 15:47:29

### 802.11n-HT40 Low Channel




Date: 16.FEB.2022 15:46:05

### 802.11n-HT40 Middle Channel



Date: 16.FEB.2022 15:45:11

### 802.11n-HT40 High Channel



Date: 16.FEB.2022 15:45:37


## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

- c. Place the EUT on a bench and set it in transmitting mode.
- d. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- e. Add a correction factor to the display.



Note: the Open Switch and Control Unit have a built-in power sensor.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	23.8 °C
<b>Relative Humidity:</b>	59.8 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Key Pei on 2022-02-16.*

*EUT operation mode: Transmitting*

Test Result: Compliant.

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b mode			
Low	2412	17.04	30
Middle	2437	16.83	30
High	2462	16.49	30
802.11g mode			
Low	2412	20.44	30
Middle	2437	20.16	30
High	2462	19.79	30
802.11n HT20 mode			
Low	2412	19.93	30
Middle	2437	19.63	30
High	2462	19.07	30
802.11n HT40 mode			
Low	2422	19.32	30
Middle	2437	19.37	30
High	2452	19.24	30


## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

- f. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- g. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- h. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- i. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- j. Repeat above procedures until all measured frequencies were complete.



### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	23.8 °C
<b>Relative Humidity:</b>	59.8 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Key Pei on 2022-02-16.*

*EUT operation mode: Transmitting*

Test Result: Compliant.

Please refer to the following plots.

### 802.11b: Band Edge, Left Side




Date: 16.FEB.2022 15:51:46

### 802.11b: Band Edge, Right Side




Date: 16.FEB.2022 15:52:57

### 802.11g: Band Edge, Left Side



Date: 16.FEB.2022 15:54:42


### 802.11g: Band Edge, Right Side



Date: 16.FEB.2022 15:53:43




### 802.11n-HT20: Band Edge, Left Side




Date: 16.FEB.2022 15:55:31

### 802.11n-HT20: Band Edge, Right Side




Date: 16.FEB.2022 15:56:07

### 802.11n-HT40: Band Edge, Left Side



Date: 16.FEB.2022 15:58:26

### 802.11n-HT40: Band Edge, Right Side



Date: 16.FEB.2022 15:57:52


## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

- k. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- l. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
- m. Set the VBW  $\geq 3 \times \text{RBW}$ .
- n. Set the span to 1.5 times the DTS bandwidth.
- o. Detector = peak.
- p. Sweep time = auto couple.
- q. Trace mode = max hold.
- r. Allow trace to fully stabilize.
- s. Use the peak marker function to determine the maximum amplitude level within the RBW.
- t. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Data

#### Environmental Conditions

<b>Temperature:</b>	23.8 °C
<b>Relative Humidity:</b>	59.8 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Key Pei on 2022-02-16.*

*EUT operation mode: Transmitting*

Test Result: Compliant.


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-6.91	$\leq 8$
Middle	2437	-7.09	$\leq 8$
High	2462	-7.49	$\leq 8$
802.11g mode			
Low	2412	-13.50	$\leq 8$
Middle	2437	-13.95	$\leq 8$
High	2462	-14.33	$\leq 8$
802.11n-HT20 mode			
Low	2412	-13.63	$\leq 8$
Middle	2437	-13.99	$\leq 8$
High	2462	-14.44	$\leq 8$
802.11n-HT40 mode			
Low	2422	-16.07	$\leq 8$
Middle	2437	-16.32	$\leq 8$
High	2452	-16.17	$\leq 8$

### Power Spectral Density, 802.11b Low Channel




Date: 16.FEB.2022 15:32:16

### Power Spectral Density, 802.11b Middle Channel




Date: 16.FEB.2022 15:32:50

### Power Spectral Density, 802.11b High Channel




Date: 16.FEB.2022 15:33:19

### Power Spectral Density, 802.11g Low Channel




Date: 16.FEB.2022 15:34:26

### Power Spectral Density, 802.11g Middle Channel




Date: 16.FEB.2022 15:34:06

### Power Spectral Density, 802.11g High Channel




Date: 16.FEB.2022 15:33:47

### Power Spectral Density, 802.11n-HT20 Low Channel



Date: 16.FEB.2022 15:34:56


### Power Spectral Density, 802.11n-HT20 Middle Channel



Date: 16.FEB.2022 15:35:18




### Power Spectral Density, 802.11n-HT20 High Channel




Date: 16.FEB.2022 15:35:41

### Power Spectral Density, 802.11n-HT40 Low Channel




Date: 16.FEB.2022 15:37:07

### Power Spectral Density, 802.11n-HT40 Middle Channel



Date: 16.FEB.2022 15:36:42

### Power Spectral Density, 802.11n-HT40 High Channel



Date: 16.FEB.2022 15:36:21

\*\*\*\*\* END OF REPORT \*\*\*\*\*