



Report No.: SEWM2302000052RG02  
Rev.: 01  
Page: 1 of 3

# Appendix B.8

## LTE Band 26(814-824)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)  
South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 t (86-512) 62992980 www.sgs.com.cn  
中国·苏州·中国（江苏）自由贸易试验区苏州片区苏州工业园区润胜路1号6号厂房南楼 邮编：215000 t (86-512) 62992980 sgs.china@sgs.com

## Transmitter Conducted Power Output

Test for Spot check the max BW power:

### Test Result

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Limit (dBm)	Verdict
Band26	10MHz	QPSK	26740	1RB#0	22.72	50	PASS
Band26	10MHz	QPSK	26740	1RB#25	22.75	50	PASS
Band26	10MHz	QPSK	26740	1RB#49	22.70	50	PASS
Band26	10MHz	QPSK	26740	25RB#0	21.66	50	PASS
Band26	10MHz	QPSK	26740	25RB#13	21.61	50	PASS
Band26	10MHz	QPSK	26740	25RB#25	21.64	50	PASS
Band26	10MHz	QPSK	26740	50RB#0	21.59	50	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## Field Strength of Spurious Radiation

### Test for spot check:

Test Band = LTE Band 26 10M\_ TM1

Test Channel = Mid

Final Data List										
NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	AF[dB/m]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1629.18	65.78	-48.44	25.59	-52.33	-13.00	39.33	188	23	Horizontal
2	2443.77	55.33	-47.22	27.79	-59.36	-13.00	46.36	255	178	Horizontal
3	3258.36	60.18	-46.18	29.50	-51.76	-13.00	38.76	168	146	Horizontal
4	4072.95	46.10	-45.43	30.72	-63.88	-13.00	50.88	147	357	Horizontal
5	4887.54	38.78	-45.08	32.33	-69.23	-13.00	56.23	162	222	Horizontal
6	5702.13	40.36	-43.56	33.25	-65.21	-13.00	52.21	232	237	Horizontal

Final Data List										
NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	AF[dB/m]	Level [dBm]	Limit [dBm]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1629.18	65.29	-48.44	25.59	-52.82	-13.00	39.82	169	308	Vertical
2	2443.77	50.08	-47.22	27.79	-64.61	-13.00	51.61	187	339	Vertical
3	3258.36	59.69	-46.18	29.50	-52.25	-13.00	39.25	214	294	Vertical
4	4072.95	49.42	-45.43	30.72	-60.56	-13.00	47.56	162	308	Vertical
5	4887.54	39.16	-45.08	32.33	-68.85	-13.00	55.85	225	31	Vertical
6	5702.13	40.88	-43.56	33.25	-64.69	-13.00	51.69	137	360	Vertical

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & AMP. The basic equation with a sample calculation is as follows:

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier (dB)

Level = Reading Level + AF + Factor -95.26

Margin = Limit – Level

---End of Attachment---

