Mercku Inc.

U-NII-DTS Declaration Letter

To whom it may concern:

We have declared below featured for FCC equipment authorization,

Device FCC ID: 2APR4-X6

(1)	DFS Device Master , Client with Radar detection capability ,
	☐ Client without radar detection capability , ☐ N/A

(2) Active / Passive Scanning , adhoc mode access point capability

Frequency Band	Active Scanning	passive scanning	Ad Hoc Mode or	Access point
(MHz)	(the device can	(where the device is	WIFI Direct	capability
	transmit a probe	can listen only with	capability	
	(beacon))	no probes)		
5180-5240	☐ Yes , ☐ No		☐ Yes , ☒ No	🛛 Yes , 🗌 No
5745-5825	☐ Yes , ☐ No		☐ Yes , ☒ No	🛛 Yes , 🗌 No
5190-5230	☐ Yes , ☒ No		☐ Yes , ☒ No	🛛 Yes , 🗌 No
5270-5310	☐ Yes , ☒ No		☐ Yes , ☒ No	🛛 Yes , 🗌 No
5755-5795	☐ Yes , ☒ No		☐ Yes , ☒ No	🛛 Yes , 🗌 No
5210-5210	☐ Yes , ☒ No		☐ Yes , ☒ No	🛛 Yes , 🗌 No
5290-5290	☐ Yes , ☒ No	🛛 Yes , 🗌 No	☐ Yes , ☒ No	🛛 Yes , 🗌 No
5775-5775	☐ Yes , ☒ No	🛛 Yes , 🗌 No	☐ Yes , ☒ No	🛛 Yes , 🗌 No
	5180-5240 5745-5825 5190-5230 5270-5310 5755-5795 5210-5210 5290-5290	(MHz) (the device can transmit a probe (beacon)) 5180-5240 □ Yes , ⋈ No 5745-5825 □ Yes , ⋈ No 5190-5230 □ Yes , ⋈ No 5270-5310 □ Yes , ⋈ No 5755-5795 □ Yes , ⋈ No 5210-5210 □ Yes , ⋈ No 5290-5290 □ Yes , ⋈ No	(MHz) (the device can transmit a probe (beacon)) (where the device is can listen only with no probes) 5180-5240 Yes, No Yes, No 5745-5825 Yes, No Yes, No 5190-5230 Yes, No Yes, No 5270-5310 Yes, No Yes, No 5755-5795 Yes, No Yes, No 5210-5210 Yes, No Yes, No 5290-5290 Yes, No Yes, No	(MHz) (the device can transmit a probe (beacon)) (where the device is can listen only with no probes) WIFI Direct capability 5180-5240 Yes, No No

(3) Country code selection ability - Yes, No If yes, pls explain how it was implemented: (pls also help to provide detail of options for each country selection)

(4)	Meet 15.202 requirement	- 🖂	Yes ,	No ,
pls ched	ck below:			

A master device is defined as a device operating in a mode in which it has the capability to transmit without receiving an enabling signal. In this mode it is able to select a channel and initiate a network by sending enabling signals to other devices

A client device is defined as a device operating in a mode in which the transmissions of the device are under control of the master. A device in client mode is not able to initiate a network.

(5) For client devices that have software configuration control to operate in different modes (active scanning in some and passive scanning in others) in different bands (devices with multiple equipment classes or those that operate on non-DFS frequencies) or modular devices which configure the modes of operations through software, the application must provide software and operations description on how the software and / or hardware is implemented to ensure that proper operations modes can not be modified by end user or an installer.

☐ Apply , ☒ No Apply ,

(If apply, pls help to provide explanation on it was implement, and how software was controlled)

Client's Signature:

Shi Ge

Date: 2023.6.2

Shi Ge