



FCC CFR47 Part 15 Subpart C ISED RSS-247 Certification Test Report

For the

Product : Digital Smart Door Lock Set
Model : GKW-2000D
FCC ID : 2APR8-GKW2000D
IC : 24013-GKW2000D
Applicant : Guardtec
FCC Rule : CFR 47 Part 15 Subpart C
ISED Rule : IC RSS-247 Issue 2

We hereby certify that the above product has been tested by us with the listed rules and found in compliance with the regulation. The test data and results are issued on the test report no. TR-W1806-003

Signature

A handwritten signature in black ink, appearing to read 'Choi, Yeong-min', is written over a horizontal line.

Choi, Yeong-min / Technical Manager

Date: 2018-06-12

Test Laboratory: ENG Co., Ltd.

It shall not be reproduced except in full, without the written approval of the ENG Co., Ltd. This document may be altered or revised by the ENG Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Report No.: TR-W1806-003



ENG Co., Ltd. 135-60 Gyeongchung-daero, Gyeongju-eup, Gyeongju-si, Gyeonggi-do, Korea 464-942

Report Form_01 (Rev.0)

FCC/ISED CERTIFICATION TEST REPORT

Project Number : EA1804C-091
Test Report Number : TR-W1806-003
Type of Equipment : Digital Smart Door Lock Set
Model Name : GKW-2000D
FCC ID : 2APR8-GKW2000D
ISED Cert. Number : 24013-GKW2000D
Multiple Model Name : N/A
Applicant : Guardtec
Address : #1203-1204, Hansin IT Tower, 272 Digital-ro, Guro-gu, Seoul, Korea 08389
Manufacturer : Guardtec
Address : #1203-1204, Hansin IT Tower, 272 Digital-ro, Guro-gu, Seoul, Korea 08389
Regulation : FCC Part 15 Subpart C Section 15.247, ISED RSS-247 Issue2
Total page of Report : 39 Pages
Date of Receipt : 2018-04-26
Date of Issue : 2018-06-12
Test Result : PASS

This test report only contains the result of a single test of the sample supplied for the examination.
It is not a generally valid assessment of the features of the respective products of the mass-production.

| | | | |
|-------------|-------------------------------------|--|------------|
| Prepared by | Song, In-young / Senior Engineer |  | 2018-06-12 |
| | | Signature | Date |
| Reviewed by | Choi, Yeong-min / Technical Manager |  | 2018-06-12 |
| | | Signature | Date |

CONTENTS

Page

| | |
|--|----|
| 1. TEST SUMMARY | 4 |
| 2. EUT (EQUIPMENT UNDER TEST) INFORMATION..... | 6 |
| 3. TEST CONDITION..... | 8 |
| 4. ANTENNA REQUIREMENT | 10 |
| 4.1 ANTENNA DESCRIPTION | 10 |
| 4.2 CONCLUSION..... | 10 |
| 5. TEST RESULT | 11 |
| 5.1 6 DB BANDWIDTH..... | 11 |
| 5.2 99 % BANDWIDTH..... | 14 |
| 5.3 MAXIMUM PEAK OUTPUT POWER | 17 |
| 5.4 PEAK POWER SPECTRAL DENSITY | 20 |
| 5.5 OUT OF BAND EMISSION | 23 |
| 5.6 RADIATED EMISSION..... | 28 |
| APPENDIX I – TEST INSTRUMENTATION | 39 |

Release Control Record

| Issue Report No. | Issued Date | Details/Revisions |
|------------------|-------------|-------------------|
| TR-W1806-003 | 2018-06-12 | Initial Release |
| - | - | - |

1. TEST SUMMARY

1.1 Regulations and results

The sample submitted for evaluation (Referred to below as the EUT) has been tested in accordance with the following regulations or standards.

| FCC Reference Section | ISED Reference Section | Description | P | F | N.T. | Note |
|------------------------|----------------------------|--|---|---|------|--------|
| 15.247(a)(2) | RSS-247 5.2 a) | 6 dB Bandwidth Occupied Bandwidth | P | | | |
| 15.247(b)(3) | RSS-247 5.4 d) | Maximum peak output power | P | | | |
| 15.247(e) | RSS-247 5.2 b) | Power spectral density | P | | | |
| 15.247(d) | RSS-247 5.5 | Band Edge Conducted spurious emission | P | | | |
| 15.205(a) 15.209(a) | RSS 247 5.5 RSS-GEN 8.9 | Radiated spurious emissions | P | | | |
| 15.207(a) | RSS GEN 8.8 | AC power line conducted emissions | | | N.T. | Note 1 |

Remark:

P means Passed

F means Failed

N.T. means Not Tested

Note1. The EUT is operated by battery only. (used manganese dry cell as type AA)

1.2 Test Methodology

The tests mentioned in clause 1.1 in this test report were performed according to FCC CFR 47 Part 2, CFR 47 Part 15 and ANSI C63.10-2013, and RSS-Gen Issue 4, KDB 558074 D01DTS Meas. Guidance v04: Measurement Procedure PK is used for power.

1.3 Additions, deviations, exclusions from standards





No additions, deviations or exclusions have been made from standard.

1.4 Purpose of the test

The test was performed to determine whether the equipment under test fulfills the requirements of the regulation stated in FCC Part 15 Subpart C Section 15.247, RGG-Gen and RSS-247

1.5 Test Facility

The measurement facilities are located at 135-60 Gyeongchung-daero, Gonjiam-eup, Gwangju-si, Gyeonggi-do 12813, Korea. Description details of test facilities were submitted to the FCC and IC, designated by the RRA (Radio Research Agency), and accredited by Korea and accredited by KOLAS (Korea Laboratory Accreditation Scheme) in Korea according to the requirement of ISO 17025.

| Laboratory Qualification | Registration No. | Mark |
|--|------------------|---|
| FCC | KR0160 |  |
| ISED(Canada) | IC 12721A |  |
| RRA | KR0160 |  |
| Korean Agency for Technology and Standards | KT733 |  |

2. EUT (Equipment Under Test) INFORMATION

2.1 General Description

The Guardtec, Model GKW-2000D (referred to as the EUT in this report) is a Digital Smart Door Lock Set. The EUT is a device for transferring Bluetooth signal to an Smart phone through wireless communication.

The product specification described herein was obtained from product data sheet or user's manual.

| | |
|--------------------------------|---|
| Operating Frequency | 2 402 ~ 2 480 MHz |
| Max. RF Output Power | -6.73 dBm |
| Modulation Types | Bluetooth Low Energy |
| Number of Channels | 40 CH |
| Channel Bandwidth | 2 MHz |
| Generated or used Freq. in EUT | 32.768 kHz, 13.56 MHz, 16 MHz, 32 MHz |
| Type of Antenna | <input checked="" type="checkbox"/> Integrated Type <input type="checkbox"/> Dedicated Type |
| Antenna Gain | -7.45 dBi |
| Operating Temperature | -20 °C ~ + 55 °C |
| Normal Test Voltage | DC 6.0 V |
| Electrical Rating | DC 6.0 V |
| Test SW Version | nRFgo Studio Version: 1.21.2.10 |
| RF power setting in TEST SW | N/A |
| Software Version | 1.0 |
| Hardware Version | 1.0 |

2.2 Available channel number and frequency

| Operating Mode: Bluetooth LE, 2 MHz Channel Spacing | | | | | |
|---|----------------|---------|----------------|---------|----------------|
| Channel | Frequency(MHz) | Channel | Frequency(MHz) | Channel | Frequency(MHz) |
| 0 | 2 402 | 14 | 2 430 | 28 | 2 458 |
| 1 | 2 404 | 15 | 2 432 | 29 | 2 460 |
| 2 | 2 406 | 16 | 2 434 | 30 | 2 462 |
| 3 | 2 408 | 17 | 2 436 | 31 | 2 464 |
| 4 | 2 410 | 18 | 2 438 | 32 | 2 466 |
| 5 | 2 412 | 19 | 2 440 | 33 | 2 468 |
| 6 | 2 414 | 20 | 2 442 | 34 | 2 470 |
| 7 | 2 416 | 21 | 2 444 | 35 | 2 472 |
| 8 | 2 418 | 22 | 2 446 | 36 | 2 474 |
| 9 | 2 420 | 23 | 2 448 | 37 | 2 476 |
| 10 | 2 422 | 24 | 2 450 | 38 | 2 478 |
| 11 | 2 424 | 25 | 2 452 | 39 | 2 480 |
| 12 | 2 426 | 26 | 2 454 | | |
| 13 | 2 428 | 27 | 2 456 | | |

2.3 Additional Model

None

3. TEST CONDITION

3.1 Equipment Used During Test

The following peripheral devices and/or interface cables were connected during the measurement:


| Description | Model No. | Serial No. | Manufacturer. |
|-----------------------------------|-----------|---------------|---------------|
| Digital Smart Door Lock Set (EUT) | GKW-2000D | N/A | Guardtec |
| Test Jig | FT232 | N/A | N/A |
| Notebook PC | E5470 | ZU10190-15008 | DELL |
| Adapter for Notebook PC | LA65NM130 | N/A | DELL |

3.2 Mode of operation during the test


Software used to control the EUT for staying in continuous transmitting mode is programmed.

The used modulation type for the testing is GFSK.


3.3 Test Setup Drawing
(Radiated Test below 1 GHz)



(Radiated Test above 1 GHz)



(Conducted Test)



3.4 EUT Modifications

- No EMC Relevant Modifications were performed by this test laboratory.

4. ANTENNA REQUIREMENT

According to FCC CFR 47 Part 15 section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provision of this section.

4.1 Antenna Description

| Frequency Band (GHz) | Antenna Type | Max Peak Gain (dBi) | Connector Type |
|----------------------|---------------------|---------------------|----------------|
| 2.4 | PCB Pattern Antenna | -7.45 | - |

4.2 Conclusion

The antenna connector type of the EUT is PCB Pattern Antenna, so the EUT met the requirement.

5. TEST RESULT

5.1 6 dB Bandwidth

5.1.1 Limit


The minimum 6 dB bandwidth shall be at least 500 kHz acc to Section 15.247 (a) (2), and RSS-247 5.2 (a).

5.1.2 Method of Measurement



Reference to KDB 558074 D01 DTS Meas Guidance v04: 8.1 Option 1

The transmitter output is connected to a spectrum analyzer with the RBW set to 100 kHz, VBW $\geq 3 \times$ RBW, peak detector and max hold.


5.1.3 Test Data

| | | | |
|------------------------------|-----------------|----------------------|---|
| Date of Test | 2018-05-02 | Temperature | (24.0 \pm 1.0) °C |
| | | Relative humidity | (48.0 \pm 3.0) % R.H. |
| Test Result | PASS | Tested by | Do-heon Kim  |
| Operating Mode: Bluetooth LE | | | |
| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) |
| Low | 2 402 | 0.65 | 0.5 |
| Middle | 2 440 | 0.66 | |
| High | 2 480 | 0.67 | |

5.1.4 Test Plots



Operating Mode: Bluetooth LE (High Channel)



5.2 99 % Bandwidth

5.2.1 Limit

Not applicable. For reporting purpose only.


5.2.2 Method of Measurement

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1 % to 5 % of the OBW.



The span is set to capture all products of the modulation process, including the emission skirts.

The VBW is set to 3 times the RBW. The sweep time is coupled and peak detection and max hold mode is used. The spectrum analyzer internal 99% bandwidth function is utilized.


5.2.3 Test Data

| | | | |
|--------------------------------|-----------------|----------------------|---|
| Date of Test | 2018-05-02 | Temperature | (24.0 ± 1.0) °C |
| | | Relative humidity | (48.0 ± 3.0) % R.H. |
| Test Result | PASS | Tested by | Do-heon Kim  |
| Operational Mode: Bluetooth LE | | | |
| Channel | Frequency (MHz) | 99 % Bandwidth (MHz) | |
| Low | 2 402 | 1.01 | |
| Middle | 2 440 | 1.02 | |
| High | 2 480 | 1.02 | |

5.2.4 Test Plots



Operating Mode: Bluetooth LE (High Channel)



5.3 Maximum Peak Output Power

5.3.1 Limit


Acc. To section 15.247 and RSS-247 5.4 d), For system using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt, based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 9.1.1 RBW \geq DTS bandwidth



The cable assembly insertion loss was entered as an offset in the spectrum analyzer to allow for direct reading of power.

5.3.3 Test Data for Output Power


| Date of Test | 2018-05-02 | Temperature | (24.0 \pm 1.0) °C | |
|------------------------------|-----------------|----------------------|--|-------------|
| | | Relative humidity | (48.0 \pm 3.0) % R.H. | |
| Test Result | PASS | Tested by | Do-heon Kim  | |
| Operating Mode: Bluetooth LE | | | | |
| Channel | Frequency (MHz) | Measured Value (dBm) | Limit (dBm) | Margin (dB) |
| Low | 2 402 | -7.18 | 30 | 37.18 |
| Middle | 2 440 | -6.73 | | 36.73 |
| High | 2 480 | -7.00 | | 37.00 |

Remark. Margin = Limit – Measured Value

5.3.4 Test Plots



Operating Mode: Bluetooth LE (High Channel)



5.4 Peak Power Spectral Density

5.4.1 Limit


Acc. To section 15.247 and RSS-247 5.2 b), the power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.4.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 10.2 Method PKPSD (peak PSD).

The transmitter output is connected to a spectrum analyzer with the RBW set from 3 kHz to 100 kHz, VBW \geq 3 X RBW, peak detector and max hold.



5.4.3 Test Data

| Date of Test | 2018-05-02 | Temperature | (24.0 \pm 1.0) °C | | | |
|------------------------------|-----------------|------------------------------|---|----------------------------|-------------|-------------|
| | | Relative humidity | (48.0 \pm 3.0) % R.H. | | | |
| Test Result | PASS | Tested by | Do-heon Kim  | | | |
| Operating Mode: Bluetooth LE | | | | | | |
| Channel | Frequency (MHz) | Measured Value (dBm/100 kHz) | Compensation Factor(dB) | Measured Value (dBm/3 kHz) | Limit (dBm) | Margin (dB) |
| Low | 2 402 | -7.69 | -15.23 | -22.92 | 8 | 30.92 |
| Middle | 2 440 | -7.05 | -15.23 | -22.28 | | 22.28 |
| High | 2 480 | -7.38 | -15.23 | -22.61 | | 22.61 |


Remark. 1. Compensation Factor(dB) = $10 * \log(\text{RBW}_{ref} / \text{RBW}_{Measured}) = -15.23$

2. Margin = Limit – Measured Value

5.4.4 Test Plots



Operating Mode: Bluetooth LE (High Channel)



5.5 Out of Band Emission


5.5.1 Limit

Acc. To section 15.247(d) and RSS-247 5.5, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section §15.205(a), must also comply the radiated emission limits specified in section §15.209(a) (see section §15.205(c))


5.5.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 11.0 Emissions in non-restricted frequency bands. The transmitter output is connected to a spectrum analyzer with the RBW set to 100 kHz, VBW \geq 3 X RBW, peak detector and max hold. Measurements utilizing these settings are made of the in-band reference level, band-edge (where measurements to the general radiated limits will not be made) and out-of-band emissions.


5.5.3 Test Data for Operating mode: Bluetooth LE

| | | | |
|--------------------|-------------|-------------------|---|
| Date of Test | 2018-05-02 | Temperature | (24.0 ± 1.0) °C |
| | | Relative humidity | (48.0 ± 3.0) % R.H. |
| Test Result | PASS | Tested by | Do-heon Kim  |


Band-edge and Restricted band – Low channel




Band-edge and Restricted band – High channel




Non-restricted band – Low Channel (1)




Non-restricted band – Low Channel (2)




Non-restricted band – Middle Channel (1)




Non-restricted band – Middle Channel (2)



Non-restricted band – High Channel (1)



Non-restricted band – High Channel (2)



5.6 Radiated Emission

5.6.1 Limit

Acc. To section 15.205,15.209, and RSS-Gen 8.9, following table shall be applied.

| Frequency Range (MHz) | Field Strength Limit (uV/m) at 3 m | Field Strength Limit (dBuV/m) at 3 m |
|-----------------------|------------------------------------|--------------------------------------|
| 30 – 88 | 100 | 40 |
| 88 – 216 | 150 | 43.5 |
| 216 – 960 | 200 | 46 |
| Above 960 | 500 | 24 |

5.6.2 Method of Measurement

Reference to KDB 558074 D01 DTS Meas Guidance v04: 12.1 Radiated emission measurements.

The radiated emissions measurements were on 3 m, semi-anechoic chamber. The EUT and other support equipment were placed on a non-conductive table 80 cm for below 1 GHz and 1.5 m for above 1 GHz above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 MHz to 25 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

For measurement below 1 GHz, the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For peak emission measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz and for average measurement, resolution bandwidth is set to 1 MHz; and the video bandwidth is set to 10 Hz, when duty cycle is more than 98 %. If duty cycle is less than 98 %, the video bandwidth is set to $\geq 1/T$, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz. The spectrum from 30 MHz to 25 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

5.6.3 Test Site Requirement for KDB 414788 D01

Acc. to KDB 414788 D01 Radiated Test Site v01, Semi Anechoic Chamber (SAC) shall be verified test results below 30 MHz with Open Area Test Site (OATS), so we compared test results between the measurements from our SAC and an OATS and found test results almost same, so we declare test result for below 30 MHz from our SAC is valid and met the requirement acc. to KDB 414788 D01 Radiated Test Site v01.

5.6.4 Measurement Uncertainty

Measurement uncertainties were not taken into account and following uncertainty levels have been estimated for tests performed on the apparatus. The measurement uncertainties are given with at least 95 % confidence.

| Frequency Range | Uncertainty | Frequency Range | Uncertainty |
|-----------------|-------------|-----------------|-------------|
| 9 kHz ~ 30 MHz | ± 2.1 dB | 30 MHz ~ 1 GHz | ± 4.8 dB |
| 1 GHz ~ 18 GHz | ± 5.0 dB | 18 GHz ~25 GHz | ± 5.3 dB |

5.6.5 Sample Calculated Example

At 80 MHz


Limit = 40.0 dBuV/m

Result = Receiver reading value + Antenna Factor + Cable Loss – Pre-amplifier gain = 30 dBuV/m


Margin = Limit – Result = 40 – 30 = 10

so the EUT has 10.0 dB margin at 80 MHz

5.6.6 Test Data


| | | | | | |
|------------------------------------|---------------|-------------------|---|-----------------|----------------------|
| Date of Test | 2018-05-23 | Temperature | (23.2 ± 2.7) °C | | |
| | | Relative humidity | (46.4 ± 5.9) % R.H. | | |
| Measurement Frequency Range | | 9 kHz ~ 25 GHz | | | |
| Test Result | PASS | Tested By | Do-heon Kim  | | |
| Frequency range | Detector Mode | Resolution BW | Video BW | Video Filtering | Measurement distance |
| Below 30 MHz | Peak or Q.P. | 9 kHz | 100 kHz | - | 3 m |
| 30 MHz ~ 1 000 MHz | Peak or Q.P. | 100 kHz | 300 kHz | - | 3 m |

5.6.6.1 Test Data below 30 MHz



| Frequency (MHz) | Receiver Reading (dBuV) | Detector Mode | Pol. | Ant. Factor (dB/m) | Corr. Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Degree) |
|---|-------------------------|---------------|------|--------------------|-------------------|-----------------|----------------|-------------|-------------|------------------|
| * Spurious emissions that 20 dB below the limits didn't be recorded | | | | | | | | | | |
| | | | | | | | | | | |

5.6.6.2 Test Data from 30 MHz to 1 GHz



| Frequency (MHz) | Pol. | Detect Mode | Reading (dB μ V) | Factor* (dB) | Loss* (dB) | Gain (dB) | Result (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|------|-------------|----------------------|--------------|------------|-----------|-----------------------|----------------------|-------------|
| 135.730 | V | Peak | 34.7 | 7.8 | 8.3 | 32.7 | 18.1 | 43.5 | 25.4 |
| 190.050 | H | Peak | 39.7 | 10.3 | 8.8 | 32.7 | 26.1 | 43.5 | 17.4 |
| 217.210 | V | Peak | 34.2 | 11.9 | 9.0 | 32.6 | 22.5 | 46.0 | 23.5 |
| 244.370 | V | Peak | 36.4 | 12.7 | 9.2 | 32.6 | 25.7 | 46.0 | 20.3 |
| 324.880 | H | Peak | 32.8 | 14.0 | 9.8 | 32.7 | 23.9 | 46.0 | 22.1 |
| 401.510 | V | Peak | 33.1 | 16.0 | 10.2 | 32.8 | 26.5 | 46.0 | 19.5 |
| 637.217 | H | Peak | 31.2 | 19.8 | 11.5 | 33.1 | 29.4 | 46.0 | 16.6 |

Note: "H" means Horizontal polarity, "V" means Vertical polarity.

GFSK lowest channel is worst case configuration.

Factor = AF + CL - AG (AF : Antenna factor, CL : Cable loss, AG: Pre-Amp gain)


Result = Reading + Corr. Factor

Margin = Limit (dB μ V/m) - Result (dB μ V/m)

Quasi-peak measurements are omitted because the peak data meets the limit.

5.6.6.3 Test Data above 1 GHz

5.6.6.3.1 Duty Cycle



Tabulated Test Data


| Operating Mode | On Time (μs) | On + Off Time (μs) | Duty Cycle (%) | Duty Factor (dB) |
|----------------|--------------|--------------------|----------------|------------------|
| Bluetooth LE | 423.0 | 626.0 | 67.57 | 1.70 |

| Detector Mode | Resolution BW | Video BW | Sweep Time | Measurement distance |
|---------------|---------------|----------|------------|----------------------|
| PEAK | 1 MHz | 3 MHz | Auto | 3 m |
| RMS | 1 MHz | 3 MHz | Auto | 3 m |


5.6.6.3.2 Test Data for Band edge (Restricted band)

Graphical Test Data – Low Channel (Peak)

Horizontal



Vertical




Tabulated Test Data – Low Channel

| Freq. (MHz) | Detector Mode | Pol. | Receiver Reading (dBuV/m) | Duty Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Deg) |
|-------------|---------------|------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|
| 2 376.2 | Peak | H | 49.79 | - | 49.79 | 74.00 | 24.21 | 190 | 180 |
| 2 375.8 | Peak | V | 56.14 | - | 56.14 | 74.00 | 17.86 | 150 | 180 |


NOTE: "H" means Horizontal polarity, "V" means Vertical polarity.

Graphical Test Data – Low Channel (Average)

Horizontal



Vertical



Tabulated Test Data – Low Channel


| Freq. (MHz) | Detector Mode | Pol. | Receiver Reading (dBuV/m) | Duty Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Deg) |
|-------------|---------------|------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|
| 2 376.2 | Average | H | 37.28 | 1.70 | 38.98 | 54.00 | 15.02 | 190 | 180 |
| 2 376.1 | Average | V | 43.43 | 1.70 | 45.13 | 54.00 | 8.87 | 150 | 180 |

NOTE: "H" means Horizontal polarity, "V" means Vertical polarity.


Result = Receiver Reading + Duty Factor

Graphical Test Data – High Channel (Peak)

Horizontal



Vertical




Tabulated Test Data – High Channel

| Freq. (MHz) | Detector Mode | Pol. | Receiver Reading (dBuV/m) | Duty Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Deg) |
|-------------|---------------|------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|
| 2 495.4 | Peak | H | 46.28 | - | 46.28 | 74.00 | 27.72 | 150 | 175 |
| 2 495.2 | Peak | V | 51.31 | - | 51.31 | 74.00 | 22.69 | 170 | 185 |


NOTE: "H" means Horizontal polarity, "V" means Vertical polarity.

Graphical Test Data – Low Channel (Average)

Horizontal



Vertical



Tabulated Test Data – High Channel


| Freq. (MHz) | Detector Mode | Pol. | Receiver Reading (dBuV/m) | Duty Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Deg) |
|-------------|---------------|------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|
| 2 495.5 | Average | H | 44.75 | 1.70 | 46.45 | 54.00 | 7.55 | 180 | 170 |
| 2 495.2 | Average | V | 50.02 | 1.70 | 51.72 | 54.00 | 2.28 | 160 | 120 |

NOTE: "H" means Horizontal polarity, "V" means Vertical polarity.

Result = Receiver Reading + Duty Factor

5.6.6.4 Test Data for Harmonic & Spurious emission (1 GHz to 18 GHz)

5.6.6.4.1 Operating mode: Bluetooth LE



| Freq. (MHz) | Detector Mode | Pol. | Ant. Factor (dB/m) | Corr. Factor (dB) | Receiver Reading (dBuV/m) | Duty Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Deg) |
|-------------|---------------|------|--------------------|-------------------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|
|-------------|---------------|------|--------------------|-------------------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|

Low / Middle / High Channel

| | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|

* Spurious emissions that 20 dB below the limits didn't be recorded

| | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|

NOTE: Peak results are met average limit, so average measurement was not performed.

Note. "H" means Horizontal polarity, "V" means Vertical polarity.


GFSK lowest channel is worst case configuration.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit - Result

5.6.6.5 Test Data for Harmonic & Spurious emission (18 GHz to 25 GHz)



| Freq. (MHz) | Detector Mode | Pol. | Ant. Factor (dB/m) | Corr. Factor (dB) | Receiver Reading (dBuV/m) | Duty Factor (dB) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Height (cm) | Azimuth (Deg) |
|---|---------------|------|--------------------|-------------------|---------------------------|------------------|-----------------|----------------|-------------|-------------|---------------|
| Low / Middle / High Channel | | | | | | | | | | | |
| | | | | | | | | | | | |
| * Spurious emissions that 20 dB below the limits didn't be recorded | | | | | | | | | | | |
| | | | | | | | | | | | |

NOTE: Peak results are met average limit, so average measurement was not performed.

Emission was scanned up to 25 GHz; No emissions were detected above the noise floor which was at least 20 dB below the specification limit

Note. "H" means Horizontal polarity, "V" means Vertical polarity.

Corr. Factor (dB) = Pre-amplifier gain - Cable Loss

Result = Receiver Reading + Antenna Factor - Corr. Factor + Duty factor

Margin = Limit - Result

Appendix I – Test Instrumentation

| Description | Model No. | Serial No. | Manufacturer. | Due for Cal Date |
|----------------------------|--------------|---------------------------|-------------------|------------------|
| Signal & Spectrum Analyzer | FSW 43 | 100578 | Rohde & Schwarz | 2019-04-26 |
| Attenuator | 56-10 | 58769 | WEINSCHTEL | 2019-01-22 |
| Test Receiver | ESU 26 | 100303 | Rohde & Schwarz | 2019-01-18 |
| Loop Antenna | HFH2-Z2 | 100341 | Rohde & Schwarz | 2019-04-21 |
| TRILOG Broadband Antenna | VULB9163 | 9163.799 | Schwarzbeck | 2019-09-14 |
| Notch Filter | BRM50702 | G318 | MICRO-TRONICS | 2018-11-08 |
| Horn Antenna | HF 907 | 102426 | Rohde & Schwarz | 2018-11-25 |
| Horn Antenna | BBHA 9170 | BBHA 9170 #783 | Schwarzbeck | 2018-11-28 |
| Attenuator | 6dB | 272.4110.50 | Rohde & Schwarz | 2019-01-18 |
| Pre-Amplifier | 310N | 344015 | Sonoma Instrument | 2019-01-18 |
| Pre-Amplifier | SCU 18D | 19006450 | Rohde & Schwarz | 2019-04-24 |
| Pre-Amplifier | CBL18265035 | 28706 | CERNEX | 2019-03-29 |
| Turn Table | DT3000-3t | 1310814 | INNCO SYSTEM | N/A |
| Antenna Master | MA4000-EP | 4600814 | INNCO SYSTEM | N/A |
| Antenna Master | MA4000-XP-ET | - | INNCO SYSTEM | N/A |
| Camera Controller | HDCon4102 | 6531445048 | PONTIS | N/A |
| CO3000 Controller | Co3000-4Port | CO3000/806/ 34130814/L | INNCO SYSTEM | N/A |
| CO3000 Controller | Co3000-4Port | CO3000/807/ 34130814/L | INNCO SYSTEM | N/A |

The measuring equipment utilized to perform the tests documented in this test report has been calibrated in accordance with manufacturer's recommendations, and is traceable to recognized national standards.