

Maximum Permissible Exposure Evaluation

FCC ID: 2APRB-BWNIP-2TA-BS4

1. Client Information

Applicant	:	Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd
Address	:	No.2 Plant ,West of Shanxi country , Dashi street, Panyu District, Guangzhou City, China
Manufacturer	:	Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd
Address	:	No.2 Plant ,West of Shanxi country , Dashi street, Panyu District, Guangzhou City, China

2. General Description of EUT

EUT Name	:	Smart IP Camera with Battery
Models No.	:	BWNIP-2TA-BS-V4, BWNIP-2TA-BS-V4-CN4, BWNIP-2TA-BS-V4-CN, WM-8BBTWN1-32B, CL-BWNP2-32B1, WM-2BWNP1-32B, 1PK-BWNIP2TABS-V4-WA2-CN4, 3PK-BWNIP2TABS-V4-WA2-CN4
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name.
Product Description	:	Operation Frequency: 802.11b/g/n(HT20): 2412MHz~2462MHz
		Number of Channel: 802.11b/g/n(HT20):11 channels
		RF Output Power: 802.11HT20: 13.840dBm(MAX)
		Antenna Gain: 3dBi FPC Antenna1# 3dBi FPC Antenna2#
		Note: The EUT have two type antennas (1# and 2# Just Silk screen difference)
Power Rating	:	Input: DC 5V Output: DC 3.7V by 5200 mAh Rechargeable Li-ion battery
Software Version	:	BWNIP-2TA-BS-V4_1.0.4
Hardware Version	:	AK3918EV330L_V200
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark	:	the evaluation report used the EUT(20211124-05-02#).

MPE Calculations for WIFI

1. Antenna Gain:

Dipole Antenna:3dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

2.4G WiFi

Mode	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]	Limit of Power Density (mW/ cm ²) (S)
802.11B	13.488	13±1	14	3	20	0.00997	1
802.11G	13.840	13±1	14	3	20	0.00997	1
802.11N(HT20)	13.840	13±1	14	3	20	0.00997	1

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 2.4WIFI:2412~2462 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.00997\text{mW} / \text{cm}^2 < \text{limit } 1\text{mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

6. Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF REPORT-----