

**TEST REPORT**

|                                 |   |
|---------------------------------|---|
| <b>Applicant:</b>               | Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd   |
| <b>Address of Applicant:</b>    | No.2 Plant ,West of Shanxi country , Dashi street, Panyu District, Guangzhou City, China                                      |
| <b>Manufacturer:</b>            | Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd   |
| <b>Address of Manufacturer:</b> | No.2 Plant ,West of Shanxi country , Dashi street, Panyu District, Guangzhou City, China                                      |
| <b>Factory:</b>                 | Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd   |
| <b>Address of Factory:</b>      | No.2 Plant ,West of Shanxi country , Dashi street, Panyu District, Guangzhou City, China                                      |
| <b>Product name:</b>            | Fisheye Camera  |
| <b>Model(s):</b>                | WCM-2FEIN-JUN   |
| <b>Rating(s):</b>               | Input: DC5V, 1A (For main)<br>Input: 100-240Vac, 50/60Hz, 0.25A (For AC/AD ADAPTER)<br>Output: 5Vdc, 1A ((For AC/AD ADAPTER)) |
| <b>Trademark:</b>               | NIGHT OWL   |
| <b>Standards:</b>               | 47 CFR PART 15 Subpart C: 2019 section 15.247   |
| <b>FCC ID:</b>                  | 2APRB-WCM-2FEIN-JUN   |
| <b>Data of Receipt:</b>         | 2019-07-12  |
| <b>Date of Test:</b>            | 2019-07-12~2019-07-17   |
| <b>Date of Issue:</b>           | 2019-07-18  |
| <b>Test Result</b>              | <b>Pass*</b>  |

\* In the configuration tested, the test item complied with the standards specified above.

**Authorized for issue by:**

**Test by:**

**Reviewed by:**

Jul.18, 2019 Eleven Liang  
Project Engineer



Jul.18, 2019 Pauler Li  
Project Manager



Pauler Li  
Handwritten signature of Pauler Li

Date Name/Position Signature

Date Name/Position Signature

**Testing Laboratory information:**

Testing Laboratory Name .....: ITL Co., Ltd  
Address : No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan,  
Guangdong, 523757 P.R.C.  
Testing location : Same as above  
Tel : 0086-769-39001678  
Fax : 0086-20-62824387  
E-mail : itl@i-testlab.com

**Possible test case verdicts:**

- test case does not apply to the test object . : N/A
- test object does meet the requirement ..... : P (Pass)
- test object does not meet the requirement . : F (Fail)

**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report would be invalid test report without all the signatures of testing technician and approver.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**General product information:**

/

## 1 Test Summary

| Test   | Test Requirement  | Test method   | Result |
|--|---|---|--------|
| Antenna Requirement                              | FCC PART 15 C<br>section 15.247 (c) and<br>Section 15.203 | FCC PART 15 C<br>section 15.247 (c) and<br>Section 15.203 | PASS   |
| Occupied Bandwidth                               | FCC PART 15 C<br>section 15.247 (a)(2)                    | ANSI C63.10:2013  | PASS   |
| Maximum Peak Output Power                        | FCC PART 15 C<br>section 15.247(b)(3)                     | ANSI C63.10: 2013   | PASS   |
| Peak Power Spectral Density                      | FCC PART 15 C<br>section 15.247(e)                        | ANSI C63.10:2013  | PASS   |
| Conducted Spurious Emission<br>(30MHz to 25GHz)  | FCC PART 15 C<br>section 15.209<br>&15.247(d)             | ANSI C63.10:2013  | PASS   |
| Radiated Spurious Emission<br>(30 MHz to 25 GHz) | FCC PART 15 C<br>section 15.209<br>&15.247(d)             | ANSI C63.10:2013  | PASS   |
| Band Edges Measurement                           | FCC PART 15 C<br>section 15.209<br>&15.247(d)             | ANSI C63.10:2013  | PASS   |
| Conducted Emissions at Mains<br>Terminals        | FCC PART 15 C<br>section 15.207                           | ANSI C63.10:2013  | PASS   |

## 2 Contents

|   | Page      |
|---|-----------|
| <b>TEST REPORT</b> .....  | <b>1</b>  |
| <b>1 TEST SUMMARY</b> .....   | <b>3</b>  |
| <b>2 CONTENTS</b> .....   | <b>4</b>  |
| <b>3 GENERAL INFORMATION</b> .....  | <b>5</b>  |
| <b>3.1 CLIENT INFORMATION</b> .....                                       | <b>5</b>  |
| <b>3.2 GENERAL DESCRIPTION OF E.U.T.</b> .....                            | <b>5</b>  |
| <b>3.3 DETAILS OF E.U.T.</b> .....  | <b>5</b>  |
| <b>3.4 DESCRIPTION OF SUPPORT UNITS</b> .....                             | <b>6</b>  |
| <b>3.5 TEST LOCATION</b> .....  | <b>6</b>  |
| <b>3.6 DEVIATION FROM STANDARDS</b> .....                                 | <b>6</b>  |
| <b>3.7 ABNORMALITIES FROM STANDARD CONDITIONS</b> .....                   | <b>6</b>  |
| <b>3.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER</b> .....              | <b>6</b>  |
| <b>3.9 TEST FACILITY</b> .....  | <b>6</b>  |
| <b>3.10 MEASUREMENT UNCERTAINTY</b> .....                                 | <b>7</b>  |
| <b>4 INSTRUMENTS USED DURING TEST</b> .....                               | <b>8</b>  |
| <b>5 TEST RESULTS</b> .....   | <b>9</b>  |
| <b>5.1 E.U.T. TEST CONDITIONS</b> .....                                   | <b>9</b>  |
| <b>5.2 ANTENNA REQUIREMENT</b> .....                                      | <b>11</b> |
| <b>5.3 OCCUPIED BANDWIDTH</b> .....                                       | <b>12</b> |
| <b>5.4 MAXIMUM PEAK OUTPUT POWER</b> .....                                | <b>20</b> |
| <b>5.5 PEAK POWER SPECTRAL DENSITY</b> .....                              | <b>28</b> |
| <b>5.6 CONDUCTED SPURIOUS EMISSIONS</b> .....                             | <b>37</b> |
| <b>5.7 RADIATED SPURIOUS EMISSIONS</b> .....                              | <b>44</b> |
| <b>5.7.1 Harmonic and other spurious emissions</b> .....                  | <b>47</b> |
| <b>5.8 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS</b> .....    | <b>60</b> |
| <b>5.9 BAND EDGES REQUIREMENT</b> .....                                   | <b>64</b> |
| <b>5.10 CONDUCTED EMISSIONS AT MAINS TERMINALS 150 KHZ TO 30MHZ</b> ..... | <b>70</b> |
| <b>5.10.1 Measurement Data</b> .....                                      | <b>72</b> |

### 3 General Information

#### 3.1 Client Information

Applicant: Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd  
 Address of Applicant: No.2 Plant ,West of Shanxi country , Dashi street, Panyu District, Guangzhou City, China

#### 3.2 General Description of E.U.T.

Name: Fisheye Camera  
 Model No.: WCM-2FEIN-JUN  
 Trade Mark: NIGHT OWL  
 Operating Frequency: 802.11 b/g/n(HT20): 2412MHz-2462MHz; 802.11 n(HT40): 2422MHz-2452MHz  
 802.11b, 802.11g, 802.11n(20MHz): 11

| Working Frequency of Each Channel: |           |         |           |
|------------------------------------|-----------|---------|-----------|
| channel                            | Frequency | channel | Frequency |
| 1                                  | 2412      | 8       | 2447      |
| 2                                  | 2417      | 9       | 2452      |
| 3                                  | 2422      | 10      | 2457      |
| 4                                  | 2427      | 11      | 2462      |
| 5                                  | 2432      |         |           |
| 6                                  | 2437      |         |           |
| 7                                  | 2442      |         |           |

Channels:

802.11n(40MHz): 7

| Working Frequency of Each Channel: |           |         |           |
|------------------------------------|-----------|---------|-----------|
| channel                            | Frequency | channel | Frequency |
| 3                                  | 2422      |         |           |
| 4                                  | 2427      |         |           |
| 5                                  | 2432      |         |           |
| 6                                  | 2437      |         |           |
| 7                                  | 2442      |         |           |
| 8                                  | 2447      |         |           |
| 9                                  | 2452      |         |           |

Type of Modulation CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM

Antenna Type: FPC antenna with 3dBi peak Gain

Function: Fisheye Camera

#### 3.3 Details of E.U.T.

EUT Power Supply: 120Vac, 60Hz

Test mode:

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List |                |                            |
|----------------|----------------|----------------------------|
| Test Mode      | Description    | Remark                     |
| TM1            | 802.11b        | 2412MHz, 2437MHz, 2462MHz, |
| TM2            | 802.11g        | 2412MHz, 2437MHz, 2462MHz, |
| TM3            | 802.11n(20MHz) | 2412MHz, 2437MHz, 2462MHz, |
| TM4            | 802.11n(40MHz) | 2422MHz, 2437MHz, 2452MHz, |

Power cord: /

### 3.4 Description of Support Units

The EUT has been tested as an independent unit for fixed frequency by testing lab.

### 3.5 Test Location

All tests were performed at:

ITL Co., Ltd

No. 8 Jinqianling Street 5, Huangjiang Town, Dongguan, Guangdong, 523757 P.R.C.

0086-769-39001678

itl@i-testlab.com

No tests were sub-contracted.

### 3.6 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

### 3.7 Abnormalities from Standard Conditions

None.

### 3.8 Other Information Requested by the Customer

None.

### 3.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS Lab code:L9342
- FCC Designation No.:CN5035
- IC Registration NO.: 12593A
- NVLAP LAB CODE: 600199-0

### 3.10 Measurement Uncertainty

The below measurement uncertainties given below are based on a 95% confidence level (base on a coverage factor (k=2).)

| Parameter                     | Uncertainty |
|-------------------------------|-------------|
| Radio frequency               | 2.25%       |
| total RF power, conducted     | ±1.34 dB    |
| RF power density , conducted  | ±1.49 dB    |
| All emissions, radiated       | ±2.72 dB    |
| Temperature                   | ±5.02 dB    |
| Humidity                      | ±0.8°C      |
| DC and low frequency voltages | ±1.5 %      |

#### 4 Instruments Used during Test

| No.     | Test Equipment                       | Manufacturer  | Model             | Serial No.         | Last Cal.  | Cal. Due   |
|---------|--------------------------------------|---------------|-------------------|--------------------|------------|------------|
| ITL-114 | Spectrum Analyzer                    | Agilent       | N9010A            | MY51250936         | 2019/01/28 | 2020/01/27 |
| ITL-154 | EMI test receiver<br>9kHz to 26.5GHz | R&S           | ESR26             | 101257             | 2019/01/29 | 2020/01/28 |
| ITL-116 | Pre Amplifier                        | HP            | 8447F             | 3113A05905         | 2019/01/28 | 2020/01/27 |
| ITL-117 | Wideband<br>Amplifier Super<br>Ultra | Mini-circuits | ZVA-183-<br>S+    | 469101134          | 2019/01/28 | 2020/01/27 |
| ITL-164 | Trilog-Broadband<br>Antenna          | Schwarzbeck   | VULB<br>9168      | 9168-0844          | 2017/11/16 | 2020/11/16 |
| ITL-110 | Horn Antenna                         | A-INFOMW      | JTXLB-<br>10180-N | J2031090612<br>133 | 2019/01/28 | 2020/01/27 |
| ITL-102 | EMI Test receiver                    | R&S           | ESCI              | 100910             | 2019/06/19 | 2020/06/18 |
| ITL-103 | Two-line v-<br>network               | R&S           | ENV216            | 100120             | 2019/06/19 | 2020/06/18 |
| ITL-115 | 50Ω Coaxial<br>Cable                 | Mini-circuits | CBL               | C001               | 2019/06/19 | 2020/06/18 |
| ITL-100 | Semi-Anechoic<br>chamber             | ETS•Lindgren  | FACT3<br>2.0      | CT09015            | 2018/12/29 | 2021/12/28 |
| ITL-101 | Shielded Room                        | ETS•Lindgren  | 8*4*3             | CT09010            | 2018/01/27 | 2021/01/26 |
| ITL-165 | Power Meter                          | R&S           | NRVS              | 838246/026         | 2018/09/28 | 2019/09/27 |
| ITL-163 | Active Loop<br>Antenna               | Schwarzbeck   | FMZB<br>1519B     | 1519B-062          | 2017/11/16 | 2020/11/16 |



## 5 Test Results

### 5.1 E.U.T. test conditions

**Test Voltage:** 120Vac, 60Hz

**Temperature:** 23.2 -25.0 °C

**Humidity:** 38-50 % RH

**Atmospheric Pressure:** 1000 -1010 mbar

**Requirements:** **15.31(e):** For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

**15.32:** Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.

**Test frequencies and frequency range:**

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

**Number of fundamental frequencies to be tested in EUT transmit band**

| Frequency range in which | Number of | Location in frequency range                 |
|--------------------------|-----------|---|
| 1 MHz or less            | 1         | Middle                                      |
| 1 MHz to 10 MHz          | 2         | 1 near top and 1 near bottom                |
| More than 10 MHz         | 3         | 1 near top, 1 near middle and 1 near bottom |

**Frequency range of radiated emission measurements**

| Lowest frequency generated  | Upper frequency range of measurement                         |
|-----------------------------|--|
| 9 kHz to below 10 GHz       | 10th harmonic of highest fundamental frequency or to 40 GHz, |
| At or above 10 GHz to below | 5th harmonic of highest fundamental frequency or to 100 GHz, |
| At or above 30 GHz          | 5th harmonic of highest fundamental frequency or to 200 GHz, |

EUT channels and frequencies list:

| Working Frequency of Each Channel: |           |         |           |
|------------------------------------|-----------|---------|-----------|
| channel                            | Frequency | channel | Frequency |
| 1                                  | 2412      | 8       | 2447      |
| 2                                  | 2417      | 9       | 2452      |
| 3                                  | 2422      | 10      | 2457      |
| 4                                  | 2427      | 11      | 2462      |
| 5                                  | 2432      |         |           |
| 6                                  | 2437      |         |           |
| 7                                  | 2442      |         |           |

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List |                |                            |
|----------------|----------------|----------------------------|
| Test Mode      | Description    | Remark                     |
| TM1            | 802.11b        | 2412MHz, 2437MHz, 2462MHz, |
| TM2            | 802.11g        | 2412MHz, 2437MHz, 2462MHz, |
| TM3            | 802.11n(20MHz) | 2412MHz, 2437MHz, 2462MHz, |
| TM4            | 802.11n(40MHz) | 2422MHz, 2437MHz, 2452MHz, |

## 5.2 Antenna requirement

### Standard requirement

15.203 requirement:

For intentional device. According to 15.203. An intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

### EUT Antenna

The antenna is a FPC antenna and no consideration of replacement. The best case gain of the antenna is 3dBi.

**Test result: The unit does meet the FCC requirements.**


### 5.3 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.247  
(a)(2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =0.5dB) from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW=100kHz. VBW = 300kHz, Sweep = auto; Detector Function = Peak. Trace = Max Hold, Set span to encompass the entire emission bandwidth of the signal.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worst case.

**Test result (6 dB bandwidth)**

| Test Mode     | Test Frequency (MHz) | 6dB bandwidth (MHz) | Limit (kHz) | Result |
|---------------|----------------------|---------------------|-------------|--------|
| 802.11b       | 2412                 | 8.554               | ≥500        | Pass   |
|               | 2437                 | 8.549               | ≥500        | Pass   |
|               | 2462                 | 9.058               | ≥500        | Pass   |
| 802.11g       | 2412                 | 16.46               | ≥500        | Pass   |
|               | 2437                 | 16.38               | ≥500        | Pass   |
|               | 2462                 | 16.39               | ≥500        | Pass   |
| 802.11n(HT20) | 2412                 | 17.56               | ≥500        | Pass   |
|               | 2437                 | 17.58               | ≥500        | Pass   |
|               | 2462                 | 17.58               | ≥500        | Pass   |
| 802.11n(HT40) | 2422                 | 36.37               | ≥500        | Pass   |
|               | 2437                 | 36.28               | ≥500        | Pass   |
|               | 2452                 | 36.32               | ≥500        | Pass   |


**The unit does meet the FCC requirements.**

6dB bandwidth:


Result plot as follows:

802.11b


Channel 1:2.412GHz:



Channel 6:2.437GHz:




Channel 11:2.462GHz:




802.11g


Channel 1:2.412GHz:



Channel 6:2.437GHz:




Channel 11:2.462GHz:






802.11n(HT20)


Channel 1:2.412GHz:



Channel 6:2.437GHz:




Channel 11:2.462GHz:




802.11n(HT40)


Channel 3:2.422GHz:



Channel 6:2.437GHz:



Channel 9:2.452GHz:



## 5.4 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247


(b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss = 0.5dB) from the antenna port to the spectrum.
2. Set span to at least 1.5 times the OBW.
3. Set RBW = 1 % to 5% of OBW, not to exceed 1 MHz
4. Set VBW  $\geq 3 \times$  RBW.
5. Number of points in sweep  $\geq [2 \times \text{span} / \text{RBW}]$ . (This gives bin-to-bin spacing  $\leq \text{RBW} / 2$ , so that narrowband signals are not lost between frequency bins.)
6. Sweep time = auto.
7. If transmit duty cycle  $< 98\%$ , use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle  $\geq 98\%$ , and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."
8. Trace average 100 traces in power averaging mode.

9. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
10. Repeat until all the test status is investigated.
11. Report the worst case.

**Test Data:**

| Test mode     | Test Channel | Test Result (dBm) | Limit (dBm) |
|---------------|--------------|-------------------|-------------|
| 802.11b       | 2412         | 8.08              | 30          |
|               | 2437         | 8.89              | 30          |
|               | 2462         | 9.01              | 30          |
| 802.11g       | 2412         | 9.12              | 30          |
|               | 2437         | 9.27              | 30          |
|               | 2462         | 9.41              | 30          |
| 802.11n(HT20) | 2412         | 7.23              | 30          |
|               | 2437         | 8.92              | 30          |
|               | 2462         | 9.07              | 30          |
| 802.11n(HT40) | 2422         | 6.47              | 30          |
|               | 2437         | 7.95              | 30          |
|               | 2452         | 8.13              | 30          |


**Remark: 1) Cable loss=0.5dB**

**The unit does meet the FCC requirements.**

Result plot as follows:

802.11b


Channel 1:2.412GHz:



Channel 6:2.437GHz:



Channel 11:2.462GHz:




802.11g

Channel 1:2.412GHz:



### Channel 6:2.437GHz:



### Channel 11:2.462GHz:





802.11n(HT20)


Channel 1:2.412GHz:



Channel 6:2.437GHz:



Channel 11:2.462GHz:



802.11n(HT40)

Channel 3:2.422GHz:



Channel 6:2.437GHz:




Channel 9:2.452GHz:



## 5.5 Peak Power Spectral Density

|                     |  |
|---------------------|--|
| Test Requirement:   | FCC Part 15 C section 15.247<br>(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density. |
| Test Method:        | ANSI C63.10:2013   |
| Test Status:        | Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channel and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.  |
| Test Configuration: |  |



## Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =0.5 dB) from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer:
  - a) Set instrument center frequency to DTS channel center frequency.
  - b) Set the instrument span to 1.5 times the OBW.
  - c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
  - d) Set the VBW  $\geq [3 \times \text{RBW}]$ .
  - e) Detector = power average (rms).
  - f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span} / \text{RBW}$ .
  - g) Manually set the sweep time to:  $\geq [10 \times (\text{number of measurement points in sweep}) \times (\text{transmission symbol period})]$ , but no less than the auto sweep time.

NOTE—The transmission symbol period (in seconds) is the reciprocal of the symbol rate (in baud or symbols per second). Note that each symbol can represent one or several data bits, and thus, the symbol rate should not be confused with the gross bit rate (expressed in bits/second). In no case should the sweep time be set less than the auto sweep time.

  - h) Perform the measurement over a single sweep.
  - i) Use the peak marker function to determine the maximum amplitude level.
  - j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).
3. Repeat until all the test status is investigated.
4. Report the worst case.

Test result:

| Test mode     | Test Channel | Test Result (dBm/3kHz) | Limit (dBm/3kHz) |
|---------------|--------------|------------------------|------------------|
| 802.11b       | 2412         | -15.76                 | 8                |
|               | 2437         | -15.16                 |                  |
|               | 2462         | -14.58                 |                  |
| 802.11g       | 2412         | -20.86                 |                  |
|               | 2437         | -20.30                 |                  |
|               | 2462         | -20.09                 |                  |
| 802.11n(HT20) | 2412         | -20.65                 |                  |
|               | 2437         | -20.05                 |                  |
|               | 2462         | -20.01                 |                  |
| 802.11n(HT40) | 2422         | -23.94                 |                  |
|               | 2437         | -23.60                 |                  |
|               | 2452         | -23.23                 |                  |

Remark: 1) Output Peak Power=Reading Peak Power+Cable loss  
2) Cable loss=0.5dB

The unit does meet the FCC requirements.


Result plot as follows:

802.11b


Channel 1: 2.412 GHz:



Channel 6: 2.437GHz:




Channel 11:2.462 GHz:




802.11g

Channel 1:2.412 GHz:






Channel 6: 2.437GHz:




Channel 11: 2.462 GHz:




802.11n (HT20)


Channel 1: 2.412 GHz:



Channel 6: 2.437GHz:




Channel 11:2.462 GHz:




802.11n (HT40)


Channel 3:2.422 GHz:



Channel 6:2.437GHz:



Channel 6:2.452 GHz:



## 5.6 Conducted Spurious Emissions


Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channel and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer: RBW=100 KHz, VBW = 300KHz. Sweep = auto; Detector Function = Peak. Trace = Max Hold, Scan up through 10th harmonic.
3. Measure the Conducted Spurious Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worst case.

Result plot as follows:

802.11b

Channel 1: 2.412 GHz



Channel 6: 2.437GHz:



Channel 11: 2.462 GHz



802.11g

Channel 1: 2.412 GHz



Channel 6: 2.437GHz:



Channel 11: 2.462 GHz





802.11n(HT20)

Channel 1: 2.412 GHz



Channel 6: 2.437GHz:



### Channel 11: 2.462 GHz



### 802.11n(HT40)

### Channel 3: 2.422 GHz



Channel 6: 2.437GHz:



Channel 9: 2.452 GHz



The unit does meet the FCC requirements.

## 5.7 Radiated Spurious Emissions

Test Requirement: FCC Part 15 C section 15.247  
(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Method: ANSI C63.10:2013

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Detector: For PK value:

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz, 9kHz for  $< 30$  MHz

VBW = 10 Hz

Sweep = auto


Detector function = peak

Trace = max hold


15.209 Limit: 40.0 dB $\mu$ V/m between 30 MHz & 88 MHz  
43.5 dB $\mu$ V/m between 88 MHz & 216 MHz  
46.0 dB $\mu$ V/m between 216 MHz & 960 MHz  
54.0 dB $\mu$ V/m above 960 MHz

### Test Configuration:


- 1) 9kHz to 30MHz emissions:



- 2) 30 MHz to 1 GHz emissions:



## 3) 1 GHz to 40 GHz emissions:



**Test Procedure: (1)** The receiver was scanned from 0.009MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. After pre-test, it was found that the worst radiation emission was get at the X position. So the data shown was the X position only. The worst case emissions were reported.

**(2)** Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

**(3)** Pre-test under all modes below 1GHz, choose the worst case mode record On the report.

## 5.7.1 Harmonic and other spurious emissions

### Worst case mode 802.11b

Test at Channel 1 (2.412 GHz) in transmitting status

### 9kHz~30MHz Test result


The Low frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

### 30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement


| No. | Freq<br>MHz | Read<br>Level<br>dBuV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBuV/m | Limit<br>Line<br>dBuV/m | Over<br>Limit<br>dB | Pol/Phase  | Remark |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|------------|--------|
| 1   | 142.520     | 31.75                 | 12.35                   | 1.42                | 28.30                  | 17.22           | 43.50                   | -26.28              | HORIZONTAL | QP     |
| 2   | 199.750     | 36.39                 | 9.42                    | 1.70                | 27.89                  | 19.62           | 43.50                   | -23.88              | HORIZONTAL | QP     |
| 3   | 335.550     | 46.18                 | 13.75                   | 2.24                | 27.41                  | 34.76           | 46.00                   | -11.24              | HORIZONTAL | QP     |
| 4   | 431.580     | 46.51                 | 15.93                   | 2.57                | 28.23                  | 36.78           | 46.00                   | -9.22               | HORIZONTAL | QP     |
| 5   | 480.080     | 50.47                 | 16.90                   | 2.72                | 28.48                  | 41.61           | 46.00                   | -4.39               | HORIZONTAL | QP     |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Vertical:**

Peak scan

Level (dBuV/m)



Quasi-peak measurement

| No. | Freq<br>MHz | Read<br>Level<br>dBuV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBuV/m | Limit<br>Line<br>dBuV/m | Over<br>Limit<br>dB | Pol/Phase | Remark |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|-----------|--------|
| 1   | 94.020      | 39.70                 | 8.62                    | 1.13                | 28.57                  | 20.88           | 43.50                   | -22.62              | VERTICAL  | QP     |
| 2   | 200.720     | 38.72                 | 9.43                    | 1.71                | 27.87                  | 21.99           | 43.50                   | -21.51              | VERTICAL  | QP     |
| 3   | 345.250     | 43.68                 | 13.99                   | 2.27                | 27.34                  | 32.60           | 46.00                   | -13.40              | VERTICAL  | QP     |
| 4   | 480.080     | 48.71                 | 16.90                   | 2.72                | 28.48                  | 39.85           | 46.00                   | -6.15               | VERTICAL  | QP     |
| 5   | 514.030     | 44.47                 | 17.62                   | 2.82                | 28.69                  | 36.22           | 46.00                   | -9.78               | VERTICAL  | QP     |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**




### Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement


| No. | Freq<br>MHz | Read<br>Level<br>dBuV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBuV/m | Limit<br>Line<br>dBuV/m | Over<br>Limit<br>dB | Pol/Phase  | Remark  |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|------------|---------|
| 1   | 4825.000    | 37.92                 | 33.36                   | 9.60                | 27.62                  | 53.26           | 74.00                   | -20.74              | HORIZONTAL | Peak    |
| 2   | 4825.000    | 25.24                 | 33.36                   | 9.60                | 27.62                  | 40.58           | 54.00                   | -13.42              | HORIZONTAL | Average |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Vertical:**

Peak scan

Level (dBuV/m)



Quasi-peak measurement

| No. | Freq<br>MHz | Read<br>Level<br>dBuV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBuV/m | Limit<br>Line<br>dBuV/m | Over<br>Limit<br>dB | Pol/Phase | Remark  |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|-----------|---------|
| 1   | 4825.000    | 37.12                 | 33.36                   | 9.60                | 27.62                  | 52.46           | 74.00                   | -21.54              | VERTICAL  | Peak    |
| 2   | 4825.000    | 25.83                 | 33.36                   | 9.60                | 27.62                  | 41.17           | 54.00                   | -12.83              | VERTICAL  | Average |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Test at Channel 6 (2.437 GHz) in transmitting status**

**9 kHz~30MHz Test result**


The Low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

**30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement**

**Horizontal:**

Peak scan

Level (dB $\mu$ V/m)



Quasi-peak measurement


| No. | Freq<br>MHz | Read<br>Level<br>dB $\mu$ V | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dB $\mu$ V/m | Limit<br>Line<br>dB $\mu$ V/m | Over<br>Limit<br>dB | Pol/Phase  | Remark |
|-----|-------------|-----------------------------|-------------------------|---------------------|------------------------|-----------------------|-------------------------------|---------------------|------------|--------|
| 1   | 94.990      | 34.83                       | 8.70                    | 1.14                | 28.60                  | 16.07                 | 43.50                         | -27.43              | HORIZONTAL | QP     |
| 2   | 198.780     | 35.59                       | 9.48                    | 1.70                | 27.86                  | 18.91                 | 43.50                         | -24.59              | HORIZONTAL | QP     |
| 3   | 341.370     | 38.58                       | 13.89                   | 2.25                | 27.37                  | 27.35                 | 46.00                         | -18.65              | HORIZONTAL | QP     |
| 4   | 480.080     | 45.71                       | 16.90                   | 2.72                | 28.48                  | 36.85                 | 46.00                         | -9.15               | HORIZONTAL | QP     |
| 5   | 514.030     | 37.46                       | 17.62                   | 2.82                | 28.69                  | 29.21                 | 46.00                         | -16.79              | HORIZONTAL | QP     |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Vertical:**

Peak scan

Level (dBuV/m)



Quasi-peak measurement

| No. | Freq<br>MHz | Read<br>Level<br>dBuV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBuV/m | Limit<br>Line<br>dBuV/m | Over<br>Limit<br>dB | Pol/Phase | Remark |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|-----------|--------|
| 1   | 93.050      | 39.60                 | 8.54                    | 1.13                | 28.53                  | 20.74           | 43.50                   | -22.76              | VERTICAL  | QP     |
| 2   | 201.690     | 39.90                 | 9.46                    | 1.71                | 27.83                  | 23.24           | 43.50                   | -20.26              | VERTICAL  | QP     |
| 3   | 351.070     | 42.65                 | 14.13                   | 2.28                | 27.35                  | 31.71           | 46.00                   | -14.29              | VERTICAL  | QP     |
| 4   | 480.080     | 48.64                 | 16.90                   | 2.72                | 28.48                  | 39.78           | 46.00                   | -6.22               | VERTICAL  | QP     |
| 5   | 514.030     | 44.46                 | 17.62                   | 2.82                | 28.69                  | 36.21           | 46.00                   | -9.79               | VERTICAL  | QP     |


**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

### Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBµV/m)



Quasi-peak measurement


| No. | Freq<br>MHz | Read<br>Level<br>dBµV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBµV/m | Limit<br>Line<br>dBµV/m | Over<br>Limit<br>dB | Pol/Phase  | Remark  |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|------------|---------|
| 1   | 4876.000    | 35.56                 | 33.40                   | 9.66                | 27.61                  | 51.01           | 74.00                   | -22.99              | HORIZONTAL | Peak    |
| 2   | 4876.000    | 27.81                 | 33.40                   | 9.66                | 27.61                  | 43.26           | 54.00                   | -10.74              | HORIZONTAL | Average |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Vertical:**

Peak scan

Level (dB $\mu$ V/m)



Quasi-peak measurement

| No. | Freq<br>MHz | Read<br>Level<br>dB $\mu$ V | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dB $\mu$ V/m | Limit<br>Line<br>dB $\mu$ V/m | Over<br>Limit<br>dB | Pol/Phase | Remark  |
|-----|-------------|-----------------------------|-------------------------|---------------------|------------------------|-----------------------|-------------------------------|---------------------|-----------|---------|
| 1   | 4876.000    | 41.74                       | 33.40                   | 9.66                | 27.61                  | 57.19                 | 74.00                         | -16.81              | VERTICAL  | Peak    |
| 2   | 4876.000    | 29.66                       | 33.40                   | 9.66                | 27.61                  | 45.11                 | 54.00                         | -8.89               | VERTICAL  | Average |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Test at Channel 11 (2.462 GHz) in transmitting status**

**9kHz~30MHz Test result**


The Low frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not report

**30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement**

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement


| No. | Freq<br>MHz | Read<br>Level<br>dBμV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBμV/m | Limit<br>Line<br>dBμV/m | Over<br>Limit<br>dB | Pol/Phase  | Remark |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|------------|--------|
| 1   | 139.610     | 33.33                 | 12.27                   | 1.41                | 28.21                  | 18.80           | 43.50                   | -24.70              | HORIZONTAL | QP     |
| 2   | 200.720     | 37.17                 | 9.43                    | 1.71                | 27.87                  | 20.44           | 43.50                   | -23.06              | HORIZONTAL | QP     |
| 3   | 334.580     | 44.73                 | 13.73                   | 2.23                | 27.42                  | 33.27           | 46.00                   | -12.73              | HORIZONTAL | QP     |
| 4   | 480.080     | 44.90                 | 16.90                   | 2.72                | 28.48                  | 36.04           | 46.00                   | -9.96               | HORIZONTAL | QP     |
| 5   | 514.030     | 40.01                 | 17.62                   | 2.82                | 28.69                  | 31.76           | 46.00                   | -14.24              | HORIZONTAL | QP     |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Vertical:**

Peak scan

Level (dB $\mu$ V/m)



Quasi-peak measurement

| No. | Freq<br>MHz | Read<br>Level<br>dB $\mu$ V | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dB $\mu$ V/m | Limit<br>Line<br>dB $\mu$ V/m | Over<br>Limit<br>dB | Pol/Phase | Remark |
|-----|-------------|-----------------------------|-------------------------|---------------------|------------------------|-----------------------|-------------------------------|---------------------|-----------|--------|
| 1   | 94.990      | 40.61                       | 8.70                    | 1.14                | 28.60                  | 21.85                 | 43.50                         | -21.65              | VERTICAL  | QP     |
| 2   | 203.630     | 38.22                       | 9.53                    | 1.72                | 27.75                  | 21.72                 | 43.50                         | -21.78              | VERTICAL  | QP     |
| 3   | 341.370     | 44.07                       | 13.89                   | 2.25                | 27.37                  | 32.84                 | 46.00                         | -13.16              | VERTICAL  | QP     |
| 4   | 480.080     | 47.04                       | 16.90                   | 2.72                | 28.48                  | 38.18                 | 46.00                         | -7.82               | VERTICAL  | QP     |
| 5   | 514.030     | 44.55                       | 17.62                   | 2.82                | 28.69                  | 36.30                 | 46.00                         | -9.70               | VERTICAL  | QP     |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**




## Spurious emissions above 1GHz

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement


| No. | Freq<br>MHz | Read<br>Level<br>dBμV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBμV/m | Limit<br>Line<br>dBμV/m | Over<br>Limit<br>dB | Pol/Phase  | Remark  |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|------------|---------|
| 1   | 4927.000    | 34.99                 | 33.44                   | 9.72                | 27.60                  | 50.55           | 74.00                   | -23.45              | HORIZONTAL | Peak    |
| 2   | 4927.000    | 27.00                 | 33.44                   | 9.72                | 27.60                  | 42.56           | 54.00                   | -11.44              | HORIZONTAL | Average |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

**Vertical:**

Peak scan

Level (dBμV/m)



Quasi-peak measurement

| No. | Freq<br>MHz | Read<br>Level<br>dBμV | Antenna<br>Factor<br>dB | Cable<br>Loss<br>dB | Preamp<br>Factor<br>dB | Level<br>dBμV/m | Limit<br>Line<br>dBμV/m | Over<br>Limit<br>dB | Pol/Phase | Remark  |
|-----|-------------|-----------------------|-------------------------|---------------------|------------------------|-----------------|-------------------------|---------------------|-----------|---------|
| 1   | 4927.000    | 37.80                 | 33.44                   | 9.72                | 27.60                  | 53.36           | 74.00                   | -20.64              | VERTICAL  | Peak    |
| 2   | 4927.000    | 29.04                 | 33.44                   | 9.72                | 27.60                  | 44.60           | 54.00                   | -9.40               | VERTICAL  | Average |

**Level=Read Level + Antenna Factor + Cable Loss - Preamp Factor**

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Correct= Antenna Factor + Cable Factor –Preamplifier Factor,

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor –Preamplifier Factor.

No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), the amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

Remark:

- 1) .For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonics of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3<sup>rd</sup> harmonic.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

**Test result: The unit does meet the FCC requirements.**

## 5.8 Radiated Emissions which fall in the restricted bands

|                   |  |
|-------------------|--|
| Test Requirement: | FCC Part 15 C section 15.247<br><br>(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).  |
| Test Method:      | ANSI C63.10:2013   |
| Test Status:      | Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.   |
| Test site:        | Measurement Distance: 3m (Semi-Anechoic Chamber)   |
| Limit:            | 40.0 dB $\mu$ V/m between 30MHz & 88MHz;<br><br>43.5 dB $\mu$ V/m between 88MHz & 216MHz;<br><br>46.0 dB $\mu$ V/m between 216MHz & 960MHz;<br><br>54.0 dB $\mu$ V/m above 960MHz.   |
| Detector:         | For PK value:<br><br>RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz<br>VBW $\geq$ RBW<br>Sweep = auto<br><br>Detector function = peak<br><br>Trace = max hold<br><br>For AV value:<br><br>RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz<br>VBW = 10Hz<br>Sweep = auto<br><br>Detector function = peak<br><br>Trace = max hold |

## Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. Only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                        | MHz                 | MHz             | GHz           |
|----------------------------|---------------------|-----------------|---------------|
| 0.090 - 0.110              | 16.42 - 16.423      | 399.9 - 410     | 4.5 - 5.15    |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614       | 5.35 - 5.46   |
| 2.1735 - 2.1905            | 16.80425 - 16.80475 | 960 - 1240      | 7.25 - 7.75   |
| 4.125 - 4.128              | 25.5 - 25.67        | 1300 - 1427     | 8.025 - 8.5   |
| 4.17725 - 4.17775          | 37.5 - 38.25        | 1435 - 1626.5   | 9.0 - 9.2     |
| 4.20725 - 4.20775          | 73 - 74.6           | 1645.5 - 1646.5 | 9.3 - 9.5     |
| 6.215 - 6.218              | 74.8 - 75.2         | 1660 - 1710     | 10.6 - 12.7   |
| 6.26775 - 6.26825          | 108 - 121.94        | 1718.8 - 1722.2 | 13.25 - 13.4  |
| 6.31175 - 6.31225          | 123 - 138           | 2200 - 2300     | 14.47 - 14.5  |
| 8.291 - 8.294              | 149.9 - 150.05      | 2310 - 2390     | 15.35 - 16.2  |
| 8.362 - 8.366              | 156.52475 -         | 2483.5 - 2500   | 17.7 - 21.4   |
| 8.37625 - 8.38675          | 156.52525           | 2655 - 2900     | 22.01 - 23.12 |
| 8.41425 - 8.41475          | 156.7 - 156.9       | 3260 - 3267     | 23.6 - 24.0   |
| 12.29 - 12.293             | 162.0125 - 167.17   | 3332 - 3339     | 31.2 - 31.8   |
| 12.51975 - 12.52025        | 167.72 - 173.2      | 3345.8 - 3358   | 36.43 - 36.5  |
| 12.57675 - 12.57725        | 240 - 285           | 3600 - 4400     |               |
| 13.36 - 13.41              | 322 - 335.4         |                 |               |

Test Result:

Pre-test under all modes; choose the worst case mode record on the report.

Test mode: 802.11b

| Frequency (MHz)     | Reading Level (dBµV/m) | Correct (dB/m) | Emission Level (dBµV/m) | Limit (dBµV/m) | Margin (dB) | Antenna polarization | Detector |
|---------------------|------------------------|----------------|-------------------------|----------------|-------------|----------------------|----------|
| <b>Low Channel</b>  |                        |                |                         |                |             |                      |          |
| 2310.000            | 23.23                  | 6.54           | 29.77                   | 74.00          | -44.23      | H                    | PK       |
| 2310.000            | 13.12                  | 6.54           | 19.66                   | 54.00          | -34.34      | H                    | AV       |
| 2390.000            | 24.42                  | 6.61           | 31.03                   | 74.00          | -42.97      | H                    | PK       |
| 2390.000            | 12.52                  | 6.61           | 19.13                   | 54.00          | -34.87      | H                    | AV       |
| 2310.000            | 28.35                  | 6.54           | 34.89                   | 74.00          | -39.11      | V                    | PK       |
| 2310.000            | 15.74                  | 6.54           | 22.28                   | 54.00          | -31.72      | V                    | AV       |
| 2390.000            | 30.25                  | 6.61           | 36.86                   | 74.00          | -37.14      | V                    | PK       |
| 2390.000            | 13.56                  | 6.61           | 20.17                   | 54.00          | -33.83      | V                    | AV       |
| <b>High Channel</b> |                        |                |                         |                |             |                      |          |
| 2483.500            | 25.43                  | 6.70           | 32.13                   | 74.00          | -41.87      | H                    | PK       |
| 2483.500            | 10.52                  | 6.70           | 17.22                   | 54.00          | -36.78      | H                    | AV       |
| 2500.000            | 24.24                  | 6.72           | 30.96                   | 74.00          | -43.04      | H                    | PK       |
| 2500.000            | 11.28                  | 6.72           | 18.00                   | 54.00          | -36.00      | H                    | AV       |
| 2483.500            | 31.24                  | 6.70           | 37.94                   | 74.00          | -36.06      | V                    | PK       |
| 2483.500            | 12.53                  | 6.70           | 19.23                   | 54.00          | -34.77      | V                    | AV       |
| 2500.000            | 31.63                  | 6.72           | 38.35                   | 74.00          | -35.65      | V                    | PK       |
| 2500.000            | 14.68                  | 6.72           | 21.40                   | 54.00          | -32.60      | V                    | AV       |

Test mode: 802.11n(HT40)

| Frequency (MHz)     | Reading Level (dB $\mu$ V/m) | Correct (dB/m) | Emission Level (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) | Antenna polarization | Detector |
|---------------------|------------------------------|----------------|-------------------------------|----------------------|-------------|----------------------|----------|
| <b>Low Channel</b>  |                              |                |                               |                      |             |                      |          |
| 2310.000            | 24.24                        | 6.54           | 30.78                         | 74.00                | -43.22      | H                    | PK       |
| 2310.000            | 13.73                        | 6.54           | 20.27                         | 54.00                | -33.73      | H                    | AV       |
| 2390.000            | 29.64                        | 6.61           | 36.25                         | 74.00                | -37.75      | H                    | PK       |
| 2390.000            | 11.15                        | 6.61           | 17.76                         | 54.00                | -36.24      | H                    | AV       |
| 2310.000            | 31.47                        | 6.54           | 38.01                         | 74.00                | -35.99      | V                    | PK       |
| 2310.000            | 14.35                        | 6.54           | 20.89                         | 54.00                | -33.11      | V                    | AV       |
| 2390.000            | 32.11                        | 6.61           | 38.72                         | 74.00                | -35.28      | V                    | PK       |
| 2390.000            | 15.62                        | 6.61           | 22.23                         | 54.00                | -31.77      | V                    | AV       |
| <b>High Channel</b> |                              |                |                               |                      |             |                      |          |
| 2483.500            | 26.13                        | 6.70           | 32.83                         | 74.00                | -41.17      | H                    | PK       |
| 2483.500            | 11.26                        | 6.70           | 17.96                         | 54.00                | -36.04      | H                    | AV       |
| 2500.000            | 27.16                        | 6.72           | 33.88                         | 74.00                | -40.12      | H                    | PK       |
| 2500.000            | 12.62                        | 6.72           | 19.34                         | 54.00                | -34.66      | H                    | AV       |
| 2483.500            | 32.73                        | 6.70           | 39.43                         | 74.00                | -34.57      | V                    | PK       |
| 2483.500            | 11.85                        | 6.70           | 18.55                         | 54.00                | -35.45      | V                    | AV       |
| 2500.000            | 33.23                        | 6.72           | 39.95                         | 74.00                | -34.05      | V                    | PK       |
| 2500.000            | 14.16                        | 6.72           | 20.88                         | 54.00                | -33.12      | V                    | AV       |

## 5.9 Band Edges Requirement


**Test Requirement:** FCC Part 15 C section 15.247  
(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

**Frequency Band:** 2400 MHz to 2483.5 MHz

**Test Method:** ANSI C63.10:2013

**Test Status:** Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

**Test Configuration:**



**Test Procedure:**

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set RBW=100 kHz, VBW=300 KHz, suitable frequency span including 1000 kHz bandwidth from band edge.
3. Measure the Conducted Spurious Emissions and Radiated Emissions of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse.



**Test result with plots as follows:**

The band edges was measured and recorded Result:


The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.


Result plot as follows:

802.11b

Channel 1: 2.412 GHz



Channel 11: 2.462 GHz




802.11g

Channel 1: 2.412 GHz




Channel 11: 2.462 GHz




802.11n(HT20)

Channel 1: 2.412 GHz



Channel 11: 2.462 GHz




802.11n(HT40)

Channel 3: 2.422 GHz



Channel 9: 2.452 GHz



Test result: The unit does meet the FCC requirements.

## 5.10 Conducted Emissions at Mains Terminals 150 kHz to 30MHz

**Test Requirement:** FCC Part 15 C section 15.207

**Test Voltage:** 120V~ 60Hz

**Test Method:** ANSI C63.10:2013 Clause 6.2

**Frequency Range:** 150 kHz to 30 MHz

**Detector:** Peak for pre-scan (9 kHz Resolution Bandwidth)

### Test Limit

**Limits for conducted disturbance at the mains ports of class B**


| Frequency Range | Class B Limit dB( $\mu$ V) |          |
|-----------------|----------------------------|----------|
|                 | Quasi-peak                 | Average  |
| 0.15 to 0.50    | 66 to 56                   | 56 to 46 |
| 0.50 to 5       | 56                         | 46       |
| 5 to 30         | 60                         | 50       |

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

### EUT Operation:

Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, channels and antenna ports (if EUT with antenna diversity architecture).

**Test Configuration:****Test procedure:**

1. The mains terminal disturbance voltage test was conducted in a shielded room.
2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H} + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

## 5.10.1 Measurement Data


An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

The following Quasi-Peak and Average measurements were performed on the EUT Live line

Peak Scan:

Level (dBuV)



Quasi-peak and Average measurement


| NO. | Freq MHz | Level dBuV | Remark  | LISN Factor dB | Cable Loss dB | Limit Line dBuV | Margin dB |
|-----|----------|------------|---------|----------------|---------------|-----------------|-----------|
| 1   | 0.166    | 41.85      | QP      | 9.43           | 0.21          | 65.18           | -23.33    |
| 2   | 0.166    | 28.97      | Average | 9.43           | 0.21          | 55.16           | -26.19    |
| 3   | 0.501    | 46.96      | QP      | 9.33           | 0.27          | 56.00           | -9.04     |
| 4   | 0.501    | 41.49      | Average | 9.33           | 0.27          | 46.00           | -4.51     |
| 5   | 0.800    | 34.99      | QP      | 9.27           | 0.29          | 56.00           | -21.01    |
| 6   | 0.800    | 29.40      | Average | 9.27           | 0.29          | 46.00           | -16.60    |
| 7   | 3.133    | 33.16      | QP      | 9.31           | 0.37          | 56.00           | -22.84    |
| 8   | 3.133    | 25.48      | Average | 9.31           | 0.37          | 46.00           | -20.52    |
| 9   | 5.000    | 30.50      | QP      | 9.29           | 0.40          | 56.00           | -25.50    |
| 10  | 5.000    | 22.30      | Average | 9.29           | 0.40          | 46.00           | -23.70    |
| 11  | 26.353   | 22.88      | QP      | 9.72           | 0.49          | 60.00           | -37.12    |
| 12  | 26.353   | 11.64      | Average | 9.72           | 0.49          | 50.00           | -38.36    |



### Neutral Line

Peak Scan:

Level (dBµV)



Quasi-peak and Average measurement

| NO. | Freq MHz | Level dBµV | Remark  | LISN Factor dB | Cable Loss dB | Limit Line dBµV | Margin dB |
|-----|----------|------------|---------|----------------|---------------|-----------------|-----------|
| 1   | 0.170    | 42.02      | QP      | 9.38           | 0.21          | 64.96           | -22.94    |
| 2   | 0.170    | 26.90      | Average | 9.38           | 0.21          | 54.94           | -28.04    |
| 3   | 0.501    | 39.85      | QP      | 9.36           | 0.27          | 56.00           | -16.15    |
| 4   | 0.501    | 32.80      | Average | 9.36           | 0.27          | 46.00           | -13.20    |
| 5   | 0.800    | 31.40      | QP      | 9.36           | 0.29          | 56.00           | -24.60    |
| 6   | 0.800    | 23.68      | Average | 9.36           | 0.29          | 46.00           | -22.32    |
| 7   | 2.050    | 28.26      | QP      | 9.39           | 0.35          | 56.00           | -27.74    |
| 8   | 2.050    | 16.88      | Average | 9.39           | 0.35          | 46.00           | -29.12    |
| 9   | 5.000    | 25.40      | QP      | 9.43           | 0.40          | 56.00           | -30.60    |
| 10  | 5.000    | 14.42      | Average | 9.43           | 0.40          | 46.00           | -31.58    |
| 11  | 26.080   | 24.97      | QP      | 9.83           | 0.49          | 60.00           | -35.03    |
| 12  | 26.080   | 12.85      | Average | 9.83           | 0.49          | 50.00           | -37.15    |

-- End of test report --