



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN0827-58B01BLX-W

Product Name: Antenna

Specification For Approval

Date: 2023.6.13

Version: 1.0

客户名称

Customer:

客户料号

Customer P/N:

腾祥料号

T X P/N:

AN0827-58B01BLX-W

规格描述

Description :

4G 白色天线 1.13mm 蓝色线 L=250mm+IPEX

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制作	路婷	TESTED BY 检测	
CHECKED BY 审核	胡超	CHECKED BY 审核	
Q.C.DEPT. 品管	梁凤珍	Q.C.DEPT. 品管	
APPROVED BY 核准	韦佳	APPROVEDBY 核准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN0827-58B01BLX-W

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)


Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2023.6.13	初版	

Product Number: AN0827-58B01BLX-W

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	824-960 MHz /1710-2700MHz
S.W.R. 驻波比	≤ 3.0 / ≤ 2.5
Antenna Gain 增益	0.85dBi /3.85dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Material of Plastic 塑胶材质	PC
Cable Type 线材规格	OD1.13mm ,BLUE
Connector Type 连接器规格	I-PEX
C. Environmental	
Storage Temperature 存储温度	- 40 °C ~ +80 °C
Operation Temperature 工作温度	- 40 °C ~ +80 °C
Antenna Color Storage life 天线颜色存储寿命	< 2 year

Product Number: AN0827-58B01BLX-W

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal 单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol. $\leq 5\%$ 符合待测物规范; 频率偏移 $\leq 5\%$	PASS
4	Torque Test 扭力	Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal 单独定义产品端子之顺时针及逆时针扭力	1. Directive DUT specification 2. Frequency Tol. $\leq 5\%$ 符合待测物规范; 频率偏移 $\leq 5\%$	PASS
5	Dimension 尺寸	Inspection of dimension, color, material, package, surface process. 检查尺寸, 颜色, 材料, 包装, 表面处理	Directive DUT specification 符合待测物规范	PASS
6	Waterproof 防水	With Reference to IEC 60529 // IP Code Definition 参考 IEC60529 IP 定义	Directive DUT specification 符合待测物规范	NA
7	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: $\geq 95\%$; NaCl solution: $\geq 5\%$; Time: 24H 温度 35°C; 湿度 $\geq 95\%$; 盐水浓度 $\geq 5\%$; 测试 24H	1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
8	Temperature and Humidity Chamber 恒温恒湿	GB / T 2423.3-2006 Temp: 80°C / 12 H; -40°C / 12H RH: $\geq 90\%$; Time: 24H 温度 80°C 测试 12H 转 -40°C 测试 12H; 湿度 $\geq 90\%$; 时间 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 恢复 2H 后, 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
9	Aging test 老化	GB / T 2423.2 - 2008 Temp 80°C; Time: 24 hours 温度 80°C, 测试 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. $\leq 5\%$ 无明显外观不良; 频率偏移 $\leq 5\%$	PASS
10	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2011/65/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN0827-58B01BLX-W

Product Name: Antenna

3. Antenna - S Parameter Test Data



4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
Frequency (MHz)	824.0	858.0	892.0	926.0	960.0	1710.0	1756.0	1802.0	1848.0	1894.0	1940.0	1986.0	2032.0	2078.0	2124.0	2170.0	2300.0	2400.0	2500.0	2600.0	2700.0
Gain (dBi)	0.76	0.85	0.11	0.19	0.18	0.23	0.88	1.74	3.43	3.37	3.69	3.85	3.35	2.86	3.32	2.19	1.52	3.32	3.47	1.16	0.61
Efficiency (%)	44.71	50.50	41.15	38.23	39.29	39.54	49.25	49.66	57.68	59.76	56.68	56.92	45.19	43.69	43.80	39.31	39.24	44.05	50.53	35.45	28.82





有源

Test BW	FDD-10MHz				TDD-20MHZ				
Channel	LTE-B1	LTE-B3	LTE-B5	LTE-B8	LTE-B34	LTE-B38	LTE-B39	LTE-B40	LTE-B41
TRP (dBm)	19.61	20.69	18.46	19.11	20.7	16.56	20.73	20.07	15.18
TIS (dBm)	-90.22	-87.14	-81.53	-82.79	-85.85	-88.08	-87.62	-91.69	-88.47





Product Number: AN0827-58B01BLX-W

Product Name: Antenna





824MHz







960MHz



1710MHz





2700MHz



5. Mechanical Drawing See attached files

1	2	3	4	5	6	7	8																																																						
HF☐ RoHS2.0☒ REACH☐ CONFIDENTIAL					<table><tr><td>SIGN</td><td>DATE</td><td>DESCRIPTION</td><td>APPROVER</td></tr><tr><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td></tr></table>			SIGN	DATE	DESCRIPTION	APPROVER																																																		
SIGN	DATE	DESCRIPTION	APPROVER																																																										
E							E																																																						
D	105±1 12.9 12.0						D																																																						
C	① ② ③ ④ 250±5.0						C																																																						
B	Note: 1. Dimension: Take * is the important dimension 2. Tolerance: Unmarked tolerance refer to the standard tolerance please						B																																																						
A	<table><tr><td>4</td><td>CR-113-ZP-A</td><td>IPEX</td><td>CU</td><td>Au Plated</td><td>1</td></tr><tr><td>3</td><td>CB-113BL</td><td>Coaxial Cable</td><td>OD1.13</td><td>BLUE</td><td>1</td></tr><tr><td>2</td><td>ANT58B-02WH35</td><td>Body 2</td><td>PC</td><td>White,新模</td><td>1</td></tr><tr><td>1</td><td>ANT58-01WH35</td><td>Body 1</td><td>PC</td><td>White</td><td>1</td></tr><tr><td>No.</td><td>Part Number</td><td>Name</td><td>Material</td><td>Finish</td><td>Q'ty</td></tr></table>					4	CR-113-ZP-A	IPEX	CU	Au Plated	1	3	CB-113BL	Coaxial Cable	OD1.13	BLUE	1	2	ANT58B-02WH35	Body 2	PC	White,新模	1	1	ANT58-01WH35	Body 1	PC	White	1	No.	Part Number	Name	Material	Finish	Q'ty	Tengxiang Electronics Co., Ltd. TITLE: 4G Antenna PART NO.: AN0827-58B01BLX-W DWG NAME: <table><tr><td>APP BY</td><td>CHK BY</td><td>RF BY</td><td>DES BY</td><td> </td><td>Tolerance</td></tr><tr><td>YCX</td><td>HC</td><td>WJ</td><td>DWF</td><td>UNITS: mm</td><td>X.X ±0.5</td></tr><tr><td>2023.06.12</td><td>2023.06.12</td><td>2023.06.12</td><td>2023.06.12</td><td>SCALE: 1/1</td><td>X.XX ±0.2</td></tr><tr><td colspan="5">REVISION: A</td><td>X° ±1°</td></tr></table>		APP BY	CHK BY	RF BY	DES BY		Tolerance	YCX	HC	WJ	DWF	UNITS: mm	X.X ±0.5	2023.06.12	2023.06.12	2023.06.12	2023.06.12	SCALE: 1/1	X.XX ±0.2	REVISION: A					X° ±1°
4	CR-113-ZP-A	IPEX	CU	Au Plated	1																																																								
3	CB-113BL	Coaxial Cable	OD1.13	BLUE	1																																																								
2	ANT58B-02WH35	Body 2	PC	White,新模	1																																																								
1	ANT58-01WH35	Body 1	PC	White	1																																																								
No.	Part Number	Name	Material	Finish	Q'ty																																																								
APP BY	CHK BY	RF BY	DES BY		Tolerance																																																								
YCX	HC	WJ	DWF	UNITS: mm	X.X ±0.5																																																								
2023.06.12	2023.06.12	2023.06.12	2023.06.12	SCALE: 1/1	X.XX ±0.2																																																								
REVISION: A					X° ±1°																																																								
1	2	3	4	5	6	7	8																																																						



產品包裝規範


PACKING CRITERION

Date: 2023.06.12

Page: 1 of 1


Part Number : AN0827-58B01BLX-W	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




20pcs/ PE bag

2.PACKING 。




1000pcs/Carton



3. SEALING 。



SIDE



FRONT



APPROVED BY : YCX

CHECKED BY : HC

DESIGNED BY : DWF