



FCC RF Test Report

APPLICANT : CHEP
EQUIPMENT : Asset Tracker
BRAND NAME : CHEP
MODEL NAME : Gen 4 Ultra Short
FCC ID : 2APRD-GEN4SHORT
STANDARD : 47 CFR Part 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TEST DATE(S) : Jul. 19, 2024 ~ Aug. 06, 2024

This product installed a RF module (Brand Name: Quectel, Model Name: BG95-M3, FCC ID: XMR201910BG95M3) during the test, only Conducted Power, ERP/EIRP and RSE test items are tested in this report, all the other test results are leveraged from module RF report.

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP, and Emission Designator	6
1.7 Testing Location	6
1.8 Test Software	7
1.9 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	9
2.3 Support Unit used in test configuration	9
2.4 Frequency List of Low/Middle/High Channels	9
3 CONDUCTED TEST RESULT.....	10
3.1 Measuring Instruments.....	10
3.2 Test Setup	10
3.3 Test Result of Conducted Test.....	10
3.4 Conducted Output Power and ERP/EIRP	11
4 RADIATED TEST ITEMS	12
4.1 Measuring Instruments.....	12
4.2 Test Setup	12
4.3 Test Result of Radiated Test.....	13
4.4 Field Strength of Spurious Radiation Measurement	14
5 LIST OF MEASURING EQUIPMENT	15
6 MEASUREMENT UNCERTAINTY	16
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG470213A	Rev. 01	Initial issue of report	Aug. 23, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
-	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	1
-	§2.1049	Occupied Bandwidth	Reporting Only	PASS	1
-	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	1
-	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	1
-	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	1
	§2.1055 §24.235		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a);	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 19.81 dB at 1672.80 MHz

Remark 1: Test results are leveraged from module RF report No “R1907A0446-R1V1” and “R1907A0446-R2”

Conformity Assessment Condition:	
1.	The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2.	The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”
Disclaimer:	
The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.	



1 General Description

1.1 Applicant

CHEP

2901 Tasman Drive Suite 101 Santa Clara, CA 95054

1.2 Manufacturer

MINEWING VIET NAM ELECTRONICS CO., LTD

Lot CN2, Yen Phong industrial park, Dong Phong commune and, Long Chau commune, Yen Phong District, Bac Ninh province, Vietnam

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Asset Tracker
Brand Name	CHEP
Model Name	Gen 4 Ultra Short
FCC ID	2APRD-GEN4SHORT
IMEI Code	866901065466072
HW Version	v14
SW Version	v10.00.0002
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GPRS/EDGE: 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz
Rx Frequency	GPRS/EDGE: 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GPRS/EDGE: 850: 32.14 dBm 1900: 29.28 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Cellular Band: 1.6 dBi PCS Band: 3.5 dBi
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)
Part 22	GSM850 (GPRS)	824.2 ~ 848.8	GMSK	1.4421
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.3258
Part 24	GSM1900 (GPRS)	1850.2 ~ 1909.8	GMSK	1.8967
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.7430

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH03-SZ	CN1256	421272



1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22(H), 24(E)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19100 MHz for GSM1900.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS 1 Tx slots Link	■ GPRS 1 Tx slots Link
	■ EDGE 1 Tx slots Link	■ EDGE 1 Tx slots Link
GSM 1900	■ GPRS 1 Tx slots Link	■ GPRS 1 Tx slots Link
	■ EDGE 1 Tx slots Link	■ EDGE 1 Tx slots Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m

2.4 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel / Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8


3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Aug. 06, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 16, 2023	Aug. 06, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Aug. 06, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 03, 2024	Aug. 06, 2024	Jul. 02, 2025	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 09, 2024	Jul. 19, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 09, 2024	Jul. 19, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 27, 2024	Jul. 19, 2024	Jun. 26, 2025	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 20, 2023	Jul. 19, 2024	Aug. 19, 2025	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 09, 2024	Jul. 19, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 09, 2024	Jul. 19, 2024	Apr. 08, 2025	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2023	Jul. 19, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 27, 2023	Jul. 19, 2024	Dec. 26, 2024	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Jul. 19, 2024	Jul. 02, 2025	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	61601000272 9	N/A	Oct. 18, 2023	Jul. 19, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 19, 2024	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 19, 2024	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	± 1.34 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.6dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.8dB
---	-------

----- THE END -----

Appendix A. Test Results of Conducted Test

Test Engineer :	Khan Zhen	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP/EIRP

GSM850	Burst Average Power (dBm)			ERP(W)		
TX Channel	128	189	251			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GPRS 1 Tx slot	32.13	31.85	32.14	1.4388	1.3490	1.4421
GPRS 2 Tx slots	32.10	31.79	32.11	1.4289	1.3305	1.4322
GPRS 3 Tx slots	30.95	30.64	31.00	1.0965	1.0209	1.1092
GPRS 4 Tx slots	29.43	29.15	29.58	0.7727	0.7244	0.7998
EDGE 1 Tx slot	25.68	25.04	25.12	0.3258	0.2812	0.2864
EDGE 2 Tx slots	25.16	24.58	24.67	0.2891	0.2529	0.2582
EDGE 3 Tx slots	23.65	23.05	23.11	0.2042	0.1778	0.1803
EDGE 4 Tx slots	22.62	22.00	22.09	0.1611	0.1396	0.1426

GSM1900	Burst Average Power (dBm)			EIRP(W)		
TX Channel	512	661	810			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GPRS 1 Tx slot	29.28	29.21	29.08	1.8967	1.8664	1.8113
GPRS 2 Tx slots	28.58	28.51	28.38	1.6144	1.5885	1.5417
GPRS 3 Tx slots	27.14	27.01	26.88	1.1588	1.1246	1.0914
GPRS 4 Tx slots	25.96	25.86	25.73	0.8831	0.8630	0.8375
EDGE 1 Tx slot	25.21	25.14	25.02	0.7430	0.7311	0.7112
EDGE 2 Tx slots	24.35	24.32	24.27	0.6095	0.6053	0.5984
EDGE 3 Tx slots	22.74	22.69	22.64	0.4207	0.4159	0.4111
EDGE 4 Tx slots	21.58	21.53	21.48	0.3221	0.3184	0.3148



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Jia Kuang	Temperature :	22~25°C
		Relative Humidity :	48~52%

GSM850 (GPRS 1 Tx slots)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-54.76	-13	-41.76	-61.02	-57.99	3.98	9.36	H
	2472.6	-51.23	-13	-38.23	-61.58	-54.78	4.85	10.55	H
	3296.8	-51.86	-13	-38.86	-64.28	-56.79	5.50	12.58	H
	4121	-59.46	-13	-46.46	-75.04	-63.93	5.98	12.60	H
	4944	-61.19	-13	-48.19	-78.68	-64.62	7.10	12.68	H
	5768	-59.28	-13	-46.28	-77.48	-62.43	7.60	12.90	H
	1648.4	-55.50	-13	-42.50	-61.65	-58.73	3.98	9.36	V
	2472.6	-52.99	-13	-39.99	-63.70	-56.54	4.85	10.55	V
	3296.8	-53.61	-13	-40.61	-66.49	-58.54	5.50	12.58	V
	4121	-59.93	-13	-46.93	-75.62	-64.40	5.98	12.60	V
	4944	-61.04	-13	-48.04	-78.50	-64.47	7.10	12.68	V
	5768	-59.09	-13	-46.09	-77.48	-62.24	7.60	12.90	V
Middle	1672.8	-50.74	-13	-37.74	-56.96	-53.99	4.00	9.40	H
	2509.2	-47.97	-13	-34.97	-58.22	-51.54	4.88	10.60	H
	3345.6	-47.86	-13	-34.86	-59.89	-52.79	5.52	12.60	H
	4182	-61.66	-13	-48.66	-77.36	-66.13	6.00	12.62	H
	5018.4	-55.06	-13	-42.06	-72.45	-58.47	7.14	12.70	H
	5856	-58.00	-13	-45.00	-76.73	-61.23	7.62	13.00	H
	1672.8	-50.66	-13	-37.66	-56.60	-53.91	4.00	9.40	V
	2509.2	-50.43	-13	-37.43	-61.01	-54.00	4.88	10.60	V
	3345.6	-52.74	-13	-39.74	-65.15	-57.67	5.52	12.60	V
	4182	-61.26	-13	-48.26	-77.17	-65.73	6.00	12.62	V
	5018.4	-58.72	-13	-45.72	-76.03	-62.13	7.14	12.70	V
	5856	-58.70	-13	-45.70	-77.61	-61.93	7.62	13.00	V
Highest	1697.6	-53.80	-13	-40.80	-60.15	-56.97	4.10	9.42	H
	2546.4	-51.37	-13	-38.37	-61.67	-54.95	4.90	10.63	H
	3395.2	-54.85	-13	-41.85	-66.85	-59.77	5.55	12.62	H
	4244	-58.37	-13	-45.37	-74.43	-62.85	6.02	12.65	H
	5096	-62.35	-13	-49.35	-79.81	-65.77	7.15	12.72	H
	5944	-58.95	-13	-45.95	-78.08	-62.18	7.64	13.02	H
	1697.6	-55.08	-13	-42.08	-61.20	-58.25	4.10	9.42	V
	2546.4	-52.95	-13	-39.95	-63.59	-56.53	4.90	10.63	V
	3395.2	-52.27	-13	-39.27	-64.83	-57.19	5.55	12.62	V
	4244	-59.49	-13	-46.49	-75.62	-63.97	6.02	12.65	V
	5096	-62.61	-13	-49.61	-80.01	-66.03	7.15	12.72	V
	5944	-56.82	-13	-43.82	-76.09	-60.05	7.64	13.02	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE 1 Tx slots)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-42.75	-13	-29.75	-49.01	-45.98	3.98	9.36	H
	2472.6	-46.34	-13	-33.34	-56.69	-49.89	4.85	10.55	H
	3296.8	-44.93	-13	-31.93	-57.35	-49.86	5.50	12.58	H
	4121	-53.00	-13	-40.00	-68.58	-57.47	5.98	12.60	H
	4944	-58.23	-13	-45.23	-75.72	-61.66	7.10	12.68	H
	5768	-57.44	-13	-44.44	-75.64	-60.59	7.60	12.90	H
	1648.4	-43.01	-13	-30.01	-49.16	-46.24	3.98	9.36	V
	2472.6	-44.05	-13	-31.05	-54.76	-47.60	4.85	10.55	V
	3296.8	-44.42	-13	-31.42	-57.30	-49.35	5.50	12.58	V
	4121	-49.00	-13	-36.00	-64.69	-53.47	5.98	12.60	V
	4944	-58.23	-13	-45.23	-75.69	-61.66	7.10	12.68	V
	5768	-57.12	-13	-44.12	-75.51	-60.27	7.60	12.90	V
Middle	1672.8	-38.45	-13	-25.45	-44.67	-41.70	4.00	9.40	H
	2509.2	-48.27	-13	-35.27	-58.52	-51.84	4.88	10.60	H
	3345.6	-44.12	-13	-31.12	-56.15	-49.05	5.52	12.60	H
	4182	-58.51	-13	-45.51	-74.21	-62.98	6.00	12.62	H
	5018.4	-60.47	-13	-47.47	-77.86	-63.88	7.14	12.70	H
	5856	-60.22	-13	-47.22	-78.95	-63.45	7.62	13.00	H
	1672.8	-32.81	-13	-19.81	-38.75	-36.06	4.00	9.40	V
	2509.2	-44.85	-13	-31.85	-55.43	-48.42	4.88	10.60	V
	3345.6	-40.12	-13	-27.12	-52.53	-45.05	5.52	12.60	V
	4182	-56.84	-13	-43.84	-72.75	-61.31	6.00	12.62	V
	5018.4	-59.31	-13	-46.31	-76.62	-62.72	7.14	12.70	V
	5856	-58.50	-13	-45.50	-77.41	-61.73	7.62	13.00	V
Highest	1697.6	-40.54	-13	-27.54	-46.89	-43.71	4.10	9.42	H
	2546.4	-45.37	-13	-32.37	-55.67	-48.95	4.90	10.63	H
	3395.2	-40.77	-13	-27.77	-52.77	-45.69	5.55	12.62	H
	4244	-57.42	-13	-44.42	-73.48	-61.90	6.02	12.65	H
	5096	-58.33	-13	-45.33	-75.79	-61.75	7.15	12.72	H
	5944	-57.04	-13	-44.04	-76.17	-60.27	7.64	13.02	H
	1697.6	-42.80	-13	-29.80	-48.92	-45.97	4.10	9.42	V
	2546.4	-44.10	-13	-31.10	-54.74	-47.68	4.90	10.63	V
	3395.2	-45.33	-13	-32.33	-57.89	-50.25	5.55	12.62	V
	4244	-57.36	-13	-44.36	-73.49	-61.84	6.02	12.65	V
	5096	-58.42	-13	-45.42	-75.82	-61.84	7.15	12.72	V
	5944	-56.54	-13	-43.54	-75.81	-59.77	7.64	13.02	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS 1 Tx slots)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-56.14	-13	-43.14	-70.68	-62.90	5.82	12.58	H
	5550.6	-62.08	-13	-49.08	-79.60	-67.80	7.28	13.00	H
	7400.8	-55.08	-13	-42.08	-77.80	-58.24	8.32	11.48	H
	3700.4	-56.02	-13	-43.02	-70.85	-62.78	5.82	12.58	V
	5550.6	-61.98	-13	-48.98	-79.55	-67.70	7.28	13.00	V
	7400.8	-55.33	-13	-42.33	-78.1	-58.49	8.32	11.48	V
Middle	3760	-54.23	-13	-41.23	-68.88	-60.98	5.85	12.60	H
	5640	-61.18	-13	-48.18	-78.93	-66.98	7.30	13.10	H
	7520	-55.99	-13	-42.99	-78.30	-59.14	8.35	11.50	H
	3760	-56.48	-13	-43.48	-71.31	-63.23	5.85	12.60	V
	5640	-61.54	-13	-48.54	-79.18	-67.34	7.30	13.10	V
	7520	-55.62	-13	-42.62	-77.81	-58.77	8.35	11.50	V
Highest	3819.6	-57.04	-13	-44.04	-71.85	-63.78	5.88	12.62	H
	5729.4	-60.82	-13	-47.82	-78.88	-66.63	7.32	13.13	H
	7639.2	-55.53	-13	-42.53	-77.80	-58.69	8.38	11.54	H
	3819.6	-57.05	-13	-44.05	-71.94	-63.79	5.88	12.62	V
	5729.4	-60.74	-13	-47.74	-78.91	-66.55	7.32	13.13	V
	7639.2	-56.02	-13	-43.02	-78.12	-59.18	8.38	11.54	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (EDGE 1 Tx slots)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-57.02	-13	-44.02	-71.56	-63.78	5.82	12.58	H
	5550.6	-62.22	-13	-49.22	-79.74	-67.94	7.28	13.00	H
	7400.8	-55.48	-13	-42.48	-78.20	-58.64	8.32	11.48	H
	3700.4	-57.46	-13	-44.46	-72.29	-64.22	5.82	12.58	V
	5550.6	-61.98	-13	-48.98	-79.55	-67.70	7.28	13.00	V
	7400.8	-55.24	-13	-42.24	-78.01	-58.40	8.32	11.48	V
Middle	3760	-55.49	-13	-42.49	-70.14	-62.24	5.85	12.60	H
	5640	-61.39	-13	-48.39	-79.14	-67.19	7.30	13.10	H
	7520	-55.77	-13	-42.77	-78.08	-58.92	8.35	11.50	H
	3760	-53.05	-13	-40.05	-67.88	-59.80	5.85	12.60	V
	5640	-61.46	-13	-48.46	-79.1	-67.26	7.30	13.10	V
	7520	-55.85	-13	-42.85	-78.04	-59.00	8.35	11.50	V
Highest	3819.6	-55.02	-13	-42.02	-69.83	-61.76	5.88	12.62	H
	5729.4	-61.02	-13	-48.02	-79.08	-66.83	7.32	13.13	H
	7639.2	-55.71	-13	-42.71	-77.98	-58.87	8.38	11.54	H
	3819.6	-55.95	-13	-42.95	-70.84	-62.69	5.88	12.62	V
	5729.4	-60.77	-13	-47.77	-78.94	-66.58	7.32	13.13	V
	7639.2	-55.84	-13	-42.84	-77.94	-59.00	8.38	11.54	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.