

## RF Exposure Evaluation Statement

**Product Name:** Bluetooth headphone

**Model No.:** PRTUKYT-ANC918

**FCC ID: 2APREANC918**

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

## Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$
$$[\sqrt{f}(\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

Operational Mode: EDR (8-DPSK worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402MHZ	1.32	±1	2.32	1.71	0.53	3.0
2441MHz	1.29	±1	2.29	1.69	0.53	
2480MHz	2.27	±1	3.27	2.12	0.67	
Conclusion: the calculated value ≤3.0, SAR is exempted.						