

RF Exposure Report

Report No.: SA180323C16F

FCC ID: 2APRXH2C

Test Model: H2C

Series Model: H3C

Received Date: Mar. 11, 2020

Test Date: Mar. 23 to 30, 2020

Issued Date: Apr. 6, 2020

Applicant: Western Digital Technologies, Inc

Address: 3355 Michelson Dr #100, Irvine, CA 92612

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**FCC Registration /
Designation Number:** 198487 / TW2021



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA180323C16F	Original release.	Apr. 6, 2020

1 Certificate of Conformity

Product: ibi Wireless

Brand: SanDisk

Test Model: H2C

Series Model: H3C

Sample Status: Engineering sample

Applicant: Western Digital Technologies, Inc

Test Date: Mar. 23 to 30, 2020

Standards: FCC Part 2 (Section 2.1091)
IEEE C95.3 -2002

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celia Chen , **Date:** Apr. 6, 2020
Celia Chen / Supervisor

Approved by : Rex Lai , **Date:** Apr. 6, 2020
Rex Lai / Associate Technical Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
1TX					
WLAN: 2412-2462	17.31	2.14	20	0.018	1
BT LE: 2402-2480	5.75	2.14	20	0.001	1
2TX					
WLAN: 2412-2462	17.18	5.15	20	0.034	1
WLAN: 5180-5240	19.26	6.20	20	0.070	1
WLAN: 5745-5825	19.22	5.33	20	0.057	1
WLAN: 5260-5320	19.11	5.69	20	0.060	1
WLAN: 5500-5700	19.15	4.86	20	0.050	1

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2.4GHz Band:
 1TX: Antenna gain: 2.14dBi
 2TX: Directional gain = 2.14dBi+10log(2)=5.15dBi
- 5.0GHz Band:
 2TX:
 5180-5240MHz: Directional gain = 3.19dBi+10log(2)=6.20dBi
 5745-5825MHz: Directional gain = 2.32dBi+10log(2)=5.33dBi
 5260-5320MHz: Directional gain = $10 \log\left[\frac{(10^{\text{Chain0}/20} + 10^{\text{Chain1}/20})^2}{2}\right] = 5.69\text{dBi}$
 5500-5700MHz: Directional gain = $10 \log\left[\frac{(10^{\text{Chain0}/20} + 10^{\text{Chain1}/20})^2}{2}\right] = 4.86\text{dBi}$
- WLAN 2.4GHz & WLAN 5GHz & BT LE cannot transmit simultaneously.

--- END ---