



# Standalone SAR test exclusion considerations: Tranceiver 1

Date: May 29, 2018

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm) <sup>Note</sup>	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm)	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
LE	-	2480.00	5.0	3.14	-0.29	0.9354	0.29	3.00

Note. Please refer to the operation description for Max. tune-up power.

### KDB 447498 D01 clausue 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances ≤ 50 mm

[ ( max. power of channel, including tune-up tolerance, mW ) / ( min. test separation distance, mm ) ] · [ √f(GHz) ] ≤ 3.0 for 1g SAR and ≤ 7.5 for 10g extremity SAR

#### Sample Calculation

$$= [ ( 0.9354\text{mW} / 5\text{mm} ) ] \times [ \sqrt{2.48\text{GHz}} ] = 0.29$$

Note. The calculation result was rounded to two decimal place for comparison.

**Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required**