

# FCC Test Report

**Applicant** : JMTek Industries( Shenzhen) Co.,Ltd

**Address** : 14G, Innovation Tech Building, Quanzhi  
Science and Technology innovation  
Park,ShaJing Street, Baoan District,  
ShenZhen, China

**Product Name** : Power Bank

**Report Date** : Dec. 20, 2023

**Shenzhen Anbotek Compliance Laboratory Limited**



# Contents

1. General Information .....	5
1.1. Client Information .....	5
1.2. Description of Device (EUT) .....	5
1.3. Auxiliary Equipment Used During Test .....	6
1.4. Description of Test Modes .....	6
1.5. Description Of Test Setup .....	7
1.6. Test Equipment List .....	8
1.7. Measurement Uncertainty .....	9
1.8. Description of Test Facility .....	9
1.9. Disclaimer .....	10
2. Summary of Test Results .....	11
3. Conducted Emission Test .....	12
3.1. Test Standard and Limit .....	12
3.2. Test Setup .....	12
3.3. Test Procedure .....	12
3.4. Test Data .....	12
4. Radiation Spurious Emission .....	15
4.1. Test Standard and Limit .....	15
4.2. Test Setup .....	15
4.3. Test Procedure .....	16
4.4. Test Data .....	16
5. Antenna Requirement .....	21
5.1. Test Standard and Requirement .....	21
5.2. Antenna Connected Construction .....	21
APPENDIX I -- TEST SETUP PHOTOGRAPH .....	22
APPENDIX II -- EXTERNAL PHOTOGRAPH .....	22
APPENDIX III -- INTERNAL PHOTOGRAPH .....	22



# TEST REPORT

Applicant : JMTEK Industries( Shenzhen) Co.,Ltd  
Manufacturer : JMTEK Industries( Shenzhen) Co.,Ltd  
Product Name : Power Bank  
Test Model No. : MPB500  
Reference Model No. : MPB500B, MPB500W  
Trade Mark : N/A  
Input: 5V $\Rightarrow$  3A, 9V $\Rightarrow$  2A, 12V $\Rightarrow$  1.5A  
Type-C Output: 5V $\Rightarrow$  3A, 9V $\Rightarrow$  2.22A, 12V $\Rightarrow$  1.67A  
Rating(s) : Wireless Output: 15W Max  
Type-C and Wireless Output: 5V $\Rightarrow$  3A  
Battery capacity: DC 3.85V, 5000mAh  
Test Standard(s) : **FCC Part15 Subpart C, Paragraph 15.209**  
Test Method(s) : **ANSI C63.10: 2020**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Nov. 13, 2023

Date of Test

Nov. 13~ 30, 2023

Prepared By

*Stella Zhu*

(Stella Zhu)

Approved &amp; Authorized Signer

*Edward Pan*

(Edward Pan)



### Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Dec. 20, 2023



## 1. General Information

### 1.1. Client Information

Applicant	:	JMTek Industries( Shenzhen) Co.,Ltd
Address	:	14G, Innovation Tech Building, Quanzhi Science and Technology innovation Park,ShaJing Street, Baoan District, ShenZhen, China
Manufacturer	:	JMTek Industries( Shenzhen) Co.,Ltd
Address	:	14G, Innovation Tech Building, Quanzhi Science and Technology innovation Park,ShaJing Street, Baoan District, ShenZhen, China
Factory	:	JMTek Industries( Shenzhen) Co.,Ltd
Address	:	14G, Innovation Tech Building, Quanzhi Science and Technology innovation Park,ShaJing Street, Baoan District, ShenZhen, China

### 1.2. Description of Device (EUT)

Product Name	:	Power Bank
Test Model No.	:	MPB500
Reference Model No.	:	MPB500B, MPB500W (Note: All samples are the same except the model number and appearance color and material of plastic shell material, so we prepare "MPB500" for test only.)
Trade Mark	:	N/A
Test Power Supply	:	DC 5V from Adapter input AC 120V/60Hz; DC 3.85V battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A

#### RF Specification

Operation Frequency	:	110.1-205kHz
Modulation Type	:	ASK
Antenna Type	:	Inductive loop coil Antenna
Antenna Gain(Peak)	:	0 dBi

**Remark:** 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



### 1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
Wireless charging load:	Manufacturer: Shenzhen Ouju Technology Co., Ltd. M/N: CD2577 Power: 5W/7.5W/10W/15W
Adapter:	Model: AD651P Output: 5V= 3A, 9V= 3A, 10V= 5A, 12V= 3A, 15V= 3A, 20V= 3.25A Input: 100-240V~1.5A, 50-60Hz

### 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	WPT Mode
Mode 2	charging Mode

For Conducted Emission	
Final Test Mode	Description
Mode 2	charging Mode



For Radiated Emission	
Final Test Mode	Description
Mode 1	WPT Mode
Mode 2	charging Mode

**Note:**

- (1) Test channel is 0.1378MHz.
- (2) All the situation(full load, half load and empty load) has been tested,only the worst situation (full load 15W) was recorded in the report.



## 1.5. Description Of Test Setup



### 1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 12, 2023	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 12, 2023	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 12, 2023	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 12, 2023	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 12, 2023	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 12, 2023	1 Year
10.	Horn Antenna	A-INFO	LB-180400- KF	J211060628	Oct. 12, 2023	1 Year
11.	Pre-amplifier	SONOMA	310N	186860	Oct. 12, 2023	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 12, 2023	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 12, 2023	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 12, 2023	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 20, 2023	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 16, 2023	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	101792	May. 26, 2023	1 Year





### 1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

### 1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.



**1.9. Disclaimer**

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



## 2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission Test	PASS
15.205/15.209	Spurious Emission	PASS




## 3. Conducted Emission Test

### 3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
 (2) The lower limit shall apply at the transition frequency.

### 3.2. Test Setup



### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.4. Test Data


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
 Operating Condition: Mode 2  
 Test Specification: DC 5V from Adapter input AC 120V/60Hz  
 Comment: Live Line  
 Temp.(°C)/Hum.(%RH): 23.5°C/65%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1580	31.85	19.83	51.68	65.56	-13.88	QP	
2	0.1860	18.62	19.83	38.45	54.21	-15.76	AVG	
3	0.5060	25.52	19.85	45.37	56.00	-10.63	QP	
4	0.5100	18.60	19.85	38.45	46.00	-7.55	AVG	
5	0.8420	23.64	19.86	43.50	56.00	-12.50	QP	
6	1.2500	23.63	19.84	43.47	56.00	-12.53	QP	
7	1.5300	14.57	19.84	34.41	46.00	-11.59	AVG	
8	1.5740	21.79	19.84	41.63	56.00	-14.37	QP	
9	1.8780	10.83	19.83	30.66	46.00	-15.34	AVG	
10	1.8940	20.66	19.83	40.49	56.00	-15.51	QP	
11	2.5500	11.61	19.84	31.45	46.00	-14.55	AVG	
12	3.5700	10.87	19.85	30.72	46.00	-15.28	AVG	



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
 Operating Condition: Mode 2  
 Test Specification: DC 5V from Adapter input AC 120V/60Hz  
 Comment: Neutral Line  
 Temp.(°C)/Hum.(%RH): 23.5°C/65%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1620	31.76	19.83	51.59	65.36	-13.77	QP	
2	0.1620	20.07	19.83	39.90	55.36	-15.46	AVG	
3	0.5100	14.73	19.85	34.58	46.00	-11.42	AVG	
4	0.8100	13.98	19.86	33.84	46.00	-12.16	AVG	
5	0.8900	24.94	19.86	44.80	56.00	-11.20	QP	
6	1.2860	25.11	19.84	44.95	56.00	-11.05	QP	
7	1.5339	14.83	19.84	34.67	46.00	-11.33	AVG	
8	1.5859	22.21	19.84	42.05	56.00	-13.95	QP	
9	1.8540	10.86	19.83	30.69	46.00	-15.31	AVG	
10	1.9460	19.76	19.83	39.59	56.00	-16.41	QP	
11	2.5579	18.32	19.84	38.16	56.00	-17.84	QP	
12	2.5579	11.31	19.84	31.15	46.00	-14.85	AVG	



## 4. Radiation Spurious Emission

### 4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		74.0	Peak	3	

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

### 4.4. Test Data

#### PASS


During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.





**Test Results (Between 9KHz – 150KHz)**

Test Mode: Mode 1  
 Distance: 3m  
 Power Source: DC 3.85V battery inside  
 Temp.(°C)/Hum.(%RH): 24.2°C/52%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor ( )	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	0.0295	12.48	20.49	32.97	118.06	-85.09	QP			
2	0.0323	6.87	20.56	27.43	117.27	-89.84	QP			
3	0.0353	12.21	20.47	32.68	116.51	-83.83	QP			
4	0.0589	4.32	20.37	24.69	112.09	-87.40	QP			
5	0.0884	-3.17	20.37	17.20	108.58	-91.38	QP			
6	0.1378	21.11	20.33	41.44	104.80	-63.36	QP			



**Test Results (Between 0.15MHz – 30MHz)**

Test Mode: Mode 1  
 Distance: 3m  
 Power Source: DC 3.85V battery inside  
 Temp.(°C)/Hum.(%RH): 24.2°C/52%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	0.1997	-1.68	20.31	18.63	101.55	-82.92	QP			
2	0.4564	7.77	20.27	28.04	94.41	-66.37	QP			
3	0.8897	1.24	20.26	21.50	68.63	-47.13	QP			
4	1.2892	-0.01	20.26	20.25	65.42	-45.17	QP			
5	1.6625	-1.48	20.27	18.79	63.22	-44.43	QP			
6	4.6469	-8.19	20.41	12.22	69.50	-57.28	QP			

**Remark:** According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.



**Test Results (Between 30MHz –1000 MHz)**


Test Mode: Mode 1  
 Distance: 3m  
 Power Source: DC 3.85V battery inside  
 Polarization: Horizontal  
 Temp.(°C)/Hum.(%RH): 21°C/56%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	46.0164	30.44	-15.31	15.13	40.00	-24.87	QP			
2	55.4147	32.69	-17.62	15.07	40.00	-24.93	QP			
3	135.0319	56.81	-22.79	34.02	43.50	-9.48	QP			
4	166.0680	50.94	-23.77	27.17	43.50	-16.33	QP			
5	419.1081	42.09	-15.89	26.20	46.00	-19.80	QP			
6	798.9797	42.86	-8.27	34.59	46.00	-11.41	QP			



Test Mode: Mode 1  
 Distance: 3m  
 Power Source: DC 3.85V battery inside  
 Polarization: Vertical  
 Temp.(°C)/Hum.(%RH): 21°C/56%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.7662	32.65	-16.23	16.42	40.00	-23.58	QP			
2	53.6932	40.10	-17.15	22.95	40.00	-17.05	QP			
3	78.1389	35.88	-19.52	16.36	40.00	-23.64	QP			
4	131.2965	58.48	-21.56	36.92	43.50	-6.58	QP			
5	404.6665	40.25	-14.37	25.88	46.00	-20.12	QP			
6	810.2654	39.38	-8.11	31.27	46.00	-14.73	QP			



## 5. Antenna Requirement

### 5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 5.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.



## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Please refer to separated files Appendix I -- Test Setup Photograph\_RF

## **APPENDIX II -- EXTERNAL PHOTOGRAPH**

Please refer to separated files Appendix II -- External Photograph

## **APPENDIX III -- INTERNAL PHOTOGRAPH**

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

