

# TEST REPORT

**Applicant:** Hunan Greatwall Computer System Co., Ltd  
**Address:** Hunan GreatWall Industrial Park, Xiangyun Middle Road, Tianyuan District, Zhuzhou, Hunan Province, China  
**Equipment Type:** LAPTOP  
**Model Name:** W15118GP  
**Brand Name:** GreatWall  
**FCC ID:** 2APUQ-W15118GP  
**Test Standard:** 47 CFR Part 15 Subpart C (refer to section 3.1)  
**Sample Arrival Date:** Feb. 28, 2024  
**Test Date:** Mar. 01, 2024 - Mar. 09, 2024  
**Date of Issue:** Apr. 10, 2024

**ISSUED BY:**

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie zhu

**Checked by:** Ye Hongji

**Approved by:** Liao Jianming  
(Technical Director)

*Julie zhu*

*Ye Hongji*

*Liao Jianming*

<b>Revision History</b>		
Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Apr. 10, 2024</u>	<u>Initial Issue</u>

## TABLE OF CONTENTS

1	GENERAL INFORMATION .....	4
1.1	Test Laboratory .....	4
1.2	Test Location .....	4
2	PRODUCT INFORMATION .....	5
2.1	Applicant Information .....	5
2.2	Manufacturer Information .....	5
2.3	General Description for Equipment under Test (EUT) .....	5
2.4	Technical Information .....	6
3	SUMMARY OF TEST RESULTS .....	8
3.1	Test Standards .....	8
3.2	Test Verdict .....	8
4	GENERAL TEST CONFIGURATIONS .....	9
4.1	Test Environments .....	9
4.2	Test Equipment List .....	9
4.3	Test Software List .....	9
4.4	Measurement Uncertainty .....	10
4.5	Description of Test Setup .....	10
4.6	Measurement Results Explanation Example .....	13
5	TEST ITEMS .....	14
5.1	Antenna Requirements .....	14
5.2	Frequency Hopping Systems .....	15
5.3	Number of Hopping Frequencies .....	17
5.4	Peak Output Power .....	18
5.5	Occupied Bandwidth .....	19

5.6	Carrier Frequency Separation .....	20
5.7	Time of Occupancy (Dwell time) .....	21
5.8	Conducted Spurious Emission & Authorized-band band-edge .....	23
5.9	Conducted Emission .....	24
5.10	Radiated Spurious Emission .....	25
5.11	Band Edge (Restricted-band band-edge).....	27
ANNEX A	TEST RESULT .....	28
A.1	Number of Hopping Frequency .....	28
A.2	Peak Output Power .....	29
A.3	20 dB and 99% bandwidth .....	32
A.4	Hopping Frequency Separation.....	37
A.5	Average Time of Occupancy .....	38
A.6	Conducted Spurious Emissions & Authorized-band band-edge .....	41
A.7	Conducted Emissions.....	48
A.8	Radiated Spurious Emission .....	50
A.9	Band Edge (Restricted-band band-edge).....	64
ANNEX B	TEST SETUP PHOTOS .....	68
ANNEX C	EUT EXTERNAL PHOTOS .....	68
ANNEX D	EUT INTERNAL PHOTOS .....	68

# 1 GENERAL INFORMATION

## 1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	Hunan Greatwall Computer System Co., Ltd
Address	Hunan GreatWall Industrial Park, Xiangyun Middle Road, Tianyuan District, Zhuzhou, Hunan Province, China

### 2.2 Manufacturer Information

Manufacturer	Hunan Greatwall Computer System Co., Ltd
Address	Hunan GreatWall Industrial Park, Xiangyun Middle Road, Tianyuan District, Zhuzhou, Hunan Province, China

### 2.3 General Description for Equipment under Test (EUT)

EUT Name	LAPTOP
Model Name Under Test	W15118GP
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	T140GR210
Software Version	23H1
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

## 2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11b, 802.11g, 802.11n
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Product Type	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	PIFA Antenna
Antenna Gain	4.84 dBi
Antenna Impedance	50 $\Omega$
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
<b>0</b>	<b>2402</b>	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	<b>78</b>	<b>2480</b>
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	<b>39</b>	<b>2441</b>	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

### 3 SUMMARY OF TEST RESULTS

#### 3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

#### 3.2 Test Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note <sup>1</sup>
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	ANNEX A.1	Pass	Note <sup>2</sup>
3	Peak Output Power	15.247(b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.3	Pass	--
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	ANNEX A.4	Pass	Note <sup>2</sup>
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	ANNEX A.5	Pass	Note <sup>2</sup>
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Hopping Mode; Low/Middle/High	ANNEX A.6	Pass	Note <sup>2</sup>
8	Conducted Emission	15.207	Low/Middle/High	ANNEX A.7	Pass	Note <sup>2</sup>
9	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	ANNEX A.8	Pass	Note <sup>2</sup>
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Low/High	ANNEX A.9	Pass	Note <sup>2</sup>

Note <sup>1</sup>: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note <sup>2</sup>:  $\pi/4$ -DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in  $\pi/4$ -DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.



## 4 GENERAL TEST CONFIGURATIONS

### 4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	47% to 69%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+21.0°C to +22.6°C
Working Voltage of the EUT	NV (Normal Voltage)	7.6 V

### 4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY50330200	2023.05.16	2024.05.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY52510065	2023.09.05	2024.09.04
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	01631	2022.02.23	2025.02.22
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2021.07.02	2024.07.01
Anechoic Chamber	RAINFORD	9m*6m*6m	144	2022.02.19	2024.09.03
Amplifier	COM-MV	LSCX_LNA1-12G-01	180602	2023.09.05	2024.09.04
Amplifier	COM-MV	XKu_LNA7-18G-01	180601	2023.09.05	2024.09.04
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2023.09.05	2024.09.04
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15
Amplifier	COM-MV	ZT30-1000M	B2018054558	2023.12.05	2024.12.04
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2021.08.15	2024.08.14
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2023.09.05	2024.09.04
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	9163-624	2021.08.20	2024.08.19
Amplifier	COM-MV	ZT30-1000M	B2017119082	2023.12.05	2024.12.04
Anechoic Chamber	RAINFORD	9m*6m*6m	101	2023.03.04	2026.03.03
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2023.09.05	2024.09.04
LISN	SCHWARZBECK	NSLK 8127	8127-687	2023.05.16	2024.05.15
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2022.02.19	2025.02.18

### 4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

### 4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%


### 4.5 Description of Test Setup

#### 4.5.1 For Antenna Port Test

$$\text{Conducted value (dBm)} = \text{Measurement value (dBm)} + \text{cable loss (dB)}$$

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

$$\text{Conducted value (dBm)} = 10 \text{ dBm} + 0.5 \text{ dB} = 10.5 \text{ dBm}$$



(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

#### 4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

#### 4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

## 4.6 Measurement Results Explanation Example

### 4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

## 5 TEST ITEMS

### 5.1 Antenna Requirements

#### 5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

#### 5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 5.2 Frequency Hopping Systems

### 5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).

Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.


Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.

For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.

Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

### 5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwidth and transmitted bandwidth are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.



## 5.3 Number of Hopping Frequencies

### 5.3.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

### 5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

### 5.3.4 Test Result

Please refer to ANNEX A.1.

## 5.4 Peak Output Power

### 5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

### 5.4.4 Test Result

Please refer to ANNEX A.2.

## 5.5 Occupied Bandwidth

### 5.5.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

### 5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

### 5.5.4 Test Result

Please refer to ANNEX A.3.

## 5.6 Carrier Frequency Separation

### 5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 5.6.4 Test Result

Please refer to ANNEX A.4.

## 5.7 Time of Occupancy (Dwell time)

### 5.7.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

Span: Zero span, centered on a hopping channel

RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where T is the expected dwell time per channel

Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel

Detector function: Peak

Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:

For GFSK and 8-DPSK:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For AFH Mode:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

{Period} = 0.4 s \* {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} \* (800 / 4) / {Number of Hopping Frequency} \* {Period}

{Period} = 0.4 s \* {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} \* (800 / 6) / {Number of Hopping Frequency} \* {Period}

{Period} = 0.4 s \* {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

#### 5.7.4 Test Result

Please refer to ANNEX A.5.

## 5.8 Conducted Spurious Emission & Authorized-band band-edge

### 5.8.1 Limit

#### FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

### 5.8.4 Test Result

Please refer to ANNEX A.6.

## 5.9 Conducted Emission

### 5.9.1 Limit

#### FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

### 5.9.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

### 5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

### 5.9.4 Test Result

Please refer to ANNEX A.7.



## 5.10 Radiated Spurious Emission

### 5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dB $\mu\text{V}/\text{m}$ ) = 20\*log[Field Strength ( $\mu\text{V}/\text{m}$ )].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

### 5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

#### 5.10.4 Test Result

Please refer to ANNEX A.8.

## 5.11 Band Edge (Restricted-band band-edge)

### 5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

### 5.11.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

### 5.11.4 Test Result

Please refer to ANNEX A.9.

# ANNEX A TEST RESULT


## A.1 Number of Hopping Frequency

### Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

### Test Plots

GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



## A.2 Peak Output Power

### Peak Power Test Data

Channel	Measured Output Peak Power						Limit		Verdict
	GFSK		$\pi/4$ -DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	7.23	5.28	8.30	6.76	8.86	7.69	21	125	Pass
Middle	6.92	4.92	7.98	6.28	8.57	7.19			Pass
High	7.00	5.01	8.12	6.49	8.61	7.26			Pass

Test Plots

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



$\pi/4$ -DQPSK LOW CHANNEL




$\pi/4$ -DQPSK MIDDLE CHANNEL




$\pi/4$ -DQPSK HIGH CHANNEL




8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



### A.3 20 dB and 99% bandwidth

#### Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.035000	0.904190
Middle	1.035000	0.901400
High	1.010000	0.901750
$\pi/4$ -DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.360000	1.197300
Middle	1.360000	1.199000
High	1.355000	1.191400
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.370000	1.193100
Middle	1.360000	1.193000
High	1.360000	1.193700




Test Plots

20 dB Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



π/4-DQPSK LOW CHANNEL



π/4-DQPSK MIDDLE CHANNEL



$\pi/4$ -DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



99% Bandwidth

GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL




GFSK HIGH CHANNEL




$\pi/4$ -DQPSK LOW CHANNEL



$\pi/4$ -DQPSK MIDDLE CHANNEL




**π/4-DQPSK HIGH CHANNEL**



**8-DPSK LOW CHANNEL**



**8-DPSK MIDDLE CHANNEL**



**8-DPSK HIGH CHANNEL**




## A.4 Hopping Frequency Separation

### Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.010	0.690	Pass
8-DPSK	1.030	0.913	Pass

### Test Plots

#### GFSK



#### 8-DPSK




## A.5 Average Time of Occupancy

### Test Data


GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38240	122.368	0.4	Pass
DH 3	1.61700	258.720	0.4	Pass
DH 5	2.88000	307.200	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
3DH 1	0.39000	124.800	0.4	Pass
3DH 3	1.63800	262.080	0.4	Pass
3DH 5	2.89100	308.373	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38240	61.184	0.4	Pass
DH 3	1.63800	131.040	0.4	Pass
DH 5	2.88000	153.600	0.4	Pass

Test Plots


GFSK DH1




GFSK DH3




GFSK DH5




8-DPSK 3DH1




8-DPSK 3DH3




### 8-DPSK 3DH5




### AFH Mode DH1



### AFH Mode DH3



### AFH Mode DH5






## A.6 Conducted Spurious Emissions & Authorized-band band-edge

### Test Data


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-36.95	6.76	-13.24	Pass
Middle	-36.78	6.46	-13.54	Pass
High	-36.50	6.60	-13.40	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-35.31	4.40	-15.61	Pass
Middle	-36.28	4.66	-15.34	Pass
High	-35.86	4.82	-15.18	Pass
Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-36.14	7.91	-12.09	Pass
8-DPSK	-35.39	7.94	-12.06	Pass

Test Plots

GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE




GFSK LOW CHANNEL, SPURIOUS

30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS


3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL, SPURIOUS  
3 GHz ~ 25 GHz




GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz



GFSK HIGH CHANNEL, SPURIOUS  
3 GHz ~ 25 GHz



8-DPSK LOW CHANNEL, CARRIER LEVEL




8-DPSK LOW CHANNEL, BAND EDGE




8-DPSK LOW CHANNEL, SPURIOUS

30 MHz ~ 3 GHz




8-DPSK LOW CHANNEL, SPURIOUS


3 GHz ~ 25 GHz




8-DPSK MIDDLE CHANNEL, CARRIER LEVEL




8-DPSK MIDDLE CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




8-DPSK MIDDLE CHANNEL, SPURIOUS  
3 GHz ~ 25 GHz




8-DPSK HIGH CHANNEL, CARRIER LEVEL




8-DPSK HIGH CHANNEL, BAND EDGE




8-DPSK HIGH CHANNEL, SPURIOUS  
30 MHz ~ 3 GHz




8-DPSK HIGH CHANNEL, SPURIOUS  
3 GHz ~ 25 GHz




### GFSK HOPPING, CARRIER LEVEL




### GFSK HOPPING BAND EDGE (LOW)




### GFSK HOPPING BAND EDGE (HIGH)




### GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz




### GFSK Hopping Mode, SPURIOUS 3GHz ~ 25 GHz




### 8-DPSK HOPPING, CARRIER LEVEL




### 8-DPSK Hopping BAND EDGE (LOW)




### 8-DPSK Hopping BAND EDGE (HIGH)



### 8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



### 8-DPSK Hopping Mode, SPURIOUS 3GHz ~ 25 GHz



## A.7 Conducted Emissions


Note <sup>1</sup>: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note <sup>2</sup>: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz ) shown here.

Note <sup>3</sup>: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

### Test Data and Plots


#### PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.248	50.92	9.77	61.82	10.90	Peak	L	Pass
1**	0.248	36.32	9.77	51.82	15.50	AV	L	Pass
2	0.498	48.50	9.98	56.03	7.53	Peak	L	Pass
2**	0.498	28.31	9.98	46.03	17.72	AV	L	Pass
3	0.888	46.56	10.27	56.00	9.44	Peak	L	Pass
3**	0.888	29.82	10.27	46.00	16.18	AV	L	Pass
4	1.396	46.54	9.75	56.00	9.46	Peak	L	Pass
4**	1.396	27.60	9.75	46.00	18.40	AV	L	Pass
5	24.574	40.99	10.83	60.00	19.01	Peak	L	Pass
5**	24.574	35.67	10.83	50.00	14.33	AV	L	Pass
6	28.570	42.70	10.93	60.00	17.30	Peak	L	Pass
6**	28.570	28.75	10.93	50.00	21.25	AV	L	Pass



PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.434	53.47	10.19	57.18	3.71	Peak	N	Pass
1**	0.434	36.97	10.19	47.18	10.21	AV	N	Pass
2	0.570	53.62	10.08	56.00	2.38	Peak	N	N/A
2*	0.570	50.53	10.08	56.00	5.47	QP	N	Pass
2**	0.570	37.12	10.08	46.00	8.88	AV	N	Pass
3	0.644	50.63	10.20	56.00	5.37	Peak	N	Pass
3**	0.644	36.33	10.20	46.00	9.67	AV	N	Pass
4	0.942	51.84	10.08	56.00	4.16	Peak	N	Pass
4**	0.942	37.42	10.08	46.00	8.58	AV	N	Pass
5	1.296	51.97	10.51	56.00	4.03	Peak	N	Pass
5**	1.296	38.79	10.51	46.00	7.21	AV	N	Pass
6	2.078	51.71	10.14	56.00	4.29	Peak	N	Pass
6**	2.078	35.95	10.14	46.00	10.05	AV	N	Pass

## A.8 Radiated Spurious Emission

Note <sup>1</sup>: The symbol of "--" in the table which means not application.

Note <sup>2</sup>: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note <sup>3</sup>: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.


Note <sup>4</sup>: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

### Test Data and Plots

#### 30 MHz to 1 GHz, ANT H


10m RE Test Case\_FCC Certification\_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	98.853	23.30	-30.70	33.0	9.70	Peak	202.00	200	Horizontal	Pass
2	201.405	22.34	-28.84	33.0	10.66	Peak	0.00	200	Horizontal	Pass
3	282.864	26.77	-25.56	35.5	8.73	Peak	0.00	200	Horizontal	Pass
4	241.650	25.21	-27.21	35.5	10.29	Peak	112.00	200	Horizontal	Pass
5	698.163	31.39	-15.12	35.5	4.11	Peak	260.00	100	Horizontal	Pass
6	888.963	31.63	-10.98	35.5	3.87	Peak	251.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case\_FCC Certification\_FCC 15C 30MHz-1GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	69.927	26.01	-28.43	29.5	3.49	Peak	360.00	123	Vertical	N/A
1*	69.927	23.64	-28.43	29.5	5.86	QP	360.00	123	Vertical	Pass
2	75.986	25.50	-29.26	29.5	4.00	Peak	350.00	155	Vertical	N/A
2*	75.986	22.36	-29.26	29.5	7.14	QP	350.00	155	Vertical	Pass
3	96.913	27.82	-31.07	33.0	5.18	Peak	0.00	100	Vertical	Pass
4	122.612	28.67	-28.05	33.0	4.33	Peak	295.00	100	Vertical	Pass
5	158.493	29.06	-25.87	33.0	3.94	Peak	279.00	100	Vertical	Pass
6	299.835	32.29	-24.97	35.5	3.21	Peak	360.00	200	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

**GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H**


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1592.800	49.74	-17.40	74.0	24.26	Peak	62.00	400	Horizontal	Pass
1**	1592.800	35.16	-17.40	54.0	18.84	AV	62.00	400	Horizontal	Pass
2	2402.100	103.74	-9.74	74.0	-29.74	Peak	230.00	100	Horizontal	N/A
2**	2402.100	103.44	-9.74	54.0	-49.44	AV	230.00	100	Horizontal	N/A
3	4919.800	51.47	-2.59	74.0	22.53	Peak	112.00	150	Horizontal	Pass
3**	4919.800	43.11	-2.59	54.0	10.89	AV	112.00	150	Horizontal	Pass
4	6618.800	54.52	0.47	74.0	19.48	Peak	112.00	200	Horizontal	Pass
4**	6618.800	45.67	0.47	54.0	8.33	AV	112.00	200	Horizontal	Pass
5	13312.800	55.75	0.87	74.0	18.25	Peak	0.00	150	Horizontal	Pass
5**	13312.800	46.33	0.87	54.0	7.67	AV	0.00	150	Horizontal	Pass
6	16069.313	56.26	1.31	74.0	17.74	Peak	355.00	100	Horizontal	Pass
6**	16069.313	46.53	1.31	54.0	7.47	AV	355.00	100	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.300	45.45	-17.45	74.0	28.55	Peak	73.00	400	Vertical	Pass
1**	1599.300	36.33	-17.45	54.0	17.67	AV	73.00	400	Vertical	Pass
2	2402.200	96.25	-9.74	74.0	-22.25	Peak	11.00	100	Vertical	N/A
2**	2402.200	95.88	-9.74	54.0	-41.88	AV	11.00	100	Vertical	N/A
3	4804.600	51.86	-2.78	74.0	22.14	Peak	360.00	200	Vertical	Pass
3**	4804.600	42.74	-2.78	54.0	11.26	AV	360.00	200	Vertical	Pass
4	6088.400	55.05	-1.26	74.0	18.95	Peak	217.00	300	Vertical	Pass
4**	6088.400	43.78	-1.26	54.0	10.22	AV	217.00	300	Vertical	Pass
5	13456.650	55.71	0.66	74.0	18.29	Peak	347.00	150	Vertical	Pass
5**	13456.650	46.18	0.66	54.0	7.82	AV	347.00	150	Vertical	Pass
6	15799.200	56.61	2.31	74.0	17.39	Peak	265.00	200	Vertical	Pass
6**	15799.200	46.54	2.31	54.0	7.46	AV	265.00	200	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1592.700	49.35	-17.40	74.0	24.65	Peak	55.00	300	Horizontal	Pass
1**	1592.700	37.68	-17.40	54.0	16.32	AV	55.00	300	Horizontal	Pass
2	2440.900	100.19	-12.38	74.0	-26.19	Peak	231.00	200	Horizontal	N/A
2**	2440.900	99.66	-12.38	54.0	-45.66	AV	231.00	200	Horizontal	N/A
3	4981.800	51.81	-1.61	74.0	22.19	Peak	294.00	150	Horizontal	Pass
3**	4981.800	43.03	-1.61	54.0	10.97	AV	294.00	150	Horizontal	Pass
4	6807.000	54.90	2.15	74.0	19.10	Peak	159.00	100	Horizontal	Pass
4**	6807.000	45.67	2.15	54.0	8.33	AV	159.00	100	Horizontal	Pass
5	13438.012	55.85	0.45	74.0	18.15	Peak	199.00	150	Horizontal	Pass
5**	13438.012	46.61	0.45	54.0	7.39	AV	199.00	150	Horizontal	Pass
6	17411.213	55.82	3.49	74.0	18.18	Peak	56.00	100	Horizontal	Pass
6**	17411.213	46.81	3.49	54.0	7.19	AV	56.00	100	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.400	49.38	-17.19	74.0	24.62	Peak	102.00	400	Vertical	Pass
1**	1597.400	33.77	-17.19	54.0	20.23	AV	102.00	400	Vertical	Pass
2	2440.900	94.12	-12.38	74.0	-20.12	Peak	4.00	100	Vertical	N/A
2**	2440.900	93.47	-12.38	54.0	-39.47	AV	4.00	100	Vertical	N/A
3	3727.200	47.96	-4.98	74.0	26.04	Peak	175.00	150	Vertical	Pass
3**	3727.200	44.66	-4.98	54.0	9.34	AV	175.00	150	Vertical	Pass
4	6801.600	54.70	1.49	74.0	19.30	Peak	268.00	300	Vertical	Pass
4**	6801.600	45.42	1.49	54.0	8.58	AV	268.00	300	Vertical	Pass
5	13319.099	55.51	0.90	74.0	18.49	Peak	225.00	150	Vertical	Pass
5**	13319.099	46.23	0.90	54.0	7.77	AV	225.00	150	Vertical	Pass
6	17474.474	56.33	2.83	74.0	17.67	Peak	18.00	100	Vertical	Pass
6**	17474.474	46.69	2.83	54.0	7.31	AV	18.00	100	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.300	47.60	-17.08	74.0	26.40	Peak	49.00	300	Horizontal	Pass
1**	1596.300	40.21	-17.08	54.0	13.79	AV	49.00	300	Horizontal	Pass
2	2479.900	99.98	-11.32	74.0	-25.98	Peak	298.00	200	Horizontal	N/A
2**	2479.900	99.30	-11.32	54.0	-45.30	AV	298.00	200	Horizontal	N/A
3	4798.400	51.60	-2.84	74.0	22.40	Peak	258.00	100	Horizontal	Pass
3**	4798.400	42.71	-2.84	54.0	11.29	AV	258.00	100	Horizontal	Pass
4	6618.000	55.85	0.38	74.0	18.15	Peak	116.00	300	Horizontal	Pass
4**	6618.000	45.01	0.38	54.0	8.99	AV	116.00	300	Horizontal	Pass
5	13323.825	56.07	0.92	74.0	17.93	Peak	193.00	150	Horizontal	Pass
5**	13323.825	47.14	0.92	54.0	6.86	AV	193.00	150	Horizontal	Pass
6	17472.637	56.48	2.86	74.0	17.52	Peak	74.00	100	Horizontal	Pass
6**	17472.637	47.30	2.86	54.0	6.70	AV	74.00	100	Horizontal	Pass



GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.200	47.20	-17.17	74.0	26.80	Peak	113.00	200	Vertical	Pass
1**	1597.200	37.29	-17.17	54.0	16.71	AV	113.00	200	Vertical	Pass
2	2479.900	93.36	-11.32	74.0	-19.36	Peak	5.00	150	Vertical	N/A
2**	2479.900	92.73	-11.32	54.0	-38.73	AV	5.00	150	Vertical	N/A
3	3727.400	46.27	-4.94	74.0	27.73	Peak	19.00	150	Vertical	Pass
3**	3727.400	43.28	-4.94	54.0	10.72	AV	19.00	150	Vertical	Pass
4	6404.800	54.32	-0.67	74.0	19.68	Peak	117.00	400	Vertical	Pass
4**	6404.800	44.70	-0.67	54.0	9.30	AV	117.00	400	Vertical	Pass
5	13435.912	56.00	0.43	74.0	18.00	Peak	347.00	150	Vertical	Pass
5**	13435.912	46.35	0.43	54.0	7.65	AV	347.00	150	Vertical	Pass
6	17427.751	56.38	3.53	74.0	17.62	Peak	76.00	300	Vertical	Pass
6**	17427.751	47.95	3.53	54.0	6.05	AV	76.00	300	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1591.500	50.48	-17.33	74.0	23.52	Peak	63.00	300	Horizontal	Pass
1**	1591.500	41.35	-17.33	54.0	12.65	AV	63.00	300	Horizontal	Pass
2	2402.000	102.84	-9.74	74.0	-28.84	Peak	236.00	100	Horizontal	N/A
2**	2402.000	100.58	-9.74	54.0	-46.58	AV	236.00	100	Horizontal	N/A
3	4980.400	52.09	-1.58	74.0	21.91	Peak	96.00	150	Horizontal	Pass
3**	4980.400	43.29	-1.58	54.0	10.71	AV	96.00	150	Horizontal	Pass
4	6609.600	55.47	0.47	74.0	18.53	Peak	62.00	300	Horizontal	Pass
4**	6609.600	46.72	0.47	54.0	7.28	AV	62.00	300	Horizontal	Pass
5	13383.937	55.71	0.63	74.0	18.29	Peak	36.00	150	Horizontal	Pass
5**	13383.937	46.60	0.63	54.0	7.40	AV	36.00	150	Horizontal	Pass
6	17421.449	56.44	3.72	74.0	17.56	Peak	274.00	300	Horizontal	Pass
6**	17421.449	48.10	3.72	54.0	5.90	AV	274.00	300	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.800	47.75	-17.23	74.0	26.25	Peak	307.00	200	Vertical	Pass
1**	1597.800	36.58	-17.23	54.0	17.42	AV	307.00	200	Vertical	Pass
2	2402.000	97.45	-9.74	74.0	-23.45	Peak	12.00	100	Vertical	N/A
2**	2402.000	94.39	-9.74	54.0	-40.39	AV	12.00	100	Vertical	N/A
3	4999.400	51.87	-2.41	74.0	22.13	Peak	30.00	100	Vertical	Pass
3**	4999.400	41.99	-2.41	54.0	12.01	AV	30.00	100	Vertical	Pass
4	6809.400	55.50	1.56	74.0	18.50	Peak	87.00	300	Vertical	Pass
4**	6809.400	45.22	1.56	54.0	8.78	AV	87.00	300	Vertical	Pass
5	13374.224	55.72	0.68	74.0	18.28	Peak	302.00	150	Vertical	Pass
5**	13374.224	45.76	0.68	54.0	8.24	AV	302.00	150	Vertical	Pass
6	17424.337	56.44	3.64	74.0	17.56	Peak	96.00	200	Vertical	Pass
6**	17424.337	47.34	3.64	54.0	6.66	AV	96.00	200	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.700	47.17	-17.22	74.0	26.83	Peak	51.00	300	Horizontal	Pass
1**	1597.700	37.53	-17.22	54.0	16.47	AV	51.00	300	Horizontal	Pass
2	2441.100	101.23	-12.38	74.0	-27.23	Peak	230.00	150	Horizontal	N/A
2**	2441.100	98.13	-12.38	54.0	-44.13	AV	230.00	150	Horizontal	N/A
3	3717.200	46.08	-5.49	74.0	27.92	Peak	150.00	150	Horizontal	Pass
3**	3717.200	42.91	-5.49	54.0	11.09	AV	150.00	150	Horizontal	Pass
4	4966.400	51.54	-1.79	74.0	22.46	Peak	0.00	200	Horizontal	Pass
4**	4966.400	42.92	-1.79	54.0	11.08	AV	0.00	200	Horizontal	Pass
5	13319.625	55.98	0.90	74.0	18.02	Peak	271.00	150	Horizontal	Pass
5**	13319.625	47.26	0.90	54.0	6.74	AV	271.00	150	Horizontal	Pass
6	15850.387	56.38	1.32	74.0	17.62	Peak	93.00	200	Horizontal	Pass
6**	15850.387	47.02	1.32	54.0	6.98	AV	93.00	200	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1594.700	47.45	-17.33	74.0	26.55	Peak	127.00	100	Vertical	Pass
1**	1594.700	33.05	-17.33	54.0	20.95	AV	127.00	100	Vertical	Pass
2	2441.000	95.19	-12.38	74.0	-21.19	Peak	2.00	150	Vertical	N/A
2**	2441.000	91.88	-12.38	54.0	-37.88	AV	2.00	150	Vertical	N/A
3	3727.200	48.90	-4.98	74.0	25.10	Peak	108.00	150	Vertical	Pass
3**	3727.200	42.83	-4.98	54.0	11.17	AV	108.00	150	Vertical	Pass
4	5400.000	51.23	-1.92	74.0	22.77	Peak	211.00	150	Vertical	Pass
4**	5400.000	46.67	-1.92	54.0	7.33	AV	211.00	150	Vertical	Pass
5	12212.088	53.22	1.09	74.0	20.78	Peak	137.00	100	Vertical	Pass
5**	12212.088	43.41	1.09	54.0	10.59	AV	137.00	100	Vertical	Pass
6	17407.801	56.12	3.39	74.0	17.88	Peak	55.00	400	Vertical	Pass
6**	17407.801	47.46	3.39	54.0	6.54	AV	55.00	400	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1598.400	48.13	-17.31	74.0	25.87	Peak	50.00	100	Horizontal	Pass
1**	1598.400	32.77	-17.31	54.0	21.23	AV	50.00	100	Horizontal	Pass
2	2480.000	100.81	-11.30	74.0	-26.81	Peak	296.00	100	Horizontal	N/A
2**	2480.000	98.18	-11.30	54.0	-44.18	AV	296.00	100	Horizontal	N/A
3	4874.600	51.91	-2.66	74.0	22.09	Peak	179.00	150	Horizontal	Pass
3**	4874.600	43.79	-2.66	54.0	10.21	AV	179.00	150	Horizontal	Pass
4	6153.400	54.44	0.38	74.0	19.56	Peak	235.00	100	Horizontal	Pass
4**	6153.400	45.62	0.38	54.0	8.38	AV	235.00	100	Horizontal	Pass
5	13395.225	55.74	0.63	74.0	18.26	Peak	260.00	150	Horizontal	Pass
5**	13395.225	46.16	0.63	54.0	7.84	AV	260.00	150	Horizontal	Pass
6	15515.175	56.47	1.40	74.0	17.53	Peak	57.00	200	Horizontal	Pass
6**	15515.175	46.75	1.40	54.0	7.25	AV	57.00	200	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case\_FCC Part 15C\_FCC 15.247(2.4G)\_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1595.600	46.46	-17.16	74.0	27.54	Peak	97.00	400	Vertical	Pass
1**	1595.600	32.47	-17.16	54.0	21.53	AV	97.00	400	Vertical	Pass
2	2480.100	95.03	-11.29	74.0	-21.03	Peak	4.00	200	Vertical	N/A
2**	2480.100	92.23	-11.29	54.0	-38.23	AV	4.00	200	Vertical	N/A
3	3713.800	46.37	-5.17	74.0	27.63	Peak	85.00	150	Vertical	Pass
3**	3713.800	42.72	-5.17	54.0	11.28	AV	85.00	150	Vertical	Pass
4	4867.000	51.62	-2.53	74.0	22.38	Peak	307.00	100	Vertical	Pass
4**	4867.000	43.24	-2.53	54.0	10.76	AV	307.00	100	Vertical	Pass
5	13325.400	56.83	0.93	74.0	17.17	Peak	136.00	200	Vertical	Pass
5**	13325.400	46.53	0.93	54.0	7.47	AV	136.00	200	Vertical	Pass
6	15846.187	55.97	1.36	74.0	18.03	Peak	198.00	150	Vertical	Pass
6**	15846.187	46.54	1.36	54.0	7.46	AV	198.00	150	Vertical	Pass

## A.9 Band Edge (Restricted-band band-edge)

Note <sup>1</sup>: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Note <sup>2</sup>: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note <sup>3</sup>: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note <sup>4</sup>: The Level (dBuV/m) has been corrected by factor.

### Test Data and Plots


#### GFSK LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2352.400	58.19	1.22	74.0	15.81	Peak	196.00	150	Horizontal	Pass
1**	2352.400	45.88	1.22	54.0	8.12	AV	196.00	150	Horizontal	Pass
2	2389.950	55.24	1.92	74.0	18.76	Peak	246.00	100	Horizontal	Pass
2**	2389.950	45.93	1.92	54.0	8.07	AV	246.00	100	Horizontal	Pass




**GFSK HIGH CHANNEL**




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.560	56.69	2.11	74.0	17.31	Peak	97.00	100	Horizontal	Pass
1**	2483.560	46.44	2.11	54.0	7.56	AV	97.00	100	Horizontal	Pass
2	2484.910	57.75	2.07	74.0	16.25	Peak	1.00	200	Horizontal	Pass
2**	2484.910	46.41	2.07	54.0	7.59	AV	1.00	200	Horizontal	Pass

8-DPSK LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2321.750	58.31	1.62	74.0	15.69	Peak	206.00	100	Horizontal	Pass
1**	2321.750	46.44	1.62	54.0	7.56	AV	206.00	100	Horizontal	Pass
2	2389.950	55.54	1.92	74.0	18.46	Peak	194.00	100	Horizontal	Pass
2**	2389.950	45.98	1.92	54.0	8.02	AV	194.00	100	Horizontal	Pass

8-DPSK HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.560	56.48	2.11	74.0	17.52	Peak	57.00	150	Horizontal	Pass
1**	2483.560	46.37	2.11	54.0	7.63	AV	57.00	150	Horizontal	Pass
2	2495.875	58.49	1.71	74.0	15.51	Peak	67.00	200	Horizontal	Pass
2**	2495.875	46.00	1.71	54.0	8.00	AV	67.00	200	Horizontal	Pass

## **ANNEX B TEST SETUP PHOTOS**

Please refer the document “BL-SZ2420611-AR.PDF”.

## **ANNEX C EUT EXTERNAL PHOTOS**

Please refer the document “BL-SZ2420611-AW.PDF”.

## **ANNEX D EUT INTERNAL PHOTOS**

Please refer the document “BL-SZ2420611-AI.PDF”.

## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--