


SW10  Wireless Remote Switch	Product Overview Removable Face Plate Light Status On/Off Button(Reset Button) Indicator Light Turn On/Parking Turn Off	Parameters Vocal 9999s Output 15A (MAX) WIFI Frequency 2.4G Modul SMD Wireless remote TX 915MHz Wireless remote switch 1. 3.5mm x 1 2. 2.8mm x 1 3. SMD Indicator 4. SMD wall bracket 5. Face Plate 6. Screw * 4 7. 3M Adhesive 8. User manual Before you install WARNING: RISK OF ELECTRIC SHOCK Incorrect installation could be dangerous or fatal. Multiple warnings may need to be displayed for early installation. Please call a professional electrician if you are unfamiliar or uncomfortable with electrical work.	Make sure your wiring is compatible. The Gosund light switch replaces single pole switches only. If your light can be turned on from two different wall switches, that's a 3-way switch and Gosund light switch is not compatible. Step 1: Shut OFF the power at the circuit breaker for the switch you are replacing. You may want to shut OFF more than one circuit breaker/switch to make sure the switch you're working on is powered OFF. IMPORTANT! USE A VOLT CONTACT VOLTAGE DETECTOR OR FLIP YOUR LIGHT SWITCH A FEW TIMES TO MAKE SURE THAT THE POWER IS OFF. Step 2: Unscrew and disconnect the wires from the old switch using a screw driver. Step 3: Identify the wires on your device as follows.	 Step 4: Install the Gosund Light Switch. Connect two wires from the Gosund Light Switch to the available Device Line(s) and neutral wire. In case you found more than one wire, just place them into this wire hub. NOTE: The wire put in the cap-like object connecting the wires. Step 5: If you have a Gosund wire (optional), disconnected from the old switch and connect to the green wire on the Gosund Light Switch.	Step 6: Unscrew the wire nut that is holding together the existing Neutral wires. Connect the white wire from the Gosund Light Switch to the outlet's exposed Neutral wires. Securely screw them together inside the wire nut. How to pair with the Gosund App? 1. Download the Gosund app from the App Store/Google Play or via QR code below. 2. Scan Gosund's QR code and wait for a "Join in the app" prompt and the "Go to Pair" button. 3. Follow on-screen instructions to complete the connection.  Connect with switch! Unplug the profile of the switch from the main power LED lights indicating the device is in the pairing state. After the pairing status of 10MHz once, green LED of the switch is started lighting.	Connect with your cellphone The first connection requires S4S. If you have connected the S2 remote, you should disconnect S3 releases firstly. A. For Easy Mode Connection-Green Indicator Light Blinking Quickly ---> Confirm that the smart switch is well installed ---> "OpenGosund App"--->Choose the "+" symbol. ---> "Switch"  ---> Confirm the light status on your switch and follow the APP's guide. (If you don't see green light quickly blinking, press ON/OFF button to reset). ---> Set a unique name for this smart switch, choose the room location.
--	--	--	--	---	---	--

料号: 4.02.000.0425 V2.0

名称: SW5-A gosund说明书

材质: 105克哑粉纸 (四菱形)

尺寸: 80X100mm