

Frequency ID	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
Frequency (MHz)	2400.0	2405.0	2410.0	2415.0	2420.0	2425.0	2430.0	2435.0	2440.0	2445.0	2450.0	2455.0	2460.0	2465.0	2470.0	2475.0	2480.0	2485.0	2490.0	2495.0	2500.0
Efficiency (dBi)	-6.09	-5.99	-6.08	-6.20	-6.19	-6.17	-6.20	-6.14	-6.05	-5.99	-5.99	-5.99	-5.97	-5.89	-5.91	-5.98	-5.98	-6.00	-6.10	-6.10	-6.03
Gain (dBi)	0.66	0.72	0.60	0.48	0.51	0.54	0.50	0.55	0.61	0.65	0.62	0.57	0.54	0.55	0.47	0.40	0.39	0.38	0.27	0.23	0.28
Efficiency (%)	24.59	25.15	24.66	23.99	24.05	24.15	23.97	24.30	24.85	25.17	25.20	25.15	25.31	25.75	25.62	25.23	25.25	25.10	24.56	24.53	24.93
Directivity (dB)	6.75	6.71	6.68	6.68	6.70	6.72	6.71	6.69	6.66	6.64	6.61	6.57	6.50	6.44	6.39	6.38	6.37	6.39	6.37	6.34	6.31
Peak Gain Position (Theta)	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00	170.00
Peak Gain Position (Phi)	308.00	308.00	308.00	307.00	307.00	307.00	307.00	306.00	306.00	306.00	306.00	306.00	305.00	305.00	305.00	304.00	304.00	304.00	303.00	303.00	303.00
Efficiency ThetaPol (%)	10.76	11.02	10.82	10.57	10.63	10.67	10.60	10.79	11.01	11.11	11.14	11.13	11.20	11.43	11.44	11.29	11.30	11.26	11.08	11.04	11.21
Efficiency PhiPol (%)	13.83	14.13	13.84	13.42	13.42	13.47	13.37	13.51	13.85	14.06	14.06	14.03	14.10	14.32	14.19	13.94	13.95	13.84	13.48	13.49	13.72
Upper Hem. Efficiency (%)	10.70	10.93	10.70	10.40	10.40	10.43	10.33	10.45	10.64	10.75	10.75	10.72	10.77	10.96	10.92	10.77	10.80	10.77	10.55	10.52	10.68
Lower Hem. Efficiency (%)	13.89	14.22	13.96	13.59	13.65	13.72	13.64	13.85	14.21	14.42	14.45	14.43	14.53	14.79	14.71	14.46	14.45	14.34	14.01	14.01	14.25
T90(H)圆度	10.29	10.63	11.09	11.50	12.01	12.27	12.42	12.50	12.14	11.89	11.55	11.34	11.06	11.07	10.96	11.10	11.15	11.39	11.70	12.00	12.21
Gain 15deg (dBi)																					
E1(XZ)波瓣宽度	17.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	18.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00	48.00
E1(XZ)前后比	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.05
E2(YZ)波瓣宽度	17.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00	17.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00	17.00	17.00
E2(YZ)前后比	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
最大增益处轴比(P)	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50
仰角10度最差(大)轴比(P)	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50	1.50
Hc(XY)波瓣宽度	127.00	127.00	127.00	127.00	127.00	126.00	126.00	125.00	127.00	127.00	129.00	130.00	132.00	132.00	134.00	136.00	137.00	137.00	137.00	138.00	138.00
Hc(XY)前后比	1.09	1.25	1.47	1.66	1.84	1.88	1.89	1.88	1.87	1.84	1.67	1.48	1.32	1.31	1.28	1.41	1.52	1.73	1.92	2.12	2.19
Empty																					

Manufacturer's Name ： ShenZhen CuCo Smart Technology Co., Ltd.
Address ： Room 201,301, Building A, No.12 Difu Road, Guxing
Community, Xixiang Street, Bao'an District ,Shenzhen, Guangdong,China
518000





