



FCC RF EXPOSURE REPORT

For

Smart Home Camera

MODEL NUMBER: CS-H6, CS-H6 (4WF, 4mm), CS-H6-R100-1J4WF

REPORT NUMBER: 4790559314-RF-7

ISSUE DATE: September 27, 2022

FCC ID:2APV2-CSH61J4

Prepared for

Hangzhou Ezviz Software Co., Ltd.
Room 302,Unit B,Building 2,No. 399,Danfeng Road Binjiang District 310052
Hangzhou China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4790559314-RF-7 Page 2 of 7

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	09/27/2022	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	. 4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
1	REQUIREMENT	G



REPORT NO.: 4790559314-RF-7 Page 4 of 7

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Hangzhou Ezviz Software Co., Ltd.

Address: Room 302, Unit B, Building 2,399 Danfeng Road, Binjiang

District, Hangzhou, Zhejiang

Manufacturer Information

Company Name: Hangzhou Ezviz Software Co., Ltd.

Address: Room 302, Unit B, Building 2,399 Danfeng Road, Binjiang

District, Hangzhou, Zhejiang

EUT Information

Operations Manager

EUT Name: Smart Home Camera

Model: CS-H6, CS-H6 (4WF, 4mm), CS-H6-R100-1J4WF

Model Difference: All the same except for the model name.

Brand: EZVIZ

Sample Received Date: September 9, 2022

Sample Status: Normal Sample ID: 5321647

Date of Tested: September 12, 2022 ~ September 26, 2022

APPLICABLE STANDARDS				
STANDARD TEST RESULTS				
FCC 47CFR§2.1091	PASS			

FCC 4/CFR92.1091	PA33	
Prepared By:	Checked By:	
Danny Grany	kebo. zhanz	
Denny Huang	Kebo Zhang	
Senior Project Engineer	Senior Project E	ngineer
Approved By:		
Stephenono		
Stephen Guo		



REPORT NO.: 4790559314-RF-7 Page 5 of 7

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187)
Accreditation Certificate	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.

REPORT NO.: 4790559314-RF-7 Page 6 of 7

4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

 $S=PG/4\pi R^2$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

REPORT NO.: 4790559314-RF-7 Page 7 of 7

CALCULATED RESULTS

Worst Case					
Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm2	mW/cm2	
WIFI 2.4G	15	3.83	0.009	1.0	Complies

Worst Case					
Mode	Output Power	Antenna Gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm2	mW/cm2	
WIFI 5G	16	3.39	0.011	1.0	Complies

Note:

- 1. The Power comes from report operation description.
- 2. The EUT cannot support simultaneous emission.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 3. Calculate by WORST-CASE mode.

END OF REPORT