

Report No.: SHEM181000947201

Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.: SHEM1906014567CR

FCC ID: 2APV2-CSK3A **IC:** 23928-CSK3A

Applicant: Hangzhou Ezviz Software Co., Ltd.

Address of Applicant: Floor 16, Unit B, Building 1, No. 555, Qianmo Road, Binjiang District,

Hangzhou City, Zhejiang Province

Manufacturer: Hangzhou Ezviz Software Co., Ltd.

Address of Manufacturer: Floor 16, Unit B, Building 1, No. 555, Qianmo Road, Binjiang District,

Hangzhou City, Zhejiang Province

Factory: Hangzhou Hikvision Electronics Co., Ltd.

Address of Factory: No. 299, Qiushi Road, Tonglu Economic Development Zone, Tonglu

County, Hangzhou.

Equipment Under Test (EUT):

EUT Name: Smart Wireless Alarm Panel

Model No.:CS-K3-AAdd Model No.:CS-K3-CTrade mark:eZVIZ

Standard(s): RSS-102 Issue 5 (March 2015)

Date of Receipt: 2019-06-25

Date of Test: 2019-06-26 to 2019-07-01

Date of Issue: 2019-08-07

Test Result: Pass*

parlan shaw

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

检验检测专用章 inspection & Testing Services for the Lectural Services and the Lecture Serv

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions or Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction is suses defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM181000947201

Page: 2 of 7

Revision Record						
Version	Description	Date	Remark			
00	Original	2019-08-07	/			
			1			

Authorized for issue by:		
	Vincent Zhu	
	Vincent Zhu / Project Engineer	
	Parlam Zhan	
	Parlam Zhan /Reviewer	



Report No.: SHEM181000947201

Page: 3 of 7

2 Contents

		P	'age
1	C	COVER PAGE	1
2	C	CONTENTS	3
3	G	GENERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	DETAILS OF E.U.T.	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	Т	TEST STANDARDS AND LIMITS	6
	4.1	IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS	6
5	N	MEASUREMENT AND CALCULATION	7
	5.1	MAXIMUM TRANSMIT POWER	7
	5.2	MDE CALCULATION	7



Report No.: SHEM181000947201

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

o.i deneral bescription of E.O.i.		
Power supply:	DC 5V by adapter	
	Adapter:	
	Model.:ADS-5RE-06 05050EPCU/EPC	
	Input:100~240V~50/60Hz 150mA	
	Battery:	
	Rechargeable Li-ion battery 3.7V 2000mAh	
Test voltage:	AC 120V 60Hz	
Cable:	DC Cable 1.5m for adapter	

3.2 Details of E.U.T.

Antenna Type	PCB Antenna
Modulation Type	FSK
Number of Channels	1
Operation Frequency	915MHz
Antenna Gain:	-1dBi



Report No.: SHEM181000947201

Page: 5 of 7

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC –Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB identifier: CN0020.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM181000947201

Page: 6 of 7

4 Test Standards and Limits

4.1 IC Radiofrequency radiation exposure limits

According RSS-102 Table 4(RF Field Strength Limits for Devices Used by the General Public)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m²)	Reference Period (minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

Note: f is frequency in MHz.

Based on nerve stimulation (NS).

** Based on specific absorption rate (SAR).

For 915MHz Devices RF Field Strength Limits is 32.29V/m



Report No.: SHEM181000947201

Page: 7 of 7

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM190601456701

Frequency	Read Level	Factor	Level	Limit Line	Over Limit	Polarization	
(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)		
	106.52	-14.04	92.48	94.00	-1.52	Horizontal	
915	101.06	-14.04	87.02	94.00	-6.98	Vertical	

5.2 MPE Calculation

For 915MHz: 92.48dBuV/m=0.042V/m < 32.29V/m

So the device is exclusion from SAR test.

-- End of the Report--