

## RF Exposure Analysis

**FCC ID: 2APV7-AVA02**

### Analysis for FCC portable use – Ava Fertility Tracker

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The maximum conducted output power for the device is 1 dBm (1.3mW).

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$$(1.3\text{mW} / 5 \text{ mm}) \times \sqrt{2.45 \text{ GHz}} = 0.4 \text{ (i.e.: } \leq 3.0 \text{ for 1-g SAR)}$$

This demonstrates the device meets the criteria for 1-g head/ body SAR test exemption.

### **Conclusion**

The Scanner is exempt from SAR testing and can be used for Portable applications.

Philipp Tholen  
VP Product and Operations

Signature: 

Date: 15/8/2018