



Test Report No.: FM190730N011



RF EXPOSURE REPORT

Applicant	Zultys, Inc.
Address	785 Lucerne Drive, Sunnyvale, CA 94085, USA

Manufacturer or Supplier	Zultys, Inc.
Address	785 Lucerne Drive, Sunnyvale, CA 94085, USA
Product	Gigabit SIP IP Phone
Brand Name	ZULTYS
Model	ZIP 45GW
Additional Model & Model Difference	N/A
Date of tests	Jul. 30, 2019 ~ Aug. 15, 2019

- FCC Part 2 (Section 2.1091)
- KDB 447498 D01
- IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Andy Zhu Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Sep. 16, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: FM190730N011

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION.....	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM190730N011

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM190730N011	Original release	Sep. 16, 2019

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: FM190730N011

1. CERTIFICATION

PRODUCT: Gigabit SIP IP Phone
BRAND NAME: ZULTYS
MODEL NO.: ZIP 45GW
ADDITIONAL MODEL: N/A
FCC ID: 2APWA-ZIP45GW
TEST SAMPLE: ENGINEERING SAMPLE
APPLICANT: Zultys, Inc.
TESTED DATES: Jul. 30, 2019 ~ Aug. 15, 2019
STANDARDS: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Frequency Band	Antenna Gain (dBi)	Antenna Type
BT 2.4GHz	3.31	FPC Antenna
Wi-Fi 2.4GHz	3.31	FPC Antenna
Wi-Fi 5GHz (5150-5250MHz)	3.42	FPC Antenna
Wi-Fi 5GHz (5250-5350MHz)	3.42	FPC Antenna
Wi-Fi 5GHz (5500-5725MHz)	3.42	FPC Antenna
Wi-Fi 5GHz (5725-5850MHz)	3.42	FPC Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT (GFSK)	2402-2480MHz	4	+2	2	6
BT (8DPSK)	2402-2480MHz	4	+2	2	6
BT-LE (GFSK)	2402-2480MHz	5	+2	3	7
802.11b	2412-2462MHz	14	+3	11	17
802.11g	2412-2462MHz	13	+3	10	16
802.11n HT20	2412-2462MHz	12	+3	9	15
802.11n HT40	2422-2452MHz	11	+3	8	14
Wi-Fi 5GHz(Band1)	5150-5250MHz	9	+4	5	13
Wi-Fi 5GHz(Band2)	5250-5350MHz	11	+4	7	15
Wi-Fi 5GHz(Band3)	5500-5725MHz	10	+4	6	16
Wi-Fi 5GHz(Band4)	5725-5850MHz	7	+4	3	11

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
BT (GFSK)	2480	3.18
BT (8DPSK)	2441	3.34
BT-LE (GFSK)	2480	6.12
802.11b	2412	15.06
802.11g	2437	13.97
802.11n HT20	2437	13.60
802.11n HT40	2437	13.46
Wi-Fi 5GHz(Band1)	5200	10.84
Wi-Fi 5GHz(Band2)	5300	14.18
Wi-Fi 5GHz(Band3)	5600	11.60
Wi-Fi 5GHz(Band4)	5785	8.03

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
BT 2.4GHz	7	3.31	20	0.002137	1.0
Wi-Fi 2.4GHz	17	3.42	20	0.021914	1.0
Wi-Fi 5GHz	16	3.42	20	0.017407	1.0

CONCLUSION:

The BT 2.4GHz and Wi-Fi can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$(0.002137/1)+(0.021914 /1) = 0.024051 < 1, \text{ which is less than the "1" limit.}$$

--- END ---