



**CFR 47 FCC PART 15 SUBPART E  
ISED RSS-247 ISSUE 2**

**CERTIFICATION TEST REPORT**

*For*

**CAPCOM® YOGA FLAME EDITION LEGACY WITH RISER ARCADE1UP/ CAPCOM®  
SHINKU HADOKEN EDITION LEGACY WITH RISER ARCADE1UP/  
CAPCOM LEGACY ARCADE GAME YOGA FLAME EDITION w/WIFI**

**MODEL NUMBER: STF-A-202110, STF-A-213510, STF-A-213514**

**FCC ID: 2APXHCAP110**

**ISED: 24128-CAP110**

**REPORT NUMBER: 4790382032-2**

**ISSUE DATE: May 11, 2022**

*Prepared for*

**WF TASTEMAKERS TRADING LIMITED (FCC)  
Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza, 1 Science  
Museum Road, TST East, Hong Kong**

**WF Tastemakers Trading Limited (ISED)  
347 Fifth Avenue Suite 1402-199, New York NY 10018 United States Of  
America (Excluding The States Of Alaska)**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-  
Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	05/11/2022	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/IC Rules	Test Results
1	6dB/26dB Bandwidth	FCC 15.407 (a)&(e) RSS-247 Clause 6.2	PASS
2	99% Occupied Bandwidth	RSS-Gen Clause 6.6	PASS
3	Conducted Output Power	FCC 15.407 (a) RSS-247 Clause 6.2	PASS
4	Power Spectral Density	FCC 15.407 (a) RSS-247 Clause 6.2	PASS
5	Radiated Bandedge and Spurious Emission	FCC 15.407 (b) FCC 15.209 FCC 15.205 RSS-247 Clause 6.2 RSS-GEN Clause 8.9	PASS
6	Conducted Emission Test for AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	PASS
7	Frequency Stability	FCC 15.407 (g)	PASS
8	Dynamic Frequency Selection	FCC 15.407 (h) RSS-247 Clause 6.3	PASS
9	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	PASS
<b>Note:</b> 1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.			



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>7</b>
<b>2. TEST METHODOLOGY .....</b>	<b>9</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>9</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>10</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>10</i>
4.2. <i>MEASUREMENT UNCERTAINTY .....</i>	<i>10</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>11</b>
5.1. <i>MAXIMUM OUTPUT POWER .....</i>	<i>11</i>
5.2. <i>CHANNEL LIST .....</i>	<i>12</i>
5.3. <i>DESCRIPTION OF EUT .....</i>	<i>13</i>
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>14</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER .....</i>	<i>15</i>
5.6. <i>THE WORSE CASE CONFIGURATIONS .....</i>	<i>17</i>
5.7. <i>DESCRIPTION OF TEST SETUP .....</i>	<i>18</i>
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED .....</b>	<b>19</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>21</b>
7.1. <i>ON TIME AND DUTY CYCLE .....</i>	<i>21</i>
7.2. <i>6/26 dB EMISSION BANDWIDTH AND 99 % OCCUPIED BANDWIDTH .....</i>	<i>22</i>
7.3. <i>CONDUCTED OUTPUT POWER .....</i>	<i>25</i>
7.4. <i>POWER SPECTRAL DENSITY .....</i>	<i>28</i>
<b>8. RADIATED TEST RESULTS .....</b>	<b>30</b>
8.1. <i>RESTRICTED BANDEDGE .....</i>	<i>36</i>
8.1.1. <i>802.11a MODE .....</i>	<i>36</i>
UNII-1 BAND .....	36
UNII-2A BAND .....	40
UNII-2C BAND .....	44
UNII-3 BAND .....	47
8.1.2. <i>802.11ac VHT20 .....</i>	<i>49</i>
UNII-1 BAND .....	49
UNII-2A BAND .....	53
UNII-2C BAND .....	57
UNII-3 BAND .....	60
8.1.3. <i>802.11ac VHT40 .....</i>	<i>62</i>
UNII-1 BAND .....	62
UNII-2A BAND .....	66
UNII-2C BAND .....	70



UNII-3 BAND .....	73
8.1.4. 802.11ac VHT80 MODE .....	75
UNII-1 BAND .....	75
UNII-2A BAND .....	77
UNII-2C BAND .....	79
UNII-3 BAND .....	82
8.2. SPURIOUS EMISSIONS (1 GHz ~ 7 GHz) .....	83
8.2.1. 802.11 a MODE .....	83
UNII-1 BAND .....	83
UNII-2A BAND .....	89
UNII-2C BAND .....	95
STRADDLE CHANNEL 144 .....	101
UNII-3 BAND .....	103
8.3. SPURIOUS EMISSIONS (7 GHz ~ 18 GHz) .....	109
8.3.1. 802.11a MODE .....	109
UNII-1 BAND .....	109
UNII-2A BAND .....	115
UNII-2C BAND .....	121
STRADDLE CHANNEL 144 .....	127
UNII-3 BAND .....	129
8.3.2. 802.11ac VHT20 MODE .....	135
UNII-1 BAND .....	135
UNII-2A BAND .....	141
UNII-2C BAND .....	147
STRADDLE CHANNEL 144 .....	153
UNII-3 BAND .....	155
8.3.3. 802.11ac VHT40 MODE .....	161
UNII-1 BAND .....	161
UNII-2A BAND .....	165
UNII-2C BAND .....	169
STRADDLE CHANNEL 142 .....	175
UNII-3 BAND .....	177
8.3.4. 802.11ac VHT80 MODE .....	181
UNII-1 BAND .....	181
UNII-2A BAND .....	183
UNII-2C BAND .....	185
STRADDLE CHANNEL 138 .....	189
UNII-3 BAND .....	191
8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz) .....	193
8.4.1. 802.11 a MODE .....	193
8.5. SPURIOUS EMISSIONS (26 GHz ~ 40 GHz) .....	195
8.5.1. 802.11 a MODE .....	195
8.6. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz) .....	197
8.6.1. 802.11 a MODE .....	197
8.7. SPURIOUS EMISSIONS BELOW 30 MHz .....	199
8.7.1. 802.11 a MODE .....	199
<b>9. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>202</b>
9.1. 802.11 a MODE .....	204



**10. FREQUENCY STABILITY.....206**

**11. DYNAMIC FREQUENCY SELECTION .....208**

**12. ANTENNA REQUIREMENTS .....212**

**13. Appendix.....213**

    13.1. *Appendix A1: Emission Bandwidth* .....213

        13.1.1. Test Result .....213

        13.1.2. Test Graphs .....214

    13.2. *Appendix A2: Occupied channel bandwidth*.....228

        13.2.1. Test Result .....228

        13.2.2. Test Graphs .....229

    13.3. *Appendix A3: Min emission bandwidth* .....243

        13.3.1. Test Result .....243

        13.3.2. Test Graphs .....244

    13.4. *Appendix B: Maximum conducted AVG output power*.....249

        13.4.1. Test Result .....249

    13.5. *Appendix C: Maximum power spectral density* .....250

        13.5.1. Test Result .....250

        13.5.2. Test Graphs .....251

    13.6. *Appendix D: Duty Cycle*.....267

        13.6.1. Test Result .....267

        13.6.2. Test Graphs .....268

    13.7. *Appendix E: Channel Move Time and Channel Closing Transmission Time*.....270

        13.7.1. Test Result .....270

        13.7.2. Test Graphs .....271

    13.8. *Appendix F: Non-Occupancy Period*.....272

        13.8.1. Test Graphs .....273

    13.1. *Appendix G: Frequency Stability* .....274



## 1. ATTESTATION OF TEST RESULTS

### FCC

#### Applicant Information

**Company Name:** WF TASTEMAKERS TRADING LIMITED  
**Address:** Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza,  
1 Science Museum Road, TST East, Hong Kong

### ISED

#### Applicant Information

**Company Name:** WF Tastemakers Trading Limited (ISED)  
**Address:** 347 Fifth Avenue Suite 1402-199, New York NY 10018 United  
States Of America (Excluding The States Of Alaska)

### FCC

#### Manufacturer Information

**Company Name:** WF TASTEMAKERS TRADING LIMITED  
**Address:** Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza,  
1 Science Museum Road, TST East, Hong Kong

### ISED

#### Manufacturer Information

**Company Name:** WF Tastemakers Trading Limited (ISED)  
**Address:** 347 Fifth Avenue Suite 1402-199, New York NY 10018 United  
States Of America (Excluding The States Of Alaska)

### EUT Information

**EUT Name:** CAPCOM® YOGA FLAME EDITION LEGACY WITH RISER  
ARCADE1UP/ CAPCOM® SHINKU HADOKEN EDITION  
LEGACY WITH RISER ARCADE1UP/CAPCOM LEGACY  
ARCADE GAME YOGA FLAME EDITION w/WIFI

**Model:** STF-A-202110

**Series Model:** STF-A-213510, STF-A-213514

**Model Difference:** Refer to clause 5.3.

**Sample Received Date:** April 24, 2022

**Sample Status:** Normal

**Sample ID:** 4895507

**Date of Tested:** April 25, 2022 ~ May 10, 2022



APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Kebo Zhang  
Project Engineer

Checked By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager





## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, CFR 47 FCC Part 2, CFR 47 FCC Part 15, KDB 789033 D02 v02r01, RSS-GEN Issue 5, RSS-247 Issue 2, KDB414788 D01 Radiated Test Site v01r01, KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02, KDB 905462 D03 UNII clients without radar detection New Rules v01r02, KDB 905462 D04 Operational Modes for DFS Testing New Rules v01 and KDB 905462 D06 802 11 Channel Plans New Rules v02.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.766 dB
Maximum Power Spectral Density Level	±1.22 dB
Frequency Stability	±2.76%
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. MAXIMUM OUTPUT POWER

#### UNII-1 BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5150 ~ 5250	11.62	14.18
n HT20		Covered by 802.11ac VHT20	
n HT40		Covered by 802.11ac VHT40	
ac VHT20		7.21	9.77
ac VHT40		11.77	14.33
ac VHT 80		8.63	11.19

#### UNII-2A BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5250 ~ 5350	11.29	13.85
n HT20		Covered by 802.11ac VHT20	
n HT40		Covered by 802.11ac VHT40	
ac VHT20		6.85	9.41
ac VHT40		11.06	13.62
ac VHT 80		8.43	10.99

#### UNII-2C BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5470 ~ 5725	13.27	15.83
n HT20		Covered by 802.11ac VHT20	
n HT40		Covered by 802.11ac VHT40	
ac VHT20		8.82	11.38
ac VHT40		11.04	13.6
ac VHT 80		9.70	12.26

#### UNII-3 BAND

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5725 ~ 5850	13.72	16.28
n HT20		Covered by 802.11ac VHT20	
n HT40		Covered by 802.11ac VHT40	
ac VHT20		9.26	11.82
ac VHT40		13.48	16.04
ac VHT 80		10.52	13.08

## 5.2. CHANNEL LIST

UNII-1 (For Bandwidth=20MHz)		UNII-1 (For Bandwidth=40MHz)		UNII-1 (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-2A (For Bandwidth=20MHz)		UNII-2A (For Bandwidth=40MHz)		UNII-2A (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

UNII-2C (For Bandwidth=20MHz)		UNII-2C (For Bandwidth=40MHz)		UNII-2C (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590	138	5690
112	5560	126	5630		
116	5580	134	5670		
120	*5600	142	5710		
124	*5620				
128	*5640				
132	5660				
136	5680				
140	5700				
144	5720				

Notes: \* not operational in Canada.

UNII-3		UNII-3		UNII-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				



### 5.3. DESCRIPTION OF EUT

EUT Name	CAPCOM® YOGA FLAME EDITION LEGACY WITH RISER ARCADE1UP/ CAPCOM® SHINKU HADOKEN EDITION LEGACY WITH RISER ARCADE1UP/CAPCOM LEGACY ARCADE GAME YOGA FLAME EDITION w/WIFI
Model Name	STF-A-202110
Series Model	STF-A-213510, STF-A-213514
Model Difference	STF-A-213510 and STF-A-213514 have the same technical construction including electronics/ electrical designs(including software and firmware), construction design/ physical design, PCB Layout with STF-A-202110. The difference between these models are only in color, cosmetic details, trade name, model number.
Radio Technology	IEEE802.11a IEEE802.11n HT20/n HT40 IEEE802.11ac VHT20/VHT40/VHT80
Operation frequency	UNII-1/UNII-2A/UNII-2C/UNII-3
Modulation	OFDM(BPSK,QPSK,16QAM,64QAM,256QAM only in ac mode)
Power Supply	AC120 V,60 Hz



#### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)	Cable loss(dBi)	Final Gain(dBi)
1	5150-5850	monopole	3.8	-1.24	2.56

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11n HT40	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT40	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT80	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
Note:		
2. WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client)		

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter	
Test Software	RFTesttool

### UNII-1

Mode	Rate	Channel	Soft set value
			ANT1
11a	6M	36	Default
		40	Default
		48	Default
11n HT20	MCS0	36	Default
		40	Default
		48	Default
11n HT40	MCS0	38	Default
		46	Default
11ac VHT20	MCS0	36	Default
		40	Default
		48	Default
11ac VHT40	MCS0	38	Default
		46	Default
11ac VHT80	MCS0	42	Default

### UNII-2A

Mode	Rate	Channel	Soft set value
			ANT 1
11a	6M	52	Default
		56	Default
		64	Default
11n HT20	MCS0	52	Default
		56	Default
		64	Default
11n HT40	MCS0	54	Default
		62	Default
11ac VHT20	MCS0	52	Default
		56	Default
		64	Default
11ac VHT40	MCS0	54	Default
		62	Default
11ac VHT80	MCS0	58	Default



## UNII-2C

Mode	Rate	Channel	Soft set value
			ANT 1
11a	6M	100	Default
		116	Default
		140	Default
		144	Default
11n HT20	MCS0	100	Default
		116	Default
		140	Default
		144	Default
11n HT40	MCS0	102	14
		118	14
		134	14
		142	14
11ac VHT20	MCS0	100	Default
		116	Default
		140	Default
		144	Default
11ac VHT40	MCS0	102	14
		118	14
		142	14
11ac VHT80	MCS0	106	Default
		122	Default
		138	Default

## UNII-3

Mode	Rate	Channel	Soft set value
			ANT1
11a	6M	149	Default
		157	Default
		165	Default
11n HT20	MCS0	149	Default
		157	Default
		165	Default
11n HT20	MCS0	151	Default
		159	Default
11ac VHT20	MCS0	149	Default
		157	Default
		165	Default
11ac VHT40	MCS0	151	Default
		159	Default
11ac VHT80	MCS0	155	Default





## 5.6. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.6.

Worst-case data rates as provided by the client were:

802.11a mode: 6 Mbps  
802.11n HT20 mode: MCS0  
802.11n HT40 mode: MCS0  
802.11ac VHT20 mode: MCS0  
802.11ac VHT40 mode: MCS0  
802.11ac VHT80 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Since 802.11ac VHT20/VHT40 mode are different from 802.11n HT20/HT40 only in control messages, so all the tests (except conducted output power and power spectral density) were performed on the worst case (802.11ac VHT20/802.11ac VHT40) mode between these 4 modes and only the worst data was recorded in this report.

## 5.7. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	/	/	/	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	/	/	/	/	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	AC/DC Adapter	Royal-Etech International Limited	BI36L-120300-I-LED	Input: 100-240 V~, 50/60 Hz 1.2 A Output: DC 12V, 3A, 36 W

### TEST SETUP

The EUT can work in engineering mode with a software.

### SETUP DIAGRAM FOR TESTS



**6. MEASURING INSTRUMENT AND SOFTWARE USED**

<b>R&amp;S TS 8997 Test System</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Apr.02,2022	Apr.01,2023
Vector Signal Generator	R&S	SMBV100A	261637	Oct.30, 2021	Oct.29, 2022
Signal Generator	R&S	SMB100A	178553	Oct.30, 2021	Oct.29, 2022
Signal Analyzer	R&S	FSV40	101118	Oct.30, 2021	Oct.29, 2022
<b>Software</b>					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
<b>Tonsend RF Test System</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.30, 2021	Oct.29, 2022
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.29, 2021	Sep.28, 2022
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.30, 2021	Oct.29, 2022
DC power supply	Keysight	E3642A	MY55159130	Oct.30, 2021	Oct.29, 2022
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Nov.20,2020	Nov.19,2022
<b>Software</b>					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	



Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.30, 2021	Oct.29, 2022
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.30, 2021	Oct.29, 2022
EMI Measurement Receiver	R&S	ESR26	101377	Oct.30, 2021	Oct.29, 2022
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.30, 2021	Oct.29, 2022
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.31, 2021	Oct.30, 2022
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.31, 2021	Oct.30, 2022
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.31, 2021	Oct.30, 2022
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Oct.31, 2021	Oct.30, 2022
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Oct.31, 2021	Oct.30, 2022
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE

#### LIMITS


None; for reporting purposes only.

#### PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set  $RBW \geq EBW$  if possible; otherwise, set RBW to the largest available value. Set  $VBW \geq RBW$ . Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$ , where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	22.5 °C	Relative Humidity	53 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V,60 Hz

#### RESULTS

Please refer to appendix D.



## 7.2. 6/26 dB EMISSION BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15, Subpart E ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
26 dB Emission Bandwidth	For reporting purposes only.	5250 ~ 5350
26 dB Emission Bandwidth	For reporting purposes only.	5470 ~ 5725 (For FCC) 5470 ~ 5600 (For ISED) 5650 ~ 5725 (For ISED)
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5150 ~ 5825 (For ISED)

### TEST PROCEDURE

ISED RSS-247 6.2.1.2 clause unwanted emission limits

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz.

**TEST PROCEDURE**

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the OBW For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: $\geq 3 \cdot \text{RBW}$ For 26 dB Bandwidth: $> \text{RBW}$ For 99 % Bandwidth: $> 3 \cdot \text{RBW}$
Trace	Max hold
Sweep	Auto couple

- a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

**Calculation for 99 % Bandwidth of UNII-2C and UNII-3 Straddle Channel:**

For Example: Fundamental Frequency: 5720 MHz

99 % OBW: 21.00 MHz

Turning Frequency: 5725 MHz

99 % Bandwidth of UNII-2C Band Portion =  $(5725 - (5720 - (21.00/2))) = 15.50$  MHz99 % Bandwidth of UNII-3 Band Portion =  $(5720 + (21.00/2) - 5725) = 5.50$  MHz**Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:**

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion =  $5725 - 5710.16 = 14.84$  MHz**Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:**


For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz

FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion =  $5728.2 - 5725 = 3.2$  MHz**TEST SETUP****TEST ENVIRONMENT**

Temperature	22.5 °C	Relative Humidity	53 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V,60 Hz

**RESULTS**

Please refer to Appendix A1&amp;A2&amp;A3.





### 7.3. CONDUCTED OUTPUT POWER

**LIMITS**

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	<input type="checkbox"/> Outdoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Indoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Fixed Point-To-Point Access Points: 1 W (30 dBm) <input checked="" type="checkbox"/> Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed the lesser of 250 mW (24dBm) or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power or e.i.r.p.	The maximum e.i.r.p. shall not exceed 200 mW (23 dBm) or 10 + 10 log <sub>10</sub> B, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz.	5150 ~ 5250
	a. The maximum conducted output power shall not exceed 250 mW (24 dBm) or 11 + 10 log <sub>10</sub> B dBm, whichever is less.  b. The maximum e.i.r.p. shall not exceed 1.0 W (30 dBm) or 17 + 10 log <sub>10</sub> B dBm, whichever is less. B is the 99 % emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.	5250 ~ 5350 5470 ~ 5600 5650 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

**Note:**

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

## **TEST PROCEDURE**

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

### **Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep):**

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW  $\geq$  3 MHz.
- (iv) Number of points in sweep  $\geq 2 \times$  span / RBW. (This ensures that bin-to-bin spacing is  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle  $<$  98 %, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq$  98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
- (viii) Trace average at least 100 traces in power averaging (rms) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

### **Method PM (Measurement using an RF average power meter):**

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
  - a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
  - b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
  - c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle,  $x$ , of the transmitter output signal as described in II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding  $10 \log (1/x)$  where  $x$  is the duty cycle (e.g.,  $10 \log (1/0.25)$  if the duty cycle is 25 %).


### **Method PM-G (Measurement using a gated RF average power meter):**

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Straddle channel power was measured using spectrum analyzer.



**TEST SETUP**



**TEST ENVIRONMENT**

Temperature	22.5 °C	Relative Humidity	53 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V,60 Hz

**RESULTS**

Please refer to appendix B.



## 7.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	<input type="checkbox"/> Outdoor Access Point: 17 dBm/MHz <input type="checkbox"/> Indoor Access Point: 17 dBm/MHz <input type="checkbox"/> Fixed Point-To-Point Access Points: 17 dBm/MHz <input checked="" type="checkbox"/> Client Devices: 11 dBm/MHz	5150 ~ 5250
	11 dBm/MHz	5250 ~ 5350 5470 ~ 5725
	30 dBm/500kHz	5725 ~ 5850

ISED RSS-247 ISSUE 2		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	5150 ~ 5250
	The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.	5250 ~ 5350 5470 ~ 5600 5650 ~ 5725
	30 dBm / 500 kHz	5725 ~ 5850

**Note:**

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyser and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto


For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow trace to fully stabilize and Use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

## **TEST SETUP**



## **TEST ENVIRONMENT**

Temperature	22.5 °C	Relative Humidity	53 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V,60 Hz

## **RESULTS**

Please refer to Appendix C.



## 8. RADIATED TEST RESULTS

### LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Refer to ISED RSS-GEN Clause 8.9, Clause 8.10 and ISED RSS-247 6.2.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30



FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b).

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4

Note:

\*1 beyond 75 MHz or more above of the band edge.


\*2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

\*3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

\*4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

**TEST SETUP AND PROCEDURE**

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.



Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and VERTICAL polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and VERTICAL polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note: The manufacturer has recommended that the EUT only be used in the Floor-standing orientation; therefore, all radiated testing was performed in the orientation. The EUT was placed on normal orientation and all radiated emissions were performed with the EUT shown on the setup photo.

**TEST ENVIRONMENT**

Temperature	23.5 °C	Relative Humidity	60 %
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V,60 Hz

**RESULTS**




### 8.1. RESTRICTED BANDEGE

#### 8.1.1. 802.11a MODE

#### UNII-1 BAND

#### RESTRICTED BANDEGE (LOW CHANNEL, VERTICAL)


#### PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	25.28	39.91	65.19	74.00	-8.81	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	5.61	39.91	45.52	54.00	-8.48	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	16.18	39.91	56.09	74.00	-17.91	peak
2	5350.000	15.22	40.08	55.30	74.00	-18.70	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.99	39.91	42.90	54.00	-11.10	AVG
2	5350.000	2.97	40.08	43.05	54.00	-10.95	AVG


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.  
 4. For the transmitting duration, please refer to clause 7.1.  
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**UNII-2A BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.20	39.91	55.11	74.00	-18.89	peak
2	5350.000	16.01	40.08	56.09	74.00	-17.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.98	39.91	42.89	54.00	-11.11	AVG
2	5350.000	3.06	40.08	43.14	54.00	-10.86	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	21.51	40.08	61.59	74.00	-12.41	peak
2	5356.980	22.46	40.12	62.58	74.00	-11.42	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	5.83	40.08	45.91	54.00	-8.09	AVG
2	5356.980	4.86	40.12	44.98	54.00	-9.02	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**UNII-2C BAND**

**RESTRICTED BANDEGE (LOW CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	20.00	40.79	60.79	68.20	-7.41	peak
2	5467.000	26.55	40.83	67.38	68.20	-0.82	peak
3	5470.000	22.14	40.85	62.99	68.20	-5.21	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	5.22	40.79	46.01	54.00	-7.99	AVG
2	5467.000	6.59	40.83	47.42	68.20	-20.78	AVG
3	5470.000	7.35	40.85	48.20	68.20	-20.00	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	21.52	40.63	62.15	68.20	-6.05	peak
2	5803.440	22.75	40.99	63.74	68.20	-4.46	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**UNII-3 BAND**

**RESTRICTED BANDEGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5649.220	17.98	40.61	58.59	68.20	-9.61	peak
2	5724.430	30.91	40.62	71.53	120.90	-49.37	peak
3	5821.720	22.58	41.17	63.75			peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5852.100	25.97	41.47	67.44	117.41	-49.97	peak
2	5954.355	18.24	41.68	59.92	68.20	-8.28	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and VERTICAL had been tested, but only the worst data was recorded in the report.






## 8.1.2. 802.11ac VHT20

UNII-1 BANDRESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	16.23	39.91	56.14	74.00	-17.86	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	3.24	39.91	43.15	54.00	-10.85	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.23	39.91	55.14	74.00	-18.86	peak
2	5350.000	15.18	40.08	55.26	74.00	-18.74	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.74	39.91	42.65	54.00	-11.35	AVG
2	5350.000	2.76	40.08	42.84	54.00	-11.16	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**UNII-2A BAND**
**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**
**PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	14.83	39.91	54.74	74.00	-19.26	peak
2	5350.000	15.05	40.08	55.13	74.00	-18.87	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.53	39.91	42.44	54.00	-11.56	AVG
2	5350.000	2.92	40.08	43.00	54.00	-11.00	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where:  $Ton$  is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	15.21	40.08	55.29	74.00	-18.71	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	3.21	40.08	43.29	54.00	-10.71	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.






**UNII-2C BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	16.54	40.79	57.33	68.20	-10.87	peak
2	5470.000	16.13	40.85	56.98	68.20	-11.22	peak


- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	3.24	40.79	44.03	54.00	-9.97	AVG
2	5470.000	3.58	40.85	44.43	68.20	-23.77	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
 4. For the transmitting duration, please refer to clause 7.1.  
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	16.91	40.63	57.54	68.20	-10.66	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**UNII-3 BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5637.980	18.12	40.64	58.76	68.20	-9.44	peak
2	5722.760	26.88	40.61	67.49	117.09	-49.60	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5854.875	19.18	41.50	60.68	111.08	-50.40	peak
2	5953.990	18.62	41.68	60.30	68.20	-7.90	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Note: Both horizontal and VERTICAL had been tested, but only the worst data was recorded in the report.



## 8.1.3. 802.11ac VHT40

UNII-1 BANDRESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)PEAK


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	21.64	39.91	61.55	74.00	-12.45	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	4.67	39.91	44.58	54.00	-9.42	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.64	39.91	55.55	74.00	-18.45	peak
2	5350.000	15.70	40.08	55.78	74.00	-18.22	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.





**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.76	39.91	42.67	54.00	-11.33	AVG
2	5350.000	2.86	40.08	42.94	54.00	-11.06	AVG


- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**UNII-2A BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.89	39.91	55.80	74.00	-18.20	peak
2	5350.000	16.44	40.08	56.52	74.00	-17.48	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.88	39.91	42.79	54.00	-11.21	AVG
2	5350.000	3.90	40.08	43.98	54.00	-10.02	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	27.65	40.08	67.73	74.00	-6.27	peak
2	5351.760	29.33	40.09	69.42	74.00	-4.58	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	6.97	40.08	47.05	54.00	-6.95	AVG


- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**UNII-2C BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	18.75	40.79	59.54	68.20	-8.66	peak
2	5466.130	25.33	40.83	66.16	68.20	-2.04	peak
3	5470.000	22.15	40.85	63.00	68.20	-5.20	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**AVG**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	4.54	40.79	45.33	54.00	-8.67	AVG
2	5466.130	5.78	40.83	46.61	68.20	-21.59	AVG
3	5470.000	6.38	40.85	47.23	68.20	-20.97	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.  
 4. For the transmitting duration, please refer to clause 7.1.  
 5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	16.76	40.63	57.39	68.20	-10.81	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.






**UNII-3 BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5630.580	17.58	40.65	58.23	68.20	-9.97	peak
2	5723.640	31.76	40.61	72.37	119.10	-46.73	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5853.000	23.59	41.48	65.07	115.36	-50.29	peak
2	5954.400	18.53	41.68	60.21	68.20	-7.99	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Both horizontal and VERTICAL had been tested, but only the worst data was recorded in the report.

**8.1.4. 802.11ac VHT80 MODE**
**UNII-1 BAND**
**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**
**PEAK**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.72	39.91	55.63	74.00	-18.37	peak
2	5350.000	15.75	40.08	55.83	74.00	-18.17	peak


- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	4.13	39.91	44.04	54.00	-9.96	AVG
2	5350.000	2.86	40.08	42.94	54.00	-11.06	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**UNII-2A BAND****RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	15.78	39.91	55.69	74.00	-18.31	peak
2	5350.000	17.31	40.08	57.39	74.00	-16.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**AVG**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	2.92	39.91	42.83	54.00	-11.17	AVG
2	5350.000	4.71	40.08	44.79	54.00	-9.21	AVG


- Note:
1. Measurement = Reading Level + Correct Factor
  2. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
  3. For duty cycle, please refer to clause 7.1.
  4. Only the worst case emission will be recorder, if it complies with the limit, the other emissions deemed to comply with the limit.



**UNII-2C BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**


**PEAK**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	18.84	40.79	59.63	68.20	-8.57	peak
2	5468.750	23.42	40.85	64.27	68.20	-3.93	peak
3	5470.000	20.87	40.85	61.72	68.20	-6.48	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

### AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	4.71	40.79	45.50	54.00	-8.50	AVG
2	5470.000	6.18	40.85	47.03	68.20	-21.17	AVG

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  4. For the transmitting duration, please refer to clause 7.1.
  5. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**

**PEAK**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	16.59	40.63	57.22	68.20	-10.98	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**UNII-3 BAND**

**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5641.600	17.48	40.63	58.11	68.20	-10.09	peak
2	5716.400	22.86	40.59	63.45	109.79	-46.34	peak
3	5716.400	22.86	40.59	63.45	109.79	-46.34	peak
4	5862.000	18.68	41.57	60.25	108.84	-48.59	peak
5	5949.600	18.81	41.71	60.52	68.20	-7.68	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Both horizontal and VERTICAL had been tested, but only the worst data was recorded in the report.

## 8.2. SPURIOUS EMISSIONS (1 GHz ~ 7 GHz)

### 8.2.1. 802.11 a MODE

#### UNII-1 BAND


#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5122.000	61.96	0.99	62.95	74.00	-11.05	peak
2	2980.000	57.87	-5.71	52.16	74.00	-21.84	peak
3	3646.000	49.90	-3.96	45.94	74.00	-28.06	peak
4	1840.000	58.83	-9.88	48.95	74.00	-25.05	peak
5	4882.000	49.62	0.18	49.80	74.00	-24.20	peak
6	5440.000	42.61	1.28	43.89	74.00	-30.11	peak
7	5122.000	28.41	0.99	29.40	54.00	-24.60	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	57.52	-5.71	51.81	74.00	-22.19	peak
2	4936.000	54.93	0.23	55.16	74.00	-18.84	peak
3	5086.000	61.90	0.78	62.68	74.00	-11.32	peak
4	5134.000	66.48	1.05	67.53	74.00	-6.47	peak
5	5476.000	50.28	1.38	51.66	74.00	-22.34	peak
6	5668.000	45.55	1.71	47.26	74.00	-26.74	peak
7	4936.000	26.07	0.23	26.30	54.00	-27.70	AVG
8	5134.000	29.53	1.05	30.58	54.00	-23.42	AVG
9	5086.000	31.57	0.78	32.35	54.00	-21.65	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	48.49	-8.51	39.98	74.00	-34.02	peak
2	2980.000	58.02	-5.71	52.31	74.00	-21.69	peak
3	3646.000	49.44	-3.96	45.48	74.00	-28.52	peak
4	4828.000	48.52	0.12	48.64	74.00	-25.36	peak
5	4978.000	49.20	0.25	49.45	74.00	-24.55	peak
6	5128.000	56.28	1.02	57.30	74.00	-16.70	peak
7	5128.000	24.95	1.02	25.97	54.00	-28.03	AVG

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	58.43	-5.71	52.72	74.00	-21.28	peak
2	4528.000	49.37	-1.36	48.01	74.00	-25.99	peak
3	4834.000	51.72	0.12	51.84	74.00	-22.16	peak
4	4834.000	26.34	0.12	26.46	54.00	-27.54	AVG
5	5068.000	58.79	0.68	59.47	74.00	-14.53	peak
6	5068.000	26.54	0.68	27.22	54.00	-26.78	AVG
7	5116.000	67.43	0.95	68.38	74.00	-5.62	peak
8	5116.000	32.65	0.95	33.60	54.00	-20.40	AVG
9	5404.000	53.76	1.18	54.94	74.00	-19.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	49.17	-8.51	40.66	74.00	-33.34	peak
2	2980.000	57.23	-5.71	51.52	74.00	-22.48	peak
3	3640.000	49.65	-3.99	45.66	74.00	-28.34	peak
4	5236.000	40.56	1.38	41.94	74.00	-32.06	peak
5	5926.000	38.50	2.19	40.69	74.00	-33.31	peak
6	6784.000	36.32	4.75	41.07	74.00	-32.93	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	57.91	-5.71	52.20	74.00	-21.80	peak
2	3646.000	48.37	-3.96	44.41	74.00	-29.59	peak
3	4906.000	48.66	0.19	48.85	74.00	-25.15	peak
4	5008.000	47.83	0.33	48.16	74.00	-25.84	peak
5	5404.000	42.03	1.18	43.21	74.00	-30.79	peak
6	6658.000	36.12	4.69	40.81	74.00	-33.19	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**UNII-2A BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	49.11	-8.51	40.60	74.00	-33.40	peak
2	2980.000	57.68	-5.71	51.97	74.00	-22.03	peak
3	3646.000	49.10	-3.96	45.14	74.00	-28.86	peak
4	5098.000	41.77	0.85	42.62	74.00	-31.38	peak
5	5662.000	38.78	1.71	40.49	74.00	-33.51	peak
6	6592.000	35.77	4.64	40.41	74.00	-33.59	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5032.000	56.03	0.46	56.49	74.00	-17.51	peak
2	2980.000	57.66	-5.71	51.95	74.00	-22.05	peak
3	3646.000	48.76	-3.96	44.80	74.00	-29.20	peak
4	5398.000	48.52	1.18	49.70	74.00	-24.30	peak
5	5092.000	51.01	0.81	51.82	74.00	-22.18	peak
6	5092.000	26.35	0.81	27.16	54.00	-26.84	AVG
7	5032.000	26.12	0.46	26.58	54.00	-27.42	AVG
8	5674.000	42.49	1.72	44.21	74.00	-29.79	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1138.000	55.51	-13.25	42.26	74.00	-31.74	peak
2	2980.000	58.05	-5.71	52.34	74.00	-21.66	peak
3	3646.000	49.46	-3.96	45.50	74.00	-28.50	peak
4	3808.000	46.74	-3.24	43.50	74.00	-30.50	peak
5	4954.000	43.68	0.24	43.92	74.00	-30.08	peak
6	5278.000	48.98	1.33	50.31	74.00	-23.69	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	58.33	-5.71	52.62	74.00	-21.38	peak
2	3442.000	51.69	-4.94	46.75	74.00	-27.25	peak
3	4984.000	47.86	0.26	48.12	74.00	-25.88	peak
4	5128.000	46.80	1.02	47.82	74.00	-26.18	peak
5	5284.000	51.03	1.33	52.36	74.00	-21.64	peak
6	6370.000	40.73	3.38	44.11	74.00	-29.89	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2314.000	48.21	-8.52	39.69	74.00	-34.31	peak
2	2980.000	57.06	-5.71	51.35	74.00	-22.65	peak
3	3646.000	50.78	-3.96	46.82	74.00	-27.18	peak
4	5386.000	43.86	1.19	45.05	74.00	-28.95	peak
5	5686.000	39.09	1.71	40.80	74.00	-33.20	peak
6	6628.000	36.16	4.69	40.85	74.00	-33.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	57.35	-5.71	51.64	74.00	-22.36	peak
2	3646.000	48.30	-3.96	44.34	74.00	-29.66	peak
3	5104.000	53.62	0.88	54.50	74.00	-19.50	peak
4	5104.000	26.47	0.88	27.35	54.00	-26.65	AVG
5	5386.000	56.87	1.19	58.06	74.00	-15.94	peak
6	5386.000	37.52	1.19	38.71	54.00	-15.29	AVG
7	5584.000	48.72	1.67	50.39	74.00	-23.61	peak
8	6592.000	36.19	4.64	40.83	74.00	-33.17	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**UNII-2C BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1060.000	51.38	-13.65	37.73	74.00	-36.27	peak
2	2320.000	48.88	-8.51	40.37	74.00	-33.63	peak
3	2980.000	57.80	-5.71	52.09	74.00	-21.91	peak
4	3646.000	49.65	-3.96	45.69	74.00	-28.31	peak
5	5446.000	41.46	1.29	42.75	74.00	-31.25	peak
6	5656.000	39.28	1.72	41.00	74.00	-33.00	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1096.000	52.50	-13.47	39.03	74.00	-34.97	peak
2	2986.000	57.39	-5.68	51.71	74.00	-22.29	peak
3	3298.000	47.32	-5.19	42.13	74.00	-31.87	peak
4	3646.000	49.13	-3.96	45.17	74.00	-28.83	peak
5	5440.000	55.53	1.28	56.81	74.00	-17.19	peak
6	5440.000	37.84	1.28	39.12	54.00	-14.88	AVG
7	5500.000	44.68	1.44	46.12	74.00	-27.88	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	49.04	-8.51	40.53	74.00	-33.47	peak
2	2980.000	57.61	-5.71	51.90	74.00	-22.10	peak
3	3646.000	49.60	-3.96	45.64	74.00	-28.36	peak
4	5110.000	39.29	0.91	40.20	74.00	-33.80	peak
5	5662.000	39.29	1.71	41.00	74.00	-33.00	peak
6	5860.000	39.06	1.95	41.01	74.00	-32.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	57.61	-5.71	51.90	74.00	-22.10	peak
2	3646.000	50.31	-3.96	46.35	74.00	-27.65	peak
3	5416.000	41.41	1.21	42.62	74.00	-31.38	peak
4	5656.000	40.19	1.72	41.91	74.00	-32.09	peak
5	6628.000	36.55	4.69	41.24	74.00	-32.76	peak
6	6844.000	35.69	4.89	40.58	74.00	-33.42	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	49.11	-8.51	40.60	74.00	-33.40	peak
2	2980.000	57.33	-5.71	51.62	74.00	-22.38	peak
3	3646.000	50.35	-3.96	46.39	74.00	-27.61	peak
4	5122.000	39.08	0.99	40.07	74.00	-33.93	peak
5	5662.000	38.71	1.71	40.42	74.00	-33.58	peak
6	5860.000	38.77	1.95	40.72	74.00	-33.28	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	57.72	-5.71	52.01	74.00	-21.99	peak
2	3646.000	49.55	-3.96	45.59	74.00	-28.41	peak
3	4558.000	44.91	-1.17	43.74	74.00	-30.26	peak
4	5752.000	50.18	1.72	51.90	74.00	-22.10	peak
5	5698.000	46.94	1.72	48.66	74.00	-25.34	peak
6	2320.000	47.34	-8.51	38.83	74.00	-35.17	peak
7	5752.000	35.36	1.72	37.08	54.00	-16.92	AVG

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**STRADDLE CHANNEL 144**

**HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	49.20	-8.51	40.69	74.00	-33.31	peak
2	2980.000	57.92	-5.71	52.21	74.00	-21.79	peak
3	3646.000	49.58	-3.96	45.62	74.00	-28.38	peak
4	4864.000	40.66	0.15	40.81	74.00	-33.19	peak
5	5398.000	42.50	1.18	43.68	74.00	-30.32	peak
6	5720.000	49.57	1.71	51.28	74.00	-22.72	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	56.72	-5.71	51.01	74.00	-22.99	peak
2	3646.000	48.65	-3.96	44.69	74.00	-29.31	peak
3	5032.000	45.68	0.46	46.14	74.00	-27.86	peak
4	5386.000	50.85	1.19	52.04	74.00	-21.96	peak
5	5602.000	45.24	1.71	46.95	74.00	-27.05	peak
6	5720.000	48.50	1.71	50.21	74.00	-23.79	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**UNII-3 BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1276.000	58.35	-12.80	45.55	74.00	-28.45	peak
2	1840.000	59.34	-9.88	49.46	74.00	-24.54	peak
3	2980.000	57.10	-5.71	51.39	74.00	-22.61	peak
4	3646.000	51.36	-3.96	47.40	74.00	-26.60	peak
5	5704.000	48.10	1.71	49.81	74.00	-24.19	peak
6	5746.000	45.67	1.72	47.39	74.00	-26.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1780.000	54.11	-10.02	44.09	74.00	-29.91	peak
2	2980.000	57.51	-5.71	51.80	74.00	-22.20	peak
3	3826.000	48.73	-3.28	45.45	74.00	-28.55	peak
4	4594.000	47.26	-0.95	46.31	74.00	-27.69	peak
5	5704.000	59.84	1.71	61.55	74.00	-12.45	peak
6	5746.000	60.95	1.72	62.67	74.00	-11.33	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.000	50.27	-8.51	41.76	74.00	-32.24	peak
2	2980.000	56.93	-5.71	51.22	74.00	-22.78	peak
3	3640.000	52.37	-3.99	48.38	74.00	-25.62	peak
4	4630.000	42.84	-0.76	42.08	74.00	-31.92	peak
5	5788.000	45.30	1.72	47.02	74.00	-26.98	peak
6	6622.000	35.65	4.69	40.34	74.00	-33.66	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2980.000	56.61	-5.71	50.90	74.00	-23.10	peak
2	3466.000	48.33	-4.85	43.48	74.00	-30.52	peak
3	3646.000	50.09	-3.96	46.13	74.00	-27.87	peak
4	4630.000	48.04	-0.76	47.28	74.00	-26.72	peak
5	5686.000	47.56	1.71	49.27	74.00	-24.73	peak
6	5788.000	48.65	1.72	50.37	74.00	-23.63	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1474.000	54.44	-12.24	42.20	74.00	-31.80	peak
2	1942.000	51.19	-9.93	41.26	74.00	-32.74	peak
3	2980.000	58.26	-5.71	52.55	74.00	-21.45	peak
4	3646.000	50.59	-3.96	46.63	74.00	-27.37	peak
5	5830.000	48.18	1.83	50.01	74.00	-23.99	peak
6	5866.000	44.65	1.97	46.62	74.00	-27.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1072.000	52.72	-13.59	39.13	74.00	-34.87	peak
2	2980.000	57.18	-5.71	51.47	74.00	-22.53	peak
3	3646.000	51.00	-3.96	47.04	74.00	-26.96	peak
4	4660.000	45.82	-0.62	45.20	74.00	-28.80	peak
5	5656.000	45.93	1.72	47.65	74.00	-26.35	peak
6	5872.000	54.36	2.00	56.36	74.00	-17.64	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


Note: All the modes had been tested, but only the worst data was recorded in the report.

### 8.3. SPURIOUS EMISSIONS (7 GHz ~ 18 GHz)

#### 8.3.1. 802.11a MODE

#### UNII-1 BAND


#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.77	5.81	44.58	74.00	-29.42	peak
2	9343.000	36.99	9.32	46.31	74.00	-27.69	peak
3	11719.000	35.81	16.71	52.52	74.00	-21.48	peak
4	12698.000	34.51	17.05	51.56	74.00	-22.44	peak
5	13501.000	33.24	19.58	52.82	74.00	-21.18	peak
6	17747.000	30.29	22.64	52.93	74.00	-21.07	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9288.000	37.10	8.98	46.08	74.00	-27.92	peak
2	10366.000	36.24	11.35	47.59	74.00	-26.41	peak
3	11807.000	34.84	17.22	52.06	74.00	-21.94	peak
4	12698.000	35.31	17.05	52.36	74.00	-21.64	peak
5	13974.000	32.11	20.63	52.74	74.00	-21.26	peak
6	17956.000	28.16	23.57	51.73	74.00	-22.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7891.000	39.17	5.74	44.91	74.00	-29.09	peak
2	9134.000	37.23	8.78	46.01	74.00	-27.99	peak
3	11686.000	36.61	16.50	53.11	74.00	-20.89	peak
4	11829.000	36.86	17.20	54.06	74.00	-19.94	peak
5	11829.000	25.06	17.20	42.26	54.00	-11.74	AVG
6	13974.000	32.24	20.63	52.87	74.00	-21.13	peak
7	17989.000	28.77	23.65	52.42	74.00	-21.58	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8221.000	37.62	7.16	44.78	74.00	-29.22	peak
2	9343.000	36.84	9.32	46.16	74.00	-27.84	peak
3	11367.000	36.79	15.08	51.87	74.00	-22.13	peak
4	11785.000	35.15	17.12	52.27	74.00	-21.73	peak
5	13996.000	31.52	20.63	52.15	74.00	-21.85	peak
6	17758.000	29.71	22.75	52.46	74.00	-21.54	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	38.76	5.95	44.71	74.00	-29.29	peak
2	9398.000	36.68	9.67	46.35	74.00	-27.65	peak
3	11499.000	35.33	15.71	51.04	74.00	-22.96	peak
4	13589.000	33.16	19.70	52.86	74.00	-21.14	peak
5	14667.000	32.99	17.59	50.58	74.00	-23.42	peak
6	17659.000	30.68	21.72	52.40	74.00	-21.60	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	37.30	7.14	44.44	74.00	-29.56	peak
2	9321.000	37.24	9.18	46.42	74.00	-27.58	peak
3	11796.000	35.40	17.19	52.59	74.00	-21.41	peak
4	12687.000	34.73	17.01	51.74	74.00	-22.26	peak
5	13952.000	31.99	20.61	52.60	74.00	-21.40	peak
6	18000.000	27.93	23.68	51.61	74.00	-22.39	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**UNII-2A BAND**

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	38.23	6.40	44.63	74.00	-29.37	peak
2	9354.000	37.39	9.39	46.78	74.00	-27.22	peak
3	10520.000	37.36	11.94	49.30	74.00	-24.70	peak
4	11807.000	35.64	17.22	52.86	74.00	-21.14	peak
5	14238.000	32.34	19.53	51.87	74.00	-22.13	peak
6	17934.000	28.40	23.52	51.92	74.00	-22.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	38.88	5.95	44.83	74.00	-29.17	peak
2	10058.000	35.71	10.69	46.40	74.00	-27.60	peak
3	10520.000	39.13	11.94	51.07	74.00	-22.93	peak
4	11829.000	35.60	17.20	52.80	74.00	-21.20	peak
5	13622.000	33.14	19.81	52.95	74.00	-21.05	peak
6	17582.000	31.23	21.00	52.23	74.00	-21.77	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.62	5.81	44.43	74.00	-29.57	peak
2	8980.000	37.33	9.29	46.62	74.00	-27.38	peak
3	10553.000	37.75	12.07	49.82	74.00	-24.18	peak
4	11796.000	35.07	17.19	52.26	74.00	-21.74	peak
5	13556.000	33.30	19.67	52.97	74.00	-21.03	peak
6	17912.000	29.03	23.46	52.49	74.00	-21.51	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8947.000	37.53	8.89	46.42	74.00	-27.58	peak
2	10553.000	37.38	12.07	49.45	74.00	-24.55	peak
3	11829.000	35.90	17.20	53.10	74.00	-20.90	peak
4	13622.000	32.22	19.81	52.03	74.00	-21.97	peak
5	13974.000	31.71	20.63	52.34	74.00	-21.66	peak
6	17868.000	28.56	23.36	51.92	74.00	-22.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7759.000	39.18	5.95	45.13	74.00	-28.87	peak
2	9552.000	36.55	10.03	46.58	74.00	-27.42	peak
3	10641.000	38.95	12.33	51.28	74.00	-22.72	peak
4	11829.000	35.40	17.20	52.60	74.00	-21.40	peak
5	13798.000	32.19	20.50	52.69	74.00	-21.31	peak
6	17274.000	31.35	20.17	51.52	74.00	-22.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18000.000	28.51	23.68	52.19	74.00	-21.81	peak
2	13974.000	32.21	20.63	52.84	74.00	-21.16	peak
3	10641.000	39.14	12.33	51.47	74.00	-22.53	peak
4	11818.000	35.38	17.20	52.58	74.00	-21.42	peak
5	9376.000	36.43	9.53	45.96	74.00	-28.04	peak
6	7847.000	38.77	5.91	44.68	74.00	-29.32	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**UNII-2C BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.91	5.81	44.72	74.00	-29.28	peak
2	9354.000	36.83	9.39	46.22	74.00	-27.78	peak
3	10993.000	39.32	13.16	52.48	74.00	-21.52	peak
4	11818.000	36.24	17.20	53.44	74.00	-20.56	peak
5	13919.000	32.26	20.58	52.84	74.00	-21.16	peak
6	17769.000	28.62	22.86	51.48	74.00	-22.52	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7891.000	38.68	5.74	44.42	74.00	-29.58	peak
2	8980.000	37.02	9.29	46.31	74.00	-27.69	peak
3	10993.000	38.49	13.16	51.65	74.00	-22.35	peak
4	11818.000	35.84	17.20	53.04	74.00	-20.96	peak
5	13963.000	32.59	20.61	53.20	74.00	-20.80	peak
6	17978.000	28.14	23.63	51.77	74.00	-22.23	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8155.000	37.67	6.81	44.48	74.00	-29.52	peak
2	9563.000	36.84	10.05	46.89	74.00	-27.11	peak
3	11818.000	35.63	17.20	52.83	74.00	-21.17	peak
4	12698.000	35.12	17.05	52.17	74.00	-21.83	peak
5	13798.000	32.18	20.50	52.68	74.00	-21.32	peak
6	17989.000	28.69	23.65	52.34	74.00	-21.66	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	38.00	7.14	45.14	74.00	-28.86	peak
2	9244.000	37.48	8.69	46.17	74.00	-27.83	peak
3	11158.000	38.92	13.93	52.85	74.00	-21.15	peak
4	11818.000	36.00	17.20	53.20	74.00	-20.80	peak
5	13908.000	32.08	20.58	52.66	74.00	-21.34	peak
6	17582.000	30.51	21.00	51.51	74.00	-22.49	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8111.000	38.05	6.40	44.45	74.00	-29.55	peak
2	9024.000	37.53	9.39	46.92	74.00	-27.08	peak
3	11829.000	36.14	17.20	53.34	74.00	-20.66	peak
4	12698.000	35.21	17.05	52.26	74.00	-21.74	peak
5	13622.000	33.36	19.81	53.17	74.00	-20.83	peak
6	17989.000	28.59	23.65	52.24	74.00	-21.76	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7814.000	38.46	6.03	44.49	74.00	-29.51	peak
2	9343.000	37.46	9.32	46.78	74.00	-27.22	peak
3	11400.000	37.02	15.28	52.30	74.00	-21.70	peak
4	11829.000	35.68	17.20	52.88	74.00	-21.12	peak
5	13908.000	33.62	20.58	54.20	74.00	-19.80	peak
6	13908.000	19.68	20.58	40.26	54.00	-13.74	AVG
7	17098.000	34.00	19.54	53.54	74.00	-20.46	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**STRADDLE CHANNEL 144**


**HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.25	8.76	46.01	74.00	-27.99	peak
2	11829.000	35.51	17.20	52.71	74.00	-21.29	peak
3	12687.000	35.04	17.01	52.05	74.00	-21.95	peak
4	13446.000	33.64	19.37	53.01	74.00	-20.99	peak
5	13919.000	32.61	20.58	53.19	74.00	-20.81	peak
6	17945.000	29.62	23.55	53.17	74.00	-20.83	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8122.000	38.24	6.49	44.73	74.00	-29.27	peak
2	9563.000	36.29	10.05	46.34	74.00	-27.66	peak
3	11796.000	35.76	17.19	52.95	74.00	-21.05	peak
4	12731.000	34.34	17.13	51.47	74.00	-22.53	peak
5	13424.000	33.06	19.28	52.34	74.00	-21.66	peak
6	17428.000	32.32	20.30	52.62	74.00	-21.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**UNII-3 BAND**

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.45	5.81	44.26	74.00	-29.74	peak
2	9079.000	37.14	9.10	46.24	74.00	-27.76	peak
3	10190.000	35.61	10.91	46.52	74.00	-27.48	peak
4	11840.000	36.39	17.20	53.59	74.00	-20.41	peak
5	13952.000	32.70	20.61	53.31	74.00	-20.69	peak
6	17758.000	29.63	22.75	52.38	74.00	-21.62	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8221.000	37.59	7.16	44.75	74.00	-29.25	peak
2	9563.000	37.58	10.05	47.63	74.00	-26.37	peak
3	11367.000	36.70	15.08	51.78	74.00	-22.22	peak
4	11829.000	35.27	17.20	52.47	74.00	-21.53	peak
5	13919.000	32.08	20.58	52.66	74.00	-21.34	peak
6	17989.000	28.95	23.65	52.60	74.00	-21.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7847.000	38.71	5.91	44.62	74.00	-29.38	peak
2	9134.000	37.54	8.78	46.32	74.00	-27.68	peak
3	11565.000	36.96	15.86	52.82	74.00	-21.18	peak
4	11818.000	35.36	17.20	52.56	74.00	-21.44	peak
5	13622.000	33.08	19.81	52.89	74.00	-21.11	peak
6	17362.000	33.07	20.19	53.26	74.00	-20.74	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8199.000	37.16	7.22	44.38	74.00	-29.62	peak
2	8991.000	36.92	9.42	46.34	74.00	-27.66	peak
3	11829.000	35.97	17.20	53.17	74.00	-20.83	peak
4	13985.000	31.99	20.63	52.62	74.00	-21.38	peak
5	17351.000	33.86	20.19	54.05	74.00	-19.95	peak
6	17351.000	22.07	20.19	42.26	54.00	-11.74	AVG
7	17648.000	30.40	21.62	52.02	74.00	-21.98	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7737.000	38.22	5.88	44.10	74.00	-29.90	peak
2	9409.000	36.53	9.70	46.23	74.00	-27.77	peak
3	11818.000	35.22	17.20	52.42	74.00	-21.58	peak
4	12687.000	35.50	17.01	52.51	74.00	-21.49	peak
5	13567.000	33.43	19.67	53.10	74.00	-20.90	peak
6	17483.000	33.05	20.45	53.50	74.00	-20.50	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7748.000	39.33	5.92	45.25	74.00	-28.75	peak
2	9365.000	37.68	9.46	47.14	74.00	-26.86	peak
3	11653.000	36.51	16.28	52.79	74.00	-21.21	peak
4	12742.000	34.35	17.15	51.50	74.00	-22.50	peak
5	13842.000	32.19	20.53	52.72	74.00	-21.28	peak
6	17483.000	32.70	20.45	53.15	74.00	-20.85	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



8.3.2. 802.11ac VHT20 MODE

UNII-1 BAND


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7808.500	38.38	6.05	44.43	74.00	-29.57	peak
2	9552.000	36.78	10.03	46.81	74.00	-27.19	peak
3	11790.500	35.51	17.15	52.66	74.00	-21.34	peak
4	12687.000	34.57	17.01	51.58	74.00	-22.42	peak
5	13919.000	31.97	20.58	52.55	74.00	-21.45	peak
6	17994.500	28.90	23.67	52.57	74.00	-21.43	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7742.500	38.95	5.90	44.85	74.00	-29.15	peak
2	9079.000	37.28	9.10	46.38	74.00	-27.62	peak
3	11779.500	35.42	17.09	52.51	74.00	-21.49	peak
4	13506.500	32.60	19.59	52.19	74.00	-21.81	peak
5	13985.000	32.33	20.63	52.96	74.00	-21.04	peak
6	17840.500	29.09	23.29	52.38	74.00	-21.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7847.000	39.16	5.91	45.07	74.00	-28.93	peak
2	8947.000	38.07	8.89	46.96	74.00	-27.04	peak
3	11829.000	35.03	17.20	52.23	74.00	-21.77	peak
4	13440.500	32.68	19.36	52.04	74.00	-21.96	peak
5	14067.500	32.51	20.31	52.82	74.00	-21.18	peak
6	17906.500	27.90	23.45	51.35	74.00	-22.65	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8963.500	38.17	9.09	47.26	74.00	-26.74	peak
2	11823.500	35.69	17.21	52.90	74.00	-21.10	peak
3	12687.000	35.26	17.01	52.27	74.00	-21.73	peak
4	13594.500	32.59	19.71	52.30	74.00	-21.70	peak
5	14018.000	32.28	20.55	52.83	74.00	-21.17	peak
6	17989.000	27.97	23.65	51.62	74.00	-22.38	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7841.500	38.46	5.93	44.39	74.00	-29.61	peak
2	8985.500	37.80	9.35	47.15	74.00	-26.85	peak
3	11801.500	35.79	17.22	53.01	74.00	-20.99	peak
4	12549.500	35.34	16.83	52.17	74.00	-21.83	peak
5	13583.500	33.75	19.71	53.46	74.00	-20.54	peak
6	17956.000	28.29	23.57	51.86	74.00	-22.14	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8963.500	37.09	9.09	46.18	74.00	-27.82	peak
2	10195.500	36.03	10.91	46.94	74.00	-27.06	peak
3	10844.500	37.08	12.72	49.80	74.00	-24.20	peak
4	11796.000	35.73	17.19	52.92	74.00	-21.08	peak
5	13891.500	32.15	20.56	52.71	74.00	-21.29	peak
6	17961.500	28.08	23.58	51.66	74.00	-22.34	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**UNII-2A BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	38.35	5.95	44.30	74.00	-29.70	peak
2	8958.000	37.71	9.02	46.73	74.00	-27.27	peak
3	11823.500	35.97	17.21	53.18	74.00	-20.82	peak
4	13539.500	33.12	19.63	52.75	74.00	-21.25	peak
5	13891.500	31.68	20.56	52.24	74.00	-21.76	peak
6	17268.500	31.67	20.17	51.84	74.00	-22.16	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8210.000	37.86	7.20	45.06	74.00	-28.94	peak
2	10052.500	35.87	10.68	46.55	74.00	-27.45	peak
3	11829.000	35.67	17.20	52.87	74.00	-21.13	peak
4	12593.500	35.13	16.81	51.94	74.00	-22.06	peak
5	13814.500	32.55	20.51	53.06	74.00	-20.94	peak
6	17835.000	28.33	23.28	51.61	74.00	-22.39	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7841.500	39.45	5.93	45.38	74.00	-28.62	peak
2	8941.500	38.85	8.83	47.68	74.00	-26.32	peak
3	11818.000	35.39	17.20	52.59	74.00	-21.41	peak
4	12346.000	35.85	16.97	52.82	74.00	-21.18	peak
5	13913.500	32.10	20.58	52.68	74.00	-21.32	peak
6	17835.000	29.09	23.28	52.37	74.00	-21.63	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7841.500	39.02	5.93	44.95	74.00	-29.05	peak
2	8985.500	37.14	9.35	46.49	74.00	-27.51	peak
3	11928.000	34.73	17.14	51.87	74.00	-22.13	peak
4	13550.500	32.38	19.66	52.04	74.00	-21.96	peak
5	13957.500	32.02	20.61	52.63	74.00	-21.37	peak
6	17763.500	29.27	22.81	52.08	74.00	-21.92	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7847.000	38.55	5.91	44.46	74.00	-29.54	peak
2	8985.500	37.45	9.35	46.80	74.00	-27.20	peak
3	11823.500	35.04	17.21	52.25	74.00	-21.75	peak
4	12637.500	34.92	16.90	51.82	74.00	-22.18	peak
5	13985.000	32.75	20.63	53.38	74.00	-20.62	peak
6	17994.500	29.25	23.67	52.92	74.00	-21.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7869.000	39.24	5.82	45.06	74.00	-28.94	peak
2	8974.500	37.30	9.22	46.52	74.00	-27.48	peak
3	11867.500	35.46	17.17	52.63	74.00	-21.37	peak
4	13418.500	33.12	19.26	52.38	74.00	-21.62	peak
5	13952.000	32.85	20.61	53.46	74.00	-20.54	peak
6	17180.500	32.07	20.04	52.11	74.00	-21.89	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**UNII-2C BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8166.000	38.01	6.90	44.91	74.00	-29.09	peak
2	8985.500	37.42	9.35	46.77	74.00	-27.23	peak
3	11823.500	35.65	17.21	52.86	74.00	-21.14	peak
4	12615.500	35.18	16.85	52.03	74.00	-21.97	peak
5	13974.000	32.10	20.63	52.73	74.00	-21.27	peak
6	17972.500	28.34	23.61	51.95	74.00	-22.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7896.500	38.76	5.73	44.49	74.00	-29.51	peak
2	8985.500	37.46	9.35	46.81	74.00	-27.19	peak
3	10294.500	36.03	11.17	47.20	74.00	-26.80	peak
4	11873.000	35.76	17.17	52.93	74.00	-21.07	peak
5	13919.000	32.56	20.58	53.14	74.00	-20.86	peak
6	17939.500	29.37	23.54	52.91	74.00	-21.09	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7836.000	39.32	5.95	45.27	74.00	-28.73	peak
2	9057.000	37.56	9.22	46.78	74.00	-27.22	peak
3	11752.000	35.60	16.92	52.52	74.00	-21.48	peak
4	13589.000	33.39	19.70	53.09	74.00	-20.91	peak
5	13963.000	32.12	20.61	52.73	74.00	-21.27	peak
6	17939.500	29.83	23.54	53.37	74.00	-20.63	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	38.08	7.14	45.22	74.00	-28.78	peak
2	8985.500	37.13	9.35	46.48	74.00	-27.52	peak
3	11933.500	35.61	17.15	52.76	74.00	-21.24	peak
4	13600.000	33.92	19.72	53.64	74.00	-20.36	peak
5	14441.500	34.84	18.70	53.54	74.00	-20.46	peak
6	17978.000	28.80	23.63	52.43	74.00	-21.57	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8259.500	37.93	7.06	44.99	74.00	-29.01	peak
2	10333.000	36.43	11.27	47.70	74.00	-26.30	peak
3	11829.000	35.63	17.20	52.83	74.00	-21.17	peak
4	13864.000	32.65	20.54	53.19	74.00	-20.81	peak
5	14425.000	32.92	18.79	51.71	74.00	-22.29	peak
6	17928.500	28.23	23.51	51.74	74.00	-22.26	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7742.500	38.43	5.90	44.33	74.00	-29.67	peak
2	9062.500	37.61	9.18	46.79	74.00	-27.21	peak
3	11785.000	35.54	17.12	52.66	74.00	-21.34	peak
4	13913.500	32.33	20.58	52.91	74.00	-21.09	peak
5	14436.000	33.51	18.74	52.25	74.00	-21.75	peak
6	17978.000	29.10	23.63	52.73	74.00	-21.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**STRADDLE CHANNEL 144**


**HARMONICS AND SPURIOUS EMISSIONS (HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7748.000	38.78	5.92	44.70	74.00	-29.30	peak
2	9376.000	37.30	9.53	46.83	74.00	-27.17	peak
3	11785.000	35.83	17.12	52.95	74.00	-21.05	peak
4	12060.000	35.61	16.99	52.60	74.00	-21.40	peak
5	13545.000	33.40	19.64	53.04	74.00	-20.96	peak
6	17928.500	28.67	23.51	52.18	74.00	-21.82	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8237.500	38.12	7.11	45.23	74.00	-28.77	peak
2	9387.000	37.24	9.60	46.84	74.00	-27.16	peak
3	11746.500	35.81	16.88	52.69	74.00	-21.31	peak
4	12720.000	34.73	17.09	51.82	74.00	-22.18	peak
5	13886.000	32.61	20.56	53.17	74.00	-20.83	peak
6	17945.000	28.09	23.55	51.64	74.00	-22.36	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.



**UNII-3 BAND**


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8232.000	38.38	7.14	45.52	74.00	-28.48	peak
2	9189.000	38.84	8.48	47.32	74.00	-26.68	peak
3	11823.500	35.31	17.21	52.52	74.00	-21.48	peak
4	12483.500	35.29	16.87	52.16	74.00	-21.84	peak
5	13957.500	32.05	20.61	52.66	74.00	-21.34	peak
6	18000.000	28.01	23.68	51.69	74.00	-22.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7753.500	39.20	5.92	45.12	74.00	-28.88	peak
2	9189.000	38.64	8.48	47.12	74.00	-26.88	peak
3	11746.500	35.39	16.88	52.27	74.00	-21.73	peak
4	12670.500	35.34	16.98	52.32	74.00	-21.68	peak
5	13864.000	32.60	20.54	53.14	74.00	-20.86	peak
6	17235.500	32.40	20.16	52.56	74.00	-21.44	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7605.000	38.14	5.45	43.59	74.00	-30.41	peak
2	8974.500	37.62	9.22	46.84	74.00	-27.16	peak
3	11829.000	35.81	17.20	53.01	74.00	-20.99	peak
4	12720.000	34.63	17.09	51.72	74.00	-22.28	peak
5	13589.000	33.12	19.70	52.82	74.00	-21.18	peak
6	17950.500	28.76	23.56	52.32	74.00	-21.68	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.




**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8265.000	38.16	7.03	45.19	74.00	-28.81	peak
2	8991.000	37.40	9.42	46.82	74.00	-27.18	peak
3	11807.000	35.52	17.22	52.74	74.00	-21.26	peak
4	13561.500	33.54	19.67	53.21	74.00	-20.79	peak
5	13957.500	32.80	20.61	53.41	74.00	-20.59	peak
6	17587.500	31.24	21.03	52.27	74.00	-21.73	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7715.000	38.72	5.81	44.53	74.00	-29.47	peak
2	9442.000	37.01	9.79	46.80	74.00	-27.20	peak
3	11823.500	35.23	17.21	52.44	74.00	-21.56	peak
4	12643.000	35.36	16.91	52.27	74.00	-21.73	peak
5	13864.000	32.60	20.54	53.14	74.00	-20.86	peak
6	17906.500	28.78	23.45	52.23	74.00	-21.77	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.  
 6. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27dBm/MHz (68.2dBuV/m) limit.