

**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**TEST REPORT**

*For*

**TIME CRISIS DELUXE EDITION**

**MODEL NUMBER: TMC-A-300111**

**REPORT NUMBER: 4790841285.2-1-RF-1**

**ISSUE DATE: July 21, 2023**

**FCC ID: 2APXHTMC  
IC: 24128-TMC**

*Prepared for*

**WF Tastemakers Trading Limited**

**FCC Address: Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza, 1  
Science Museum Road, TST East, Hong Kong**

**ISED Address: 347 Fifth Avenue Suite 1402-199, New York NY 10018 United  
States Of America (Excluding The States Of Alaska)**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-  
Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

## Revision History

Rev.	Issue Date	Revisions	Revised By
V0	July 21, 2023	Initial Issue	

### Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C><ISED RSS-247 ISSUE 2> when <Accuracy Method> decision rule is applied.

## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>6</b>
<b>2. TEST METHODOLOGY.....</b>	<b>8</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>8</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>9</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>9</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>9</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>10</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>10</i>
5.2. <i>CHANNEL LIST .....</i>	<i>10</i>
5.3. <i>MAXIMUM EIRP .....</i>	<i>10</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>11</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>11</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>12</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>13</i>
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED.....</b>	<b>14</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>17</b>
7.1. <i>CONDUCTED OUTPUT POWER.....</i>	<i>17</i>
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>	<i>18</i>
7.3. <i>POWER SPECTRAL DENSITY .....</i>	<i>20</i>
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION.....</i>	<i>22</i>
7.5. <i>DUTY CYCLE.....</i>	<i>24</i>
<b>8. RADIATED TEST RESULTS.....</b>	<b>25</b>
8.1. <i>RESTRICTED BANDEDGE .....</i>	<i>33</i>
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ) .....</i>	<i>46</i>
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ) .....</i>	<i>52</i>
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ) .....</i>	<i>76</i>
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ) .....</i>	<i>79</i>
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ).....</i>	<i>81</i>
<b>9. ANTENNA REQUIREMENT .....</b>	<b>83</b>
<b>10. AC POWER LINE CONDUCTED EMISSION .....</b>	<b>84</b>
<b>11. TEST DATA.....</b>	<b>88</b>

---

11.1.	<i>APPENDIX A: DTS BANDWIDTH</i> .....	88
11.1.1.	Test Result.....	88
11.1.2.	Test Graphs .....	89
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i> .....	93
11.2.1.	Test Result.....	93
11.2.2.	Test Graphs .....	94
11.3.	<i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER</i> .....	98
11.3.1.	Test Result.....	98
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i> .....	99
11.4.1.	Test Result.....	99
11.4.2.	Test Graphs .....	100
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i> .....	104
11.5.1.	Test Result.....	104
11.5.2.	Test Graphs .....	105
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i> .....	108
11.6.1.	Test Result.....	108
11.6.2.	Test Graphs .....	109
11.7.	<i>APPENDIX G: DUTY CYCLE</i> .....	121
11.7.1.	Test Result.....	121
11.7.2.	Test Graphs .....	122

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: WF Tastemakers Trading Limited  
Address: FCC Address: Unit 05 and unit 06, 6th Floor, Greenfield Tower  
Concordia Plaza, 1 Science Museum Road, TST East, Hong  
Kong  
ISED Address: 347 Fifth Avenue Suite 1402-199, New York NY  
10018 United States Of America (Excluding The States Of  
Alaska)

### Manufacturer Information

Company Name: WF Tastemakers Trading Limited  
Address: FCC Address: Unit 05 and unit 06, 6th Floor, Greenfield Tower  
Concordia Plaza, 1 Science Museum Road, TST East, Hong  
Kong  
ISED Address: 347 Fifth Avenue Suite 1402-199, New York NY  
10018 United States Of America (Excluding The States Of  
Alaska)

### EUT Information

EUT Name: TIME CRISIS DELUXE EDITION  
Model: TMC-A-300111  
Brand: ARCADE1UP  
Sample Received Date: April 19, 2023  
Sample Status: Normal  
Sample ID: 6053096  
Date of Tested: April 19, 2023 to July 21, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2	Pass


Prepared By:



Fanny Huang

Engineer Project Associate

Checked By:



Denny Huang

Senior Project Engineer

Approved By:



Stephen Guo

Operations Manager

## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISED RSS-GEN Issue 5

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.                  Facility Name:                  Chamber D, the VCCI registration No. is G-20019 and R-20004                  Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	TIME CRISIS DELUXE EDITION
Model	TMC-A-300111
Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Radio Technology:	IEEE 802.11b/g/n-HT20/n-HT40
Normal Test Voltage:	AC 120 V, 60 Hz

### 5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

### 5.3. MAXIMUM EIRP

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)	Maximum AVG EIRP (dBm)
b	2412 ~ 2462	1-11[11]	12.87	14.71
g	2412 ~ 2462	1-11[11]	9.31	11.15
n HT20	2412 ~ 2462	1-11[11]	8.67	10.51
n HT40	2422 ~ 2452	3-9[7]	8.56	10.4

#### 5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

#### 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		MP Tool					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	default	default	default	/		
802.11g	1	default	default	default			
802.11n HT20	1	default	default	default			
802.11n HT40	1	/			default	default	default

### WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps  
 802.11g mode: 6 Mbps  
 802.11n HT20 mode: MCS0  
 802.11n HT40 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

## 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)	Cable loss(dBi)	Final Gain(dBi)
1	2412-2462	Monopole	3.26	-1.42	1.84

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	<input checked="" type="checkbox"/> TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
Note: 1. WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client)		

Note: The value of the antenna gain was declared by customer.

## 5.7. SUPPORT UNITS FOR SYSTEM TEST

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	/	/	/	/

### I/O CABLES

Item	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	/	/	/	/	/


### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	AC/DC Adapter	Royal-Etech International Limited	BI36L-120300-I-LED	Input: 100-240 V~, 50/60 Hz 1.2 A Output: DC 12V, 3A, 36 W

### TEST SETUP

The EUT can work in an engineer mode with software.

### SETUP DIAGRAM FOR TESTS



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.31,2023	Mar.30,2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.17, 2022	Oct.16, 2023
Signal Generator	R&S	SMB100A	178553	Oct.17, 2022	Oct.16, 2023
Signal Analyzer	R&S	FSV40	101118	Oct.17, 2022	Oct.16, 2023
Software					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.17, 2022	Oct.16, 2023
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.28, 2022	Sep.27, 2023
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.17, 2022	Oct.16, 2023
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.17, 2022	Oct.16, 2023
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.17, 2022	Oct.16, 2023
DC power supply	Keysight	E3642A	MY55159130	Oct.17, 2022	Oct.16, 2023
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.17, 2022	Oct.16, 2023
Attenuator	Aglient	8495B	2814a12853	Oct.18, 2022	Oct.17, 2023
RF Control Unit	Tonscend	JS0806-2	23B80620666	April 18,2023	April 17,2024
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.17, 2022	Oct.16, 2023
Two-Line V-Network	R&S	ENV216	101983	Oct.17, 2022	Oct.16, 2023
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.17, 2022	Oct.16, 2023
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.17, 2022	Oct.16, 2023
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.17, 2022	Oct.16, 2023
EMI Measurement Receiver	R&S	ESR26	101377	Oct.17, 2022	Oct.16, 2023
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.17, 2022	Oct.16, 2023
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.17, 2022	Oct.16, 2023
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.17, 2022	Oct.16, 2023
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.17, 2022	Oct.16, 2023
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01202035	Oct.17, 2022	Oct.16, 2023
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.01, 2022	Nov.30, 2023
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Dec.01, 2022	Nov.30, 2023
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Dec.01, 2022	Nov.30, 2023

Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Dec.01, 2022	Nov.30, 2023
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Dec.01, 2022	Nov.30, 2023
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.01, 2022	Nov.30, 2023
Band Reject Filter	Wainwright	WRCD5-1879-1879.85-1880.15-1881-40SS	1	Dec.01, 2022	Nov.30, 2023
Notch Filter	Wainwright	WHJ10-882-980-7000-40SS	1	Dec.01, 2022	Nov.30, 2023
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.22, 2022	Oct.21, 2023
Barometer	Yiyi	Baro	N/A	Oct.24, 2022	Oct.23, 2023
Attenuator	Agilent	8495B	2814a12853	Oct.18, 2022	Oct.17, 2023



## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25.2°C	Relative Humidity	55.7%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

#### TEST DATE / ENGINEER

Test Date	April 29, 2023	Test By	Walker Yuan
-----------	----------------	---------	-------------

#### TEST RESULTS

Please refer to section "Test Data" - Appendix C

## 7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: ≥3 × RBW For 99 % Occupied Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.2°C	Relative Humidity	55.7%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST DATE / ENGINEER**

Test Date	April 29, 2023	Test By	Walker Yuan
-----------	----------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A&B

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x OBW bandwidth
Trace	Average
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



**TEST ENVIRONMENT**

Temperature	25.2°C	Relative Humidity	55.7%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST DATE / ENGINEER**

Test Date	April 29, 2023	Test By	Walker Yuan
-----------	----------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix D

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

**TEST SETUP****TEST ENVIRONMENT**

Temperature	25.2°C	Relative Humidity	55.7%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST DATE / ENGINEER**

Test Date	April 29, 2023	Test By	Walker Yuan
-----------	----------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix E&F

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	25.2°C	Relative Humidity	55.7%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

### TEST DATE / ENGINEER

Test Date	April 29, 2023	Test By	Walker Yuan
-----------	----------------	---------	-------------

### TEST RESULTS

Please refer to section "Test Data" - Appendix G



## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (uA/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands <sup>Note 1</sup>		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.80475 - 16.80525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.


FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.  
<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz



The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T

video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5.ON TIME AND DUTY CYCLE.

7.

Note: The manufacturer has recommended that the EUT only be used in the Floor-standing orientation; therefore, all radiated testing was performed in the orientation. The EUT was placed on normal orientation and all radiated emissions were performed with the EUT shown on the setup photo.

For Band edge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Horizontal and Vertical have been tested, only the worst data was recorded in the report.
8. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 1GHz-3GHz:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the Peak values are less than the Average limit of 54 dBuV/m, the Average result is deemed to comply with Average limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 3GHz-18GHz:

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If the Peak values are less than the Average limit of 54 dBuV/m, the Average result is deemed to comply with Average limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 9kHz-30MHz:

Note:

1. Measurement = Reading Level + Correct Factor.  
( $\text{dBuA/m} = \text{dBuV/m} - 20\text{Log}_{10}[120\pi] = \text{dBuV/m} - 51.5$ ).
2. If the Peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 18GHz-26GHz:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the Peak values are less than the Average limit of 54 dBuV/m, the Average result is deemed to comply with Average limit.
3. Peak: Peak detector.
4. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 30MHz-1GHz:

Note:

1. Result Level = Read Level + Correct Factor.
2. If the Peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
4. All modes and channels have been tested, only the worst data was recorded in the report.

### **TEST ENVIRONMENT**

Temperature	25.3°C	Relative Humidity	59%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

### **TEST DATE / ENGINEER**


Test Date	May 25, 2023	Test By	Rex Huang
-----------	--------------	---------	-----------

### **TEST RESULTS**




## 8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2319.240	19.61	31.95	51.56	74.00	-22.44	peak
2	2390.000	13.90	32.16	46.06	74.00	-27.94	peak

Test Mode:	802.11b PK	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2319.360	19.98	31.95	51.93	74.00	-22.07	peak
2	2390.000	13.76	32.16	45.92	74.00	-28.08	peak

Test Mode:	802.11b PK	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.18	32.44	46.62	74.00	-27.38	peak
2	2484.325	16.74	32.44	49.18	74.00	-24.82	peak

Test Mode:	802.11g PK	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2319.840	18.82	31.95	50.77	74.00	-23.23	peak
2	2390.000	16.19	32.16	48.35	74.00	-25.65	peak

Test Mode:	802.11g PK	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	21.10	32.44	53.54	74.00	-20.46	peak
2	2484.710	24.35	32.44	56.79	74.00	-17.21	peak

Test Mode:	802.11g AV	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	3.00	32.44	35.44	54.00	-18.56	AVG
2	2484.710	3.05	32.44	35.49	54.00	-18.51	AVG

Test Mode:	802.11n HT20 PK	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2319.720	19.00	31.95	50.95	74.00	-23.05	peak
2	2390.000	14.82	32.16	46.98	74.00	-27.02	peak


Test Mode:	802.11n HT20 PK	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.07	32.44	58.51	74.00	-15.49	peak
2	2483.940	26.98	32.44	59.42	74.00	-14.58	peak




Test Mode:	802.11n HT20 AV	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	2.95	32.44	35.39	54.00	-18.61	AVG
2	2483.940	2.96	32.44	35.40	54.00	-18.60	AVG

Test Mode:	802.11n HT40 PK	Channel:	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.260	17.65	31.95	49.60	74.00	-24.40	peak
2	2387.490	21.59	32.15	53.74	74.00	-20.26	peak
3	2390.000	21.78	32.16	53.94	74.00	-20.06	peak

Test Mode:	802.11n HT40 AV	Channel:	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2320.260	3.26	31.95	35.21	54.00	-18.79	AVG
2	2387.490	2.02	32.15	34.17	54.00	-19.83	AVG
3	2390.000	2.49	32.16	34.65	54.00	-19.35	AVG

Test Mode:	802.11n HT40 PK	Channel:	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.17	32.44	58.61	74.00	-15.39	peak
2	2484.950	27.08	32.44	59.52	74.00	-14.48	peak


Test Mode:	802.11n HT40 AV	Channel:	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	3.71	32.44	36.15	54.00	-17.85	AVG
2	2484.950	3.41	32.44	35.85	54.00	-18.15	AVG


## 8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1206.000	48.83	-14.07	34.76	74.00	-39.24	peak
2	1656.000	50.86	-12.20	38.66	74.00	-35.34	peak
3	2320.000	52.32	-9.42	42.90	74.00	-31.10	peak
4	2546.000	53.39	-8.36	45.03	74.00	-28.97	peak
5	2578.000	58.77	-8.26	50.51	74.00	-23.49	peak
6	2984.000	53.23	-7.03	46.20	74.00	-27.80	peak

Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1206.000	52.23	-14.07	38.16	74.00	-35.84	peak
2	1452.000	52.03	-12.93	39.10	74.00	-34.90	peak
3	2320.000	56.62	-9.42	47.20	74.00	-26.80	peak
4	2412.000	50.49	-8.93	41.56	/	/	fundamental
5	2590.000	51.45	-8.22	43.23	74.00	-30.77	peak
6	2982.000	52.18	-7.03	45.15	74.00	-28.85	peak


Test Mode:	802.11b	Channel:	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1052.000	49.83	-14.79	35.04	74.00	-38.96	peak
2	1440.000	48.46	-12.98	35.48	74.00	-38.52	peak
3	1920.000	47.31	-11.32	35.99	74.00	-38.01	peak
4	2320.000	52.76	-9.42	43.34	74.00	-30.66	peak
5	2437.000	46.63	-8.80	37.83	/	/	fundamental
6	2984.000	53.22	-7.03	46.19	74.00	-27.81	peak




Test Mode:	802.11b	Channel:	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1050.000	52.08	-14.80	37.28	74.00	-36.72	peak
2	1444.000	51.60	-12.97	38.63	74.00	-35.37	peak
3	1656.000	49.83	-12.20	37.63	74.00	-36.37	peak
4	2320.000	55.56	-9.42	46.14	74.00	-27.86	peak
5	2437.000	51.28	-8.80	42.48	/	/	fundamental
6	2986.000	52.55	-7.03	45.52	74.00	-28.48	peak

Test Mode:	802.11b	Channel:	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1040.000	49.57	-14.84	34.73	74.00	-39.27	peak
2	1656.000	51.19	-12.20	38.99	74.00	-35.01	peak
3	1988.000	48.09	-11.10	36.99	74.00	-37.01	peak
4	2320.000	54.18	-9.42	44.76	74.00	-29.24	peak
5	2600.000	52.74	-8.19	44.55	74.00	-29.45	peak
6	2984.000	53.49	-7.03	46.46	74.00	-27.54	peak


Test Mode:	802.11b	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1252.000	50.86	-13.86	37.00	74.00	-37.00	peak
2	1442.000	52.20	-12.98	39.22	74.00	-34.78	peak
3	1850.000	49.50	-11.55	37.95	74.00	-36.05	peak
4	2290.000	54.42	-9.58	44.84	74.00	-29.16	peak
5	2320.000	57.42	-9.42	48.00	74.00	-26.00	peak
6	2986.000	51.97	-7.03	44.94	74.00	-29.06	peak


### 8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	43.26	-0.26	43.00	74.00	-31.00	peak
2	9270.000	35.61	10.59	46.20	74.00	-27.80	peak
3	10230.000	34.65	12.46	47.11	74.00	-26.89	peak
4	11685.000	32.43	17.10	49.53	74.00	-24.47	peak
5	13965.000	28.13	21.89	50.02	74.00	-23.98	peak
6	18000.000	23.09	25.69	48.78	74.00	-25.22	peak

Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.74	-0.26	44.48	74.00	-29.52	peak
2	9180.000	35.30	10.56	45.86	74.00	-28.14	peak
3	10950.000	34.38	14.60	48.98	74.00	-25.02	peak
4	11715.000	31.82	17.19	49.01	74.00	-24.99	peak
5	14040.000	28.25	21.79	50.04	74.00	-23.96	peak
6	18000.000	23.87	25.69	49.56	74.00	-24.44	peak

Test Mode:	802.11b	Channel:	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7035.000	37.49	6.67	44.16	74.00	-29.84	peak
2	8910.000	36.52	9.82	46.34	74.00	-27.66	peak
3	10020.000	34.96	12.06	47.02	74.00	-26.98	peak
4	11415.000	33.62	16.29	49.91	74.00	-24.09	peak
5	13995.000	28.35	21.95	50.30	74.00	-23.70	peak
6	18000.000	24.05	25.69	49.74	74.00	-24.26	peak

Test Mode:	802.11b	Channel:	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6660.000	38.86	5.02	43.88	74.00	-30.12	peak
2	9165.000	36.12	10.55	46.67	74.00	-27.33	peak
3	10860.000	34.53	14.27	48.80	74.00	-25.20	peak
4	11820.000	32.25	17.47	49.72	74.00	-24.28	peak
5	14085.000	28.37	21.61	49.98	74.00	-24.02	peak
6	17985.000	23.26	25.60	48.86	74.00	-25.14	peak


Test Mode:	802.11b	Channel:	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7905.000	37.35	6.31	43.66	74.00	-30.34	peak
2	8895.000	35.91	9.71	45.62	74.00	-28.38	peak
3	10665.000	34.17	13.58	47.75	74.00	-26.25	peak
4	11655.000	32.11	17.01	49.12	74.00	-24.88	peak
5	13920.000	28.68	21.79	50.47	74.00	-23.53	peak
6	17970.000	23.82	25.51	49.33	74.00	-24.67	peak




Test Mode:	802.11b	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7710.000	37.53	6.33	43.86	74.00	-30.14	peak
2	9135.000	35.56	10.55	46.11	74.00	-27.89	peak
3	11040.000	34.17	14.91	49.08	74.00	-24.92	peak
4	11745.000	32.27	17.27	49.54	74.00	-24.46	peak
5	13965.000	28.37	21.89	50.26	74.00	-23.74	peak
6	17985.000	23.19	25.60	48.79	74.00	-25.21	peak

Test Mode:	802.11g	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7755.000	37.73	6.31	44.04	74.00	-29.96	peak
2	8040.000	38.94	6.34	45.28	74.00	-28.72	peak
3	8955.000	36.92	10.16	47.08	74.00	-26.92	peak
4	10710.000	34.40	13.73	48.13	74.00	-25.87	peak
5	13665.000	28.20	21.25	49.45	74.00	-24.55	peak
6	17985.000	23.11	25.60	48.71	74.00	-25.29	peak

Test Mode:	802.11g	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4305.000	43.46	-2.38	41.08	74.00	-32.92	peak
2	6630.000	38.38	4.86	43.24	74.00	-30.76	peak
3	7890.000	37.99	6.31	44.30	74.00	-29.70	peak
4	11280.000	32.80	15.80	48.60	74.00	-25.40	peak
5	13515.000	29.17	20.93	50.10	74.00	-23.90	peak
6	18000.000	23.71	25.69	49.40	74.00	-24.60	peak

Test Mode:	802.11g	Channel:	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	40.47	-0.15	40.32	74.00	-33.68	peak
2	7305.000	37.60	6.47	44.07	74.00	-29.93	peak
3	9195.000	36.30	10.56	46.86	74.00	-27.14	peak
4	11160.000	33.99	15.36	49.35	74.00	-24.65	peak
5	13515.000	29.78	20.93	50.71	74.00	-23.29	peak
6	17970.000	24.69	25.51	50.20	74.00	-23.80	peak

Test Mode:	802.11g	Channel:	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4665.000	41.65	-0.83	40.82	74.00	-33.18	peak
2	7815.000	37.59	6.32	43.91	74.00	-30.09	peak
3	9060.000	36.94	10.51	47.45	74.00	-26.55	peak
4	11265.000	33.96	15.74	49.70	74.00	-24.30	peak
5	13965.000	27.65	21.89	49.54	74.00	-24.46	peak
6	17985.000	23.49	25.60	49.09	74.00	-24.91	peak

Test Mode:	802.11g	Channel:	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4755.000	40.86	-0.48	40.38	74.00	-33.62	peak
2	7095.000	37.44	6.62	44.06	74.00	-29.94	peak
3	9135.000	36.04	10.55	46.59	74.00	-27.41	peak
4	11055.000	35.09	14.96	50.05	74.00	-23.95	peak
5	13530.000	29.33	20.96	50.29	74.00	-23.71	peak
6	18000.000	23.60	25.69	49.29	74.00	-24.71	peak

Test Mode:	802.11g	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7305.000	37.44	6.47	43.91	74.00	-30.09	peak
2	9120.000	35.87	10.53	46.40	74.00	-27.60	peak
3	10785.000	34.29	14.01	48.30	74.00	-25.70	peak
4	11715.000	32.03	17.19	49.22	74.00	-24.78	peak
5	12690.000	31.40	18.02	49.42	74.00	-24.58	peak
6	17985.000	23.25	25.60	48.85	74.00	-25.15	peak


Test Mode:	802.11n HT20	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7740.000	38.04	6.32	44.36	74.00	-29.64	peak
2	9240.000	36.20	10.58	46.78	74.00	-27.22	peak
3	11340.000	32.89	16.01	48.90	74.00	-25.10	peak
4	11730.000	32.35	17.22	49.57	74.00	-24.43	peak
5	13920.000	28.19	21.79	49.98	74.00	-24.02	peak
6	17805.000	24.27	24.54	48.81	74.00	-25.19	peak




Test Mode:	802.11n HT20	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7635.000	37.21	6.33	43.54	74.00	-30.46	peak
2	9150.000	36.18	10.54	46.72	74.00	-27.28	peak
3	10170.000	35.81	12.34	48.15	74.00	-25.85	peak
4	11730.000	32.22	17.22	49.44	74.00	-24.56	peak
5	14205.000	29.47	21.11	50.58	74.00	-23.42	peak
6	17985.000	24.38	25.60	49.98	74.00	-24.02	peak

Test Mode:	802.11n HT20	Channel:	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5295.000	40.42	0.69	41.11	74.00	-32.89	peak
2	9060.000	36.64	10.51	47.15	74.00	-26.85	peak
3	10215.000	36.23	12.43	48.66	74.00	-25.34	peak
4	11025.000	34.39	14.85	49.24	74.00	-24.76	peak
5	13920.000	28.11	21.79	49.90	74.00	-24.10	peak
6	18000.000	24.16	25.69	49.85	74.00	-24.15	peak

Test Mode:	802.11n HT20	Channel:	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3645.000	47.80	-4.62	43.18	74.00	-30.82	peak
2	7275.000	36.64	6.49	43.13	74.00	-30.87	peak
3	9150.000	36.17	10.54	46.71	74.00	-27.29	peak
4	10800.000	34.30	14.06	48.36	74.00	-25.64	peak
5	13515.000	29.18	20.93	50.11	74.00	-23.89	peak
6	17970.000	24.01	25.51	49.52	74.00	-24.48	peak

Test Mode:	802.11n HT20	Channel:	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7170.000	37.08	6.56	43.64	74.00	-30.36	peak
2	9135.000	36.70	10.55	47.25	74.00	-26.75	peak
3	10965.000	34.70	14.64	49.34	74.00	-24.66	peak
4	11940.000	31.90	17.80	49.70	74.00	-24.30	peak
5	13890.000	28.39	21.72	50.11	74.00	-23.89	peak
6	18000.000	23.73	25.69	49.42	74.00	-24.58	peak

Test Mode:	802.11n HT20	Channel:	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7275.000	36.86	6.49	43.35	74.00	-30.65	peak
2	9195.000	36.28	10.56	46.84	74.00	-27.16	peak
3	10215.000	35.74	12.43	48.17	74.00	-25.83	peak
4	11730.000	33.34	17.22	50.56	74.00	-23.44	peak
5	13935.000	27.91	21.82	49.73	74.00	-24.27	peak
6	17955.000	24.85	25.42	50.27	74.00	-23.73	peak

Test Mode:	802.11n HT40	Channel:	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7305.000	37.32	6.47	43.79	74.00	-30.21	peak
2	9255.000	36.46	10.59	47.05	74.00	-26.95	peak
3	10860.000	34.16	14.27	48.43	74.00	-25.57	peak
4	12645.000	31.09	17.92	49.01	74.00	-24.99	peak
5	13590.000	28.70	21.09	49.79	74.00	-24.21	peak
6	17700.000	25.20	23.91	49.11	74.00	-24.89	peak

Test Mode:	802.11n HT40	Channel:	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3645.000	47.91	-4.62	43.29	74.00	-30.71	peak
2	10155.000	35.59	12.32	47.91	74.00	-26.09	peak
3	11055.000	33.17	14.96	48.13	74.00	-25.87	peak
4	13515.000	28.51	20.93	49.44	74.00	-24.56	peak
5	14070.000	28.00	21.67	49.67	74.00	-24.33	peak
6	17700.000	25.46	23.91	49.37	74.00	-24.63	peak


Test Mode:	802.11n HT40	Channel:	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4845.000	41.17	-0.15	41.02	74.00	-32.98	peak
2	7890.000	38.42	6.31	44.73	74.00	-29.27	peak
3	9210.000	36.21	10.57	46.78	74.00	-27.22	peak
4	11310.000	33.54	15.91	49.45	74.00	-24.55	peak
5	13575.000	29.72	21.06	50.78	74.00	-23.22	peak
6	17985.000	24.63	25.60	50.23	74.00	-23.77	peak




Test Mode:	802.11n HT40	Channel:	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7035.000	36.44	6.67	43.11	74.00	-30.89	peak
2	8970.000	36.28	10.26	46.54	74.00	-27.46	peak
3	10215.000	35.53	12.43	47.96	74.00	-26.04	peak
4	11700.000	32.40	17.14	49.54	74.00	-24.46	peak
5	13620.000	29.26	21.15	50.41	74.00	-23.59	peak
6	17700.000	26.21	23.91	50.12	74.00	-23.88	peak

Test Mode:	802.11n HT40	Channel:	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5670.000	39.96	1.33	41.29	74.00	-32.71	peak
2	8010.000	38.19	6.32	44.51	74.00	-29.49	peak
3	9135.000	36.56	10.55	47.11	74.00	-26.89	peak
4	11010.000	33.62	14.81	48.43	74.00	-25.57	peak
5	13560.000	29.61	21.04	50.65	74.00	-23.35	peak
6	17895.000	24.98	25.07	50.05	74.00	-23.95	peak


Test Mode:	802.11n HT40	Channel:	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5295.000	40.58	0.69	41.27	74.00	-32.73	peak
2	7635.000	37.92	6.33	44.25	74.00	-29.75	peak
3	9060.000	36.66	10.51	47.17	74.00	-26.83	peak
4	11730.000	32.04	17.22	49.26	74.00	-24.74	peak
5	13920.000	29.33	21.79	51.12	74.00	-22.88	peak
6	17985.000	24.87	25.60	50.47	74.00	-23.53	peak


### 8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11b	Channel:	2412
Polarity:	FACE ON	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	76.22	-101.40	-25.18	47.60	-76.68	-3.90	-72.78	peak
2	0.0212	70.04	-101.35	-31.31	41.07	-82.81	-10.43	-72.38	peak
3	0.0279	67.67	-101.38	-33.71	38.69	-85.21	-12.81	-72.40	peak
4	0.0466	63.17	-101.46	-38.29	34.23	-89.79	-17.27	-72.52	peak
5	0.0656	62.36	-101.55	-39.19	31.26	-90.69	-20.24	-70.45	peak
6	0.0922	60.51	-101.74	-41.23	28.31	-92.73	-23.19	-69.54	peak

Test Mode:	802.11b	Channel:	2412
Polarity:	FACE ON	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1595	75.86	-101.65	-25.79	23.55	-77.29	-27.95	-49.34	peak
2	0.1794	73.27	-101.68	-28.41	22.53	-79.91	-28.97	-50.94	peak
3	0.2078	69.74	-101.73	-31.99	21.25	-83.49	-30.25	-53.24	peak
4	0.2530	67.64	-101.80	-34.16	19.54	-85.66	-31.96	-53.70	peak
5	0.3251	63.21	-101.88	-38.67	17.36	-90.17	-34.14	-56.03	peak
6	0.3800	61.02	-101.94	-40.92	16.01	-92.42	-35.49	-56.93	peak


Test Mode:	802.11b	Channel:	2412
Polarity:	FACE ON	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5917	63.74	-62.08	1.66	32.16	-49.84	-19.34	-30.50	peak
2	1.4818	58.11	-62.05	-3.94	24.19	-55.44	-27.31	-28.13	peak
3	3.7100	55.20	-61.41	-6.21	29.54	-57.71	-21.96	-35.75	peak
4	6.2445	54.63	-61.32	-6.69	29.54	-58.19	-21.96	-36.23	peak
5	10.7299	52.98	-60.83	-7.85	29.54	-59.35	-21.96	-37.39	peak
6	16.6021	53.52	-60.96	-7.44	29.54	-58.94	-21.96	-36.98	peak


### 8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18144.000	48.77	-5.48	43.29	74.00	-30.71	peak
2	19392.000	49.12	-5.57	43.55	74.00	-30.45	peak
3	21032.000	47.65	-4.87	42.78	74.00	-31.22	peak
4	22160.000	47.08	-4.31	42.77	74.00	-31.23	peak
5	23744.000	46.65	-3.20	43.45	74.00	-30.55	peak
6	25000.000	45.86	-2.10	43.76	74.00	-30.24	peak

Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18112.000	50.46	-5.47	44.99	74.00	-29.01	peak
2	18712.000	49.40	-5.40	44.00	74.00	-30.00	peak
3	19992.000	49.35	-5.45	43.90	74.00	-30.10	peak
4	21400.000	48.54	-4.72	43.82	74.00	-30.18	peak
5	22792.000	48.11	-3.65	44.46	74.00	-29.54	peak
6	25736.000	45.94	-0.68	45.26	74.00	-28.74	peak




## 8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	86.2600	52.18	-21.95	30.23	40.00	-9.77	QP
2	156.1000	47.51	-17.88	29.63	43.50	-13.87	QP
3	217.2100	56.10	-17.36	38.74	46.00	-7.26	QP
4	268.6200	58.35	-17.61	40.74	46.00	-5.26	QP
5	389.8700	50.68	-12.90	37.78	46.00	-8.22	QP
6	442.2500	47.64	-11.94	35.70	46.00	-10.30	QP

Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.9400	53.96	-18.55	35.41	40.00	-4.59	QP
2	91.1100	55.92	-22.06	33.86	43.50	-9.64	QP
3	129.9100	53.27	-19.31	33.96	43.50	-9.54	QP
4	218.1800	54.23	-17.42	36.81	46.00	-9.19	QP
5	297.7200	47.28	-15.43	31.85	46.00	-14.15	QP
6	442.2500	48.26	-11.94	36.32	46.00	-9.68	QP

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### DESCRIPTION

Pass

## 10. AC POWER LINE CONDUCTED EMISSION


### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 12 mm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

**TEST ENVIRONMENT**


Temperature	25.2°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST DATE / ENGINEER**

Test Date	May 26, 2023	Test By	Wite Chen
-----------	--------------	---------	-----------

**TEST RESULTS**

Test Mode:	802.11b	Channel:	2412
Line:	Line	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1507	45.53	9.49	55.02	65.96	-10.94	QP
2	0.1507	31.67	9.49	41.16	55.96	-14.80	AVG
3	0.1819	41.68	9.55	51.23	64.40	-13.17	QP
4	0.1819	31.23	9.55	40.78	54.40	-13.62	AVG
5	0.3784	31.52	9.53	41.05	58.31	-17.26	QP
6	0.3784	21.24	9.53	30.77	48.31	-17.54	AVG
7	0.5076	31.14	9.50	40.64	56.00	-15.36	QP
8	0.5076	22.83	9.50	32.33	46.00	-13.67	AVG
9	3.5433	24.99	9.61	34.60	56.00	-21.40	QP
10	3.5433	21.51	9.61	31.12	46.00	-14.88	AVG
11	12.5839	27.75	9.66	37.41	60.00	-22.59	QP
12	12.5839	21.78	9.66	31.44	50.00	-18.56	AVG

**Note:**

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Channel:	2412
Line:	Neutral	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1703	42.94	9.53	52.47	64.95	-12.48	QP
2	0.1703	30.54	9.53	40.07	54.95	-14.88	AVG
3	0.3323	30.66	9.55	40.21	59.39	-19.18	QP
4	0.3323	23.01	9.55	32.56	49.39	-16.83	AVG
5	0.4850	32.27	9.50	41.77	56.25	-14.48	QP
6	0.4850	18.36	9.50	27.86	46.25	-18.39	AVG
7	0.5753	27.98	9.50	37.48	56.00	-18.52	QP
8	0.5753	14.82	9.50	24.32	46.00	-21.68	AVG
9	4.5553	23.27	9.61	32.88	56.00	-23.12	QP
10	4.5553	19.65	9.61	29.26	46.00	-16.74	AVG
11	12.8558	27.82	9.66	37.48	60.00	-22.52	QP
12	12.8558	21.86	9.66	31.52	50.00	-18.48	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

## 11. TEST DATA


### 11.1. APPENDIX A: DTS BANDWIDTH


#### 11.1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	7.76	2407.92	2415.68	≥0.5	PASS
		2437	7.60	2433.40	2441.00	≥0.5	PASS
		2462	8.08	2457.92	2466.00	≥0.5	PASS
11G	Ant1	2412	14.68	2404.40	2419.08	≥0.5	PASS
		2437	15.08	2429.40	2444.48	≥0.5	PASS
		2462	15.08	2454.44	2469.52	≥0.5	PASS
11N20SISO	Ant1	2412	16.00	2404.44	2420.44	≥0.5	PASS
		2437	16.08	2429.40	2445.48	≥0.5	PASS
		2462	16.32	2453.80	2470.12	≥0.5	PASS
11N40SISO	Ant1	2422	35.12	2404.40	2439.52	≥0.5	PASS
		2437	35.12	2419.40	2454.52	≥0.5	PASS
		2452	35.12	2434.40	2469.52	≥0.5	PASS




### 11.1.2. Test Graphs







11G\_Ant1\_2412




11G\_Ant1\_2437




11G\_Ant1\_2462




11N20SISO\_Ant1\_2412




11N20SISO\_Ant1\_2437




11N20SISO\_Ant1\_2462



11N40SISO\_Ant1\_2422



11N40SISO\_Ant1\_2437




11N40SISO\_Ant1\_2452




## 11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

### 11.2.1. Test Result


Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant1	2412	12.897	2405.5606	2418.4577	PASS
		2437	12.861	2430.5467	2443.4077	PASS
		2462	12.848	2455.5613	2468.4095	PASS
11G	Ant1	2412	17.031	2403.4857	2420.5162	PASS
		2437	16.992	2428.5145	2445.5062	PASS
		2462	16.919	2453.4879	2470.4072	PASS
11N20SISO	Ant1	2412	17.96	2403.0267	2420.9864	PASS
		2437	17.884	2428.0474	2445.9318	PASS
		2462	17.907	2453.0335	2470.9405	PASS
11N40SISO	Ant1	2422	36.158	2403.9802	2440.1383	PASS
		2437	36.362	2418.8370	2455.1990	PASS
		2452	36.301	2433.8954	2470.1965	PASS

## 11.2.2. Test Graphs







**11G\_Ant1\_2462**



11N20SISO\_Ant1\_2412






11N20SISO\_Ant1\_2437



11N20SISO\_Ant1\_2462





**11N40SISO\_Ant1\_2452**

### 11.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

#### 11.3.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	12.72	≤30.00	PASS
		2437	12.87	≤30.00	PASS
		2462	12.78	≤30.00	PASS
11G	Ant1	2412	9.25	≤30.00	PASS
		2437	9.31	≤30.00	PASS
		2462	9.25	≤30.00	PASS
11N20SISO	Ant1	2412	8.66	≤30.00	PASS
		2437	8.67	≤30.00	PASS
		2462	8.63	≤30.00	PASS
11N40SISO	Ant1	2422	8.56	≤30.00	PASS
		2437	8.53	≤30.00	PASS
		2452	8.46	≤30.00	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor


2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.


## 11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY

### 11.4.1. Test Result


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-17.76	≤8.00	PASS
		2437	-17.55	≤8.00	PASS
		2462	-17.62	≤8.00	PASS
11G	Ant1	2412	-23.97	≤8.00	PASS
		2437	-24.21	≤8.00	PASS
		2462	-21.88	≤8.00	PASS
11N20SISO	Ant1	2412	-21.51	≤8.00	PASS
		2437	-24.25	≤8.00	PASS
		2462	-21.86	≤8.00	PASS
11N40SISO	Ant1	2422	-20.99	≤8.00	PASS
		2437	-23.8	≤8.00	PASS
		2452	-23.37	≤8.00	PASS

### 11.4.2. Test Graphs







11G\_Ant1\_2412




11G\_Ant1\_2437




11G\_Ant1\_2462




11N20SISO\_Ant1\_2412




11N20SISO\_Ant1\_2437




11N20SISO\_Ant1\_2462



11N40SISO\_Ant1\_2422



11N40SISO\_Ant1\_2437



11N40SISO\_Ant1\_2452


## 11.5. APPENDIX E: BAND EDGE MEASUREMENTS


### 11.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	4.36	-38.13	≤-25.64	PASS
		High	2462	4.87	-37.16	≤-25.13	PASS
11G	Ant1	Low	2412	-1.34	-38.22	≤-31.34	PASS
		High	2462	-1.03	-37.25	≤-31.03	PASS
11N20SISO	Ant1	Low	2412	-1.77	-38.28	≤-31.77	PASS
		High	2462	-1.55	-37.37	≤-31.55	PASS
11N40SISO	Ant1	Low	2422	-4.60	-37.82	≤-34.6	PASS
		High	2452	-4.34	-37.07	≤-34.34	PASS




### 11.5.2. Test Graphs







11G\_Ant1\_High\_2462




11N20SISO\_Ant1\_Low\_2412



11N20SISO\_Ant1\_High\_2462



11N40SISO\_Ant1\_Low\_2422




11N40SISO\_Ant1\_High\_2452


## 11.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION

### 11.6.1. Test Result


Test Mode	Antenna	Channel	FreqRange [Mhz]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	4.99	---	PASS
			30~1000	-47.05	≤-25.01	PASS
			1000~26500	-37.8	≤-25.01	PASS
		2437	Reference	5.55	---	PASS
			30~1000	-48.41	≤-24.45	PASS
			1000~26500	-37.76	≤-24.45	PASS
		2462	Reference	5.31	---	PASS
			30~1000	-47.88	≤-24.69	PASS
			1000~26500	-37.84	≤-24.69	PASS
11G	Ant1	2412	Reference	-0.87	---	PASS
			30~1000	-48.25	≤-30.87	PASS
			1000~26500	-36.93	≤-30.87	PASS
		2437	Reference	-0.78	---	PASS
			30~1000	-48.3	≤-30.78	PASS
			1000~26500	-36.99	≤-30.78	PASS
		2462	Reference	-0.84	---	PASS
			30~1000	-47.91	≤-30.84	PASS
			1000~26500	-37.73	≤-30.84	PASS
11N20SISO	Ant1	2412	Reference	-1.49	---	PASS
			30~1000	-48.68	≤-31.49	PASS
			1000~26500	-37.68	≤-31.49	PASS
		2437	Reference	-1.24	---	PASS
			30~1000	-48.22	≤-31.24	PASS
			1000~26500	-36.8	≤-31.24	PASS
		2462	Reference	-1.28	---	PASS
			30~1000	-46.66	≤-31.28	PASS
			1000~26500	-37.11	≤-31.28	PASS
11N40SISO	Ant1	2422	Reference	-4.06	---	PASS
			30~1000	-48.26	≤-34.06	PASS
			1000~26500	-38.11	≤-34.06	PASS
		2437	Reference	-4.10	---	PASS
			30~1000	-48.47	≤-34.1	PASS
			1000~26500	-37.47	≤-34.1	PASS
		2452	Reference	-4.26	---	PASS
			30~1000	-47.82	≤-34.26	PASS
			1000~26500	-36.38	≤-34.26	PASS

### 11.6.2. Test Graphs







11B\_Ant1\_2437\_0~Reference




11B\_Ant1\_2437\_30~1000




11B\_Ant1\_2437\_1000~26500




11B\_Ant1\_2462\_0~Reference




11B\_Ant1\_2462\_30~1000




11B\_Ant1\_2462\_1000~26500



11G\_Ant1\_2412\_0~Reference




11G\_Ant1\_2412\_30~1000




11G\_Ant1\_2412\_1000~26500







11G\_Ant1\_2437\_0~Reference




11G\_Ant1\_2437\_30~1000




11G\_Ant1\_2437\_1000~26500




11G\_Ant1\_2462\_0~Reference




11G\_Ant1\_2462\_30~1000




11G\_Ant1\_2462\_1000~26500




11N20SISO\_Ant1\_2412\_0~Reference




11N20SISO\_Ant1\_2412\_30~1000




11N20SISO\_Ant1\_2412\_1000~26500




11N20SISO\_Ant1\_2437\_0~Reference




11N20SISO\_Ant1\_2437\_30~1000




11N20SISO\_Ant1\_2437\_1000~26500




11N20SISO\_Ant1\_2462\_0~Reference




11N20SISO\_Ant1\_2462\_30~1000




11N20SISO\_Ant1\_2462\_1000~26500




11N40SISO\_Ant1\_2422\_0~Reference




11N40SISO\_Ant1\_2422\_30~1000




11N40SISO\_Ant1\_2422\_1000~26500




11N40SISO\_Ant1\_2437\_0~Reference




11N40SISO\_Ant1\_2437\_30~1000




11N40SISO\_Ant1\_2437\_1000~26500



11N40SISO\_Ant1\_2452\_0~Reference



11N40SISO\_Ant1\_2452\_30~1000



11N40SISO\_Ant1\_2452\_1000~26500



## 11.7. APPENDIX G: DUTY CYCLE

### 11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11b	8.36	8.4	0.9952	99.52	0.02	N/A	0.01
11g	1.39	1.43	0.9720	97.20	0.12	0.72	1
11n HT20	1.29	1.34	0.9627	96.27	0.17	0.78	1
11n HT40	0.64	0.69	0.9275	92.75	0.33	1.56	2

**Note:**

Duty Cycle Correction Factor =  $10 \log (1/x)$ .


Where: x is Duty Cycle (Linear)


Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW  $\leq RBW/100$  (i.e., 10 kHz) but not less than 10 Hz.

### 11.7.2. Test Graphs





END OF REPORT