



FCC RF EXPOSURE REPORT

For

X-MEN[™] WITH RISER, X-MEN[™] WITH RISER & STOOL

MODEL NUMBER: XMN-A-01088, XMN-A-01253

FCC ID: 2APXHXM

REPORT NUMBER: 4789954603.2-3

ISSUE DATE: June 8, 2021

Prepared for

WF Tastemakers Trading Limited (FCC) Unit 05 and unit 06, 6th Floor, Greenfield Tower Concordia Plaza, 1 Science Museum Road, TST East, Hong Kong

WF TASTEMAKERS TRADING LIMITED (ISED) 980 Avenue of the Americas, 3rd Floor New York NY 10018 American Samoa

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	06/08/2021	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	.4
2.	TEST METHODOLOGY	.5
3.	FACILITIES AND ACCREDITATION	.5
4.	REQUIREMENT	.6



1. ATTESTATION OF TEST RESULTS

APPLICABLE STANDARDS STANDARD TEST RESULTS FCC 47CFR§2.1091 PASS

Prepared By:

Brany Denny

Checked By:

Sherry lies



Denny Huang Project Engineer Shawn Wen Laboratory Leader

Approved By:

herbur

Stephen Guo Laboratory Manager

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

	-
	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
Approxitation	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Accreditation Certificate	has been registered and fully described in a report filed with ISED.
Certificate	The Company Number is 21320 and the test lab Conformity Assessment
	Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch This report shall not be reproduced except in full, without the written approval of UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch. FORM No.: 10-SL-F0112



4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

	RF	EXP	OSURE	LIMIT	
--	----	-----	-------	-------	--

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

 $\begin{array}{l} S=PG/4\pi R^2 \\ Where: \\ S=power density \\ P=power input to antenna \\ G=power gain of the antenna in the direction of interest relative to an isotropic radiator \\ R=distance to the center of radiation of the antenna \end{array}$



CALCULATED RESULTS

WiFi Mode					
Frequency Range	Output Power	Output Power	Power Density	Power Density Limit	Result
MHz	dBm	mW	mW/cm ²	mW/cm ²	
2412 ~ 2462	17.5	56.2	0.035	1.0	Complies

Note: 1. Antenna Gain=5.0dBi (Numeric 3.16), π =3.141.

2. The Power comes from turn-up power which is declared by customer.

3. The minimum separation distance of the device is greater than 20 cm.

4. Calculate by WORST-CASE mode.

END OF REPORT