



ASAP Technology (Jiangxi) Co., Ltd  
Ji'an Industrial Park, Ji'an, Jiangxi 343100, China

## Declaration

Applicant: Asap Technology(Jiangxi) Co., Ltd.  
FCC ID:2APXNLACA090

To whom it may be concern:

We the undersigned hereby confirm that the device meeting all requirements of KDB 680106 D01 v03 section 5.b) as below, for more details please refer to the description and RF exposure test report.

- 1) Power transfer frequency is less than 1 MHz.  
Reply: This device power transfer frequency is 110-205kHz.
- 2) Output power from each primary coil is less than or equal to 15 watts.  
Reply: This device output power from each primary coil is 5 Watts.
- 3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.  
Reply: This device includes only single primary coil.
- 4) Client device is placed directly in contact with the transmitter.  
Reply: Client device is placed directly in contact with the EUT.
- 5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  
Reply: This device belongs to the mobile device and subjects to mobile exposure conditions only.
- 6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.  
Reply: The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from the transmitting coils are demonstrated to be less than 50% of the MPE limit. The test results are shown in the RF exposure test report.

If you have questions or need further information, please contact the undersigned.

*Xiaolan Deng*

---

Xiaolan Deng  
Manager

Date: June 19, 2018