

# Human Exposure Report


**Application No.:** SZEM1912021086CR  
**Applicant:** ASAP Technology (Jiangxi) Co., Ltd.  
**Address of Applicant:** Ji'an Industrial Park Ji'an, Jiangxi China 343100  
**Manufacturer:** ASAP Technology (Jiangxi) Co., Ltd.  
**Address of Manufacturer:** Ji'an Industrial Park Ji'an, Jiangxi China 343100  
**Factory:** LUXSHARE-ICT (VIETNAM) LIMITED  
**Address of Factory:** E Lot, Quang Chau Industrial zone, Quang Chau Commune, Viet Yen district, Bac Giang Province, Vietnam

**Equipment Under Test (EUT):**  
**EUT Name:** Night Light Wireless Charger  
**Model No.:** LACA117, WIAAQU100012444 ♣  
 ♣ Please refer to section 3.2 of this report which indicates which model was actually tested and which were electrically identical.

**Trade mark:** onn.  
**FCC ID:** 2APXNLACA117  
**Standards:** 47 CFR PART 1, Subpart I, Section 1.1310  
**Date of Receipt:** 2019-12-11  
**Date of Test:** 2019-12-13 to 2019-12-19  
**Date of Issue:** 2019-12-24

<b>Test Result :</b>	<b>Pass*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above



Keny Xu  
 EMC Laboratory Manager



<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2019-12-24		Original

<b>Authorized for issue by:</b>			
			
		<hr/> <b>Bill Chen /Project Engineer</b>	
			
		<hr/> <b>Eric Fu /Reviewer</b>	



## 2 Contents

<b>1</b>	<b>COVER PAGE</b> .....	<b>1</b>
<b>2</b>	<b>CONTENTS</b> .....	<b>3</b>
<b>3</b>	<b>GENERAL INFORMATION</b> .....	<b>4</b>
3.1	DETAILS OF E.U.T. ....	4
3.2	DESCRIPTION OF SUPPORT UNITS .....	4
3.3	TEST LOCATION.....	5
3.4	TEST FACILITY.....	5
3.5	DEVIATION FROM STANDARDS.....	5
3.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	5
<b>4</b>	<b>EQUIPMENTS USED DURING TEST</b> .....	<b>6</b>
<b>5</b>	<b>TEST RESULTS</b> .....	<b>7</b>
5.1	RF EXPOSURE TEST .....	7
5.1.1	<i>E.U.T. Operation</i> .....	7
<b>6</b>	<b>PHOTOGRAPHS- RF EXPOSURE SETUP</b> .....	<b>9</b>



### 3 General Information

#### 3.1 Details of E.U.T.

Power Supply: Adapter:  
Model:LACW011  
Input:AC 100-240V ~ 50/60Hz 0.35A  
Output: DC 5V 2.4A  
Wireless Charger  
Input: DC 5V 2.4A  
Output: 5W Max  
Output:LED(1W Max )

Cable: DC cable:150cm unshielded

Operation frequency: 110.096-148.077kHz

Antenna Type: Loop Antenna

Modulation Type: Load Modulation

Antenna Gain: 0dBi

#### 3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
SAMSUNG Galaxy S8	SAMSUNG	SM-G9500	R28J9140LPB

#### Declaration of EUT Family Grouping:

Model No.: LACA117, WIAAQU100012444

Only the model WIAAQU100012444 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model No. and the appearance.



### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 3.5 Deviation from Standards

None.

### 3.6 Abnormalities from Standard Conditions

None.



## 4 Equipments Used during Test

Item	Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
1	Electric and Magnetic Field Analyzer	Narda	EHP-50F	EMC092	2019-05-07	2020-05-06



## 5 Test Results

### 5.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

Measurement Distance: 15cm

Limit:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

#### 5.1.1 E.U.T. Operation

##### Operating Environment:

Temperature: 24.0 °C      Humidity: 52% RH      Atmospheric Pressure: 1015 mbar

##### EUT Operation:

This device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



**5.1.2 Measurement Data**

**Output Voltage=DC 5V; The max output power =5W**

**Magnetic Field Emissions**

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
139 kHz	15	Side 1	0.0938	0.815
		Side 2	0.0621	0.815
		Side 3	0.0805	0.815
		Side 4	0.0765	0.815
		Top	0.0488	0.815

**Mobile phone has been charge at zero charge, intermediate charge, and full charge.**

**Magnetic Field Emissions**

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
139 kHz	15	Side 1	0.1049	0.0892	0.0855	0.815
		Side 2	0.0738	0.0622	0.0572	0.815
		Side 3	0.0893	0.0756	0.0713	0.815
		Side 4	0.0859	0.0705	0.0658	0.815
		Top	0.0610	0.0487	0.0446	0.815





## 6 Photographs- RF exposure setup

Refer to RF Exposure Setup Photos.

- End of the Report -

