

Human Exposure Report

Application No.: SZEM1911020749CR
Applicant: ASAP Technology(Jiangxi) Co., Ltd.
Address of Applicant: Ji'an Industrial Park, Ji'an, Jiangxi, 343100, China
Manufacturer: ASAP Technology(Jiangxi) Co., Ltd.
Address of Manufacturer: Ji'an Industrial Park, Ji'an, Jiangxi, 343100, China
Factory: LUXSHARE-ICT (VIETNAM) LIMITED
Address of Factory: E Lot, Quang Chau Industrial zone, Quang Chau Commune, Viet Yen district, Bac Giang Province, Vietnam


Equipment Under Test (EUT):
EUT Name: Foldable Wireless Charging Pad
Model No.: LACA124, WIABLK100008474 ♣
 ♣ Please refer to section 3.1 of this report which indicates which model was actually tested and which were electrically identical.

Trade mark: onn.
FCC ID: 2APXNLACA124
Standards: 47 CFR PART 1, Subpart I, Section 1.1310
 47 CFR PART 2, Subpart J, Section 2.1091

Date of Receipt: 2019-11-29
Date of Test: 2019-12-07 to 2020-01-14
Date of Issue: 2020-01-14

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above



Keny Xu
 EMC Laboratory Manager





Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-01-14		Original

Authorized for issue by:				
		<i>Bill Chen</i>		
		Bill Chen /Project Engineer		
		<i>Eric Fu</i>		
		Eric Fu /Reviewer		



2 Contents

1	COVER PAGE	1
2	CONTENTS	3
3	GENERAL INFORMATION	4
3.1	DETAILS OF E.U.T.	4
3.2	DESCRIPTION OF SUPPORT UNITS	4
3.3	TEST LOCATION.....	5
3.4	TEST FACILITY.....	5
3.5	DEVIATION FROM STANDARDS.....	5
3.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4	EQUIPMENTS USED DURING TEST	6
5	TEST RESULTS	7
5.1	RF EXPOSURE TEST	7
5.1.1	<i>E.U.T. Operation</i>	7-10



3 General Information

3.1 Details of E.U.T.

Power Supply: Input: DC 5V-12V 1.5A Max
Output: 10W Max

Operation frequency: 126.122-128.846kHz

Antenna Type: Loop Antenna

Modulation Type: Load Modulation

Antenna Gain: 0dBi

Remark: Tests were conducted in all three load modes and the worst case 10W is reported only.

Remark:

Model No.: LACA124, WIABLK100008474

Only the model WIABLK100008474 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model No. and the appearance.

3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
iPhone 8	Apple	A1863	F4GVQ656JC6D
SAMSUNG Galaxy S8	SAMSUNG	SM-G9500	R28J9140LPB
Adapter	SAMSUNG	EP-TA200	R37J8YA7W71DK3
Micro USB cable	PHILIPS	SWR2101	SEA0700



3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.



4 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Due date
1	Electric and Magnetic Field Analyzer	Narda	EHP-50F	EMC092	2020-02-05



5 Test Results

5.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

Measurement Distance: 15cm

Limit:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

5.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 52% RH Atmospheric Pressure: 1015 mbar

EUT Operation:

This device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



5.1.2 Measurement Data

Horizontal

Output Voltage=DC 9V; The max output power =10W;

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
127 kHz	15	Side 1	0.0845	0.815
		Side 2	0.0409	0.815
		Side 3	0.0803	0.815
		Side 4	0.0634	0.815
		Top	0.0356	0.815

Mobile phone has been charge at zero charge, intermediate charge, and full charge.

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
127 kHz	15	Side 1	0.0958	0.0811	0.0762	0.815
		Side 2	0.0504	0.0395	0.0348	0.815
		Side 3	0.0898	0.0785	0.0748	0.815
		Side 4	0.0730	0.0609	0.0569	0.815
		Top	0.0485	0.0339	0.0291	0.815



Flat

Output Voltage=DC 5V; The max output power =10W;Calculation of resistor value=5Ω

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
127 kHz	15	Side 1	0.1027	0.815
		Side 2	0.0633	0.815
		Side 3	0.0951	0.815
		Side 4	0.0585	0.815
		Top	0.0448	0.815

Mobile phone has been charge at zero charge, intermediate charge, and full charge.

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
127 kHz	15	Side 1	0.1152	0.1024	0.0981	0.815
		Side 2	0.0761	0.0623	0.0585	0.815
		Side 3	0.1054	0.0939	0.0895	0.815
		Side 4	0.0674	0.0561	0.0519	0.815
		Top	0.0536	0.0419	0.0372	0.815



Vertical

Output Voltage=DC 5V; The max output power =10W;Calculation of resistor value=5Ω

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
127 kHz	15	Side 1	0.0633	0.815
		Side 2	0.0428	0.815
		Side 3	0.0714	0.815
		Side 4	0.0595	0.815
		Top	0.0327	0.815

Mobile phone has been charge at zero charge, intermediate charge, and full charge.

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
127 kHz	15	Side 1	0.0752	0.0622	0.0584	0.815
		Side 2	0.0522	0.0366	0.0319	0.815
		Side 3	0.0833	0.0717	0.0674	0.815
		Side 4	0.0719	0.0597	0.0553	0.815
		Top	0.0430	0.0273	0.0231	0.815

- End of the Report -

