

ASAP Technology (jiangxi) Co., Ltd

TEST REPORT

SCOPE OF WORK

SAR Assessment– 080-08-3787

REPORT NUMBER

240430021SZN-002

ISSUE DATE

05 June 2024

[REVISED DATE]

[-----]

PAGES

5

DOCUMENT CONTROL NUMBER

RF Exposure

© 2017 INTERTEK



Test Report

Applicant : ASAP Technology (jiangxi) Co., Ltd
Ji'an Industrial Park, Ji'an, Jiangxi 343100 China

Sample Description
Product : Wireless charger

Model No. : 080-08-3787

Electrical Rating : Input: 5V/3A, 9V/2.22A
Wireless Output: 15W

Date Received : April 30, 2024
Date Test Conducted : April 30, 2024 to April 30, 2024

Test Requested : Test for compliance with CFR 47 part 1
Test Method : Environmental evaluation and exposure limit according
to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310
KDB 680106 D01 RF Exposure Wireless Charging v04

Test Result : Pass
Conclusion : When determining of test conclusion, measurement
uncertainty of tests have been considered.

***** End of Page *****

Prepared and Checked By:

Approved By:

Tenet Cao
Assistant Engineer

Ryan Chen
Sr. Project Engineer
Date: 05 June 2024

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch


101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288

Fax: (86 755) 8601 6751

Test Report

Test Setup Configuration



Note:

- The RF exposure test is performed in the shield room.
- The test distance is measured from the center of the test probe along all three axes of the device, from 0 cm to 20 cm, from the edge of the device coil in minimum 2 cm increments.

Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Cal. Date	Due Date
SZ186-06	The Magnetic Amplitude and Gradient Probe System	SPEAG	MAGPy-8D3D+E3D	2024-03-07	2025-03-07

This product was tested in the following configuration:

Description	Manufacturer	Detail
Mobile phone	Samsung (Provided by Intertek)	Model: Samsung (SM-G9300)
Adapter	dealworthy™ (Provided by Client)	Model: 080-08-3787 Input: 100-240Vac 50/60Hz 0.5A Output: 5Vdc 3A, 9Vdc 2.22A

Justification

The EUT was powered by an adapter with 120V/60Hz input during the test. All power input voltages (DC 5V=3A, 9V=2.22A) and all rated output powers have been tested. And have considered all the following EUT modes of operation to pre-scan the test system.

Pertest mode	Description
Mode 1	Standby mode
Mode 2	Mobile phone is charging at 1% battery power
Mode 3	Mobile phone is charging at 50% battery power
Mode 4	Mobile phone is charging at 99% battery power
Mode 5	Continuous maximum power

Note:

- H-field data are measured in minimal increments of 2 cm from the edge of the device along all three axes of the device, from 0 cm to 20 cm, one axis is consistent with the axis of the main coil, all modes and distances have been fully tested. The worst-case testing data were recorded in this report.
- Mode 5 is a special product sample provided by the customer for this test, which allows the equipment to operate at maximum power without a client device.

Reference Limit:

Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	(100) *	30

Note: * = Plane wave equivalent power density

Test Result:

During test, the mobile phone is being charged.

Worst Case Operating Mode: Mode 2 for 2cm distance; Mode 2 for 4cm to 20cm distance

Center of the probe to the probe outer edge is 1.85 cm, so the test distance can only reach 2cm.

H-field strength measurement result at 2cm to 20 cm:

Test Position	Test distance(cm)										Limits (A/m)
	2	4	6	8	10	12	14	16	18	20	
Side 1	1.041	0.353	0.051	0.032	0.052	0.029	0.016	0.012	0.010	0.007	1.63
Side 2	1.013	0.392	0.303	0.024	0.043	0.021	0.015	0.011	0.009	0.008	1.63
Side 3	0.933	0.271	0.060	0.051	0.039	0.021	0.016	0.011	0.010	0.006	1.63
Side 4	1.011	0.356	0.133	0.034	0.041	0.020	0.017	0.010	0.009	0.007	1.63
Top	0.823	0.195	0.042	0.031	0.024	0.021	0.018	0.013	0.011	0.009	1.63

H-field strength at 0cm:

Validation:

To determine the H-field strength of 0mm, an extrapolation function by setting to Probe tip in the software of MAGPy handheld system has been used.

The validation for this extrapolation is as follows:

Test mode	Distance (cm)	Estimated value (A/m)	30% tolerance (A/m)		Measured value (A/m)
			Min	Max	
Mode 5	1.85	1.29 (probe tip to EUT)	0.90	1.68	1.29 (probe center to EUT)
Mode 5	3.7	0.59 (probe tip to EUT)	0.41	0.77	0.57 (probe center to EUT)
Mode 5	5.55	0.12 (probe tip to EUT)	0.08	0.16	0.09 (probe center to EUT)
Conclusion: Estimated value has 30% agreement with actual measurement, verified the probe tip function.					

Note:

1. According to KDB 680106 D01 V04, the validation is considered sufficient if a 30% agreement between the Estimated value and the (E- and/ H-field) probe measurements is demonstrated.
2. Estimated value is obtained from the tip function of the probe.

Estimated H-field Result at 0 cm:

EUT Operation mode	Side 1(A/m)	Side 2(A/m)	Side 3(A/m)	Side 4(A/m)	Top(A/m)	Limits (A/m)
Mode 5	1.29	1.22	1.28	1.24	1.16	1.63

Configuration photo of the test:

Please refer to RF Exposure setup photos. pdf.

***** End of Report*****