



FCC PART 15B TEST REPORT

No. 23T04Z80961-18

for

Wingtech Group (Hong Kong) Limited

5G Mobile Phone

Model name: TMRV075G

FCC ID: 2APXW-TMRV075G

with

Hardware Version: V1.0

Software Version: TMRV075G_0.03.03

Issued Date: 2024-03-04

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
23T04Z80961-18	Rev.0	1 st edition	2024-03-04

Note: the latest revision of the test report supersedes all previous version.



CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE.....	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION.....	5
2.2. MANUFACTURER INFORMATION.....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT.....	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	6
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS.....	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT.....	8
6. SUMMARY OF TEST RESULTS.....	9
7. TEST EQUIPMENTS UTILIZED.....	10
ANNEX A: MEASUREMENT RESULTS	11

1. Test Laboratory

1.1. Testing Location

CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

1.2. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2024-01-31

Testing End Date: 2024-02-22


1.4. Signature



Wang Xue
(Prepared this test report)



Zhang Ying
(Reviewed this test report)



Zhang Xia
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Wingtech Group (Hong Kong) Limited
Address: Flat/RM 1903 19/F, Podium Plaza, 5 Hanoi Road, Tsim Sha Tsui, KL, HK
Contact sharui
Email sharui@wingtech.com
Tel. +86-21-53529900
Fax: /

2.2. Manufacturer Information

Company Name: Wingtech Group (Hong Kong) Limited
Address: Flat/RM 1903 19/F, Podium Plaza, 5 Hanoi Road, Tsim Sha Tsui, KL, HK
Contact sharui
Email sharui@wingtech.com
Tel. +86-21-53529900
Fax: /

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	5G Mobile Phone
Model Name	TMRV075G
FCC ID:	2APXW-TMRV075G

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	862503070025820/	V1.0	TMRV075G_0.03.03
	862503070025838		
EUT2	862503070027362/	V1.0	TMRV075G_0.03.03
	862503070027370		

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	Manufacture
AE1	Battery1	TM002	SCUD (FUJIAN) Electronics Co., Ltd.
AE2	Charger1	/	Provided by laboratory
AE3	USB Cable1	USB AM TO TYPE-C2.0	Huizhou Washin Electronics Co., LTD

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1 + AE1 +AE2+AE3	Charger1+MP3+F Camera +GSM 850 idle
Set.2	EUT1 + AE1 +AE2+AE3	Charger1+R Camera + WCDMA B5 idle
Set.3	EUT1 + AE1 + AE3	USB + LTE B5 idle
Set.4	EUT1 + AE1 + Cable + EUT2	OTG + NR n71 idle

Note:

Equipment Under Test (EUT) is a model of GSM/UMTS/LTE Mobile phone.

It supports

GSM Band	850/900/1800/1900
UMTS Band	FDD Band II(W1900) /FDD Band IV(W1700)/FDD V(W850)
LTE Band	FDD Bands 2/4/5/7/12/25/26/66/71,TDD Band 41
NR Band	n25/n41/n66/n71/n77

It has MP3, Camera, USB memory, Bluetooth V5.1, Wi-Fi (802.11a/b/g/n/ac, 802.11n supports 20MHz and 40MHz bandwidth, 802.11ac supports 20MHz, 40MHz and 80MHz bandwidth) and GPNSS function.

The device contains receivers which tune and operate between 30MHz-960MHz in the following mode: GSM 850, WCDMA850, LTE Band 5/12/26/71, NR Band n71. All licensed band

receivers that tune in the range of 30MHz-960MHz are investigated. Only the worst-case emissions are reported.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2019
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 M Ω
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB.
Electrical insulation	> 2 M Ω
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(huayuan North Road)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(huayuan North Road)

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESW44	103023	R&S	2024-07-08	1 Year
2	LISN	ENV216	101200	R&S	2024-07-04	1 Year
3	Test Receiver	ESCI 7	100344	R&S	2024-03-20	1 Year
4	EMI Antenna	VULB 9163	01222	SCHWARZBECK	2024-02-28	1 Year
5	EMI Antenna	3115	6914	ETS-Lindgren	2024-06-07	1 Year
6	Universal Communication Tester	CMW500	116588	R&S	2024-12-20	1 Year
7	Universal Communication Tester	E7515B	MY60102215	Keysight	2024-07-09	1 Year

Test software information		
Test Item	Software	Version
Radiated Emission	EMC32	V11.50.00
Conducted Emission	EMC32	V8.53.0

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB/OTG mode of MS and charging mode of MS) at distances of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode

The MS is operating in the USB mode, OTG mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode, and is connected to the other device for charging in OTG mode and is connected to a charger in the case of charging mode.

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz-960MHz, as listed in section 3.4, are investigated. Only the worst case emissions are reported.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

The model of the PC is M4000E-17, and the serial number of the PC is M706GWXD. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note : I/O information : Printer – USB, Mouse – PS/2, Keyboard – USB.

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz-960MHz, as listed in section 3.4, are investigated. Only the worst case emissions are reported.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit ($\mu\text{V/m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/3MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{Rpl} = P_{\text{Mea}} + G_A + G_{PL}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): $U = 4.84 \text{ dB}$, $k=2$.

Measurement results for Set.1:

Charing Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17731.740	46.60	-29.67	45.25	31.02	54.00	7.40	V
17961.580	46.60	-29.06	46.66	29.00	54.00	7.40	V
17985.380	46.50	-29.06	46.66	28.90	54.00	7.50	V
17999.320	46.50	-29.06	46.66	28.90	54.00	7.50	V
17977.220	46.40	-29.06	46.66	28.80	54.00	7.60	V
17734.460	46.30	-29.67	45.25	30.72	54.00	7.70	V

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17810.280	57.40	-29.63	45.95	41.08	74.00	16.60	H
17760.300	57.30	-29.63	45.95	40.97	74.00	16.70	V
17775.600	57.20	-29.63	45.95	40.87	74.00	16.80	V
17771.180	56.80	-29.63	45.95	40.47	74.00	17.20	H
17996.940	56.40	-29.06	46.66	38.80	74.00	17.60	V
17977.220	56.40	-29.06	46.66	38.80	74.00	17.60	H

Measurement results for Set.2:
Charing Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17874.540	46.70	-29.39	45.95	30.14	54.00	7.30	V
17988.100	46.70	-29.06	46.66	29.10	54.00	7.30	V
17975.860	46.70	-29.06	46.66	29.10	54.00	7.30	V
17992.860	46.70	-29.06	46.66	29.10	54.00	7.30	V
17760.980	46.60	-29.63	45.95	30.27	54.00	7.40	H
17987.760	46.50	-29.06	46.66	28.90	54.00	7.50	V

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17868.420	57.00	-29.39	45.95	40.44	74.00	17.00	V
17992.180	56.80	-29.06	46.66	39.20	74.00	17.20	H
17759.620	56.80	-29.61	45.95	40.46	74.00	17.20	H
17950.360	56.80	-28.94	46.66	39.08	74.00	17.20	V
17965.320	56.60	-29.06	46.66	39.00	74.00	17.40	V
17868.080	56.60	-29.39	45.95	40.04	74.00	17.40	H

Measurement results for Set.3:
USB Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17762.680	47.10	-29.63	45.95	30.77	54.00	6.90	H
17889.840	46.80	-29.53	45.95	30.38	54.00	7.20	H
17758.260	46.70	-29.61	45.95	30.36	54.00	7.30	H
17733.440	46.70	-29.67	45.25	31.12	54.00	7.30	V
17808.240	46.60	-29.63	45.95	30.28	54.00	7.40	V
17744.660	46.60	-29.61	45.95	30.26	54.00	7.40	V

USB Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17978.920	57.80	-29.06	46.66	40.20	74.00	16.20	H
17989.120	56.80	-29.06	46.66	39.20	74.00	17.20	H
17713.720	56.70	-29.73	45.25	41.19	74.00	17.30	V
17981.640	56.60	-29.06	46.66	39.00	74.00	17.40	H
17767.780	56.40	-29.63	45.95	40.07	74.00	17.60	H
17793.280	56.30	-29.89	45.95	40.23	74.00	17.70	V

Measurement results for Set.4:
OTG Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17774.240	47.20	-29.63	45.95	30.87	54.00	6.80	H
17760.640	47.10	-29.63	45.95	30.77	54.00	6.90	H
17775.600	47.10	-29.63	45.95	30.77	54.00	6.90	H
17770.840	47.10	-29.63	45.95	30.77	54.00	6.90	H
17770.500	47.00	-29.63	45.95	30.67	54.00	7.00	H
17891.200	46.80	-29.53	45.95	30.38	54.00	7.20	V

OTG Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17749.420	57.60	-29.61	45.95	41.26	74.00	16.40	H
17826.600	57.30	-29.68	45.95	41.02	74.00	16.70	H
17775.260	56.80	-29.63	45.95	40.47	74.00	17.20	H
17976.540	56.80	-29.06	46.66	39.20	74.00	17.20	V
17785.800	56.80	-29.89	45.95	40.73	74.00	17.20	V
17983.000	56.70	-29.06	46.66	39.10	74.00	17.30	V

Measurement results for Set.1:

Full Spectrum




Fig A.1 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
49.206000	11.73	29.54	17.81	120.000	100.0	V	84.0
55.220000	12.38	29.54	17.16	120.000	176.0	V	136.0
103.526000	8.76	33.06	24.30	120.000	275.0	V	302.0
161.338000	16.06	33.06	17.00	120.000	100.0	V	103.0
196.549000	23.22	33.06	9.84	120.000	100.0	V	46.0
214.494000	21.62	33.06	11.44	120.000	100.0	V	66.0

Full Spectrum




Fig A.2 Radiated Emission from 1GHz to 18GHz

Measurement results for Set.2:

Full Spectrum




Fig A.3 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	PoI	Azimuth (deg)
46.102000	10.46	29.54	19.08	120.000	286.0	H	-45.0
50.079000	10.37	29.54	19.17	120.000	222.0	V	45.0
55.899000	11.03	29.54	18.51	120.000	175.0	V	65.0
103.041000	8.21	33.06	24.85	120.000	275.0	H	135.0
162.793000	10.09	33.06	22.97	120.000	125.0	V	135.0
195.773000	16.37	33.06	16.69	120.000	100.0	V	47.0

Full Spectrum




Fig A.4 Radiated Emission from 1GHz to 18GHz

Measurement results for Set.3:

Full Spectrum




Fig A.5 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	PoI	Azimuth (deg)
31.067000	24.70	29.54	4.84	120.000	175.0	V	-45.0
33.201000	22.27	29.54	7.27	120.000	100.0	V	225.0
147.176000	20.83	33.06	12.23	120.000	100.0	V	13.0
215.949000	21.01	33.06	12.05	120.000	322.0	H	264.0
548.756000	22.53	35.56	13.03	120.000	275.0	V	-7.0
589.690000	27.58	35.56	7.98	120.000	225.0	V	-6.0

Full Spectrum




Fig A.6 Radiated Emission from 1GHz to 18GHz

Measurement results for Set.4:

Full Spectrum




Fig A.7 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
47.363000	10.21	29.54	19.33	120.000	223.0	V	264.0
53.377000	9.94	29.54	19.60	120.000	308.0	V	135.0
104.011000	8.16	33.06	24.90	120.000	308.0	V	13.0
198.392000	7.71	33.06	25.35	120.000	275.0	V	45.0
325.074000	10.40	35.56	25.16	120.000	325.0	H	225.0
752.650000	18.49	35.56	17.07	120.000	275.0	H	225.0

Full Spectrum




Fig A.8 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL M4000E-17, and the serial number of the PC is M706GWXD. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note : I/O information : Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U= 3.08$ dB, $k=2$.

Charging Mode, Set.1:





Fig A.9 Conducted Emission from 150kHz to 30MHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.378000	39.4	2000.0	9.000	On	L1	19.7	19.0	58.3	
0.490000	41.0	2000.0	9.000	On	L1	19.7	15.2	56.2	
0.818000	35.6	2000.0	9.000	On	L1	19.7	20.4	56.0	
1.314000	32.3	2000.0	9.000	On	L1	19.6	23.7	56.0	
4.790000	36.0	2000.0	9.000	On	L1	19.6	20.0	56.0	
8.510000	37.4	2000.0	9.000	On	L1	19.7	22.6	60.0	

Final Result 2


Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.378000	24.3	2000.0	9.000	On	L1	19.7	24.0	48.3	
0.490000	26.9	2000.0	9.000	On	L1	19.7	19.3	46.2	
1.122000	21.0	2000.0	9.000	On	L1	19.7	25.0	46.0	
1.398000	19.4	2000.0	9.000	On	L1	19.6	26.6	46.0	
4.986000	27.2	2000.0	9.000	On	L1	19.6	18.8	46.0	
7.922000	28.3	2000.0	9.000	On	L1	19.7	21.7	50.0	

Charging Mode, Set.2:

Fig A.10 Conducted Emission from 150kHz to 30MHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.378000	39.7	2000.0	9.000	On	L1	19.7	18.7	58.3	
0.462000	38.8	2000.0	9.000	On	L1	19.7	17.9	56.7	
0.814000	34.8	2000.0	9.000	On	N	19.6	21.2	56.0	
4.918000	36.2	2000.0	9.000	On	L1	19.6	19.8	56.0	
9.118000	37.3	2000.0	9.000	On	L1	19.7	22.7	60.0	
10.766000	35.5	2000.0	9.000	On	L1	19.7	24.5	60.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.354000	25.7	2000.0	9.000	On	L1	19.7	23.2	48.9	
0.478000	27.2	2000.0	9.000	On	L1	19.7	19.2	46.4	
0.766000	21.5	2000.0	9.000	On	L1	19.7	24.5	46.0	
4.918000	27.1	2000.0	9.000	On	L1	19.6	18.9	46.0	
8.194000	28.4	2000.0	9.000	On	L1	19.7	21.6	50.0	
10.738000	25.6	2000.0	9.000	On	L1	19.7	24.4	50.0	

USB Mode, Set.3:

Fig A.11 Conducted Emission from 150kHz to 30MHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.462000	44.2	2000.0	9.000	On	N	19.7	12.5	56.7	
1.186000	39.8	2000.0	9.000	On	N	19.6	16.2	56.0	
1.554000	40.2	2000.0	9.000	On	N	19.6	15.8	56.0	
3.326000	38.2	2000.0	9.000	On	N	19.6	17.8	56.0	
4.982000	37.4	2000.0	9.000	On	L1	19.6	18.6	56.0	
6.466000	45.3	2000.0	9.000	On	N	19.6	14.7	60.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.394000	31.4	2000.0	9.000	On	L1	19.7	16.6	48.0	
0.466000	41.3	2000.0	9.000	On	N	19.7	5.3	46.6	
0.782000	30.1	2000.0	9.000	On	N	19.7	15.9	46.0	
1.362000	32.8	2000.0	9.000	On	L1	19.6	13.2	46.0	
2.126000	25.6	2000.0	9.000	On	L1	19.6	20.4	46.0	
6.470000	36.3	2000.0	9.000	On	L1	19.7	13.7	50.0	

END OF REPORT