

# FCC PART 15C TEST REPORT

No. **I18Z60820-IOT07** 

for

Wingtech Group (Hong Kong) Limited

Muti-band GSM/WCDMA/LTE phone with Bluetooth.WLAN

**Model Name: VFD 525** 

FCC ID: 2APXWVFD525

with

Hardware Version: 88909\_1\_12

Software Version: VFD-525-ZA-B23

Issued Date: 2018-6-11



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email: cttl\_terminals@caict.ac.cn, website: www.caict.ac.cn




## **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I18Z60820-IOT07	Rev.0	1st edition	2018-6-11



## **CONTENTS**

1.	TES	ST LABORATORY	5
1.	.1.	TESTING LOCATION	5
1.	.2.	TESTING ENVIRONMENT	5
1.	.3.	PROJECT DATA	5
1.	.4.	SIGNATURE	5
2.	CLI	IENT INFORMATION	6
2.	.1.	APPLICANT INFORMATION	6
2.	.2.	MANUFACTURER INFORMATION	6
3.	EQ	UIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.	.1.	ABOUT EUT	7
3.	.2.	INTERNAL IDENTIFICATION OF EUT	7
3.	.3.	INTERNAL IDENTIFICATION OF AE	7
3.	.4.	NORMAL ACCESSORY SETTING	7
3.	.5.	GENERAL DESCRIPTION	7
4.	RE	FERENCE DOCUMENTS	8
4.	.1.	DOCUMENTS SUPPLIED BY APPLICANT	8
4.	.2.	REFERENCE DOCUMENTS FOR TESTING	8
5.	TES	ST RESULTS	9
5.	.1.	SUMMARY OF TEST RESULTS	9
5.	.2.	STATEMENTS	9
6.	TES	ST FACILITIES UTILIZED 1	.0
7.	ME	ASUREMENT UNCERTAINTY	1
7.	.1.	PEAK OUTPUT POWER - CONDUCTED	1
7.	.2.	Frequency Band Edges	.1
7.	.3.	Transmitter Spurious Emission - Conducted	.1
7.	.4.	Transmitter Spurious Emission - Radiated	.1
7.	.5.	TIME OF OCCUPANCY (DWELL TIME)	.1
7.	.6.	20dB Bandwidth	.1
7.	.7.	CARRIER FREQUENCY SEPARATION 1	2
7.	.8.	AC POWERLINE CONDUCTED EMISSION	2
AN]	NEX	A: DETAILED TEST RESULTS 1	.3
A	.1. M	MEASUREMENT METHOD	3
		EAK OUTPUT POWER – CONDUCTED	
A	3. Fi	REQUENCY BAND EDGES – CONDUCTED	5
A	.4. T	RANSMITTER SPURIOUS EMISSION - CONDUCTED	:2
A	5. T	RANSMITTER SPURIOUS EMISSION - RADIATED	.7
A	6. T	IME OF OCCUPANCY (DWELL TIME)5 ©Copyright. All rights reserved by CTT	8 L.





A	NNEX E: ACCREDITATION CERTIFICATE	85
	A.10. AC POWERLINE CONDUCTED EMISSION	81
	A.9. NUMBER OF HOPPING CHANNELS	77
	A.8. CARRIER FREQUENCY SEPARATION	74
	A.7. 20dB Bandwidth	68



## 1. Test Laboratory

## 1.1. Testing Location

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China100191

Radiated testing Location: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China100191

Radiated testing Location: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology

Development Area, Beijing, P. R. China 100176

1.2. Testing Environment

Normal Temperature: 15-35℃ Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2018-5-10 Testing End Date: 2018-6-11

1.4. Signature

Wu Le

(Prepared this test report)

Sun Zhenyu

(Reviewed this test report)

Lv Songdong

(Approved this test report)



## 2. Client Information

## 2.1. Applicant Information

Company Name:	Wingtech Group (Hong Kong) Limited			
Address /Post:	Flat/RM 1903, 19/F, Podium Plaza 5 Hanoi Road, Tsim Sha Tsu Kowloon, Hong Kong			
City:	/			
Postal Code:	/			
Country:	/			
Telephone:	1			
Fax:				

## 2.2. Manufacturer Information

Company Name:	Wingtech Group (Hong Kong) Limited				
Address /Post:	Flat/RM 1903, 19/F, Podium Plaza 5 Hanoi Road, Tsim Sha Tsu Kowloon, Hong Kong				
City:	/				
Postal Code:	/				
Country:	/				
Telephone:	/				
Fax:					



## 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

### 3.1. About EUT

Description Muti-band GSM/WCDMA/LTE phone with Bluetooth.WLAN

Model Name VFD 525

FCC ID 2APXWVFD525

Frequency Band ISM 2400MHz~2483.5MHz Type of Modulation GFSK/π/4 DQPSK/8DPSK

Number of Channels 79

Power Supply 3.85V DC by Battery

### 3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	<b>HW Version</b>	SW Version
EUT1	356984090009510	88909_1_12	VFD-525-ZA-B23
EUT2	356984090006987	88909_1_12	VFD-525-ZA-B23

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE

AE ID*	Description
AE1	Battery
AE2	Charger
AE3	USB cable

<sup>\*</sup>AE ID: is used to identify the test sample in the lab internally.

## 3.4. Normal Accessory setting

Fully charged battery should be used during the test.

### 3.5. General Description

The Equipment Under Test (EUT) is a model of Muti-band GSM/WCDMA/LTE phone with Bluetooth.WLAN with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.



## 4. Reference Documents

## 4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

## 4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	
FCC Part15	15.209 Radiated emission limits, general requirements;	2016
	15.247 Operation within the bands 902–928MHz,	
	2400-2483.5 MHz, and 5725-5850 MHz.	
ANSI C63.10	American National Standard of Procedures for	June,2013
ANSI 603.10	Compliance Testing of Unlicensed Wireless Devices	Julie,2013



## 5. Test Results

## 5.1. Summary of Test Results

Abbreviations used in this clause:

- **P** Pass, The EUT complies with the essential requirements in the standard.
- F Fail, The EUT does not comply with the essential requirements in the standard
- NA Not Applicable, The test was not applicable
- NP Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power - Conducted	15.247 (b)(1)	Р
Frequency Band Edges	15.247 (d)	Р
Transmitter Spurious Emission - Conducted	15.247 (d)	Р
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	Р
Time of Occupancy (Dwell Time)	15.247 (a) (1)(iii)	Р
20dB Bandwidth	15.247 (a)(1)	NA
Carrier Frequency Separation	15.247 (a)(1)	Р
Number of hopping channels	15.247 (a)(b)(iii)	Р
AC Powerline Conducted Emission	15.107, 15.207	Р

Please refer to ANNEX A for detail.

The measurement is made according to ANSI C63.10.

### 5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2



## 6. Test Facilities Utilized

## **Conducted test system**

No.	Equipment	Model	Serial Number	Manufacturer	Calibratio n Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	1 year	2018-09-30
2	Bluetooth Tester	CBT32	100649	Rohde & Schwarz	1 year	2018-09-29
3	LISN	ESH3-Z5	825562/0 28	Rohde & Schwarz	1 year	2019-01-31
4	Test Receiver	ESCI 3	100766	Rohde & Schwarz	1 year	2019-04-16
5	Shielding Room	S81	/	ETS-Lindgren	/	/

## Radiated emission test system

INA	Naulated emission test system					
No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	1 year	2018-12-27
2	BiLog Antenna	VULB9163	9163-514	Schwarzbeck	3 years	2020-02-23
3	EMI Antenna	3117	00139065	ETS-Lindgren	3 Years	2020-11-15
4	EMI Antenna	3116	2663	ETS-Lindgren	3 Years	2020-05-31
5	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	1 year	2018-07-22
6	Station Simulator	CMW500	159408	Rohde & Schwarz	1 year	2019-04-12



## 7. Measurement Uncertainty

## 7.1. Peak Output Power - Conducted

#### **Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

## 7.2. Frequency Band Edges

## **Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

## 7.3. Transmitter Spurious Emission - Conducted

### **Measurement Uncertainty:**

Frequency Range	Uncertainty (k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

## 7.4. Transmitter Spurious Emission - Radiated

## **Measurement Uncertainty:**

Frequency Range	Uncertainty (k=2)
< 1 GHz	4.86dB
> 1 GHz	5.26dB

## 7.5. Time of Occupancy (Dwell Time)

## **Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.88ms

## 7.6. 20dB Bandwidth

#### **Measurement Uncertainty:**



## 7.7. Carrier Frequency Separation

## **Measurement Uncertainty:**

Measurement Uncertainty (k=2) 61.936Hz
--

## 7.8. AC Powerline Conducted Emission

## **Measurement Uncertainty:**

Measurement Uncertainty (k=2)	3.38dB
-------------------------------	--------




## **ANNEX A: Detailed Test Results**

#### A.1. Measurement Method

#### A.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



#### A.1.2. Radiated Emission Measurements


The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;





## A.2. Peak Output Power - Conducted

## Method of Measurement: See ANSI C63.10-clause 7.8.5

a) Use the following spectrum analyzer settings:

Span: 6MHzRBW: 3MHzVBW: 3MHz

Sweep time: 2.5msDetector function: peak

• Trace: max hold

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power.

#### **Measurement Limit:**

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

#### Measurement Results:

### For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	4.03	4.63	4.63	Р

## For π/4 DQPSK

Channel	Ch 0	Ch 39	Ch 78	Conclusion
	2402 MHz	2441 MHz	2480 MHz	
Peak Conducted	3.76	4.22	4.49	P
Output Power (dBm)	3.70	4.22	4.43	

## For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	4.20	4.52	4.78	Р

**Conclusion: PASS** 



## A.3. Frequency Band Edges – Conducted

#### Method of Measurement: See ANSI C63.10-clause 7.8.6

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).

- Span: 10 MHz

Resolution Bandwidth: 100 kHzVideo Bandwidth: 300 kHz

Sweep Time:AutoDetector: PeakTrace: max hold

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

#### **Measurement Limit:**

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20

#### **Measurement Result:**

#### For GFSK

Channel	Hopping	Band Edge Power ( dBc)		Conclusion
0	Hopping OFF	Fig.1	-58.55	Р
0	Hopping ON	Fig.2	-65.43	Р
70	Hopping OFF	Fig.3	-63.94	Р
78	Hopping ON	Fig.4	-65.45	Р

#### For π/4 DQPSK

Channel	Hopping	Band Edge Power ( dBc)		Conclusion
0	Hopping OFF	Fig.5	-56.73	Р
	Hopping ON	Fig.6	-62.53	Р
70	Hopping OFF	Fig.7	-61.28	Р
78	Hopping ON	Fig.8	-61.07	Р

### For 8DPSK

Channel	Hopping	Band Edge Power ( dBc)		Conclusion
0	Hopping OFF	Fig.9	-58.99	Р
U	Hopping ON	Fig.10	-61.84	Р



79	Hopping OFF	Fig.11	-61.45	Р
70	Hopping ON	Fig.12	-60.75	Р

Conclusion: PASS
Test graphs as below




Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off




Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On






Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off




Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On






Fig.5. Frequency Band Edges:  $\pi/4$  DQPSK, Channel 0, Hopping Off




Fig.6. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping On






Fig.7. Frequency Band Edges:  $\pi/4$  DQPSK, Channel 78, Hopping Off




Fig.8. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping On






Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off




Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On






Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off




Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On



## A.4. Transmitter Spurious Emission - Conducted

#### Method of Measurement: See ANSI C63.10-clause 7.8.8

Measurement Procedure - Reference Level

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW = 300 kHz.
- 3. Set the span to 5-30 % greater than the EBW.
- 4. Detector = peak.
- 5. Sweep time = auto couple.
- 6. Trace mode = max hold.
- 7. Allow trace to fully stabilize.
- 8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

- 1. Set RBW = 100 kHz.
- 2. Set VBW = 300 kHz.
- 3. Set span to encompass the spectrum to be examined.
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.
- 7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

#### **Measurement Limit:**

Standard	Limit
ECC 47 CED Dort 15 247 (d)	20dB below peak output power in 100 kHz
FCC 47 CFR Part 15.247 (d)	bandwidth

#### Measurement Results:

#### For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	Center Frequency	Fig.13	Р



2402 MHz	30 MHz ~ 1 GHz	Fig.14	Р
	1 GHz ~ 3 GHz	Fig.15	Р
	3 GHz ~ 10 GHz	Fig.16	Р
	10 GHz ~ 26 GHz	Fig.17	Р
	Center Frequency	Fig.18	Р
Ch 20	30 MHz ~ 1 GHz	Fig.19	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.20	Р
	3 GHz ~ 10 GHz	Fig.21	Р
	10 GHz ~ 26 GHz	Fig.22	Р
	Center Frequency	Fig.23	Р
Oh 70	30 MHz ~ 1 GHz	Fig.24	Р
Ch 78 2480 MHz	1 GHz ~ 3 GHz	Fig.25	Р
2 100 1011 12	3 GHz ~ 10 GHz	Fig.26	Р
	10 GHz ~ 26 GHz	Fig.27	Р

## For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
	Center Frequency	Fig.28	Р
Oh O	30 MHz ~ 1 GHz	Fig.29	Р
Ch 0 2402 MHz	1 GHz ~ 3 GHz	Fig.30	Р
2.022	3 GHz ~ 10 GHz	Fig.31	Р
	10 GHz ~ 26 GHz	Fig.32	Р
	Center Frequency	Fig.33	Р
Oh 20	30 MHz ~ 1 GHz	Fig.34	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.35	Р
	3 GHz ~ 10 GHz	Fig.36	Р
	10 GHz ~ 26 GHz	Fig.37	Р
	Center Frequency	Fig.38	Р
Ch 70	30 MHz ~ 1 GHz	Fig.39	Р
Ch 78 2480 MHz	1 GHz ~ 3 GHz	Fig.40	Р
2 100 1011 12	3 GHz ~ 10 GHz	Fig.41	Р
	10 GHz ~ 26 GHz	Fig.42	Р

## For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
	Center Frequency	Fig.43	Р
Ch O	30 MHz ~ 1 GHz	Fig.44	Р
Ch 0 2402 MHz	1 GHz ~ 3 GHz	Fig.45	Р
2 102 11112	3 GHz ~ 10 GHz	Fig.46	Р
	10 GHz ~ 26 GHz	Fig.47	Р



	Center Frequency	Fig.48	Р
Ch 20	30 MHz ~ 1 GHz	Fig.49	Р
Ch 39 2441 MHz	1 GHz ~ 3 GHz	Fig.50	Р
	3 GHz ~ 10 GHz	Fig.51	Р
	10 GHz ~ 26 GHz	Fig.52	Р
	Center Frequency	Fig.53	Р
Ch 70	30 MHz ~ 1 GHz	Fig.54	Р
Ch 78 2480 MHz	1 GHz ~ 3 GHz	Fig.55	Р
	3 GHz ~ 10 GHz	Fig.56	Р
	10 GHz ~ 26 GHz	Fig.57	Р

Conclusion: PASS
Test graphs as below




Fig.13. Conducted spurious emission: GFSK, Channel 0,2402MHz






Fig.14. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz




Fig.15. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz






Fig.16. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz




Fig.17. Conducted spurious emission: GFSK, Channel 0,10GHz - 26GHz






Fig.18. Conducted spurious emission: GFSK, Channel 39, 2441MHz




Fig.19. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz






Fig.20. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz




Fig.21. Conducted spurious emission: GFSK, Channel 39, 3GHz - 10GHz






Fig.22. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz




Fig.23. Conducted spurious emission: GFSK, Channel 78, 2480MHz






Fig.24. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz




Fig.25. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz






Fig.26. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz




Fig.27. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz






Fig.28. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 0,2402MHz




Fig.29. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 0, 30MHz - 1GHz






Fig.30. Conducted spurious emission: π/4 DQPSK, Channel 0, 1GHz - 3GHz




Fig.31. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 0, 3GHz - 10GHz






Fig.32. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 0,10GHz - 26GHz




Fig.33. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 39, 2441MHz






Fig.34. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 39, 30MHz - 1GHz




Fig.35. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 39, 1GHz - 3GHz






Fig.36. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 39, 3GHz - 10GHz




Fig.37. Conducted spurious emission: π/4 DQPSK, Channel 39, 10GHz – 26GHz






Fig.38. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 78, 2480MHz




Fig.39. Conducted spurious emission: π/4 DQPSK, Channel 78, 30MHz - 1GHz






Fig.40. Conducted spurious emission:  $\pi/4$  DQPSK, Channel 78, 1GHz - 3GHz




Fig.41. Conducted spurious emission: π/4 DQPSK, Channel 78, 3GHz - 10GHz






Fig.42. Conducted spurious emission: π/4 DQPSK, Channel 78, 10GHz - 26GHz




Fig.43. Conducted spurious emission: 8DPSK, Channel 0,2402MHz






Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz




Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz






Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz




Fig.47. Conducted spurious emission: 8DPSK, Channel 0,10GHz - 26GHz






Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz




Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz






Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz






Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz






Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz






Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz



## A.5. Transmitter Spurious Emission - Radiated

#### **Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

#### Limit in restricted band:

Frequency of emission	Field strength(uV/m)	Field strength(dBuV/m)
(MHz)		
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

#### **Test Condition**

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission	RBW/VBW	Sweep Time(s)	
(MHz)			
30-1000	100KHz/300KHz	5	
1000-4000	1MHz/1MHz	15	
4000-18000	1MHz/1MHz	1MHz/1MHz 40	
18000-26500	1MHz/1MHz	20	

#### **Measurement Results:**

Result=P<sub>Mea</sub>+ARPL

#### For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	1 GHz ~ 3 GHz	1	Р
2402 MHz	3 GHz ~ 18 GHz	/	Р
	9 kHz ~ 30 MHz	1	Р
Ch 39 2441 MHz	30 MHz ~ 1 GHz	/	Р
	1 GHz ~ 3 GHz	/	Р
	3 GHz ~ 18 GHz	/	Р
Ch 78	1 GHz ~ 3 GHz	/	Р
2480 MHz	3 GHz ~ 18 GHz	/	Р
Power	2.38GHz~2.4GHzL	Fig.58	Р
Power	2.45GHz~2.5GHzH	Fig.59	Р