



## FCC 47 CFR PART 15 SUBPART C

for

**MainStream Main Unit Wireless presenter**

**Model: MUV1, MUV2, MUV3, MUV4, MUV5, MUV6**

**Brand: MainStream**

**Test Report Number:**

**C180524Z01-RP1-3**

**Issued Date: June 12, 2018**

Issued for

**Certus Eiger Ltd.**

**814, Houston Center, Mody Road, TST East, Kowloon, Hong Kong**

Issued by:

**Compliance Certification Services (Shenzhen) Inc.**

No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,

Guan Lan Town, Baoan District, Shenzhen, China

TEL: 86-755-28055000

FAX: 86-755-28055221

E-Mail: service@ccssz.com



Certificate Number: 2861.01

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 12, 2018	Initial Issue	ALL	Sinphy Xie



**TABLE OF CONTENTS**

**1 TEST CERTIFICATION ..... 4**

**2 TEST RESULT SUMMARY ..... 5**

**3 EUT DESCRIPTION..... 6**

**4 TEST METHODOLOGY..... 8**

    4.1. DESCRIPTION OF TEST MODES ..... 8

**5 SETUP OF EQUIPMENT UNDER TEST ..... 9**

    5.1. DESCRIPTION OF SUPPORT UNITS..... 9

    5.2. CONFIGURATION OF SYSTEM UNDER TEST ..... 9

**6 FACILITIES AND ACCREDITATIONS ..... 12**

    6.1. FACILITIES ..... 12

    6.2. ACCREDITATIONS ..... 12

    6.3. MEASUREMENT UNCERTAINTY ..... 12

**7 FCC PART 15.247 REQUIREMENTS ..... 13**

    7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT ..... 13

    7.2. SPURIOUS EMISSIONS MEASUREMENT ..... 20

    7.3. 6dB BANDWIDTH MEASUREMENT ..... 55

    7.4. ANTENNA GAIN ..... 63

    7.5. PEAK OUTPUT POWER ..... 64

    7.6. BAND EDGES MEASUREMENT ..... 66

    7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT..... 83



# 1 TEST CERTIFICATION

<b>Product</b>	MainStream Main Unit Wireless presenter
<b>Model</b>	MUV1, MUV2, MUV3, MUV4, MUV5, MUV6
<b>Brand</b>	MainStream
<b>Tested</b>	May 24~ June 12, 2018
<b>Applicant</b>	<b>Certus Eiger Ltd.</b> 814, Houston Center, Mody Road, TST East, Kowloon, Hong Kong
<b>Manufacturer</b>	<b>Certus Eiger Ltd.</b> 814, Houston Center, Mody Road, TST East, Kowloon, Hong Kong

APPLICABLE STANDARDS			
Standard	Test Type	Standard	Test Type
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	<ul style="list-style-type: none"> <li>● Spurious Emissions</li> <li>● Conducted Measurement</li> <li>● Radiated Emissions</li> </ul>
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

**We hereby certify that:**

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

**Approved by:**

**Reviewed by:**

---

**Eve Wang**  
Supervisor of EMC Dept.  
Compliance Certification Services (Shenzhen) Inc.

---

**Nancy Fu**  
Supervisor of Report Dept.  
Compliance Certification Services (Shenzhen) Inc.



## 2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	<ul style="list-style-type: none"><li>● Spurious Emissions</li><li>● Conducted Measurement</li><li>● Radiated Emissions</li></ul>	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.  
2. The information of measurement uncertainty is available upon the customer's request.



### 3 EUT DESCRIPTION

<b>Product</b>	MainStream Main Unit Wireless presenter
<b>Model Number</b>	MUV1, MUV2, MUV3, MUV4, MUV5, MUV6
<b>Brand</b>	MainStream
<b>Model Discrepancy</b>	They are identical to each other except for market designation for marketing purpose.
<b>Identify Number</b>	C180524Z01-RP1-3
<b>Received Date</b>	May 25, 2018
<b>Power Supply</b>	DC5V supplied by the adapter
<b>Adapter Specification</b>	<b>Adapter 1:</b> Moso Power Supply Technology Co., Ltd. Model: MSA-C2000IC5.0-12W-US Input: 100-240Vac 50/60Hz 0.5A max. Output: 5.0Vdc 2A DC cable: Unshielded, 1.20m(with a core) <b>Adapter 2:</b> Shenzhen TEKA Technology Co.,Ltd. MODEL: TEKA012-0502000XX INPUT: 100-240Vac 50/60Hz 0.35A MAX OUTPUT: 5Vdc 2A DC cable: Unshielded, 1.20m(with a core)
<b>HDMI Cable</b>	Shielded, 1.50m
<b>Transmit Power</b>	IEEE 802.11b mode: 16.62dBm IEEE 802.11g mode: 22.90dBm IEEE 802.11n HT20 MHz mode: 22.11dBm IEEE 802.11n HT40 MHz mode: 20.30dBm
<b>Modulation Technique</b>	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
<b>Transmit Data Rate</b>	IEEE 802.11b: 11Mbps(CCK) with fall back rates of 5.5/2/1Mbps IEEE 802.11g: 54Mbps with fall back rates of 48/36/24/18/12/9 /6Mbps IEEE 802.11n HT20: 65Mbps with fall back rates of 65/58.5/52/ 39/26/19.5/13/6.5Mbps IEEE 802.11n HT40: 135Mbps with fall back rates of 135/121.5/108/ 81/54/40.5/27/13.5Mbps
<b>Number of Channels</b>	IEEE 802.11b mode: 11 Channels IEEE 802.11g mode: 11 Channels IEEE 802.11n HT20 MHz mode: 11 Channels IEEE 802.11n HT40 MHz mode: 7 Channels
<b>Antenna Specification</b>	Internal antenna with 2dBi gain (Max)
<b>Channels Spacing</b>	IEEE 802.11b/g ,802.11n HT20/HT40 : 5MHz
<b>Temperature Range</b>	0°C ~ +45°C
<b>Hardware Version</b>	1.7
<b>Software Version</b>	4.9



- Note:** 1. *The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*
2. *This submittal(s) (test report) is intended for FCC ID: 2APYB-9C1D3E filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.*



## 4 TEST METHODOLOGY

### 4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Used the “RFTestTool-com.ampak.rftesttool-1.0-1.apk” software to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: Normal (AC120V/60Hz)	<input checked="" type="checkbox"/>
	Mode 2: Normal (AC240V/50Hz)	<input checked="" type="checkbox"/>
Radiated Emission	Mode 1: Continuously Transmitting	<input checked="" type="checkbox"/>

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and power line conducted emission below 30MHz, which worst case was in normal link mode.

IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 MHz mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

IEEE 802.11n HT40 MHz mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 13.5Mbps data rate were chosen for full testing.





## 5 SETUP OF EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Monitor	P2317H	CN-02J06R-7426 1-727-3A88-A00	N/A	DELL	Shielded 1.50m	Unshielded 1.50m
2	Keyboard	PR1101V	539130-001	N/A	DELL	Shielded 1.50m	N/A
3	Mouse	WB365PA#AB 2	2HTJMB101178-3 17	N/A	DELL	Shielded 1.45m	N/A

**Note:**

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### 5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

**5.3. TEST INSTRUMENTS**

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	01/27/2018	01/26/2019
LISN	EMCO	3825/2	8901-1459	01/27/2018	01/26/2019
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	01/29/2018	01/28/2019
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

Radiated Emission Test Site 966 (2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	01/27/2018	01/26/2019
Amplifier	EMEC	EM330	060661	01/27/2018	01/26/2019
High Noise Amplifier	Agilent	8449B	3008A01838	01/27/2018	01/26/2019
Loop Antenna	COM-POWER	AL-130	121044	01/30/2018	01/29/2019
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2018	02/20/2019
Horn Antenna	SCHWARZBECK	BBHA9120	D286	01/27/2018	01/26/2019
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	01/24/2018	01/23/2019
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	01/29/2018	01/28/2019
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

Antenna Conducted Spurious Emission					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

6dB Bandwidth					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019



Antenna Gain					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Peak Output Power					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2495A	1204003	01/27/2018	01/26/2019
Power Sensor	Anritsu	MA2411B	1126150	01/27/2018	01/26/2019

Band edges					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

Peak Power Spectral Density					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	01/27/2018	01/26/2019

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. N.C.R = No Calibration Request.



## 6 FACILITIES AND ACCREDITATIONS

### 6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

<b>USA</b>	<b>A2LA</b>
<b>China</b>	<b>CNAS</b>

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>USA</b>	<b>FCC</b>
<b>Japan</b>	<b>VCCI (C-4815,R-4320,T-2317, G-10624)</b>
<b>Canada</b>	<b>INDUSTRY CANADA</b>

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccssz.com>

### 6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

<b>Parameter</b>	<b>Uncertainty</b>
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



## 7 FCC PART 15.247 REQUIREMENTS

### 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

#### 7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.




### 7.1.2. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.



7.1.3. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.1.4. DATA SAMPLE


Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XXXX	32.69	25.65	11.52	44.21	37.17	65.78	55.79	-21.57	-18.62	Pass

- Factor = Insertion loss of LISN + Cable Loss
- Result = Quasi-peak Reading/ Average Reading + Factor
- Limit = Limit stated in standard
- Margin = Result (dBuV) – Limit (dBuV)



7.1.5. TEST RESULTS

<b>Model No.</b>	MUV1	<b>RBW,VBW</b>	9 kHz
<b>Environmental Conditions</b>	22°C, 45% RH	<b>Test Mode</b>	Mode 1
<b>Tested by</b>	Luja Huang	<b>Line</b>	L1
<b>Test Date</b>	May 30, 2018	<b>Test Voltage</b>	AC 120V/60Hz




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1819	33.10	20.42	19.63	52.73	40.05	64.39	54.40	-11.66	-14.35	Pass
1.2740	26.98	14.23	19.60	46.58	33.83	56.00	46.00	-9.42	-12.17	Pass
2.0220	24.69	5.25	19.72	44.41	24.97	56.00	46.00	-11.59	-21.03	Pass
2.2940	26.39	6.38	19.72	46.11	26.10	56.00	46.00	-9.89	-19.90	Pass
2.5260	28.12	8.65	19.72	47.84	28.37	56.00	46.00	-8.16	-17.63	Pass
2.7940	24.79	6.69	19.72	44.51	26.41	56.00	46.00	-11.49	-19.59	Pass

REMARKS: L1 = Line One (Live Line)





<b>Model No.</b>	MUV1	<b>RBW,VBW</b>	9 kHz
<b>Environmental Conditions</b>	22°C, 45% RH	<b>Test Mode</b>	Mode 1
<b>Tested by</b>	Luja Huang	<b>Line</b>	L2
<b>Test Date</b>	May 30, 2018	<b>Test Voltage</b>	AC 120V/60Hz




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1860	32.59	19.13	19.53	52.12	38.66	64.21	54.21	-12.09	-15.55	Pass
0.4500	24.64	8.06	19.53	44.17	27.59	56.87	46.88	-12.70	-19.29	Pass
1.2940	23.33	11.09	19.60	42.93	30.69	56.00	46.00	-13.07	-15.31	Pass
2.5540	27.95	7.46	19.74	47.69	27.20	56.00	46.00	-8.31	-18.80	Pass
2.7860	28.80	10.24	19.75	48.55	29.99	56.00	46.00	-7.45	-16.01	Pass
24.7460	26.69	11.90	20.62	47.31	32.52	60.00	50.00	-12.69	-17.48	Pass

**REMARKS:** L2 = Line Two (Neutral Line)



<b>Model No.</b>	MUV1	<b>RBW,VBW</b>	9 kHz
<b>Environmental Conditions</b>	22°C, 45% RH	<b>Test Mode</b>	Mode 2
<b>Tested by</b>	Luja Huang	<b>Line</b>	L1
<b>Test Date</b>	May 30, 2018	<b>Test Voltage</b>	AC 240V/50Hz




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1740	35.86	21.38	19.63	55.49	41.01	64.76	54.77	-9.27	-13.76	Pass
0.3420	26.54	9.55	19.59	46.13	29.14	59.15	49.15	-13.02	-20.01	Pass
1.2860	23.65	11.01	19.60	43.25	30.61	56.00	46.00	-12.75	-15.39	Pass
2.5059	30.46	14.15	19.72	50.18	33.87	56.00	46.00	-5.82	-12.13	Pass
2.7780	33.38	15.07	19.72	53.10	34.79	56.00	46.00	-2.90	-11.21	Pass
7.5620	22.53	7.15	19.89	42.42	27.04	60.00	50.00	-17.58	-22.96	Pass

**REMARKS:** L1 = Line One (Live Line)



<b>Model No.</b>	MUV1	<b>RBW,VBW</b>	9 kHz
<b>Environmental Conditions</b>	22°C, 45% RH	<b>Test Mode</b>	Mode 2
<b>Tested by</b>	Luja Huang	<b>Line</b>	L2
<b>Test Date</b>	May 30, 2018	<b>Test Voltage</b>	AC 240V/50Hz



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1500	34.34	16.47	19.52	53.86	35.99	65.99	56.00	-12.13	-20.01	Pass
0.2100	32.53	12.53	19.54	52.07	32.07	63.20	53.21	-11.13	-21.14	Pass
1.2579	22.66	8.10	19.60	42.26	27.70	56.00	46.00	-13.74	-18.30	Pass
2.5180	30.61	10.42	19.74	50.35	30.16	56.00	46.00	-5.65	-15.84	Pass
2.7460	32.46	12.99	19.74	52.20	32.73	56.00	46.00	-3.80	-13.27	Pass
22.4540	24.37	7.04	20.43	44.80	27.47	60.00	50.00	-15.20	-22.53	Pass

REMARKS: L2 = Line Two (Neutral Line)



## 7.2. SPURIOUS EMISSIONS MEASUREMENT

### 7.2.1. CONDUCTED EMISSIONS MEASUREMENT

#### 7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b) (3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

#### 7.2.1.2. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.



The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.



Measurements are made over the 9 kHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz · it is only recorded 10MHz to 26GHz.



### 7.2.1.3. TEST RESULTS

#### Test Plot IEEE 802.11b mode











IEEE 802.11g mode



CH Low (10MHz ~26.5GHz)





CH Low (2.31GHz ~2.43GHz)














### IEEE 802.11n HT20 MHz mode


#### CH Low (10MHz ~26.5GHz)



#### CH Low (2.31GHz ~2.43GHz)











### IEEE 802.11n HT40 MHz mode



#### CH Low (10MHz ~26.5GHz)



#### CH Low (2.31GHz ~2.45GHz)











**7.2.2. RADIATED EMISSIONS MEASUREMENT**

**7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT**

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**NOTE:**(1) The lower limit shall apply at the transition frequencies.  
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).



### 7.2.2.2. Measuring Instruments and Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

### 7.2.2.3. TEST PROCEDURE (please refer to measurement standard)

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Pre measurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position,



correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Pre measurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.



**Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

**3) Sequence of testing 1 GHz to 18 GHz**

**Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

**Pre measurement:**

- The turntable rotates from  $0^\circ$  to  $315^\circ$  using  $45^\circ$  steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.



**Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

**4) Sequence of testing above 18 GHz**

**Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

**Pre measurement:**

- The antenna is moved spherical over the EUT in different polarisations of the antenna.


**Final measurement:**

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.




### 7.2.2.4. TEST SETUP

#### Below 30MHz




#### Below 1 GHz





**Above 1 GHz**



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



7.2.2.5. DATA SAPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	36.37	-12.20	24.17	40.00	-15.83	V	QP

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Q.P. = Quasi-peak Reading

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Peak = Peak Reading  
 AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m)  
 Result (dBuV/m) = Reading (dBuV) + Correction Factor



**7.2.2.6. TEST RESULTS****Below 1 GHz****Test Mode:** TX / IEEE 802.11b(CH Low)**Tested by:** Saber Huang**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
48.4300	56.73	-20.43	36.30	40.00	-3.70	V	QP
199.7500	44.38	-22.73	21.65	43.50	-21.85	V	QP
416.0600	40.81	-15.49	25.32	46.00	-20.68	V	QP
602.3000	28.15	-12.81	15.34	46.00	-30.66	V	QP
695.4200	28.49	-12.05	16.44	46.00	-29.56	V	QP
879.7200	34.47	-9.98	24.49	46.00	-21.51	V	QP
127.0000	44.84	-20.87	23.97	43.50	-19.53	H	QP
190.0500	51.02	-22.86	28.16	43.50	-15.34	H	QP
320.0300	31.14	-18.93	12.21	46.00	-33.79	H	QP
416.0600	32.74	-15.49	17.25	46.00	-28.75	H	QP
529.5500	27.98	-13.90	14.08	46.00	-31.92	H	QP
642.0700	28.00	-12.48	15.52	46.00	-30.48	H	QP

**Notes:**


1. No emission found between lowest internal used/generated frequency to 30MHz.
2. Pre-scan all mode and recorded the worst case results in this report (802.11b (Low Channel))

**Remark:**


1. Radiated emissions measured in frequency range from 9 kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
2. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120 kHz.
4. Frequency (MHz). = Emission frequency in MHz  
Reading (dBμV/m) = Receiver reading  
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain  
Limit (dBμV/m) = Limit stated in standard  
Margin (dB) = Measured (dBμV/m) – Limits (dBμV/m)  
Antenna Pole (H/V) = Current carrying line of reading



### Vertical



### Horizontal





**Above 1 GHz**

**Test Mode:** TX / IEEE 802.11b(CH Low)

**Tested by:** Saber Huang

**Ambient temperature:** 24°C **Relative humidity:** 52% RH

**Date:** June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2899.000	42.97	-1.54	41.43	74.00	-32.57	V	peak
3619.000	42.74	-0.02	42.72	74.00	-31.28	V	peak
4087.000	41.78	1.90	43.68	74.00	-30.32	V	peak
4456.000	41.91	3.20	45.11	74.00	-28.89	V	peak
4825.000	41.09	4.41	45.50	74.00	-28.50	V	peak
5320.000	40.61	5.55	46.16	74.00	-27.84	V	peak
1333.000	46.82	-7.30	39.52	74.00	-34.48	H	Peak
1954.000	52.20	-5.29	46.91	74.00	-27.09	H	Peak
2620.000	45.31	-2.04	43.27	74.00	-30.73	H	Peak
3358.000	42.08	-0.76	41.32	74.00	-32.68	H	Peak
3988.000	42.17	1.54	43.71	74.00	-30.29	H	peak
4591.000	42.51	3.65	46.16	74.00	-27.84	H	peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11b (CH Mid)

Tested by: Saber Huang

Ambient temperature: 24°C Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3376.000	42.23	-0.73	41.50	74.00	-32.50	V	Peak
3727.000	41.42	0.44	41.86	74.00	-32.14	V	Peak
4222.000	42.60	2.37	44.97	74.00	-29.03	V	Peak
4582.000	40.39	3.62	44.01	74.00	-29.99	V	Peak
4987.000	40.82	4.94	45.76	74.00	-28.24	V	Peak
5194.000	39.28	5.33	44.61	74.00	-29.39	V	Peak
3376.000	41.37	-0.73	40.64	74.00	-33.36	H	Peak
3646.000	41.51	0.10	41.61	74.00	-32.39	H	Peak
4051.000	40.61	1.77	42.38	74.00	-31.62	H	Peak
4663.000	39.86	3.88	43.74	74.00	-30.26	H	Peak
4951.000	40.86	4.82	45.68	74.00	-28.32	H	Peak
5455.000	39.64	5.79	45.43	74.00	-28.57	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11b (CH High)

Tested by: Saber Huang

Ambient temperature: 24°C Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1468.000	44.90	-6.94	37.96	74.00	-36.04	V	Peak
1639.000	44.06	-6.62	37.44	74.00	-36.56	V	Peak
2062.000	43.83	-4.66	39.17	74.00	-34.83	V	Peak
2152.000	44.72	-4.17	40.55	74.00	-33.45	V	Peak
4780.000	40.69	4.26	44.95	74.00	-29.05	V	Peak
5383.000	40.46	5.66	46.12	74.00	-27.88	V	Peak
1630.000	44.37	-6.64	37.73	74.00	-36.27	H	Peak
2107.000	44.40	-4.41	39.99	74.00	-34.01	H	Peak
3232.000	42.58	-0.97	41.61	74.00	-32.39	H	Peak
4186.000	41.87	2.24	44.11	74.00	-29.89	H	Peak
4420.000	40.84	3.07	43.91	74.00	-30.09	H	Peak
5068.000	40.46	5.10	45.56	74.00	-28.44	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11g(CH Low)

Tested by: Saber Huang

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1855.000	42.93	-5.92	37.01	74.00	-36.99	V	Peak
2170.000	44.70	-4.07	40.63	74.00	-33.37	V	Peak
3331.000	41.81	-0.80	41.01	74.00	-32.99	V	Peak
4051.000	41.32	1.77	43.09	74.00	-30.91	V	Peak
4429.000	40.37	3.10	43.47	74.00	-30.53	V	Peak
5284.000	40.61	5.49	46.10	74.00	-27.90	V	Peak
2647.000	43.58	-2.00	41.58	74.00	-32.42	H	Peak
3682.000	41.16	0.25	41.41	74.00	-32.59	H	Peak
4357.000	40.67	2.85	43.52	74.00	-30.48	H	Peak
5455.000	40.61	5.79	46.40	74.00	-27.60	H	Peak
6310.000	39.73	6.58	46.31	74.00	-27.69	H	Peak
7354.000	39.58	8.39	47.97	74.00	-26.03	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11g (CH Mid)

**Tested by:** Saber Huang

**Ambient temperature:** 24°C

**Relative humidity:** 52% RH

**Date:** June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1945.000	47.68	-5.35	42.33	74.00	-31.67	V	Peak
2809.000	44.26	-1.70	42.56	74.00	-31.44	V	Peak
3241.000	43.49	-0.96	42.53	74.00	-31.47	V	Peak
3745.000	42.15	0.51	42.66	74.00	-31.34	V	Peak
4546.000	41.25	3.50	44.75	74.00	-29.25	V	Peak
4879.000	41.72	4.59	46.31	74.00	-27.69	V	Peak
2242.000	44.98	-3.67	41.31	74.00	-32.69	H	Peak
2656.000	44.79	-1.98	42.81	74.00	-31.19	H	Peak
2836.000	43.97	-1.66	42.31	74.00	-31.69	H	Peak
3565.000	43.23	-0.25	42.98	74.00	-31.02	H	Peak
4087.000	41.89	1.90	43.79	74.00	-30.21	H	Peak
4663.000	42.51	3.88	46.39	74.00	-27.61	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11g (CH High)

Tested by: Saber Huang

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2260.000	45.63	-3.58	42.05	74.00	-31.95	V	Peak
2593.000	45.17	-2.09	43.08	74.00	-30.92	V	Peak
3340.000	42.99	-0.79	42.20	74.00	-31.80	V	Peak
4123.000	41.48	2.02	43.50	74.00	-30.50	V	Peak
4663.000	40.83	3.88	44.71	74.00	-29.29	V	Peak
5797.000	41.38	5.99	47.37	74.00	-26.63	V	Peak
2125.000	44.20	-4.31	39.89	74.00	-34.11	H	Peak
2530.000	43.76	-2.21	41.55	74.00	-32.45	H	Peak
3673.000	41.60	0.21	41.81	74.00	-32.19	H	Peak
4231.000	40.97	2.40	43.37	74.00	-30.63	H	Peak
4924.000	41.88	4.73	46.61	74.00	-27.39	H	Peak
5401.000	40.02	5.69	45.71	74.00	-28.29	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



**Test Mode:** TX / IEEE 802.11n HT20 MHz (CH Low)**Tested by:** Saber Huang**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2530.000	44.94	-2.21	42.73	74.00	-31.27	V	Peak
3088.000	43.59	-1.21	42.38	74.00	-31.62	V	Peak
3817.000	42.38	0.82	43.20	74.00	-30.80	V	Peak
4087.000	42.32	1.90	44.22	74.00	-29.78	V	Peak
4636.000	42.15	3.79	45.94	74.00	-28.06	V	Peak
4969.000	42.37	4.88	47.25	74.00	-26.75	V	Peak
2143.000	46.15	-4.22	41.93	74.00	-32.07	H	Peak
2521.000	45.41	-2.22	43.19	74.00	-30.81	H	Peak
2899.000	43.77	-1.54	42.23	74.00	-31.77	H	Peak
3745.000	42.56	0.51	43.07	74.00	-30.93	H	Peak
4051.000	42.24	1.77	44.01	74.00	-29.99	H	Peak
5104.000	41.91	5.17	47.08	74.00	-26.92	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11n HT20 MHz (CH Mid)

Tested by: Saber Huang

Ambient temperature: 24°C Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3250.000	43.28	-0.94	42.34	74.00	-31.66	V	Peak
4258.000	40.81	2.50	43.31	74.00	-30.69	V	Peak
4321.000	42.09	2.72	44.81	74.00	-29.19	V	Peak
5257.000	39.91	5.44	45.35	74.00	-28.65	V	Peak
5626.000	40.16	5.92	46.08	74.00	-27.92	V	Peak
6571.000	39.76	7.01	46.77	74.00	-27.23	V	Peak
1756.000	47.39	-6.36	41.03	74.00	-32.97	H	Peak
2260.000	44.43	-3.58	40.85	74.00	-33.15	H	Peak
4069.000	41.19	1.83	43.02	74.00	-30.98	H	Peak
4591.000	40.86	3.65	44.51	74.00	-29.49	H	Peak
5527.000	40.35	5.88	46.23	74.00	-27.77	H	Peak
6220.000	40.62	6.44	47.06	74.00	-26.94	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / EEE 802.11n HT20 MHz (CH High)

Tested by: Saber Huang

Ambient temperature: 24°C      Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2575.000	43.89	-2.12	41.77	74.00	-32.23	V	Peak
2917.000	42.90	-1.51	41.39	74.00	-32.61	V	Peak
3376.000	42.82	-0.73	42.09	74.00	-31.91	V	Peak
4114.000	40.88	1.99	42.87	74.00	-31.13	V	Peak
4465.000	40.46	3.23	43.69	74.00	-30.31	V	Peak
5671.000	40.23	5.94	46.17	74.00	-27.83	V	Peak
2242.000	43.89	-3.67	40.22	74.00	-33.78	H	Peak
2638.000	43.28	-2.01	41.27	74.00	-32.73	H	Peak
3673.000	40.41	0.21	40.62	74.00	-33.38	H	Peak
3979.000	41.81	1.50	43.31	74.00	-30.69	H	Peak
4564.000	41.27	3.56	44.83	74.00	-29.17	H	Peak
5122.000	40.04	5.20	45.24	74.00	-28.76	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11n HT40 MHz (CH Low)

Tested by: Saber Huang

Ambient temperature: 24°C      Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2584.000	45.29	-2.11	43.18	74.00	-30.82	V	Peak
3412.000	41.11	-0.67	40.44	74.00	-33.56	V	Peak
3880.000	42.76	1.08	43.84	74.00	-30.16	V	Peak
4357.000	40.30	2.85	43.15	74.00	-30.85	V	Peak
4933.000	41.55	4.76	46.31	74.00	-27.69	V	Peak
5581.000	40.79	5.90	46.69	74.00	-27.31	V	Peak
1747.000	47.22	-6.38	40.84	74.00	-33.16	H	Peak
2629.000	43.48	-2.03	41.45	74.00	-32.55	H	Peak
3340.000	42.10	-0.79	41.31	74.00	-32.69	H	Peak
4240.000	41.38	2.43	43.81	74.00	-30.19	H	Peak
5041.000	40.48	5.05	45.53	74.00	-28.47	H	Peak
5932.000	40.35	6.05	46.40	74.00	-27.60	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / IEEE 802.11n HT40 MHz (CH Mid)

Tested by: Saber Huang

Ambient temperature: 24°C      Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2647.000	43.95	-2.00	41.95	74.00	-32.05	V	Peak
3844.000	41.75	0.93	42.68	74.00	-31.32	V	Peak
4474.000	41.60	3.26	44.86	74.00	-29.14	V	Peak
4717.000	40.98	4.06	45.04	74.00	-28.96	V	Peak
5131.000	40.59	5.21	45.80	74.00	-28.20	V	Peak
5941.000	39.91	6.06	45.97	74.00	-28.03	V	Peak
1747.000	47.04	-6.38	40.66	74.00	-33.34	H	Peak
2521.000	44.37	-2.22	42.15	74.00	-31.85	H	Peak
3394.000	41.90	-0.70	41.20	74.00	-32.80	H	Peak
3943.000	42.21	1.35	43.56	74.00	-30.44	H	Peak
4591.000	41.60	3.65	45.25	74.00	-28.75	H	Peak
5068.000	40.45	5.10	45.55	74.00	-28.45	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Test Mode: TX / EEE 802.11n HT40 MHz (CH High)

Tested by: Saber Huang

Ambient temperature: 24°C

Relative humidity: 52% RH

Date: June 5, 2018

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1747.000	46.49	-6.38	40.11	74.00	-33.89	V	Peak
2521.000	43.76	-2.22	41.54	74.00	-32.46	V	Peak
2971.000	42.90	-1.41	41.49	74.00	-32.51	V	Peak
3970.000	41.34	1.46	42.80	74.00	-31.20	V	Peak
4672.000	40.77	3.91	44.68	74.00	-29.32	V	Peak
5509.000	40.89	5.87	46.76	74.00	-27.24	V	Peak
1747.000	47.76	-6.38	41.38	74.00	-32.62	H	Peak
2656.000	43.79	-1.98	41.81	74.00	-32.19	H	Peak
3196.000	41.82	-1.03	40.79	74.00	-33.21	H	Peak
4501.000	40.34	3.35	43.69	74.00	-30.31	H	Peak
5140.000	40.17	5.23	45.40	74.00	-28.60	H	Peak
5716.000	40.49	5.96	46.45	74.00	-27.55	H	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



## 7.3. 6dB BANDWIDTH MEASUREMENT

### 7.3.1. LIMITS


According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 7.3.2. TEST PROCEDURES (please refer to measurement standard)

#### 8.2 Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e.,  $RBW = 100 \text{ kHz}$ ,  $VBW \geq 3 \text{ RBW}$ , peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6 \text{ dB}$ .

### 7.3.3. TEST SETUP





7.3.4. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	9058	>500	PASS
Mid	2437	8589		PASS
High	2462	9067		PASS

Test mode: IEEE 802.11g

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	16310	>500	PASS
Mid	2437	16320		PASS
High	2462	16320		PASS

Test mode: IEEE 802.11n HT20 MHz

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	16910	>500	PASS
Mid	2437	17280		PASS
High	2462	17290		PASS



Test mode: IEEE 802.11n HT40 MHz


Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2422	35560	>500	PASS
Mid	2437	36010		PASS
High	2452	35750		PASS










### Test Plot














### IEEE 802.11n HT40 MHz mode







## 7.4. ANTENNA GAIN

### MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the DSSS mode is used.

### MEASUREMENT PARAMETERS

Measurement parameter	
Detector	Peak
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	3 MHz
Trace-Mode	Max hold

### LIMITS

FCC	IC
Antenna Gain	
6 dBi	

### TEST RESULTS

#### IEEE 802.11b

T <sub>nom</sub>	V <sub>nom</sub>	Lowest channel 2412MHz	Middle channel 2437MHz	Highest channel 2462MHz
Conducted power [dBm/MHz] Measured with DSSS modulation		5.52	5.49	5.82
Radiated power [dBm/MHz] Measured with DSSS modulation		6.89	7.02	7.14
Gain [dBi] Calculated		1.37	1.53	1.32
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		



## 7.5. PEAK OUTPUT POWER

### 7.5.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 7.5.2. TEST PROCEDURES (please refer to measurement standard)

#### 9.1.1 RBW $\geq$ DTS bandwidth


This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS bandwidth*.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq$  3 RBW.
- c) Set span  $\geq$  3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### 9.1.3 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

### 7.5.3. TEST SETUP







**7.5.4. TEST RESULTS**

*No non-compliance noted*

**Test Data**

**Test mode: IEEE 802.11b**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	16.33	0.04295	Peak	1	PASS
Mid	2437	16.29	0.04256			PASS
High	2462	16.62	0.04592			PASS
Low	2412	13.69	0.02339	AVG	1	PASS
Mid	2437	13.65	0.02317			PASS
High	2462	13.96	0.02489			PASS

**Test mode: IEEE 802.11g**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	21.75	0.14962	Peak	1	PASS
Mid	2437	22.46	0.17620			PASS
High	2462	22.90	0.19498			PASS
Low	2412	12.87	0.01936	AVG	1	PASS
Mid	2437	13.09	0.02037			PASS
High	2462	13.27	0.02123			PASS

**Test mode: IEEE 802.11n HT20 MHz**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2412	21.17	0.13092	Peak	1	PASS
Mid	2437	21.50	0.14125			PASS
High	2462	22.11	0.16255			PASS
Low	2412	11.83	0.01524	AVG	1	PASS
Mid	2437	12.33	0.01710			PASS
High	2462	12.29	0.01694			PASS

**Test mode: IEEE 802.11n HT40 MHz**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Peak / AVG	Limit (W)	Result
Low	2422	19.87	0.09705	Peak	1	PASS
Mid	2437	20.30	0.10715			PASS
High	2452	19.66	0.09247			PASS
Low	2422	11.32	0.01355	AVG	1	PASS
Mid	2437	11.59	0.01442			PASS
High	2452	11.16	0.01306			PASS



## 7.6. BAND EDGES MEASUREMENT


### 7.6.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

### 7.6.2. TEST PROCEDURES (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=1/T / Sweep=AUTO / Detector=PEAK
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### 7.6.3. TEST SETUP






7.6.4. TEST RESULTS



Test Plot

IEEE 802.11b mode

Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	56.06	-2.86	53.20	74.00	-20.80	Peak	Vertical
2.	2413.320	103.54	-2.73	100.81	---	---	Peak	Vertical
1.	2390.000	43.85	-2.86	40.99	54.00	-13.01	Average	Vertical
2.	2412.720	99.66	-2.74	96.92	---	---	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	57.54	-2.86	54.68	74.00	-19.32	Peak	Horizontal
2.	2413.440	110.11	-2.73	107.38	---	---	Peak	Horizontal
1.	2390.000	45.19	-2.86	42.33	54.00	-11.67	Average	Horizontal
2.	2411.160	106.14	-2.75	103.39	---	---	Average	Horizontal



**Band Edges (CH High)**




No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2463.400	109.75	-2.46	107.29	---	---	Peak	Vertical
2.	2483.500	59.17	-2.35	56.82	74.00	-17.18	Peak	Vertical
1.	2461.200	105.95	-2.47	103.48	---	---	Average	Vertical
2.	2483.500	46.21	-2.35	43.86	54.00	-10.14	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2463.150	103.54	-2.46	101.08	---	---	Peak	Horizontal
2.	2483.500	56.49	-2.35	54.14	74.00	-19.86	Peak	Horizontal
1.	2461.200	100.42	-2.47	97.95	---	---	Average	Horizontal
2.	2483.500	44.49	-2.35	42.14	54.00	-11.86	Average	Horizontal



IEEE 802.11g mode  
Band Edges (CH Low)



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	70.52	-2.86	67.66	74.00	-6.34	Peak	Vertical
2.	2411.280	105.37	-2.75	102.62	---	---	Peak	Vertical
1.	2390.000	49.25	-2.86	46.39	54.00	-7.61	Average	Vertical
2.	2411.280	95.65	-2.75	92.90	---	---	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	74.01	-2.86	71.15	74.00	-2.85	Peak	Horizontal
2.	2411.160	112.09	-2.75	109.34	---	---	Peak	Horizontal
1.	2390.000	53.38	-2.86	50.52	54.00	-3.48	Average	Horizontal
2.	2411.160	102.34	-2.75	99.59	---	---	Average	Horizontal






**Band Edges (CH High)**




No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2462.600	112.93	-2.46	110.47	---	---	Peak	Vertical
2.	2483.500	74.23	-2.35	71.88	74.00	-2.12	Peak	Vertical
1.	2461.150	102.76	-2.47	100.29	---	---	Average	Vertical
2.	2483.500	54.67	-2.35	52.32	54.00	-1.68	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2461.050	106.53	-2.47	104.06	---	---	Peak	Horizontal 
2.	2483.500	69.14	-2.35	66.79	74.00	-7.21	Peak	Horizontal 
1.	2462.750	95.06	-2.46	92.60	---	---	Average	Horizontal 
2.	2483.500	49.68	-2.35	47.33	54.00	-6.67	Average	Horizontal 



IEEE 802.11n HT20 MHz mode  
Band Edges (CH Low)





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	69.31	-2.86	66.45	74.00	-7.55	Peak	Vertical
2.	2412.480	105.13	-2.74	102.39	---	---	Peak	Vertical
1.	2390.000	48.96	-2.86	46.10	54.00	-7.90	Average	Vertical
2.	2412.600	93.39	-2.74	90.65	---	---	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	74.79	-2.86	71.93	74.00	-2.07	Peak	Horizontal 
2.	2410.320	112.52	-2.75	109.77	---	---	Peak	Horizontal 
1.	2390.000	52.83	-2.86	49.97	54.00	-4.03	Average	Horizontal 
2.	2411.040	99.29	-2.75	96.54	---	---	Average	Horizontal 



**Band Edges (CH High)**





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2460.000	111.92	-2.48	109.44	---	---	Peak	Vertical
2.	2483.500	70.49	-2.35	68.14	74.00	-5.86	Peak	Vertical
1.	2462.800	100.82	-2.46	98.36	---	---	Average	Vertical
2.	2483.500	51.77	-2.35	49.42	54.00	-4.58	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2462.950	105.14	-2.46	102.68	---	---	Peak	Horizontal
2.	2483.500	65.78	-2.35	63.43	74.00	-10.57	Peak	Horizontal
1.	2462.700	94.19	-2.46	91.73	---	---	Average	Horizontal
2.	2483.500	47.80	-2.35	45.45	54.00	-8.55	Average	Horizontal



IEEE 802.11n HT40 MHz mode  
Band Edges (CH Low)



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	70.27	-2.86	67.41	74.00	-6.59	Peak	Vertical
2.	2423.820	107.59	-2.68	104.91	---	---	Peak	Vertical
1.	2390.000	55.36	-2.86	52.50	54.00	-1.50	Average	Vertical
2.	2423.400	98.01	-2.68	95.33	---	---	Average	Vertical





No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	72.27	-2.86	69.41	74.00	-4.59	Peak	Horizontal
2.	2423.400	105.41	-2.68	102.73	---	---	Peak	Horizontal
1.	2390.000	54.95	-2.86	52.09	54.00	-1.91	Average	Horizontal
2.	2423.120	95.12	-2.68	92.44	---	---	Average	Horizontal







**Band Edges (CH High)**



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2448.550	107.71	-2.54	105.17	---	---	Peak	Vertical
2.	2483.500	68.73	-2.35	66.38	74.00	-7.62	Peak	Vertical
1.	2453.310	97.83	-2.52	95.31	---	---	Average	Vertical
2.	2483.500	52.90	-2.35	50.55	54.00	-3.45	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2453.660	101.40	-2.51	98.89	---	---	Peak	Horizontal 
2.	2483.500	62.78	-2.35	60.43	74.00	-13.57	Peak	Horizontal 
1.	2453.170	91.72	-2.52	89.20	---	---	Average	Horizontal 
2.	2483.500	48.90	-2.35	46.55	54.00	-7.45	Average	Horizontal 



## 7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT

### 7.7.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


### 7.7.2. TEST PROCEDURES (please refer to measurement standard)

§15.247(e) specifies a conducted power spectral density (PSD) limit of 8 dBm in any 3 kHz band segment within the fundamental EBW during any time interval of continuous transmission. The same method as used to determine the conducted output power shall be used to determine the power spectral density (i.e., if peak-detected fundamental power was measured then use the peak PSD procedure and if average fundamental power was measured then use the average PSD procedure).

#### 10.2 Method PKPSD (peak PSD)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 7.7.3. TEST SETUP





**7.7.4. TEST RESULTS**

*No non-compliance noted*

**Test Data**

**Test mode: IEEE 802.11b**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-7.164	8	PASS
Mid	2437	-8.545		PASS
High	2462	-7.336		PASS

**Test mode: IEEE 802.11g**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-10.041	8	PASS
Mid	2437	-9.754		PASS
High	2462	-9.157		PASS

**Test mode: IEEE 802.11n HT20 MHz**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-11.727	8	PASS
Mid	2437	-11.494		PASS
High	2462	-10.057		PASS


**Test mode: IEEE 802.11n HT40 MHz**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2422	-11.972	8	PASS
Mid	2437	-12.623		PASS
High	2452	-12.708		PASS




**Test Plot**  
**IEEE 802.11b mode**



**PPSD (CH Low)**



**PPSD (CH Mid)**









IEEE 802.11n HT20 MHz mode

