



BUREAU VERITAS

Test Report No.: RF190305N010



Certificate # 2951.01

TEST REPORT

Applicant	Huabo Smart Living Technology Co.,Ltd.
Address	Chenghua Industrial Zone,Wenguan Road,Chenghai District,Shantou City,Guangdong China.

Manufacturer or Supplier	Huabo Smart Living Technology Co.,Ltd.
Address	Chenghua Industrial Zone,Wenguan Road,Chenghai District,Shantou City,Guangdong China.
Product	Toy RC Flip Stunt Rally
Brand Name	Sharper Image/Blue Hat Toy Company
Model	HB2019B
Additional Model & Model Difference	1010677、 1010927、 1010930、 2905161
Date of tests	Mar. 07 to Mar. 14, 2019

the tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C, Section 15.235

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Evans He
Project Engineer / EMC Department

Approved by David Huang
Supervisor/ EMC Department

Evans He

David Huang

Date: Mar. 15, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS	4
2 MEASUREMENT UNCERTAINTY.....	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF EUT.....	5
3.2 DESCRIPTION OF TEST MODES.....	6
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	6
3.4 DESCRIPTION OF SUPPORT UNITS	6
4 TEST TYPES AND RESULTS	7
4.1 RADIATED EMISSION MEASUREMENT.....	7
4.1.1 <i>LIMITS OF RADIATED EMISSION MEASUREMENT</i>	7
4.1.2 <i>TEST INSTRUMENTS</i>	8
4.1.3 <i>TEST PROCEDURES</i>	9
4.1.4 <i>DEVIATION FROM TEST STANDARD</i>	9
4.1.5 <i>TEST SETUP</i>	10
4.1.6 <i>EUT OPERATING CONDITIONS</i>	10
4.1.7 <i>TEST RESULTS</i>	11
4.2 BANDWIDTH MEASUREMENT.....	16
4.2.1 <i>LIMITS OF BANDWIDTH MEASUREMENT</i>	16
4.2.2 <i>TEST INSTRUMENTS</i>	16
4.2.3 <i>TEST PROCEDURE</i>	18
4.2.4 <i>DEVIATION FROM TEST STANDARD</i>	18
4.2.5 <i>TEST SETUP</i>	18
4.2.6 <i>EUT OPERATING CONDITIONS</i>	18
4.2.7 <i>TEST RESULTS</i>	19
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	20
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	21



BUREAU
VERITAS

Test Report No.: RF190305N010

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF 190305N010	Original release	Mar. 15, 2019



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.235)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
§15.207 (a)	Conducted Emission	N/A	EUT is powered by battery
§15.209 §15.235(a)	Radiated Emission	PASS	Compliant
§15.235(b)	Measured Bandwidth	PASS	Compliant
§15.203	Antenna Requirement	N/A	No antenna connector is used

NOTE: Test Lab Information:

Lab: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Test Lab Address: Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District Shenzhen, Guangdong, 518108, People's Republic of China

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9kHz~30MHz	3.11dB
	30MHz ~ 1GHz	5.12dB
	1GHz ~ 18GHz	5.34dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Toy RC Flip Stunt Rally
MODEL NO.	HB2019B
ADDITIONAL MODEL NO.	1010677、1010927、1010930、2905161
FCC ID	2APYEHB2019B49
NOMINAL VOLTAGE	DC 9V from Battery
MODULATION TYPE	AM
OPERATING FREQUENCY	49.860MHz
NUMBER OF CHANNEL	1
ANTENNA TYPE	Spring Antenna with 0 dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 190305N010) for detailed product photo.
4. Additional models (see about table) are identical with the test model HB2019B except the color of the appearance、trade name and model name for trading purpose.



3.2 DESCRIPTION OF TEST MODES

The EUT was tested under the following mode.

FREQUENCY	TEST MODE
49.860MHz	Transmitting

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, 15.235

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards. This is a single application for certification of a transmitter. The receiver for this transmitter is authorized by Declaration of Conformity procedure

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessories or support units.



4 TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.235(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [$\mu\text{V/m}$]	Field Strength of Fundamental Emission [Average] [$\mu\text{V/m}$]
49.82 – 49.90	100,000 (100 dB $\mu\text{V/m}$)	10,000 (80 dB $\mu\text{V/m}$)

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

Instrument	Model	Serial #	Cal Date	Cal Due
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	Feb 11, 19	Feb. 10, 20
EMI test receiver	ESL6	1300.5001K06-100262-eQ	Jan, 05, 19	Jan. 04, 20
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	Jan, 05, 19	Jan. 04, 20
Bilog Antenna (30MHz~6GHz)	JB6	A110712	Feb 08, 19	Feb. 07, 20
Bilog Antenna (30MHz~2GHz)	JB1	A112017	Jan 26, 19	Jan. 25, 20
A-INFOMW Horn Antenna (1~18GHz)	AH-118	71259	Jan 26, 19	Jan. 25, 20
Pre-Amplifier (100MHz-26.5GHz)	EMC 012645	980077	May 18, 18	May 17, 19
Pre-Amplifier (18GHz-40GHz)	EMC 184045	980102	Nov. 08,18	Nov. 07,19
EMCO Horn Antenna (1~18GHz)	AH-118	71283	Feb 02, 19	Feb. 01, 20
OPT 010 AMPLIFIER (0.1~1300MHz)	8447E	2727A02430	Dec. 09, 18	Dec. 08, 19
Horn Antenna	BBHA 9170	BBHA9170147	Mar. 14, 18	Mar. 13, 19
Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	Dec. 09, 18	Dec. 08, 19
Large Loop Antenna	RF300	Rf300	Dec. 09, 18	Dec. 08, 19
Universal Radio Communication Tester	CMU200	121393	Feb 11, 19	Feb. 10, 20
Positioning Controller	UC3000	MF780208282	Dec. 09, 18	Dec. 08, 19
Test Software	EZ-EMC	ver.lcp-03A1	N/A	N/A

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 749762.



4.1.3 TEST PROCEDURES

The basic test procedure was in accordance with ANSI C63.10 (section 6).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. $\text{Result level(dBuV/m)} = \text{Reading level(dBuV)} + \text{Correction Factor(dB/m)}$
3. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier)
4. $\text{Correction Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier).
5. $\text{Margin value} = \text{Result level} - \text{Limit value}$.
6. $\text{Fundamental AV value} = \text{PK Emission} + \text{AV factor}$.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Turned on the power of equipment.
- Hold down the TX of button, and then the EUT was operating.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



4.1.7 TEST RESULTS

FIELD STRENGTH OF FUNDAMENTAL

No.	Freq. (MHz)	Antenna Polarization	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	49.86(PK)	V	-13.13	68.98	55.85	100	-44.15
2	49.86(AV)	V	-5.97	-	49.88	80	-30.12
3	49.86(PK)	H	-13.13	47.74	34.61	100	-65.39
4	49.86(AV)	H	-5.97	-	28.64	80	-51.36

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The emission levels of other frequencies were less than 20dB margin against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.
 6. The average value of fundamental frequency is: Average value = Peak value +AV factor, where the AV factor is calculated from following formula: AV factor=20 log (Duty cycle) = 20 log (50.26%) = -5.97dB.



BUREAU VERITAS


Test Report No.: RF190305N010

$T_p = 76.00\text{ms}$

$T_{on} = T_{on1} * \text{Number} + T_{on2} * \text{Number} = 4 * 1.55 + 64 * 0.5 = 38.2\text{ms}$


$\text{Duty Cycle} = T_{on} / T_p * 100\% = 38.2 / 76.00 = 50.26\%$

$T_p = 76.00\text{ms}$






Ton1=1.55ms



Ton2= 0.5ms






FREQUENCY RANGE	9KHz ~ 1GHz	DETECTOR FUNCTION	Quasi-Peak (QP)
------------------------	-------------	--------------------------	-----------------

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m										
No.	Frequency (MHz)	Reading (dBuV/m)	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	35.8747	30.77	16.91	22.26	0.77	26.19	40.00	-13.81	100	143
2	41.7130	28.11	12.77	22.28	0.78	19.38	40.00	-20.62	100	62
3	102.0014	26.44	10.75	22.32	1.13	16.00	43.50	-27.50	100	298
4	163.1818	25.11	12.35	22.27	1.38	16.57	43.50	-26.93	100	305
5	334.8589	24.15	14.33	22.19	1.96	18.25	46.00	-27.75	100	141
6	955.4381	30.06	22.78	20.77	3.20	35.27	46.00	-10.73	100	327

REMARKS:

1. Result (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Ant_F (dB/m) + Cab_L (dB) - PA_G (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.






FREQUENCY RANGE	9KHz ~ 1GHz	DETECTOR FUNCTION	Quasi-Peak (QP)
------------------------	-------------	--------------------------	-----------------

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m										
No.	Frequency (MHz)	Reading (dBuV/m)	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)
1	35.8747	30.49	16.91	22.26	0.77	25.91	40.00	-14.09	100	12
2	52.0251	34.19	8.18	22.39	0.79	20.77	40.00	-19.23	100	178
3	66.0342	30.21	7.60	22.39	0.90	16.32	40.00	-23.68	200	45
4	99.5281	36.94	10.29	22.32	1.11	26.02	43.50	-17.48	100	29
5	149.4857	28.88	12.60	22.34	1.34	20.48	43.50	-23.02	100	108
6	955.4381	29.86	22.78	20.77	3.20	35.07	46.00	-10.93	100	49

REMARKS:

1. Result (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Ant_F (dB/m) + Cab_L (dB) - PA_G (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.





4.2 BANDWIDTH MEASUREMENT

4.2.1 LIMITS OF BANDWIDTH MEASUREMENT

The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in Section 15.209.

FREQUENCY (MHz)	Limits
	[MHz]
49.860	within 49.81~49.91

4.2.2 TEST INSTRUMENTS

Instrument	Model	Serial #	Cal Date	Cal Due
Power Sensor	Dare RPR3006C/P/W	N/A	Jan. 05, 19	Jan. 04, 20
Power Sensor	Dare RPR3006C/P/W	N/A	Jan. 05, 19	Jan. 04, 20
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	Feb. 11, 19	Feb. 10, 20
EMI test receiver	ESL6	1300.5001K06- 100262-eQ	Jan. 05, 19	Jan. 04, 20
Power Splitter	1#	1#	Dec. 09, 18	Dec. 08, 19
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	Jan. 05, 19	Jan. 04, 20
DC Power Supply	E3640A	MY40004013	Jan. 05, 19	Jan. 04, 20
Bilog Antenna (30MHz~6GHz)	JB6	A110712	Feb. 08, 19	Feb. 07, 20
Bilog Antenna (30MHz~2GHz)	JB1	A112017	Jan. 26, 19	Jan. 25, 20
A-INFOMW Horn Antenna (1~18GHz)	AH-118	71259	Jan. 26, 19	Jan. 25, 20
Pre-Amplifier (100MHz-26.5GHz)	EMC 012645	980077	May 18, 18	May 17, 19
Pre-Amplifier (18GHz-40GHz)	EMC 184045	980102	Nov. 08, 18	Nov. 07, 19
EMCO Horn Antenna (1~18GHz)	AH-118	71283	Feb. 02, 19	Feb. 01, 20
OPT 010 AMPLIFIER (0.1~1300MHz)	8447E	2727A02430	Dec. 09, 18	Dec. 08, 19
Horn Antenna	BBHA 9170	BBHA9170147	Mar. 14, 18	Mar. 13, 19



BUREAU VERITAS Test Report No.: RF190305N010

Microwave Preamplifier (0.5 ~ 18GHz)	PAM-118	443008	Dec. 09, 18	Dec. 08, 19
Attenuator	MINI	N/A	Dec. 09, 18	Dec. 08, 19
Test Software	EZ-EMC	ver.lcp-03A1	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.




4.2.3 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 26dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



4.2.6 EUT OPERATING CONDITIONS


Same as item 4.1.6



4.2.7 TEST RESULTS

Lower & Upper Test Frequency Point (MHz)	Test Frequency (MHz)	P/F
Lower	49.8430	PASS
Upper	49.8775	PASS

Test Data:





BUREAU Test Report No.: RF190305N010
VERITAS

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



BUREAU Test Report No.: RF190305N010
VERITAS

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---