

RF Exposure Evaluation

1 Measuring Standard

KDB 680106 D01 RF Exposure Wireless Charging Apps v03

2 Requirements

According to the item 5 of KDB 680106 D01v03:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

(1) Power transfer frequency is less than 1MHz.

(2) Output power from each primary coil is less than or equal to 15 watts.

(3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

(4) Client device is placed directly in contact with the transmitter.

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Remark: Meet all the above requirements.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)		
	(A) Limits for Occupational/Controlled Exposures					
0.3-3.0	614	1.63	*(100)	6		
3.0-30	1842/f	4.89/f	*(900/f ²)	6		
30-300	61.4	0.163	1.0	6		
300-1500	/	/	f/300	6		
1500-100,000	/	1	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	*(180/f ²)	30		
30-300	27.5	0.073	0.2	30		
300-1500	/	1	f/1500	30		
1500-100,000	/	1	1.0	30		
F=frequency in MHz *=Plane-wave equivalent power density						

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).



3 Test Setup



4 Test Procedure

1) The RF exposure test was performed in anechoic chamber.

2) The measurement probe was placed at test distance (15 cm from all sides and 20 cm from the top) which is between the edge of the charger and the geometric center of probe.

3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.

4) The EUT was measured according to the dictates of KDB 680106 D01v03.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

5 Test Instruments list

Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Exposure Level Tester	Narda	ELT-400	N-0231	June 29 2017	June 28 2018
Electric and Magnetic	Nordo	ELT probe 100 pm ²	MOGZE	lune 20 2017	lune 29 2019
field probe 100cm ²	Narua			June 29 2017	

6 Test Result

E-Filed Strength at 15 cm from the edges surrounding the EUT (V/m)

Frequency Range: 0.1115MHz~0.205MHz					
Charging level	Test	Test	Test	Test	Limits
	Position A	Position B	Position C	Position D	(V/m)
0%	1.39	1.37	1.35	1.32	614
50%	1.37	1.35	1.33	1.30	614
100%	1.37	1.36	1.30	1.30	614

E-Filed Strength at 20 cm from the top of the EUT (V/m)

Frequency Range: 0.1115MHz~0.205MHz				
Charging level	Test	Limits		
	Position E	(V/m)		
0%	1.25	614		
50%	1.21	614		
100%	1.19	614		

H-Filed Strength at 15 cm from the edges surrounding the EUT (A/m)

Frequency Range: 0.1115MHz~0.205MHz					
Charging level	Test	Test	Test	Test	Limits
	Position A	Position B	Position C	Position D	(A/m)
0%	0.53	0.52	0.52	0.50	1.63
50%	0.51	0.50	0.49	0.47	1.63
100%	0.49	0.48	0.48	0.46	1.63

H-Filed Strength at 20 cm from the top of the EUT (A/m)

Frequency Range: 0.1115MHz~0.205MHz				
Charging level	Test	Limits		
	Position E	(A/m)		
0%	0.32	1.63		
50%	0.32	1.63		
100%	0.31	1.63		

Test Engineer:

Bill. yuan

Reviewer:

ndy un

Date: June 27 2018

Date: June 27 2018

Global United Technology Services Co., Ltd. No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



7 Test Set-up Photo

