

MEASUREMENT REPORT FCC PART 15.407 UNII

Applicant Name:
 Cummins Inc.
 500 Central Avenue MC 14750
 Columbus, Indiana 47201
 United States

Date of Testing:
 5/27/21 – 6/1/21
Test Site/Location:
 PCTEST Lab. Columbia, MD, USA
Test Report Serial No.:
 1M2105140054-01-R1.2AP


FCC ID:	2APZK3002
APPLICANT:	Cummins Inc.

Application Type: Class II Permissive Change
Model: CAN-WiFi GW
EUT Type: CAN WiFi Gateway
Frequency Range: 5180 – 5825MHz
Modulation Type: OFDM
FCC Classification: Unlicensed National Information Infrastructure (UNII)
FCC Rule Part(s): Part 15 Subpart E (15.407)
Test Procedure(s): ANSI C63.10-2013, KDB 789033 D02 v02r01
Class II Permissive Change : External antenna and attenuator

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2105140054-01-R1.2AP) supersedes and replaces the previously issued test report(s) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
 President



FCC ID: 2APZK3002		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 1 of 20

T A B L E O F C O N T E N T S

1.0	INTRODUCTION	3
1.1	Scope.....	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION	4
2.1	Equipment Description	4
2.2	Device Capabilities.....	4
2.3	Antenna Description.....	5
2.4	Test Configuration.....	5
2.5	Software and Firmware	5
2.6	EMI Suppression Device(s)/Modifications.....	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Radiated Emissions.....	6
3.3	Environmental Conditions.....	6
4.0	ANTENNA REQUIREMENTS	7
5.0	MEASUREMENT UNCERTAINTY	8
6.0	TEST EQUIPMENT CALIBRATION DATA.....	9
7.0	TEST RESULTS	10
7.1	Summary.....	10
7.2	Radiated Spurious Emission Measurements – Above 1GHz	11
7.6.1	Radiated Spurious Emission Measurements.....	14
7.3	Radiated Band Edge Measurements (20MHz BW).....	19
8.0	CONCLUSION.....	20

FCC ID: 2APZK3002	 Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway	Page 2 of 20	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISED.

FCC ID: 2APZK3002	 PCTEST [®] Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 3 of 20

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Cummins CAN WiFi Gateway FCC ID: 2APZK3002**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

Test Device Serial No.: 1904049, 1904042

2.2 Device Capabilities

This device contains the following capabilities:

802.11a/n UNII 5GHz

Band 1		Band 2A	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260
:	:	:	:
42	5210	56	5280
:	:	:	:
48	5240	64	5320

Table 2-1. 802.11a/n (20MHz) Frequency / Channel Operations

Notes:

- 5GHz NII operation is possible in 20MHz channel bandwidth. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013 and KDB 789033 D02 v02r01. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycle		
802.11 Mode/Band		Duty Cycle %
		ANT1
5 GHz	a	97.2
	n (HT20)	96.1

Table 2-2. Measured Duty Cycles

FCC ID: 2APZK3002	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway	Page 4 of 20	

2.3 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna Gain (dBi)
5.20	23
5.30	23

Table 2-3. Antenna Peak Gain

NOTE:

Actual antenna gain is found by equation: 23dBi – 20dB attenuator = 3dBi. This complies and is consistent with the MPE Test Report of the original application which states that the highest antenna gain to be used for 5GHz is 3dBi at a 20cm distance.

2.4 Test Configuration

The EUT was tested per the guidance of KDB 789033 D02 v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing. Software was provided to control the EUT transmission mode and frequency. The EUT was connected to a laptop PC via PEAK adapter cable and RS232 cable. During testing, the external antenna (Huber and Sunher model 1354.17.0001) was connected to the EUT via 20dB attenuator and reverse SMA cable. See section 3.2 for radiated emissions test setups.

2.5 Software and Firmware

The test was conducted with Base SW:1.2.0, APP SW: 2.0.4_RC3, and Ublox SW:6.0.1-04 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: 2APZK3002	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 5 of 20

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 1GHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the polarization of the EUT antenna through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 474788 D01.

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: 2APZK3002	 Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway	Page 6 of 20	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT use a **unique coupling**.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: 2APZK3002	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway	Page 7 of 20

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: 2APZK3002	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 8 of 20

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Emco	3116	Horn Antenna (18 - 40GHz)	8/7/2018	Triennial	8/7/2021	9203-2178
Rohde & Schwarz	FSW26	2Hz-26.5GHz Signal and Spectrum Analyzer	2/10/2021	Annual	2/10/2022	103187
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	8/17/2020	Annual	8/17/2021	MY52350166
Emco	3115	Horn Antenna (1-18GHz)	6/18/2020	Biennial	6/18/2022	9704-5182
-	AP1	EMC Cable and Switch System	3/9/2021	Annual	3/9/2022	AP1

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: 2APZK3002	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 9 of 20

7.0 TEST RESULTS

7.1 Summary

Company Name: Cummins Inc.
 FCC ID: 2APZK3002
 FCC Classification: Unlicensed National Information Infrastructure Tx (NII)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.407(b.1), (2), (3), (4)	RSS-247 [6.2]	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b) (RSS-247 [6.2])	RADIATED	PASS	Section 7.2
15.205, 15.407(b.1), (4), (5), (6)	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Section 7.3

Table 7-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst-case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.3.1.

FCC ID: 2APZK3002	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway	Page 10 of 20	

7.2 Radiated Spurious Emission Measurements – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW), 802.11n (40MHz BW), and 802.11ac (80MHz)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-2 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V}/\text{m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-2. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5
KDB 789033 D02 v02r01 – Section G

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span}/\text{RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: 2APZK3002	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 11 of 20

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

2. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
3. Span was set greater than 1MHz
4. RBW = 120kHz
5. Detector = CISPR quasi-peak
6. Sweep time = auto couple
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

FCC ID: 2APZK3002	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 12 of 20

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-2.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-2. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. N/A
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels


- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

Radiated Band Edge Measurement Offset


- The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:
 Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: 2APZK3002	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 13 of 20

7.6.1 Radiated Spurious Emission Measurements




Plot 7-1. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40)




Plot 7-2. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56)

FCC ID: 2APZK3002	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 14 of 20

Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-3. Radiated Spurious Plot 18GHz - 26.5GHz (802.11a)



Plot 7-4. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a)

FCC ID: 2APZK3002	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 15 of 20

Radiated Spurious Emission Measurements

§15.407(b) §15.205 & §15.209: RSS-Gen [8.9]

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10360.00	Peak	V	153	155	-63.50	15.26	0.00	58.76	68.20	-9.44
* 15540.00	Average	V	-	-	-81.76	22.49	0.00	47.73	53.98	-6.25
* 15540.00	Peak	V	-	-	-71.17	22.49	0.00	58.32	73.98	-15.66
* 20720.00	Average	V	150	275	-58.69	4.48	-9.54	43.24	53.98	-10.74
* 20720.00	Peak	V	150	275	-52.71	4.48	-9.54	49.23	73.98	-24.75
25900.00	Peak	V	-	-	-55.85	6.92	-9.54	48.52	68.20	-19.68

Table 7-3. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5200MHz
 Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10400.00	Peak	V	147	158	-64.33	15.57	0.00	58.24	68.20	-9.96
* 15600.00	Average	V	-	-	-82.69	23.12	0.00	47.43	53.98	-6.55
* 15600.00	Peak	V	-	-	-71.60	23.12	0.00	58.52	73.98	-15.46
* 20800.00	Average	V	150	270	-57.09	4.88	-9.54	45.25	53.98	-8.73
* 20800.00	Peak	V	150	270	-52.71	4.88	-9.54	49.63	73.98	-24.35
26000.00	Peak	V	-	-	-55.26	7.10	-9.54	49.31	68.20	-18.89

Table 7-4. Radiated Measurements

FCC ID: 2APZK3002		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1-2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 16 of 20

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	V	150	158	-65.35	15.91	0.00	57.56	68.20	-10.64
* 15720.00	Average	V	-	-	-82.90	23.84	0.00	47.94	53.98	-6.04
* 15720.00	Peak	V	-	-	-71.93	23.84	0.00	58.91	73.98	-15.07
* 20960.00	Average	V	150	291	-58.89	5.01	-9.54	43.57	53.98	-10.41
* 20960.00	Peak	V	150	291	-52.69	5.01	-9.54	49.78	73.98	-24.20
26200.00	Peak	V	-	-	-55.31	6.99	-9.54	49.13	68.20	-19.07

Table 7-5. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	V	149	157	-65.05	16.43	0.00	58.38	68.20	-9.82
* 15780.00	Average	V	-	-	-82.34	23.21	0.00	47.87	53.98	-6.11
* 15780.00	Peak	V	-	-	-71.69	23.21	0.00	58.52	73.98	-15.46
* 21040.00	Average	V	150	271	-58.88	4.89	-9.54	43.47	53.98	-10.51
* 21040.00	Peak	V	150	271	-52.83	4.89	-9.54	49.52	73.98	-24.46
26300.00	Peak	V	-	-	-54.12	7.06	-9.54	50.40	68.20	-17.80

Table 7-6. Radiated Measurements

FCC ID: 2APZK3002	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1-2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 17 of 20

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5280MHz
 Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
10560.00	Peak	V	283	166	-66.54	16.25	0.00	56.71	68.20	-11.49
* 15840.00	Average	V	-	-	-82.32	22.92	0.00	47.60	53.98	-6.38
* 15840.00	Peak	V	-	-	-70.87	22.92	0.00	59.05	73.98	-14.93
* 21120.00	Average	V	150	281	-61.03	5.08	-9.54	41.51	53.98	-12.47
* 21120.00	Peak	V	150	281	-52.96	5.08	-9.54	49.59	73.98	-24.39
26400.00	Peak	V	-	-	-53.07	7.43	-9.54	51.82	68.20	-16.38

Table 7-7. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
* 10640.00	Average	V	164	167	-77.16	17.64	0.00	47.48	53.98	-6.50
* 10640.00	Peak	V	164	167	-65.53	17.64	0.00	59.11	73.98	-14.87
* 15960.00	Average	V	-	-	-82.45	22.98	0.00	47.53	53.98	-6.45
* 15960.00	Peak	V	-	-	-71.08	22.98	0.00	58.90	73.98	-15.08
* 21280.00	Average	V	150	273	-62.68	5.14	-9.54	39.92	53.98	-14.06
* 21280.00	Peak	V	150	273	-54.78	5.14	-9.54	47.81	73.98	-26.17
26600.00	Peak	V	150	274	-54.64	7.21	-9.54	50.04	68.20	-18.16

Table 7-8. Radiated Measurements


FCC ID: 2APZK3002	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1-2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 18 of 20

7.3 Radiated Band Edge Measurements (20MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5180MHz
 Channel: 36




Plot 7-5. Radiated Lower Band Edge Plot (Average – UNII Band 1)




Plot 7-6. Radiated Lower Band Edge Plot (Peak – UNII Band 1)

Worst Case Mode: 802.11n
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5320MHz
 Channel: 64



Plot 7-7. Radiated Upper Band Edge Plot (Average – UNII Band 2A)



Plot 7-8. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: 2APZK3002	 PCTEST® Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 19 of 20

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Cummins CAN WiFi Gateway FCC ID: 2APZK3002** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules.

FCC ID: 2APZK3002	 <small>Proud to be part of  element</small>	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2105140054-01-R1.2AP	Test Dates: 5/27/21 – 6/1/21	EUT Type: CAN WiFi Gateway		Page 20 of 20