

FCC Report (WIFI)

Applicant: Shenzhen Bright Lighting Technology Co.,Ltd

Address of Applicant: Bldg 18 Shancheng Industrial Park Shiyan Town Baoan District, Shenzhen, Guangdong 518108

Manufacturer: Shenzhen Bright Lighting Technology Co.,Ltd

Address of Manufacturer: Bldg 18 Shancheng Industrial Park Shiyan Town Baoan District, Shenzhen, Guangdong 518108

Equipment Under Test (EUT)

Product Name: LED Smart bulb

Model No.: See section 5.1

FCC ID: 2AQ22-BRTA60RGBW

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: Sep 19, 2018

Date of Test: Sep 22-Oct 19, 2018

Date of report issued: Oct 22, 2018

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	Oct 22, 2018	Original

Prepared By:




Date:

Oct 22, 2018

Project Engineer

Check By:



Date:

Sep 30, 2018

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY.....	7
5.5 TEST LOCATION	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	14
7.4 CHANNEL BANDWIDTH	15
7.5 POWER SPECTRAL DENSITY	22
7.6 BAND EDGES.....	26
7.6.1 Radiated Emission Method.....	26
7.6.2 Radiated Emission Method.....	30
8 TEST SETUP PHOTO	44
9 EUT CONSTRUCTIONAL DETAILS	46

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013.

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	LED Smart bulb
Model No.:	BRT-A60-2-9DW,BRT-A60-1-9RGBW,BRT-A60-2-9RGBW,BRT-A60-1-9RGBCW,BRT-A60-2-9RGBCW,BRT-A60-1-9RGBWW,BRT-A60-2-9RGBWW,BRT-A60-1-9DW, BRT-A60-1-96500, LP-IOTDMLWH BRT-A60-2-96500,BRT-A60-1-94000,BRT-A60-2-94000, BRT-A60-1-92700,BRT-A60-2-92700,BRT-A60-1-7RGBW, BRT-A60-2-7RGBW,BRT-A60-1-7RGBCW,BRT-A60-2-7RGBCW, BRT-A60-1-7RGBWW,BRT-A60-2-7RGBWW,BRT-A60-1-7DW, BRT-A60-2-7DW,BRT-A60-1-76500,BRT-A60-2-76500, BRT-A60-1-74000,BRT-A60-2-74000,BRT-A60-1-72700, BRT-A60-2-72700,BRT-A60-1-5RGBW,BRT-A60-2-5RGBW, BRT-A60-1-5RGBCW,BRT-A60-2-5RGBCW,BRT-A60-1-5R,GBWWBRT-A60-2-5RGBWW,BRT-A60-1-5DW,BRT-A60-2-5DW,BRT-A60-1-56500,BRT-A60-2-56500,BRT-A60-1-54000,BRT-A60-2-54000,BRT-A60-1-52700,BRT-A60-2-52700,LP-IOTMLWH (The just appearance different, the PCB boards inside are identical.)
Serial No.:	180872801
Test sample(s) ID:	GTS201809000132-1
Sample(s) Status	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20): 13
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20) Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Integrated PCB antenna
Antenna gain:	3.23dBi
Power supply:	AC 120V/60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	12	2467MHz
						13	2472MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2442MHz
Highest channel	2472MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:			
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.			
Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

5.3 Description of Support Units

N/A

5.4 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018. ● Industry Canada (IC) —Registration No.: 9079A-2 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.
--

5.5 Test Location

All tests were performed at:
<p>Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p>

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019


Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019

Conducted:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test results and Measurement Data


7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:</p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
EUT Antenna:	
<p><i>The antenna is integral antenna, the best case gain of the antenna is 3.23dBi</i></p> <div style="display: flex; align-items: center;">  </div>	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Test Frequency Range:	150KHz to 30MHz														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	<p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 														
Test Instruments:	Refer to section 6.0 for details														
Test mode:	Refer to section 5.2 for details														
Test voltage:	AC120V 60Hz														


Mode:	Transmitting mode	Test by:	Jason
Temp./Hum.(%H):	26°C/56%RH	Phase:	L



No.	Frequency (MHz)	Reading (dBuV)	Lisn/Isn (dB)	Cab_L (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.2805	21.60	9.51	0.24	31.35	60.80	-29.45	QP	
2	0.2805	15.15	9.51	0.24	24.90	50.80	-25.90	AVG	
3	0.8880	22.32	9.58	0.23	32.13	56.00	-23.87	QP	
4	0.8880	14.65	9.58	0.23	24.46	46.00	-21.54	AVG	
5	1.5270	20.68	9.65	0.21	30.54	56.00	-25.46	QP	
6	1.5270	11.81	9.65	0.21	21.67	46.00	-24.33	AVG	
7	2.1840	17.47	9.7	0.2	27.37	56.00	-28.63	QP	
8	2.1840	9.94	9.7	0.2	19.84	46.00	-26.16	AVG	
9	2.7690	17.23	9.7	0.2	27.13	56.00	-28.87	QP	
10	2.7690	9.71	9.7	0.2	19.61	46.00	-26.39	AVG	
11	3.9705	17.22	9.7	0.21	27.13	56.00	-28.87	QP	
12	3.9705	9.25	9.7	0.21	19.16	46.00	-26.84	AVG	

Remarks: 1. Result=Reading+Lisn+Cab_L
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.


Mode:	Transmitting mode	Test by:	Jason
Temp./Hum.(%H):	26°C/56%RH	Phase:	N



No.	Frequency (MHz)	Reading (dBuV)	Lisn/Isn (dB)	Cab_L (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.2805	19.75	9.51	0.24	29.50	60.80	-31.30	QP	
2	0.2805	13.86	9.51	0.24	23.61	50.80	-27.19	AVG	
3	0.4020	18.61	9.51	0.24	28.36	57.81	-29.45	QP	
4	0.4020	11.78	9.51	0.24	21.53	47.81	-26.28	AVG	
5	0.9285	21.33	9.59	0.23	31.15	56.00	-24.85	QP	
6	0.9285	13.15	9.59	0.23	22.97	46.00	-23.03	AVG	
7	1.5225	18.02	9.65	0.21	27.88	56.00	-28.12	QP	
8	1.5225	10.15	9.65	0.21	20.01	46.00	-25.99	AVG	
9	2.0535	16.65	9.7	0.2	26.55	56.00	-29.45	QP	
10	2.0535	8.69	9.7	0.2	18.59	46.00	-27.41	AVG	
11	3.3360	16.11	9.7	0.2	26.01	56.00	-29.99	QP	
12	3.3360	8.18	9.7	0.2	18.08	46.00	-27.92	AVG	

Remarks: 1. Result=Reading+Lisn+Cab_L
 2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.


7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	30dBm
Test setup:	 <p>The diagram shows a Power Meter and an E.U.T. connected by a red cable. They are positioned on a table labeled 'Non-Conducted Table'. Below the table is a shaded area labeled 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Peak Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	9.61	9.78	10.20	30.00	Pass
Middle	10.66	9.86	10.11		
Highest	10.32	9.79	10.02		

7.4 Channel Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	>500KHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Test CH	6dB Emission Bandwidth (MHz)			Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	9.514	16.610	17.679	>500	Pass
Middle	9.507	16.586	17.681		
Highest	9.499	16.606	17.701		
Test CH	99%Occupancy Bandwidth (MHz)			Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)		
Lowest	14.926	16.489	17.574	N/A	N/A
Middle	14.936	16.472	17.556		
Highest	14.898	16.490	17.589		

Test plot as follows:


Test mode:802.11b



Lowest channel




Middle channel




Highest channel


Test mode:802.11g



Lowest channel




Middle channel




Highest channel


Test mode:802.11n(HT20)



Lowest channel




Middle channel



Highest channel

7.5 Power Spectral Density


Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	8dBm/3kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Test CH	Power Spectral Density (dBm)			Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	-9.369	-14.950	-14.530	8.00	Pass
Middle	-9.381	-14.590	-13.680		
Highest	-7.640	-16.420	-14.120		

Test plot as follows:


Test mode:	802.11b
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode: 802.11g



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)



Lowest channel



Middle channel



Highest channel

7.6 Band edges

7.6.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz				Average
					Peak
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test 				

	worst case mode is recorded in the report.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	51.69	27.26	5.85	38.42	46.38	74.00	-27.62	Vertical
2390.00	55.24	27.31	5.66	38.26	49.95	74.00	-24.05	Vertical
2310.00	54.30	27.32	5.85	38.42	49.05	74.00	-24.95	Horizontal
2390.00	59.68	27.31	5.66	38.26	54.39	74.00	-19.61	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	42.88	27.26	5.85	38.42	37.57	54.00	-16.43	Vertical
2390.00	45.99	27.31	5.66	38.26	40.70	54.00	-13.30	Vertical
2310.00	42.56	27.32	5.85	38.42	37.31	54.00	-16.69	Horizontal
2390.00	48.49	27.31	5.66	38.26	43.20	54.00	-10.80	Horizontal

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	68.77	27.37	5.89	38.47	63.56	74.00	-10.44	Horizontal
2500.00	66.01	27.38	5.69	38.27	60.81	74.00	-13.19	Horizontal
2483.50	59.86	27.37	5.89	38.47	54.65	74.00	-19.35	Vertical
2500.00	60.03	27.38	5.69	38.28	54.82	74.00	-19.18	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	54.69	27.37	5.89	38.47	49.48	54.00	-4.52	Horizontal
2500.00	56.20	27.38	5.69	38.27	51.00	54.00	-3.00	Horizontal
2483.50	47.63	27.37	5.89	38.47	42.42	54.00	-11.58	Vertical
2500.00	48.29	27.38	5.69	38.28	43.08	54.00	-10.92	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	48.59	27.26	5.85	38.42	43.28	74.00	-30.72	Horizontal
2390.00	50.17	27.31	5.66	38.26	44.88	74.00	-29.12	Horizontal
2310.00	46.21	27.32	5.85	38.42	40.96	74.00	-33.04	Vertical
2390.00	48.58	27.31	5.66	38.26	43.29	74.00	-30.71	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	42.38	27.26	5.85	38.42	37.07	54.00	-16.93	Horizontal
2390.00	45.53	27.31	5.66	38.26	40.24	54.00	-13.76	Horizontal
2310.00	41.36	27.32	5.85	38.42	36.10	54.00	-17.90	Vertical
2390.00	43.38	27.31	5.66	38.26	38.09	54.00	-15.91	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.23	27.37	5.89	38.47	39.02	74.00	-34.98	Horizontal
2500.00	47.46	27.38	5.69	38.27	42.26	74.00	-31.74	Horizontal
2483.50	50.47	27.37	5.89	38.47	45.26	74.00	-28.74	Vertical
2500.00	44.16	27.38	5.69	38.28	38.95	74.00	-35.05	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.56	27.37	5.89	38.47	44.35	54.00	-9.65	Horizontal
2500.00	41.42	27.38	5.69	38.27	36.22	54.00	-17.78	Horizontal
2483.50	45.40	27.37	5.89	38.47	40.19	54.00	-13.81	Vertical
2500.00	49.31	27.38	5.69	38.28	44.10	54.00	-9.90	Vertical

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	48.60	27.26	5.85	38.42	43.29	74.00	-30.71	Horizontal
2390.00	50.14	27.31	5.66	38.26	44.85	74.00	-29.15	Horizontal
2310.00	46.28	27.32	5.85	38.42	48.89	74.00	-25.11	Vertical
2390.00	48.62	27.31	5.66	38.26	43.33	74.00	-30.67	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	42.39	27.26	5.85	38.42	37.08	54.00	-16.92	Horizontal
2390.00	45.51	27.31	5.66	38.26	40.22	54.00	-13.78	Horizontal
2310.00	41.39	27.32	5.85	38.42	36.14	54.00	-17.86	Vertical
2390.00	43.42	27.31	5.66	38.26	38.13	54.00	-15.87	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	54.30	27.37	5.89	38.47	49.09	74.00	-24.91	Horizontal
2500.00	47.41	27.38	5.69	38.27	42.21	74.00	-31.79	Horizontal
2483.50	50.42	27.37	5.89	38.47	45.21	74.00	-28.79	Vertical
2500.00	43.64	27.38	5.69	38.28	38.43	74.00	-35.57	Vertical


Average value:



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.51	27.37	5.89	38.47	44.30	54.00	-9.70	Horizontal
2500.00	41.33	27.38	5.69	38.27	36.13	54.00	-17.87	Horizontal
2483.50	45.44	27.37	5.89	38.47	40.23	54.00	-13.77	Vertical
2500.00	49.27	27.38	5.69	38.28	44.06	54.00	-9.94	Vertical

Remark:

3. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
4. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
	 <p>The diagram illustrates the test setup for radiated emissions from 9kHz to 30MHz. It shows a Turn Table with an EUT (Equipment Under Test) on top, positioned 80cm from the ground. A Test Antenna is placed 1m from the EUT. The measurement distance is 3m. The antenna is connected to a Receiver and a Preamplifier.</p>				
For radiated emissions from 30MHz to 1GHz					

	 <p>For radiated emissions above 1GHz</p> 
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass
Test voltage:	AC120V 60Hz

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement data:


■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ **Below 1GHz**

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's data was showed.


Mode:	Transmitting mode:802.11b TX 2412MHz	Test by:	Jason
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Antenna (dB/m)	Cable (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	53.1313	10.03	12.02	1.15	23.20	40.00	-16.80	QP
2	125.8863	14.81	8.63	1.66	25.10	43.50	-18.40	QP
3	138.3873	16.74	7.43	1.73	25.90	43.50	-17.60	QP
4	187.7529	15.51	9.58	1.91	27.00	43.50	-16.50	QP
5	280.0237	15.96	12.86	2.38	31.20	46.00	-14.80	QP
6	387.9920	12.52	15.26	2.72	30.50	46.00	-15.50	QP

Remarks: 1. Result=Reading+Antenna+Cable
 2. If Peak Result complies with QP Limit, QP Result is deemed to comply with QP Limit.

Mode:	Transmitting mode:802.11b TX	Test by:	Jason
	2412MHz		
Temp./Hum.(%H):	26°C/56%RH	Polarization:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Antenna (dB/m)	Cable (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	52.9453	21.53	12.03	1.14	34.70	40.00	-5.30	QP
2	79.8002	22.22	7.5	1.38	31.10	40.00	-8.90	QP
3	88.9639	19.64	10.28	1.38	31.30	43.50	-12.20	QP
4	136.9391	25.54	7.54	1.72	34.80	43.50	-8.70	QP
5	187.0956	18.39	9.51	1.9	29.80	43.50	-13.70	QP
6	480.5276	15.52	17.11	2.97	35.60	46.00	-10.40	QP

Remarks: 1. Result=Reading+Antenna+Cable
 2. If Peak Result complies with QP Limit, QP Result is deemed to comply with QP Limit.

■ Above 1GHz

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	39.22	31.79	8.62	32.10	47.53	74.00	-26.47	Vertical
7236.00	33.54	36.19	11.68	31.97	49.44	74.00	-24.56	Vertical
9648.00	32.23	38.07	14.16	31.56	52.90	74.00	-21.10	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	38.06	31.79	8.62	32.10	46.37	74.00	-27.63	Horizontal
7236.00	33.38	36.19	11.68	31.97	49.28	74.00	-24.72	Horizontal
9648.00	31.85	38.07	14.16	31.56	52.52	74.00	-21.48	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.39	31.79	8.62	32.10	36.70	54.00	-17.30	Vertical
7236.00	22.43	36.19	11.68	31.97	38.33	54.00	-15.67	Vertical
9648.00	22.60	38.07	14.16	31.56	43.27	54.00	-10.73	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	27.65	31.79	8.62	32.10	35.96	54.00	-18.04	Horizontal
7236.00	21.98	36.19	11.68	31.97	37.88	54.00	-16.12	Horizontal
9648.00	21.61	38.07	14.16	31.56	42.28	54.00	-11.72	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” , means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	38.46	31.85	8.66	32.12	46.85	74.00	-27.15	Vertical
7326.00	33.73	36.37	11.71	31.91	49.90	74.00	-24.10	Vertical
9768.00	33.33	38.27	14.25	31.56	54.29	74.00	-19.71	Vertical
12210.00	*					74.00		Vertical
14652.00	*					74.00		Vertical
17094.00	*					74.00		Vertical
4884.00	39.08	31.85	8.66	32.12	47.47	74.00	-26.53	Horizontal
7326.00	32.44	36.37	11.71	31.91	48.61	74.00	-25.39	Horizontal
9768.00	33.25	38.27	14.25	31.56	54.21	74.00	-19.79	Horizontal
12210.00	*					74.00		Horizontal
14652.00	*					74.00		Horizontal
17094.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	29.39	31.85	8.66	32.12	37.78	54.00	-16.22	Vertical
7326.00	22.07	36.37	11.71	31.91	38.24	54.00	-15.76	Vertical
9768.00	22.60	38.27	14.25	31.56	43.56	54.00	-10.44	Vertical
12210.00	*					54.00		Vertical
14652.00	*					54.00		Vertical
17094.00	*					54.00		Vertical
4884.00	29.24	31.85	8.66	32.12	37.63	54.00	-16.37	Horizontal
7326.00	21.54	36.37	11.71	31.91	37.71	54.00	-16.29	Horizontal
9768.00	22.98	38.27	14.25	31.56	43.94	54.00	-10.06	Horizontal
12210.00	*					54.00		Horizontal
14652.00	*					54.00		Horizontal
17094.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4944.00	43.35	31.90	8.70	32.15	51.80	74.00	-22.20	Vertical
7416.00	34.00	36.49	11.76	31.83	50.42	74.00	-23.58	Vertical
9888.00	36.34	38.62	14.31	31.77	57.50	74.00	-16.50	Vertical
12360.00	*					74.00		Vertical
14832.00	*					74.00		Vertical
17304.00	*					74.00		Vertical
4944.00	42.90	31.90	8.70	32.15	51.35	74.00	-22.65	Horizontal
7416.00	33.02	36.49	11.76	31.83	49.44	74.00	-24.56	Horizontal
9888.00	32.56	38.62	14.31	31.77	53.72	74.00	-20.28	Horizontal
12360.00	*					74.00		Horizontal
14832.00	*					74.00		Horizontal
17304.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4944.00	34.39	31.90	8.70	32.15	42.84	54.00	-11.16	Vertical
7416.00	23.95	36.49	11.76	31.83	40.37	54.00	-13.63	Vertical
9888.00	24.87	38.62	14.31	31.77	46.03	54.00	-7.97	Vertical
12360.00	*					54.00		Vertical
14832.00	*					54.00		Vertical
17304.00	*					54.00		Vertical
4944.00	33.34	31.90	8.70	32.15	41.79	54.00	-12.21	Horizontal
7416.00	22.44	36.49	11.76	31.83	38.86	54.00	-15.14	Horizontal
9888.00	21.85	38.62	14.31	31.77	43.01	54.00	-10.99	Horizontal
12360.00	*					54.00		Horizontal
14832.00	*					54.00		Horizontal
17304.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	38.76	31.79	8.62	32.10	47.07	74.00	-26.93	Vertical
7236.00	33.25	36.19	11.68	31.97	49.15	74.00	-24.85	Vertical
9648.00	32.02	38.07	14.16	31.56	52.69	74.00	-21.31	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	37.67	31.79	8.62	32.10	45.98	74.00	-28.02	Horizontal
7236.00	33.12	36.19	11.68	31.97	49.02	74.00	-24.98	Horizontal
9648.00	31.65	38.07	14.16	31.56	52.32	74.00	-21.68	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	27.97	31.79	8.62	32.10	36.28	54.00	-17.72	Vertical
7236.00	22.15	36.19	11.68	31.97	38.05	54.00	-15.95	Vertical
9648.00	22.40	38.07	14.16	31.56	43.07	54.00	-10.93	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	27.29	31.79	8.62	32.10	35.60	54.00	-18.40	Horizontal
7236.00	21.73	36.19	11.68	31.97	37.63	54.00	-16.37	Horizontal
9648.00	21.43	38.07	14.16	31.56	42.10	54.00	-11.90	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	38.08	31.85	8.66	32.12	46.47	74.00	-27.53	Vertical
7326.00	33.49	36.37	11.71	31.91	49.66	74.00	-24.34	Vertical
9768.00	33.16	38.27	14.25	31.56	54.12	74.00	-19.88	Vertical
12210.00	*					74.00		Vertical
14652.00	*					74.00		Vertical
17094.00	*					74.00		Vertical
4884.00	38.76	31.85	8.66	32.12	47.15	74.00	-26.85	Horizontal
7326.00	32.23	36.37	11.71	31.91	48.40	74.00	-25.60	Horizontal
9768.00	33.09	38.27	14.25	31.56	54.05	74.00	-19.95	Horizontal
12210.00	*					74.00		Horizontal
14652.00	*					74.00		Horizontal
17094.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	29.04	31.85	8.66	32.12	37.43	54.00	-16.57	Vertical
7326.00	21.83	36.37	11.71	31.91	38.00	54.00	-16.00	Vertical
9768.00	22.44	38.27	14.25	31.56	43.40	54.00	-10.60	Vertical
12210.00	*					54.00		Vertical
14652.00	*					54.00		Vertical
17094.00	*					54.00		Vertical
4884.00	28.94	31.85	8.66	32.12	37.33	54.00	-16.67	Horizontal
7326.00	21.34	36.37	11.71	31.91	37.51	54.00	-16.49	Horizontal
9768.00	22.83	38.27	14.25	31.56	43.79	54.00	-10.21	Horizontal
12210.00	*					54.00		Horizontal
14652.00	*					54.00		Horizontal
17094.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4944.00	42.70	31.90	8.70	32.15	51.15	74.00	-22.85	Vertical
7416.00	33.59	36.49	11.76	31.83	50.01	74.00	-23.99	Vertical
9888.00	36.04	38.62	14.31	31.77	57.20	74.00	-16.80	Vertical
12360.00	*					74.00		Vertical
14832.00	*					74.00		Vertical
17304.00	*					74.00		Vertical
4944.00	42.34	31.90	8.70	32.15	50.79	74.00	-23.21	Horizontal
7416.00	32.66	36.49	11.76	31.83	49.08	74.00	-24.92	Horizontal
9888.00	32.29	38.62	14.31	31.77	53.45	74.00	-20.55	Horizontal
12360.00	*					74.00		Horizontal
14832.00	*					74.00		Horizontal
17304.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4944.00	33.78	31.90	8.70	32.15	42.23	54.00	-11.77	Vertical
7416.00	23.55	36.49	11.76	31.83	39.97	54.00	-14.03	Vertical
9888.00	24.58	38.62	14.31	31.77	45.74	54.00	-8.26	Vertical
12360.00	*					54.00		Vertical
14832.00	*					54.00		Vertical
17304.00	*					54.00		Vertical
4944.00	32.82	31.90	8.70	32.15	41.27	54.00	-12.73	Horizontal
7416.00	22.09	36.49	11.76	31.83	38.51	54.00	-15.49	Horizontal
9888.00	21.58	38.62	14.31	31.77	42.74	54.00	-11.26	Horizontal
12360.00	*					54.00		Horizontal
14832.00	*					54.00		Horizontal
17304.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*”, means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	38.52	31.79	8.62	32.10	46.83	74.00	-27.17	Vertical
7236.00	33.10	36.19	11.68	31.97	49.00	74.00	-25.00	Vertical
9648.00	31.91	38.07	14.16	31.56	52.58	74.00	-21.42	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	37.47	31.79	8.62	32.10	45.78	74.00	-28.22	Horizontal
7236.00	32.99	36.19	11.68	31.97	48.89	74.00	-25.11	Horizontal
9648.00	31.55	38.07	14.16	31.56	52.22	74.00	-21.78	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	27.74	31.79	8.62	32.10	36.05	54.00	-17.95	Vertical
7236.00	22.00	36.19	11.68	31.97	37.90	54.00	-16.10	Vertical
9648.00	22.29	38.07	14.16	31.56	42.96	54.00	-11.04	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	27.10	31.79	8.62	32.10	35.41	54.00	-18.59	Horizontal
7236.00	21.60	36.19	11.68	31.97	37.50	54.00	-16.50	Horizontal
9648.00	21.33	38.07	14.16	31.56	42.00	54.00	-12.00	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	37.88	31.85	8.66	32.12	46.27	74.00	-27.73	Vertical
7326.00	33.36	36.37	11.71	31.91	49.53	74.00	-24.47	Vertical
9768.00	33.07	38.27	14.25	31.56	54.03	74.00	-19.97	Vertical
12210.00	*					74.00		Vertical
14652.00	*					74.00		Vertical
17094.00	*					74.00		Vertical
4884.00	38.59	31.85	8.66	32.12	46.98	74.00	-27.02	Horizontal
7326.00	32.12	36.37	11.71	31.91	48.29	74.00	-25.71	Horizontal
9768.00	33.01	38.27	14.25	31.56	53.97	74.00	-20.03	Horizontal
12210.00	*					74.00		Horizontal
14652.00	*					74.00		Horizontal
17094.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	28.85	31.85	8.66	32.12	37.24	54.00	-16.76	Vertical
7326.00	21.71	36.37	11.71	31.91	37.88	54.00	-16.12	Vertical
9768.00	22.35	38.27	14.25	31.56	43.31	54.00	-10.69	Vertical
12210.00	*					54.00		Vertical
14652.00	*					54.00		Vertical
17094.00	*					54.00		Vertical
4884.00	28.78	31.85	8.66	32.12	37.17	54.00	-16.83	Horizontal
7326.00	21.23	36.37	11.71	31.91	37.40	54.00	-16.60	Horizontal
9768.00	22.75	38.27	14.25	31.56	43.71	54.00	-10.29	Horizontal
12210.00	*					54.00		Horizontal
14652.00	*					54.00		Horizontal
17094.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4944.00	42.35	31.90	8.70	32.15	50.80	74.00	-23.20	4924.00
7416.00	33.37	36.49	11.76	31.83	49.79	74.00	-24.21	7386.00
9888.00	35.89	38.62	14.31	31.77	57.05	74.00	-16.95	9848.00
12360.00	*					74.00		Vertical
14832.00	*					74.00		Vertical
17304.00	*					74.00		Vertical
4944.00	42.05	31.90	8.70	32.15	50.50	74.00	-23.50	Horizontal
7416.00	32.47	36.49	11.76	31.83	48.89	74.00	-25.11	Horizontal
9888.00	32.15	38.62	14.31	31.77	53.31	74.00	-20.69	Horizontal
12360.00	*					74.00		Horizontal
14832.00	*					74.00		Horizontal
17304.00	*					74.00		Horizontal

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4944.00	33.47	31.90	8.70	32.15	41.92	54.00	-12.08	Vertical
7416.00	23.34	36.49	11.76	31.83	39.76	54.00	-14.24	Vertical
9888.00	24.44	38.62	14.31	31.77	45.60	54.00	-8.40	Vertical
12360.00	*					54.00		Vertical
14832.00	*					54.00		Vertical
17304.00	*					54.00		Vertical
4944.00	32.55	31.90	8.70	32.15	41.00	54.00	-13.00	Horizontal
7416.00	21.90	36.49	11.76	31.83	38.32	54.00	-15.68	Horizontal
9888.00	21.44	38.62	14.31	31.77	42.60	54.00	-11.40	Horizontal
12360.00	*					54.00		Horizontal
14832.00	*					54.00		Horizontal
17304.00	*					54.00		Horizontal

Remark:

- 1 *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
- 2 *“*”, means this data is the too weak instrument of signal is unable to test.*

8 Test Setup Photo

Radiated Emission



Conducted Emission




9 EUT Constructional Details



External Photos





Internal Photos



Internal Photos



Internal Photos



Wifi antenna

