

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT: Left

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-1.157	0.77	-1±1	0	1.00	<5	0.30997	3.00	YES
	2.441	-0.093	0.98	-1±1	0	1.00	<5	0.31247	3.00	YES
	2.480	-2.824	0.52	-2±1	-1	0.79	<5	0.25018	3.00	YES
$\pi/4$ -DQPSK	2.402	-3.551	0.44	-3±1	-2	0.63	<5	0.19558	3.00	YES
	2.441	-2.435	0.57	-3±1	-2	0.63	<5	0.19716	3.00	YES
	2.480	-2.109	0.62	-3±1	-2	0.63	<5	0.19873	3.00	YES

BT: Right

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.469	1.11	0±1	1	1.26	<5	0.39023	3.00	YES
	2.441	-0.550	0.88	0±1	1	1.26	<5	0.39338	3.00	YES
	2.480	-0.831	0.83	0±1	1	1.26	<5	0.39651	3.00	YES
$\pi/4$ -DQPSK	2.402	1.230	1.33	1±1	2	1.58	<5	0.49127	3.00	YES
	2.441	0.220	1.05	1±1	2	1.58	<5	0.49524	3.00	YES
	2.480	-0.075	0.98	0±1	1	1.26	<5	0.39651	3.00	YES

Conclusion:

For the max result : $0.49524 \leq 3.0$ for 1g SAR, No SAR is required.

Alex

Signature:

Date: 2022-03-23

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.