

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT: Left

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-2.666	0.54	-2±1	-1	0.79	<5	0.24622	3.00	YES
	2.441	-2.564	0.55	-2±1	-1	0.79	<5	0.24821	3.00	YES
	2.480	-2.026	0.63	-2±1	-1	0.79	<5	0.25018	3.00	YES
$\pi/4$ -DQPSK	2.402	-2.368	0.58	-2±1	-1	0.79	<5	0.24622	3.00	YES
	2.441	-2.052	0.62	-2±1	-1	0.79	<5	0.24821	3.00	YES
	2.480	-1.489	0.71	-2±1	-1	0.79	<5	0.25018	3.00	YES

BT: Right

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-3.230	0.48	-3±1	-2	0.63	<5	0.19558	3.00	YES
	2.441	-2.900	0.51	-3±1	-2	0.63	<5	0.19716	3.00	YES
	2.480	-2.251	0.60	-3±1	-2	0.63	<5	0.19873	3.00	YES
$\pi/4$ -DQPSK	2.402	-2.569	0.55	-2±1	-1	0.79	<5	0.24622	3.00	YES
	2.441	-2.213	0.60	-2±1	-1	0.79	<5	0.24821	3.00	YES
	2.480	-1.545	0.70	-2±1	-1	0.79	<5	0.25018	3.00	YES

Conclusion:

For the max result : $0.25018 \leq 3.0$ for 1g SAR, No SAR is required.

Alex

Signature:

Date: 2022-03-26

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.