

TEST REPORT						
FCC ID:	2AQ2W-BQ12					
Test Report No::	TCT230911E044					
Date of issue::	Sep. 20, 2023					
Testing laboratory:	SHENZHEN TONGCE TEST	TING LAB				
Testing location/ address:	2101 & 2201, Zhenchang Fa Subdistrict, Bao'an District, S People's Republic of China					
Applicant's name::	Shenzhen Doageas Technol	ogy Co., Ltd.				
Address:	5/F, 4th Bldg, Hedian Industr Shenzhen, Guangdong 5181	·	onghua,			
Manufacturer's name:	Shenzhen Doageas Technol	ogy Co., Ltd.				
Address:	5/F, 4th Bldg, Hedian Industrial Park, Guanlan, Longhua, Shenzhen, Guangdong 518110, China.					
Standard(s)::	KDB 447498 D01 General RF Exposure Guidance v06					
Product Name:	Digital Clock & Bluetooth Speaker & Phone Stand & Wireless Charger					
Trade Mark:	DOAGEAS	(F.				
Model/Type reference:	BQ12					
Rating(s)::	DC 9V or Rechargeable Li-io	on Battery DC 3.7V				
Date of receipt of test item	Sep. 11, 2023					
Date (s) of performance of test:	Sep. 11, 2023 - Sep. 20, 202	23				
Tested by (+signature):	Ronaldo LUO	P. rald day	A9F7			
Check by (+signature):	Beryl ZHAO	Boy Comp	OT)			
Approved by (+signature):	Tomsin	Tomsies	847			

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.





Table of Contents

1.							
			-				
2.	Gei	neral Inf	ormation				4
3.0		_		-			
4.	Tes	st Result	s and Me	easureme	ent Data .	 	 6



1. General Product Information

1.1. EUT description

Product Name:	Digital Clock & Bluetooth Speaker & Phone Stand & Wireless Charger			
Model/Type reference:	BQ12			
Sample Number:	TCT230911E011-0101			
Operation Frequency:	2402MHz~2480MHz			
Modulation Type:	GFSK, π/4-DQPSK, 8DPSK			
Antenna Type:	PCB Antenna			
Antenna Gain:	-0.68dBi			
Rating(s):	DC 9V or Rechargeable Li-ion Battery DC 3.7V			

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list None. None



2. General Information

2.1. Test environment and mode

Item	Normal condition					
Temperature	+25°C					
Voltage	DC 3.7V					
Humidity	56%					
Atmospheric Pressure:	1008 mbar					
Test Mode:						
Transmitting Keep the EUT in continuous transmitting by select c mode:						

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment Model No.		Serial No.	Trade Name		
/		1	1	1	

Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



Page 4 of 6



3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339



Page 5 of 6



4. Test Results and Measurement Data

According to KDB 447498 D01 General RF Exposure Guidance v06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

BDR+EDR:

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 00	2.402	-0.29	-1±1	0	1.00	5	0.31	3.0

Result:

Base on the calculation value, No SAR measurement is required.

*****END OF REPORT*****

Page 6 of 6