



**中认信通**  
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



## TEST REPORT

**Applicant: Shenzhen VanTop Technology & Innovation Co., Ltd.**

Address: 502, 5th Flr. BLDG 4, MinQi Technology Park, No. 65 Lishan Road,  
Taoyuan Street, Nanshan District, Shenzhen, China

**FCC ID: 2AQ3A-E30T**

**IC: 24268-E30T**

**HVIN: VQ01**

**Product Name: Projector**

**Standard(s): 47 CFR Part 15, Subpart E(15.407)**  
**RSS-247 Issue 2, February 2017**  
**RSS-Gen, Issue 5, February 2021 Amendment 2**  
**ANSI C63.10-2013**  
**KDB 789033 D02 General U-NII Test Procedures New**  
**Rules v02r01**

The above equipment has been tested and found compliance with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number: CR21090087-00B**

**Date Of Issue: 2021-10-19**

**Reviewed By: Sun Zhong**

*Sun Zhong*

Title: Manager

**Test Laboratory: China Certification ICT Co., Ltd (Dongguan)**

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

## Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

## Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## CONTENTS

<b>TEST FACILITY .....</b>	<b>2</b>
<b>DECLARATIONS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b>	<b>5</b>
<b>1.2 DESCRIPTION OF TEST CONFIGURATION.....</b>	<b>7</b>
1.2.2 Support Equipment List and Details .....	7
1.2.3 Support Cable List and Details .....	7
1.2.4 Block Diagram of Test Setup.....	8
<b>1.3 MEASUREMENT UNCERTAINTY .....</b>	<b>9</b>
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>11</b>
<b>3.1 AC LINE CONDUCTED EMISSIONS.....</b>	<b>11</b>
3.1.1 Applicable Standard.....	11
3.1.2 EUT Setup.....	12
3.1.3 EMI Test Receiver Setup .....	12
3.1.4 Test Procedure .....	13
3.1.5 Corrected Amplitude & Margin Calculation.....	13
<b>3.2 RADIATION SPURIOUS EMISSIONS.....</b>	<b>14</b>
3.2.1 Applicable Standard.....	14
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....	17
3.2.4 Test Procedure .....	17
3.2.5 Corrected Amplitude & Margin Calculation.....	17
<b>3.3 EMISSION BANDWIDTH: .....</b>	<b>18</b>
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure .....	18
<b>3.4 MAXIMUM CONDUCTED OUTPUT POWER:.....</b>	<b>20</b>
3.4.1 Applicable Standard.....	20
3.4.2 EUT Setup.....	20
3.4.3 Test Procedure .....	21
<b>3.5 MAXIMUM POWER SPECTRAL DENSITY: .....</b>	<b>22</b>
3.5.1 Applicable Standard.....	22
3.5.2 EUT Setup.....	22
3.5.3 Test Procedure .....	23
<b>3.7 DUTY CYCLE:.....</b>	<b>24</b>
3.7.1 EUT Setup.....	24
3.7.2 Test Procedure .....	24
<b>3.8 ANTENNA REQUIREMENT.....</b>	<b>25</b>
3.8.1 Applicable Standard.....	25
3.8.2 Judgment.....	25

**3.9 ADDITIONAL REQUIREMENT .....26**  
    3.9.1 Applicable Standard.....26  
**3.9.2 JUDGMENT.....27**

**4. Test DATA AND RESULTS ..... 28**  
    **4.1 AC LINE CONDUCTED EMISSIONS.....28**  
    **4.2 RADIATION SPURIOUS EMISSIONS .....31**  
    **4.3 EMISSION BANDWIDTH: .....41**  
    **4.4 MAXIMUM CONDUCTED OUTPUT POWER: .....54**  
    **4.5 MAXIMUM POWER SPECTRAL DENSITY: .....55**  
    **4.6 DUTY CYCLE:.....63**

**5. RF EXPOSURE EVALUATION ..... 65**  
    **5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....65**  
        5.1.1 APPLICABLE STANDARD.....65  
        5.1.2 PROCEDURE.....65  
        5.1.3 CALCULATED RESULT .....65  
    **5.2 EXEMPTION LIMITS FOR ROUTINE EVALUATION – RF EXPOSURE EVALUATION 66**  
        5.2.1 APPLICABLE STANDARD.....66  
        5.2.2 CALCULATED RESULT .....66

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	Projector
<b>EUT Model:</b>	Leisure E30T
<b>FCC Multiple Model:</b>	Leisure 530W, Leisure E30,Leisure E30WT,Leisure E30TB,Leisure 540W, Leisure 550W, Leisure 560W, Leisure 570W, Leisure 580W, Leisure 590W, Leisure D30, Leisure D30T, Leisure 480W, Leisure D80T, Leisure 495W, Leisure D95, Leisure E10, Leisure E20, Leisure E40, Leisure E50, Leisure E60, Leisure E70, Leisure E80, Leisure E90, A01011, A01012, A01013, A01014, A01015, A01016, A01017, A01018, A01019, A01020
<b>IC Multiple Model:</b>	Leisure E30TB, Leisure E30WT, A01011, A01012
<b>Operation Frequency:</b>	5180-5240 MHz (802.11a/n ht20) 5190-5230 MHz(802.11n ht40) 5745-5825 MHz (802.11a/n ht20) 5755-5795 MHz(802.11n ht40)
<b>Maximum Peak Output Power (Conducted):</b>	11.92 dBm (5150-5250 MHz) 12.50 dBm (5725-5850 MHz)
<b>Modulation Type:</b>	OFDM
<b>Rated Input Voltage:</b>	AC 120V/60Hz
<b>Serial Number:</b>	CR21090087-RF-S1
<b>EUT Received Date:</b>	2021.09.30
<b>EUT Received Status:</b>	Good
Note: The Multiple models are identical with Test model, please refer to the declaration letter for more detail, which was provided by manufacturer.	

### Operation Frequency Detail:

#### For 802.11a/n ht20:

5150-5250MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	149	5745
40	5200	153	5765
44	5220	157	5785
48	5240	161	5805
/	/	165	5825

Per section 15.31(m), the lowest frequency, middle frequency, and highest frequency were performed the test as below:

Test Channel	Test Frequency (MHz)	
	5150-5250MHz Band	5725-5850MHz Band
Lowest	5180	5745
Middle	5200	5785
Highest	5240	5825

**For 802.11n ht40:**

5150-5250MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	151	5755
46	5230	159	5795

Per section 15.31(m), the lowest frequency, middle frequency, and highest frequency were performed the test as below:

Test Channel	Test Frequency (MHz)	
	5150-5250MHz Band	5725-5850MHz Band
Lowest	5190	5755
Highest	5230	5795

**Antenna Information Detail▲:**

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203& RSS-Gen Requirement
Shenzhen VanTop Technology & Innovation Co., Ltd.	FPC	50	1.59dBi/ 5.15~5.85GHz	Compliance

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

**Accessory Information:**

Accessory Description	Manufacturer	Model	Parameters
Power Cable	VanTop	Unknown	Un-shielding, 1.2m
Video Cable	VanTop	Unknown	Un-shielding, 0.2m
Remote	VanTop	Unknown	IR Remote

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

<b>EUT Operation Mode:</b>		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.			
<b>Equipment Modifications:</b>		No			
<b>EUT Exercise Software:</b>		SecureCRT			
The software " SecureCRT "was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲:					
Frequency Band	Test Modes	Data Rate	Power Level Setting		
			Lowest Channel	Middle Channel	Highest Channel
5150-5250 MHz	802.11a	6Mbps	50	48	45
	802.11n ht20	MCS0	50	48	45
5725-5850 MHz	802.11a	6Mbps	48	45	45
	802.11n ht20	MCS0	48	45	45


### 1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
SanDisk	TF card	SDDR-C531	TF001
SanDisk	U disk	AQ32G	UD001
Laptop	Lenovo	E450	PF-OMRADG
Huawei	Earphone	Unknown	EP001
GIGC	DVD	BDP-G4350	BDP-G4350-02

### 1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Earphone cable	No	No	1.2	EUT	Earphone
HDMI	Yes	No	1.2	EUT	DVD
HDMI	Yes	No	1.2	EUT	Laptop
AV Cable	Yes	No	2.0	EUT	DVD

### 1.2.4 Block Diagram of Test Setup





### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

## 2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC line conducted emissions	Compliance
FCC§15.205& §15.209 &§15.407(b) RSS-247 Clause 6.2	Undesirable Emission& Restricted Bands	Compliance
FCC§15.407(a) (e) RSS-247 Clause 6.2 RSS-Gen Clause 6.7	Emission Bandwidth	Compliance
FCC§15.407(a) RSS-247 Clause 6.2	Conducted Transmitter Output Power	Compliance
FCC§15.407 (a) RSS-247 Clause 6.2	Power Spectral Density	Compliance
§15.203	Antenna Requirement	Compliance
RSS-247 Clause 6.4	Additional requirements	Compliance
§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
RSS-102 Clause 2.5.2	Exemption Limits For Routine Evaluation-RF Exposure Evaluation	Compliance

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### 3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiation Spurious Emissions

### 3.2.1 Applicable Standard

FCC §15.407 (b);

*Undesirable emission limits.* Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(4) For transmitters operating solely in the 5.725-5.850 GHz band:

(i) All emissions shall be limited to a level of - 27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

(8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.

(10) The provisions of § 15.205 apply to intentional radiators operating under this section.

(11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

(c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

RSS-247 Clause 6.2

Frequency band 5150-5250 MHz

#### 6.2.1.2 Unwanted emission limits

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

## Frequency band 5725-5850 MHz

### 6.2.4.2 Unwanted emission limits

Devices operating in the band 5725-5850 MHz with antenna gain greater than 10 dBi can have unwanted emissions that comply with either the limits in this section or in section 5.5 until six (6) months after the publication date of this standard for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2018.


Devices operating in the band 5725-5850 MHz with antenna gain of 10 dBi or less can have unwanted emissions that comply with either the limits in this section or in section 5.5 until April 1, 2018 for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2020.



Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

- 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- 27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

### 3.2.2 EUT Setup

#### Below 1GHz:



**1-26.5 GHz:****26.5-40 GHz:**

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407, RSS-247, RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



### 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### 3.2.4 Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as:  $E [dB\mu V/m] = EIRP[dBm] + 95.2$ , for  $d = 3$  meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m or 1m

Distance extrapolation Factor =  $20 \log (\text{specific distance } [3m]/\text{test distance } [1.5m])$  dB= 6.02 dB  
or

Distance extrapolation Factor =  $20 \log (\text{specific distance } [3m]/\text{test distance } [1m])$  dB= 9.54 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

### 3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For 30MHz-1GHz:

Result = Reading + Factor

For 1GHz-40GHz

Result = Reading + Factor- Distance extrapolation Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

### 3.3 Emission Bandwidth:

#### 3.3.1 Applicable Standard

FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

RSS-247 Clause 6.2.1.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

RSS-247 Clause 6.2.4.1

For equipment operating in the band 5725-5850 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

#### 3.3.2 EUT Setup



#### 3.3.3 Test Procedure

##### 26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

**99% Occupied Bandwidth:**

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

**6 dB emission bandwidth:**

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

### 3.4 Maximum conducted output power:

#### 3.4.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 6.2.1.1


For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10}B$ , dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or  $10 + 10 \log_{10}B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

RSS-247 Clause 6.2.4.1

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

#### 3.4.2 EUT Setup



### **3.4.3 Test Procedure**

According to ANSI C63.10-2013 Section 11.9.1.3

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

### 3.5 Maximum power spectral density:

#### 3.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 6.2.1.1

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10}B$ , dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or  $10 + 10 \log_{10}B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

RSS-247 Clause 6.2.4.1

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

#### 3.5.2 EUT Setup



### 3.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

**Method SA-3** (power averaging (rms) detection with max hold):

(i) Set span to encompass the entire EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set sweep trigger to “free run.”

(iii) Set RBW = 1 MHz.

(iv) Set VBW  $\geq$  3 MHz

(v) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This ensures that bin-to-bin spacing is  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)

(vi) Sweep time  $\leq$  (number of points in sweep)  $\times T$ , where  $T$  is defined in II.B.1.a).

Note: If this results in a sweep time less than the auto sweep time of the analyzer, Method SA-3 Alternative shall not be used. (The purpose of this step is to ensure that averaging time in each bin is less than or equal to the minimum time of a transmission.)

(vii) Detector = power averaging (rms).


(viii) Trace mode = max hold.

(ix) Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.

For devices operating in the band 5.725–5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used.

### 3.7 Duty Cycle:

#### 3.7.1 EUT Setup



#### 3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
- 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)



## 3.8 Antenna Requirement

### 3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-GEN Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### 3.8.2 Judgment

Please refer to the Antenna Information detail in Section 1.

### 3.9 Additional requirement

#### 3.9.1 Applicable Standard

According to RSS-247 Clause 6.4 Additional requirement

The following requirements shall apply:

- a) The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. A description on how this is done shall accompany the application for equipment certification. Note that this is not intended to prohibit transmission of control or signalling information or the use of repetitive codes where required by the technology.
- b) All LE-LAN devices must contain security features to protect against modification of software by unauthorized parties.

Manufacturers must implement security features in any digitally modulated devices capable of operating in any of the frequency ranges within the 5 GHz band, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software must prevent the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers may use various means, including the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment certification.

Manufacturers must take steps to ensure that DFS functionality cannot be disabled by the operator of the LE-LAN device.

- c) The user manual for LE-LAN devices shall contain instructions related to the restrictions mentioned in the above sections, namely that:
  - i. the device for operation in the band 5150–5250 MHz is only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems;<sup>4</sup>
  - ii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the bands 5250-5350 MHz and 5470-5725 MHz shall be such that the equipment still complies with the e.i.r.p. limit;
  - iii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the band 5725-5850 MHz shall be such that the equipment still complies with the e.i.r.p. limits as appropriate; and
  - iv. where applicable, antenna type(s), antenna models(s), and worst-case tilt angle(s) necessary to remain compliant with the e.i.r.p. elevation mask requirement set forth in section 6.2.2.3 shall be clearly indicated.

### **3.9.2 Judgment**

RSS-247 Clause 6.4 a):

The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. Please refer to the declaration

RSS-247 Clause 6.4 b):

The devices must contain security features to protect against modification of software by unauthorized parties. Please refer to the declaration

RSS-247 Clause 6.4 c):

The device operates on 5150-5250MHz, and 5725-5850MHz, all the EIPR compliance with RSS-247 requirement. Please refer to the conducted output power test result.

## 4. Test DATA AND RESULTS

### 4.1 AC Line Conducted Emissions

Serial Number:	CR21090087-RF-S1	Test Date:	2021-10-14
Test Site:	CE	Test Mode:	Transmitting (802.11a 5785MHz was the worst)
Tester:	Nick Tang	Test Result:	Pass

#### Environmental Conditions:


Temperature: (°C)	21.9	Relative Humidity: (%)	68	ATM Pressure: (kPa)	100.8
----------------------	------	------------------------------	----	------------------------	-------

#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101132	2021-04-25	2022-04-24
R&S	EMI Test Receiver	ESR3	102726	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2021-08-08	2022-08-07
Audix	Test Software	E3	190306 (V9)	N/A	N/A


\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Line:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.181	22.93	9.61	32.54	54.43	21.89	Average
2	0.181	40.80	9.61	50.41	64.43	14.02	QP
3	0.247	21.00	9.61	30.61	51.84	21.23	Average
4	0.247	36.57	9.61	46.18	61.84	15.66	QP
5	0.494	15.18	9.61	24.79	46.11	21.32	Average
6	0.494	25.77	9.61	35.38	56.11	20.73	QP
7	1.192	16.93	9.62	26.55	46.00	19.45	Average
8	1.192	25.65	9.62	35.27	56.00	20.73	QP
9	2.676	15.66	9.64	25.31	46.00	20.69	Average
10	2.676	23.87	9.64	33.51	56.00	22.49	QP
11	4.437	14.03	9.65	23.69	46.00	22.31	Average
12	4.437	24.52	9.65	34.17	56.00	21.83	QP

Neutral:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.183	24.00	9.61	33.61	54.33	20.72	Average
2	0.183	40.98	9.61	50.59	64.33	13.74	QP
3	0.252	22.73	9.61	32.34	51.70	19.36	Average
4	0.252	36.68	9.61	46.29	61.70	15.41	QP
5	0.451	15.78	9.61	25.39	46.86	21.47	Average
6	0.451	28.02	9.61	37.63	56.86	19.23	QP
7	1.206	15.98	9.62	25.61	46.00	20.39	Average
8	1.206	24.28	9.62	33.90	56.00	22.10	QP
9	2.448	7.88	9.64	17.52	46.00	28.48	Average
10	2.448	20.23	9.64	29.87	56.00	26.13	QP
11	4.508	10.55	9.66	20.21	46.00	25.79	Average
12	4.508	20.73	9.66	30.39	56.00	25.61	QP

## 4.2 Radiation Spurious Emissions

Serial Number:	CR21090087-RF-S1	Test Date:	2021-10-13
Test Site:	966-1,966-2	Test Mode:	Transmitting
Tester:	Great Qiao	Test Result:	Pass

### Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	62	ATM Pressure: (kPa)	100.3
----------------------	------	------------------------------	----	------------------------	-------


### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
Audix	Test Software	E3	201021 (V9)	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2023-02-04
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2021-02-05	2023-02-04
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-08-08	2022-08-07
AH	Preamplifier	PAM-1840VH	190	2020-11-20	2021-11-19
Mini Circuits	High Pass Filter	VHF-6010+	31119	2021-08-08	2022-08-07
E-Microwave	Band Rejection Filter	5150-5850MHz	OE01902423	2021-08-08	2022-08-07

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## 1) 30MHz-1GHz(802.11a 5785MHz was the worst)


## Horizontal:



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	67.675	51.40	-16.94	34.46	40.00	5.54	QP
2	150.538	51.25	-12.29	38.96	43.50	4.54	QP
3	162.611	51.29	-12.54	38.75	43.50	4.75	QP
4	222.170	54.15	-12.99	41.16	46.00	4.84	QP
5	244.232	55.11	-13.13	41.98	46.00	4.02	QP
6	289.002	55.10	-11.28	43.82	46.00	2.18	QP



## Vertical:



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector
1	69.114	55.70	-16.82	38.88	40.00	1.12	QP
2	155.364	48.81	-12.33	36.48	43.50	7.02	Peak
3	163.755	48.68	-12.64	36.04	43.50	7.46	Peak
4	246.815	47.81	-13.17	34.64	46.00	11.36	Peak
5	289.002	51.42	-11.28	40.14	46.00	5.86	QP
6	506.479	43.38	-6.12	37.26	46.00	8.74	Peak

2) 1GHz-40GHz:  
5150-5250MHz

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
802.11a,Low Channel: 5180MHz							
5180.00	68.24	PK	H	38.67	100.89	N/A	N/A
5180.00	58.18	AV	H	38.67	90.83	N/A	N/A
5180.00	66.75	PK	V	38.67	99.4	N/A	N/A
5180.00	57.81	AV	V	38.67	90.46	N/A	N/A
5150.00	29.46	PK	H	38.64	62.08	74	11.92
5150.00	17.41	AV	H	38.64	50.03	54	3.97
10360.00	34.47	PK	H	18.43	46.88	68.2	21.32
15540.00	35.21	PK	H	21.33	50.52	74	23.48
15540.00	25.36	AV	H	21.33	40.67	54	13.33
802.11a,Middle Channel: 5200 MHz							
5200.00	68.51	PK	H	38.70	101.19	N/A	N/A
5200.00	58.71	AV	H	38.70	91.39	N/A	N/A
5200.00	66.24	PK	V	38.70	98.92	N/A	N/A
5200.00	56.76	AV	V	38.70	89.44	N/A	N/A
10400.00	34.72	PK	H	18.47	47.17	68.2	21.03
15600.00	35.13	PK	H	20.98	50.09	74	23.91
15600.00	23.01	AV	H	20.98	37.97	54	16.03
802.11a,High Channel: 5240 MHz							
5240.00	68.52	PK	H	38.85	101.35	N/A	N/A
5240.00	59.27	AV	H	38.85	92.1	N/A	N/A
5240.00	68.03	PK	V	38.85	100.86	N/A	N/A
5240.00	58.58	AV	V	38.85	91.41	N/A	N/A
5350.00	26.23	PK	H	39.03	59.24	74	14.76
5350.00	14.63	AV	H	39.03	47.64	54	6.36
10480.00	34.84	PK	H	18.17	46.99	68.2	21.21
15720.00	35.23	PK	H	21.25	50.46	74	23.54
15720.00	23.74	AV	H	21.25	38.97	54	15.03
802.11n ht20,Low Channel: 5180MHz							
5180.00	66.89	PK	H	38.67	99.54	N/A	N/A
5180.00	58.05	AV	H	38.67	90.7	N/A	N/A
5180.00	66.21	PK	V	38.67	98.86	N/A	N/A
5180.00	57.17	AV	V	38.67	89.82	N/A	N/A
5150.00	30.74	PK	H	38.64	63.36	74	10.64
5150.00	18.03	AV	H	38.64	50.65	54	3.35
10360.00	34.98	PK	H	18.43	47.39	68.2	20.81
15540.00	35.67	PK	H	21.33	50.98	74	23.02
15540.00	22.45	AV	H	21.33	37.76	54	16.24
802.11n ht20, Middle Channel: 5200 MHz							
5200.00	67.01	PK	H	38.70	99.69	N/A	N/A
5200.00	57.47	AV	H	38.70	90.15	N/A	N/A
5200.00	66.52	PK	V	38.70	99.2	N/A	N/A
5200.00	57.19	AV	V	38.70	89.87	N/A	N/A
10400.00	34.75	PK	H	18.47	47.2	68.2	21
15600.00	35.11	PK	H	20.98	50.07	74	23.93
15600.00	23.03	AV	H	20.98	37.99	54	16.01

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Detector					
802.11n ht20, High Channel: 5240 MHz							
5240.00	68.19	PK	H	38.85	101.02	N/A	N/A
5240.00	59.81	AV	H	38.85	92.64	N/A	N/A
5240.00	63.52	PK	V	38.85	96.35	N/A	N/A
5240.00	54.78	AV	V	38.85	87.61	N/A	N/A
5350.00	26.57	PK	H	39.03	59.58	74	14.42
5350.00	15.32	AV	H	39.03	48.33	54	5.67
10480.00	34.65	PK	H	18.17	46.8	68.2	21.4
15720.00	35.26	PK	H	21.25	50.49	74	23.51
15720.00	22.46	AV	H	21.25	37.69	54	16.31
802.11n ht40, Low Channel: 5190 MHz							
5190.00	63.71	PK	H	38.69	96.38	N/A	N/A
5190.00	54.48	AV	H	38.69	87.15	N/A	N/A
5190.00	63.34	PK	V	38.69	96.01	N/A	N/A
5190.00	54.06	AV	V	38.69	86.73	N/A	N/A
5150.00	33.76	PK	H	38.64	66.38	74	7.62
5150.00	20.28	AV	H	38.64	52.9	54	1.1
10380.00	34.87	PK	H	18.45	47.3	68.2	20.9
15570.00	35.62	PK	H	21.15	50.75	74	23.25
15570.00	22.68	AV	H	21.15	37.81	54	16.19
802.11n ht40, High Channel: 5230 MHz							
5230.00	64.62	PK	H	38.81	97.41	N/A	N/A
5230.00	55.81	AV	H	38.81	88.6	N/A	N/A
5230.00	64.59	PK	V	38.81	97.38	N/A	N/A
5230.00	55.92	AV	V	38.81	88.71	N/A	N/A
5350.00	27.95	PK	H	39.03	60.96	74	13.04
5350.00	15.27	AV	H	39.03	48.28	54	5.72
10460.00	34.81	PK	H	18.25	47.04	68.2	21.16
15690.00	35.26	PK	H	21.21	50.45	74	23.55
15690.00	23.11	AV	H	21.21	38.3	54	15.7

Note:

Result = Reading + Factor- Distance extrapolation Factor

For 1-26.5GHz:

Distance extrapolation Factor =  $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$  dB= 6.02 dB

For 26.5-40GHz:

Distance extrapolation Factor =  $20 \log (\text{specific distance [3m]}/\text{test distance [1m]})$  dB= 9.54 dB

## 5725-5850MHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector					
802.11a,Low Channel: 5745MHz							
5745.00	68.68	PK	H	39.46	102.12	N/A	N/A
5745.00	59.19	AV	H	39.46	92.63	N/A	N/A
5745.00	65.93	PK	V	39.46	99.37	N/A	N/A
5745.00	56.55	AV	V	39.46	89.99	N/A	N/A
5725.00	39.01	PK	H	39.48	72.47	122.2	49.73
5720.00	30.01	PK	H	39.49	63.48	110.8	47.32
5700.00	30	PK	H	39.51	63.49	105.2	41.71
5650.00	27.49	PK	H	39.49	60.96	68.2	7.24
11490.00	40.12	PK	H	19.99	54.09	74	19.91
11490.00	28.25	AV	H	19.99	42.22	54	11.78
17235.00	34.58	PK	H	25.85	54.41	68.2	13.79
802.11a,Middle Channel: 5785 MHz							
5785.00	68.75	PK	H	39.43	102.16	N/A	N/A
5785.00	58.91	AV	H	39.43	92.32	N/A	N/A
5785.00	65.88	PK	V	39.43	99.29	N/A	N/A
5785.00	56.66	AV	V	39.43	90.07	N/A	N/A
11570.00	38.11	PK	H	19.66	51.75	74	22.25
11570.00	26.33	AV	H	19.66	39.97	54	14.03
17355.00	34.56	PK	H	26.67	55.21	68.2	12.99
802.11a,High Channel: 5825 MHz							
5825.00	68.35	PK	H	39.46	101.79	N/A	N/A
5825.00	58.28	AV	H	39.46	91.72	N/A	N/A
5825.00	65.14	PK	V	39.46	98.58	N/A	N/A
5825.00	54.19	AV	V	39.46	87.63	N/A	N/A
5850.00	39.41	PK	H	39.49	72.88	122.2	49.32
5855.00	39.38	PK	H	39.51	72.87	110.8	37.93
5875.00	26.61	PK	H	39.60	60.19	105.2	45.01
5925.00	26.84	PK	H	39.68	60.5	68.2	7.7
11650.00	38.52	PK	H	20.04	52.54	74	21.46
11650.00	26.47	AV	H	20.04	40.49	54	13.51
17475.00	35.14	PK	H	27.93	57.05	68.2	11.15
802.11n ht20,Low Channel: 5745MHz							
5745.00	67.91	PK	H	39.46	101.35	N/A	N/A
5745.00	58.66	AV	H	39.46	92.1	N/A	N/A
5745.00	63.41	PK	V	39.46	96.85	N/A	N/A
5745.00	54.13	AV	V	39.46	87.57	N/A	N/A
5725.00	51.02	PK	H	39.48	84.48	122.2	37.72
5720.00	40.78	PK	H	39.49	74.25	110.8	36.55
5700.00	32.78	PK	H	39.51	66.27	105.2	38.93
5650.00	27.62	PK	H	39.49	61.09	68.2	7.11
11490.00	43.25	PK	H	19.99	57.22	74	16.78
11490.00	31.26	AV	H	19.99	45.23	54	8.77
17235.00	34.62	PK	H	25.85	54.45	68.2	13.75

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector					
802.11n ht20, Middle Channel: 5785 MHz							
5785.00	68.02	PK	H	39.43	101.43	N/A	N/A
5785.00	58.84	AV	H	39.43	92.25	N/A	N/A
5785.00	64.51	PK	V	39.43	97.92	N/A	N/A
5785.00	55.03	AV	V	39.43	88.44	N/A	N/A
11570.00	39.26	PK	H	19.66	52.9	74	21.1
11570.00	27.44	AV	H	19.66	41.08	54	12.92
17355.00	34.62	PK	H	26.67	55.27	68.2	12.93
802.11n ht20, High Channel: 5825 MHz							
5825.00	68.34	PK	H	39.46	101.78	N/A	N/A
5825.00	58.93	AV	H	39.46	92.37	N/A	N/A
5825.00	64.91	PK	V	39.46	98.35	N/A	N/A
5825.00	55.34	AV	V	39.46	88.78	N/A	N/A
5850.00	40.91	PK	H	39.49	74.38	122.2	47.82
5855.00	36.75	PK	H	39.51	70.24	110.8	40.56
5875.00	27.37	PK	H	39.60	60.95	105.2	44.25
5925.00	27.04	PK	H	39.68	60.7	68.2	7.5
11650.00	39.21	PK	H	20.04	53.23	74	20.77
11650.00	27.58	AV	H	20.04	41.6	54	12.4
17475.00	34.29	PK	H	27.93	56.2	68.2	12
802.11n ht40, Low Channel: 5755 MHz							
5755.00	65.24	PK	H	39.45	98.67	N/A	N/A
5755.00	56.53	AV	H	39.45	89.96	N/A	N/A
5755.00	62.91	PK	V	39.45	96.34	N/A	N/A
5755.00	54.09	AV	V	39.45	87.52	N/A	N/A
5725.00	49.32	PK	H	39.48	82.78	122.2	39.42
5720.00	48.52	PK	H	39.49	81.99	110.8	28.81
5700.00	37.78	PK	H	39.51	71.27	105.2	33.93
5650.00	26.69	PK	H	39.49	60.16	68.2	8.04
11510.00	38.21	PK	H	19.99	52.18	74	21.82
11510.00	26.68	AV	H	19.99	40.65	54	13.35
17265.00	34.79	PK	H	26.34	55.11	68.2	13.09
802.11n ht40, High Channel: 5795 MHz							
5795.00	65.43	PK	H	39.43	98.84	N/A	N/A
5795.00	56.25	AV	H	39.43	89.66	N/A	N/A
5795.00	62.47	PK	V	39.43	95.88	N/A	N/A
5795.00	52.79	AV	V	39.43	86.2	N/A	N/A
5850.00	36.67	PK	H	39.49	70.14	122.2	52.06
5855.00	36.45	PK	H	39.51	69.94	110.8	40.86
5875.00	27.79	PK	H	39.60	61.37	105.2	43.83
5925.00	26.02	PK	H	39.68	59.68	68.2	8.52
11590.00	38.31	PK	H	19.55	51.84	74	22.16
11590.00	26.97	AV	H	19.55	40.5	54	13.5
17385.00	34.72	PK	H	26.53	55.23	68.2	12.97

Note:

Result = Reading + Factor- Distance extrapolation Factor

For 1-26.5GHz:




Distance extrapolation Factor =  $20 \log(\text{specific distance [3m]}/\text{test distance [1.5m]})$  dB= 6.02 dB


For 26.5-40GHz:

Distance extrapolation Factor =  $20 \log(\text{specific distance [3m]}/\text{test distance [1m]})$  dB= 9.54 dB

**Worst Test plots(802.11a 5825 MHz was the worst)  
Horizontal:**



Fundamental  
Test with Band  
Rejection Filter







Vertical:

Fundamental Test with Band Rejection Filter







**4.3 Emission Bandwidth:**

Serial Number:	CR21090087-RF-S1	Test Date:	2021-10-08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Yu Mo	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	28.7	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100
----------------------	------	------------------------------	----	------------------------	-----

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ0010	C0010	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:****5150-5250MHz:**

Mode	Frequency (MHz)	26 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11 a	5180	21.520	17.006
	5200	21.760	17.086
	5240	21.520	17.325
802.11n ht20	5180	23.600	18.044
	5200	21.680	17.884
	5240	22.640	18.124
802.11n ht40	5190	41.600	37.206
	5230	41.760	37.206

**5725-5850MHz:**

Mode	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	6 dB Emission Bandwidth Limit (MHz)	99% Occupied Bandwidth (MHz)
802.11 a	5745	16.400	0.5	17.166
	5785	16.320	0.5	17.086
	5825	16.080	0.5	17.006
802.11n ht20	5745	17.120	0.5	18.044
	5785	17.360	0.5	18.044
	5825	17.360	0.5	17.964
802.11n ht40	5755	35.840	0.5	37.365
	5795	35.680	0.5	37.046

Note: the 99% Occupied Bandwidth have not fall into the band 5250-5350MHz or 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.


5150-5250MHz:

26dB Emission Bandwidth


<p>802.11a Lowest Channel</p>	
<p>802.11a Middle Channel</p>	
<p>802.11a Highest Channel</p>	

### 26dB Emission Bandwidth


802.11n ht20  
Lowest Channel



802.11n ht20  
Middle Channel




802.11n ht20  
Highest Channel




### 26dB Emission Bandwidth




802.11n ht40  
Lowest Channel



802.11n ht40  
Highest Channel



### 99% Emission Bandwidth

<p>802.11a Lowest Channel</p>	 <p>The spectrum plot shows a signal centered at 5.18 GHz with a 40 MHz span. The y-axis represents power in dBm, ranging from -70 to 10. The signal has a peak level of -4.40 dBm. The plot includes a 1Pk Max marker and a 17.005988024 MHz bandwidth measurement. The date and time are 8.OCT.2021 22:16:49.</p>
<p>802.11a Middle Channel</p>	 <p>The spectrum plot shows a signal centered at 5.2 GHz with a 40 MHz span. The y-axis represents power in dBm, ranging from -70 to 10. The signal has a peak level of -3.52 dBm. The plot includes a 1Pk Max marker and a 17.085828343 MHz bandwidth measurement. The date and time are 8.OCT.2021 22:27:17.</p>
<p>802.11a Highest Channel</p>	 <p>The spectrum plot shows a signal centered at 5.24 GHz with a 40 MHz span. The y-axis represents power in dBm, ranging from -70 to 10. The signal has a peak level of -2.62 dBm. The plot includes a 1Pk Max marker and a 17.325349381 MHz bandwidth measurement. The date and time are 8.OCT.2021 22:28:23.</p>

**99% Emission Bandwidth**

802.11n ht20  
Lowest Channel



802.11n ht20  
Middle Channel



802.11n ht20  
Highest Channel



**99% Emission Bandwidth**

802.11n ht40  
Lowest Channel



802.11n ht40  
Highest Channel




5725-5850MHz:

<b>6dB Emission Bandwidth</b>	
802.11a Lowest Channel	<p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz                  Att 30 dB SWT 1 ms VBW 300 kHz Mode Sweep                  1Pk Max                  M1[1] -14.22 dBm                  D1[1] 16.4000 MHz                  D2 -13.360 dBm                  CF 5.745 GHz 501 pts Span 40.0 MHz                  Date: 8.OCT.2021 23:29:46</p>
802.11a Middle Channel	<p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz                  Att 30 dB SWT 1 ms VBW 300 kHz Mode Sweep                  1Pk Max                  M1[1] -13.53 dBm                  D1[1] 16.3200 MHz                  D2 -14.230 dBm                  CF 5.785 GHz 501 pts Span 40.0 MHz                  Date: 8.OCT.2021 23:31:49</p>
802.11a Highest Channel	<p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 0.50 dB RBW 100 kHz                  Att 30 dB SWT 1 ms VBW 300 kHz Mode Sweep                  1Pk Max                  M1[1] -14.49 dBm                  D1[1] 16.0800 MHz                  D2 -14.700 dBm                  CF 5.825 GHz 501 pts Span 40.0 MHz                  Date: 8.OCT.2021 23:35:17</p>




### 6dB Emission Bandwidth


802.11n ht20  
Lowest Channel



802.11n ht20  
Middle Channel




802.11n ht20  
Highest Channel




### 6dB Emission Bandwidth

802.11n ht40  
Lowest Channel



802.11n ht40  
Highest Channel



**99% Emission Bandwidth**


802.11a  
Lowest Channel



802.11a  
Middle Channel



802.11a  
Highest Channel



**99% Emission Bandwidth**

<p>802.11n ht20 Lowest Channel</p>	
<p>802.11n ht20 Middle Channel</p>	
<p>802.11n ht20 Highest Channel</p>	

**99% Emission Bandwidth**

802.11n ht40  
Lowest Channel



802.11n ht40  
Highest Channel



**4.4 Maximum Conducted Output Power:**

Serial Number:	CR21090087-RF-S1	Test Date:	2021-10-08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Yu Mo	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	28.7	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100
----------------------	------	---------------------------	----	------------------------	-----

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY5315004	2021-09-12	2022-09-12
Unknown	Coaxial Cable	C0010	C0010/04	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:****5150-5250 MHz:**

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)		Max.EIRP Average Output Power (dBm)	
		Result	FCC Limit	Result	RSS-247 Limit
802.11a	5180	10.76	23	12.35	22.31
	5200	10.63	23	12.22	22.33
	5240	11.92	23	13.51	22.39
802.11n ht20	5180	11.46	23	13.05	22.56
	5200	11.64	23	13.23	22.52
	5240	11.85	23	13.44	22.58
802.11n ht40	5190	11.41	23	13	22.31
	5230	11.56	23	13.15	22.33

Note: The device is a client device.

**5725-5850 MHz:**

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power(dBm)	
		Result	Limit
802.11a	5745	12.33	30
	5785	12.23	30
	5825	11.74	30
802.11n ht20	5745	12.50	30
	5785	12.26	30
	5825	11.86	30
802.11n ht40	5755	12.25	30
	5795	12.16	30

**4.5 Maximum power spectral density:**

Serial Number:	CR21090087-RF-S1	Test Date:	2021-10-08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Yu Mo	Test Result:	Pass

**Environmental Conditions:**

Temperature: (°C)	28.7	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100
----------------------	------	------------------------------	----	------------------------	-----

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ0010	C0010	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data:**

Test Modes	Test Frequency (MHz)	Maximum Conducted Power Spectral Density (dBm/MHz)		Maximum EIRP Power Spectral Density (dBm/MHz)	
		Result	FCC Limit	Result	RSS-247 Limit
802.11a	5180	-2.57	11	-0.98	10
	5200	-1.84	11	-0.25	10
	5240	-1.22	11	0.37	10
802.11n ht20	5180	-2.47	11	-0.88	10
	5200	-3.39	11	-1.8	10
	5240	-2.65	11	-1.06	10
802.11n ht40	5190	-6.95	11	-5.36	10
	5230	-5.39	11	-3.8	10


Note:  
The device is a client device.  
Method SA-3 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test.

Test Modes	Test Frequency (MHz)	Maximum Conducted Power Spectral Density (dBm/500kHz)	
		Result	Limit
802.11a	5745	-4.00	30
	5785	-4.23	30
	5825	-4.70	30
802.11n ht20	5745	-4.01	30
	5785	-4.48	30
	5825	-3.72	30
802.11n ht40	5755	-6.66	30
	5795	-6.65	30
802.11ac vht80	5775	-4.00	30




Note: Method SA-3 in KDB 789033 D02 General UNII Test Procedures New Rules v02r01 was used for PSD test.



5150-5250MHz:



**Maximum power spectral density**




<p>802.11n ht20 Lowest Channel</p>	 <p>CF 5.18 GHz 501 pts Span 40.0 MHz</p> <p>Date: 8.OCT.2021 22:40:49</p>
<p>802.11n ht20 Middle Channel</p>	 <p>CF 5.2 GHz 501 pts Span 40.0 MHz</p> <p>Date: 8.OCT.2021 22:43:30</p>
<p>802.11n ht20 Highest Channel</p>	 <p>CF 5.24 GHz 501 pts Span 40.0 MHz</p> <p>Date: 8.OCT.2021 22:44:36</p>

**Maximum power spectral density**

<p>802.11n ht40 Lowest Channel</p>	<p>Spectrum          Ref Level 20.00 dBm Offset 0.50 dB RBW 1 MHz          Att 30 dB SWT 1 ms VBW 3 MHz Mode Sweep          1Pm Max          M1[1] -6.95 dBm          5.204210 GHz          CF 5.19 GHz 501 pts Span 80.0 MHz          Date: 8.OCT.2021 22:46:37</p>
<p>802.11n ht40 Highest Channel</p>	<p>Spectrum          Ref Level 20.00 dBm Offset 0.50 dB RBW 1 MHz          Att 30 dB SWT 1 ms VBW 3 MHz Mode Sweep          1Pm Max          M1[1] -5.39 dBm          5.217860 GHz          CF 5.23 GHz 501 pts Span 80.0 MHz          Date: 8.OCT.2021 22:48:24</p>

5725-5850MHz

Maximum power spectral density


<p>802.11a Lowest Channel</p>	 <p>The spectrum plot shows a channel centered at 5.7390120 GHz. The y-axis represents power spectral density in dBm, ranging from -70 to 10. The x-axis represents frequency in MHz, with a span of 40.0 MHz. The plot shows a signal with a peak power of -4.00 dBm. The channel is identified as M1[1]. The carrier frequency (CF) is 5.745 GHz. The measurement was taken on 08.10.2021 at 23:56:13.</p>
<p>802.11a Middle Channel</p>	 <p>The spectrum plot shows a channel centered at 5.7901900 GHz. The y-axis represents power spectral density in dBm, ranging from -70 to 10. The x-axis represents frequency in MHz, with a span of 40.0 MHz. The plot shows a signal with a peak power of -4.23 dBm. The channel is identified as M1[1]. The carrier frequency (CF) is 5.785 GHz. The measurement was taken on 08.10.2021 at 23:59:16.</p>
<p>802.11a Highest Channel</p>	 <p>The spectrum plot shows a channel centered at 5.8203690 GHz. The y-axis represents power spectral density in dBm, ranging from -70 to 10. The x-axis represents frequency in MHz, with a span of 40.0 MHz. The plot shows a signal with a peak power of -4.70 dBm. The channel is identified as M1[1]. The carrier frequency (CF) is 5.825 GHz. The measurement was taken on 09.10.2021 at 00:00:16.</p>

**Maximum power spectral density**


<p>802.11n ht20 Lowest Channel</p>	<p>Spectrum          Ref Level 20.00 dBm Offset 0.50 dB RBW 500 kHz          Att 30 dB SWT 1 ms VBW 2 MHz Mode Sweep          1Rm Max          MI[1] -4.01 dBm          5.7390920 GHz          CF 5.745 GHz 501 pts Span 40.0 MHz          Measuring... 09.10.2021 00:01:10          Date: 9.OCT.2021 00:01:10</p>
<p>802.11n ht20 Middle Channel</p>	<p>Spectrum          Ref Level 20.00 dBm Offset 0.50 dB RBW 500 kHz          Att 30 dB SWT 1 ms VBW 2 MHz Mode Sweep          1Rm Max          MI[1] -4.48 dBm          5.7921060 GHz          CF 5.785 GHz 501 pts Span 40.0 MHz          Measuring... 09.10.2021 00:01:52          Date: 9.OCT.2021 00:01:52</p>
<p>802.11n ht20 Highest Channel</p>	<p>Spectrum          Ref Level 20.00 dBm Offset 0.50 dB RBW 500 kHz          Att 30 dB SWT 1 ms VBW 2 MHz Mode Sweep          1Rm Max          MI[1] -3.72 dBm          5.8191720 GHz          CF 5.825 GHz 501 pts Span 40.0 MHz          Measuring... 09.10.2021 00:03:01          Date: 9.OCT.2021 00:03:01</p>

**Maximum power spectral density**

802.11n ht40  
Lowest Channel



802.11n ht40  
Highest Channel



**4.6 Duty Cycle:**

Serial Number:	CR21090087-RF-S1	Test Date:	2021-10-09
Test Site:	RF	Test Mode:	Transmitting
Tester:	Yu Mo	Test Result:	N/A

**Environmental Conditions:**

Temperature: (°C)	28.2	Relative Humidity: (%)	66	ATM Pressure: (kPa)	100.3
----------------------	------	------------------------------	----	------------------------	-------


**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJ0010	C0010	Each time	N/A

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


**Test Data:**

Test mode	T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)
802.11a	2.128	2.208	96.38
802.11n ht20	1.952	2.048	95.31
802.11n ht40	0.968	1.088	88.97




### Duty Cycle

802.11n ht20



802.11n ht40





## 5. RF EXPOSURE EVALUATION

### 5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

#### 5.1.1 Applicable Standard

FCC §15.247 (i) & §1.1310 & §2.1091

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### 5.1.2 Procedure

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

#### 5.1.3 Calculated Result

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	1.59	1.44	24	251.19	20.00	0.0721	1.0
5150-5250	1.59	1.44	12	15.85	20.00	0.0045	1.0
5725-5850	1.59	1.44	13	19.95	20.00	0.0057	1.0

Note: The WLAN 2.4G and 5G can't transmit simultaneously.

**Result:** The device meet FCC MPE at 20 cm distance

## 5.2 EXEMPTION LIMITS FOR ROUTINE EVALUATION – RF EXPOSURE EVALUATION

### 5.2.1 Applicable Standard

RSS-102 § (2.5.2):

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

### 5.2.2 Calculated Result

Mode	Frequency (MHz)	Antenna Gain	Conducted output power including Tune-up Tolerance	EIRP		Exemption limits (mW)	Exemption
		(dBi)	(dBm)	(dBm)	(mW)		
WLAN 2.4GHz	2412-2462	1.59	24	25.59	362.24	2684	Yes
WLAN 5.2GHz	5150-5250	1.59	12	13.59	22.86	4525	Yes
WLAN 5.8GHz	5725-5850	1.59	13	14.59	28.77	4857	Yes

*Note: The WLAN 2.4G and 5G can't transmit simultaneously.*

**Result:** Compliance. The device is compliance exemption from Routine Evaluation Limits –RF exposure Evaluation.

\*\*\*\*\* END OF REPORT \*\*\*\*\*