



RF Exposure Evaluation Report

For Check-Cap Ltd.

Equipment Under Test:

C-Scan cap transceiver

Model: SUB-108010-00

***From The Standards Institution
Of Israel
Industry Division
Electronics & Telematics Laboratory
EMC Branch***



Certificate Number: AT-1359



1. Applicant information

Applicant:	Check-Cap Ltd.
Address:	Aba Hushi 29 Ave., POB 1271, Isfiya, Israel
Sample for test selected by:	The customer
The date of tests:	17 September 2020

Equipment under test information

Description of Equipment Under Test (EUT):	C-Scan cap transceiver.
Model:	SUB-108010-00
Software version of radio unit:	4.1.2
Hardware version:	PCBA-108011-01
Manufactured by:	Check-Cap Ltd.

2. Test performance

Location:	SII EMC Section
Purpose of test:	To prove the safety of radiation harmfulness to the human body for our product
Test specifications:	FCC KDB 447498 D01 General RF Exposure Guidance v06

This Test Report contains 3 pages and may be used only in full.	This Test Report applies only to the specimen tested and may not be applied to other specimens of the same product.
---	---

3. Summary of test:

Using the general SAR test exclusion guidance in Section 4.3.1 of KDB 447498 D01 v06, we show the device meeting the SAR exemption.

Electronics and
Telematics Laboratory

October 2020

Name: Eng. Yuri Rozenberg
Position: Head of EMC Branch.

Name: Michael Feldman.
Position: Test engineer.



4. FCC and ISEDC Exemption Limits for Routine Evaluation

FCC SAR test exclusions per KDB 447498

KDB 447498 D01 General RF Exposure Guidance v06 Section: 4.3.1.

Standalone SAR test exclusion considerations states:

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,} \right]$$

where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds.

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

SAR Exclusion Calculation Results

Freq. [GHz]	d [mm]	Max. power [mW]	Calculation result	Exclusion threshold	SAR Exclusion applicable (Yes/No)
0.4335	5	0.000023	0.000003	3.0	Yes

SAR test exclusion threshold is < 3 for separation distance of 5 mm. Therefore, SAR test is not required.