

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong


FCC PART 15 SUBPART C TEST REPORT**FCC PART 15.247****Report Reference No.**.....: **GTSR18080197-WLAN01****FCC ID**.....: **2AQ4K-M6**

Compiled by

(position+printed name+signature)...: File administrators Jimmy Wang

Supervised by

(position+printed name+signature)...: Test Engineer Aaron Tan



Approved by

(position+printed name+signature)...: Manager Jason Hu

Date of issue.....: Sep.25, 2018

Representative Laboratory Name.: **Shenzhen Global Test Service Co.,Ltd.**

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong, China

Applicant's name.....: **Shandong Praytech Optoelectronic Technology Co.,Ltd.**

Address: F2,Blue Venture Valley,South of Keji Road,East of Longhai Road,Nanhai New District, Weihai City,Shandong Province, China

Test specificationStandard: **FCC Part 15.247**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Music projector

Trade Mark: /

Manufacturer: Shandong Praytech Optoelectronic Technology Co.,Ltd.

Model/Type reference.....: M6

Listed Models: H4

Difference: All the same except the model number

Modulation Type: IEEE 802.11b/802.11g/802.11n

Operation Frequency.....: From 2412 - 2462MHz

Hardware Version: V2.00

Software Version: V01

Rating: DC 7.4V from Battery or DC 5V from adapter

Result.....: **PASS**

TEST REPORT

Test Report No. : GTSR18080197-WLAN01	Sep. 25, 2018 Date of issue
---	--------------------------------

Equipment under Test : **Music projector**

Model /Type : **M6**

Listed Models : **H4**

Applicant : **Shandong Praytech Optoelectronic Technology Co.,Ltd.**

Address : F2,Blue Venture Valley,South of Keji Road,East of Longhai Road,Nanhai New District, Weihai City,Shandong Province, China

Manufacturer : **Shandong Praytech Optoelectronic Technology Co.,Ltd.**

Address : F2,Blue Venture Valley,South of Keji Road,East of Longhai Road,Nanhai New District, Weihai City,Shandong Province, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1.	<u>TEST STANDARDS</u>	<u>4</u>
2.	<u>SUMMARY</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment Under Test	5
2.4.	Short description of the Equipment under Test (EUT)	5
2.5.	EUT operation mode	5
2.6.	Block Diagram of Test Setup	6
2.7.	Special Accessories	6
2.8.	Related Submittal(s) / Grant (s)	6
2.9.	Modifications	6
3.	<u>TEST ENVIRONMENT</u>	<u>7</u>
3.1.	Address of the test laboratory	7
3.2.	Test Facility	7
3.3.	Environmental conditions	7
3.4.	Test Description	8
3.5.	Statement of the measurement uncertainty	9
3.6.	Equipments Used during the Test	10
4.	<u>TEST CONDITIONS AND RESULTS.....</u>	<u>11</u>
4.1.	AC Power Conducted Emission	11
4.2.	Radiated Emission.....	16
4.3.	Maximum Peak Output Power.....	23
4.4.	Power Spectral Density	26
4.5.	6dB Bandwidth	31
4.6.	Band Edge Compliance of RF Emission	37
4.7.	Spurious RF Conducted Emission	51
4.8.	Antenna Requirement.....	64
5.	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>65</u>
6.	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>67</u>

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V05](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

[KDB 662911 D01 Multiple Transmitter Output v02r01](#): Emissions Testing of Transmitters with Multiple Outputs in the Same Band

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Sep. 19, 2018
Testing commenced on	:	Sep. 19, 2018
Testing concluded on	:	Sep. 25, 2018

2.2. Product Description

Name of EUT	Music projector
Trade Mark:	/
Model Number	M6
Listed Models	H4
Power Supply	DC 7.4V from Battery or DC 5V from adapter
WLAN	Supported 802.11b/802.11g/802.11n
Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz
Directional gain	@2.4G GANT +10log(N)dbi =0.98+10log2=3.99dbi < 6 dbi @5G GANT +10log(N)dbi =0.98+10log2=3.99dbi < 6 dbi
Antenna Type	internal antenna
Antenna gain	0.98 dBi@2.4G&@5G for ANT1 , 0.82 dBi@2.4G&@5G for ANT2

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 7.4V

2.4. Short description of the Equipment under Test (EUT)

This is a Music projector.

For more details, refer to the user's manual of the EUT.


2.5. EUT operation mode

The application provider specific test software(Realtek MPtool) to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

2.6. Block Diagram of Test Setup



2.7. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
TOSHIBA	Tablet PC	Satellite S40Dt-A	D26T	DOC

2.8. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AQ4K-M6** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.9. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2018.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(e)	Power spectral density	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(a)(2)	Spectrum bandwidth – 6 dB bandwidth	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(b)(1)	Maximum output power	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	Band edge compliance conducted	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.205	Band edge compliance radiated	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	TX spurious emissions conducted	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	TX spurious emissions radiated	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11b	-/-	802.11b	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11b	-/-	802.11b	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

Remark:

1. The measurement uncertainty is not included in the test result.

2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9KHz~1GHz& Radiated Emission 1GHz~10 th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5Mbps	3/9

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2017/09/20	2018/09/19
LISN	R&S	ESH2-Z5	893606/008	2017/09/20	2018/09/19
Bilog Antenna	Schwarzbeck	VULB9163	976	2016/09/20	2019/09/19
EMI Test Receiver	R&S	ESCI7	101102	2017/09/20	2018/09/19
Spectrum Analyzer	Agilent	N9020A	MY48010425	2017/09/20	2018/09/19
Spectrum Analyzer	R&S	FSP40	100019	2018/06/05	2019/06/04
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2016/09/20	2019/09/19
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2016/09/20	2019/09/19
Broadband Horn Antenna	SCHWARZBEC K	BBHA 9170	971	2016/09/20	2019/09/19
Amplifier	Schwarzbeck	BBV 9743	#202	2017/09/20	2018/09/19
Amplifier	EMCI	EMC051845B	980355	2017/09/20	2018/09/19
Temperature/Humidity Meter	Gangxing	CTH-608	02	2017/09/20	2018/09/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	KL142031	2017/09/20	2018/09/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	KL142032	2017/09/20	2018/09/19
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2017/09/20	2018/09/19
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2017/09/20	2018/09/19
Data acquisition card	Agilent	U2531A	TW53323507	2017/09/20	2018/09/19
Power Sensor	Agilent	U2021XA	MY5365004	2017/09/20	2018/09/19
EMI Test Software	R&S	ES-K1	V1.7.1	2017/09/20	2018/09/19
EMI Test Software	JS Tonscend	JS32-RE	2.0.1.5	2017/09/20	2018/09/19

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 5V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS


Remark: We measured Conducted Emission at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode in AC 120V/60Hz and AC 240V/50Hz, Pre-test AC conducted emission at power from AC mains mode and at charge from PC mode, recorded worst case..

Power supply:

AC 120V/60Hz(adapter)

Polarization

L


**MEASUREMENT RESULT:**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.222000	53.60	10.0	63	9.1	QP	L1	GND
0.645000	44.40	9.7	56	11.6	QP	L1	GND
1.198500	39.40	9.6	56	16.6	QP	L1	GND
2.499000	32.30	9.5	56	23.7	QP	L1	GND
11.040000	26.70	8.7	60	33.3	QP	L1	GND
12.507000	25.90	8.5	60	34.1	QP	L1	GND

MEASUREMENT RESULT:

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.217500	39.40	10.0	53	13.5	AV	L1	GND
0.424500	28.40	9.8	47	19.0	AV	L1	GND
1.189500	27.60	9.6	46	18.4	AV	L1	GND
3.822000	14.40	9.4	46	31.6	AV	L1	GND
9.600000	17.70	8.9	50	32.3	AV	L1	GND
13.897500	17.30	8.3	50	32.7	AV	L1	GND


Power supply:	AC 120V/60Hz(adapter)	Polarization	N
---------------	-----------------------	--------------	---

**MEASUREMENT RESULT:**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.213000	52.50	10.0	63	10.6	QP	N	GND
0.541500	41.90	9.8	56	14.1	QP	N	GND
1.275000	43.70	9.6	56	12.3	QP	N	GND
2.350500	40.90	9.5	56	15.1	QP	N	GND
6.139500	31.40	9.2	60	28.6	QP	N	GND
24.103500	26.00	9.0	60	34.0	QP	N	GND

MEASUREMENT RESULT:

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.213000	43.00	10.0	53	10.1	AV	N	GND
0.640500	32.60	9.7	46	13.4	AV	N	GND
1.279500	31.30	9.6	46	14.7	AV	N	GND
2.346000	27.80	9.5	46	18.2	AV	N	GND
11.877000	22.10	8.6	50	27.9	AV	N	GND
12.615000	21.20	8.5	50	28.8	AV	N	GND




MEASUREMENT RESULT:

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	49.30	10.0	65	16.0	QP	L1	GND
0.591000	41.20	9.7	56	14.8	QP	L1	GND
1.171500	32.30	9.6	56	23.7	QP	L1	GND
4.812000	28.30	9.3	56	27.7	QP	L1	GND
10.293000	28.30	8.8	60	31.7	QP	L1	GND
12.988500	26.70	8.4	60	33.3	QP	L1	GND

MEASUREMENT RESULT:

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	34.90	10.0	55	20.4	AV	L1	GND
0.591000	31.80	9.7	46	14.2	AV	L1	GND
1.176000	26.60	9.6	46	19.4	AV	L1	GND
4.960500	19.20	9.3	46	26.8	AV	L1	GND
7.903500	20.80	9.0	50	29.2	AV	L1	GND
12.673500	19.10	8.5	50	30.9	AV	L1	GND

Power supply:	AC 240V/50Hz(adapter)	Polarization	N
---------------	-----------------------	--------------	---



MEASUREMENT RESULT:

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	53.30	10.0	65	11.8	QP	N	GND
0.505500	38.30	9.8	56	17.7	QP	N	GND
1.860000	36.10	9.5	56	19.9	QP	N	GND
2.454000	33.40	9.5	56	22.6	QP	N	GND
8.619000	25.60	9.0	60	34.4	QP	N	GND
13.537500	27.40	8.4	60	32.6	QP	N	GND


MEASUREMENT RESULT:

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	40.20	10.0	55	14.9	AV	N	GND
0.591000	34.00	9.7	46	12.0	AV	N	GND
1.266000	28.00	9.6	46	18.0	AV	N	GND
2.197500	25.70	9.5	46	20.3	AV	N	GND
10.689000	18.80	8.8	50	31.2	AV	N	GND
13.578000	17.20	8.4	50	32.8	AV	N	GND


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We tested at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode at the antenna single transmitting mode and 802.11n HT20/802.11n HT40 at the Mimo mode in AC 120V/60Hz, and recored the worst data at the antenna single transmitting mode.

For 9 KHz-30MHz

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


For 30MHz-1GHz

Horizontal



NO.	Freq. [MHz]	Reading [dBμV/m]	Result Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle[°]	Polarity
1	41.640	46.93	32.39	-14.54	40.00	7.61	100	201	Vertical
2	71.953	51.85	32.88	-18.97	40.00	7.12	100	146	Vertical
3	199.265	46.79	30.22	-16.57	43.50	13.28	100	193	Vertical

Vertical



NO.	Freq. [MHz]	Reading [dBμV/m]	Result Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle[°]	Polarity
1	47.703	39.64	25.61	-14.03	40.00	14.39	100	78	Horizontal
2	106.145	40.31	23.27	-17.04	43.50	20.23	100	196	Horizontal
3	173.560	45.31	26.5	-18.81	43.50	17.00	100	102	Horizontal
4	204.600	44.52	28.18	-16.34	43.50	15.32	100	301	Horizontal

Note:

1. Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11n HT20 mode (Middle Channel, Combined Antenna Chain1 and Antenna Chain2)).
2. Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor
3. Margin value = Emission level-Limits

For 1GHz to 25GHz

802.11b(Worst Case at Antenna Chain 1)

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11b-2412MHz									
V	4824	33.85	30.28	7.01	26.63	44.51	74	-27.78	Pk
H	4824	35.84	30.28	7.01	26.63	46.5	74	-28.98	PK
V	7236	28.41	36.59	8.91	24.98	48.93	74	-26.35	Pk
H	7236	29.68	36.59	8.91	24.98	50.2	74	-27.03	PK
802.11b-2437MHz									
V	4874	36.14	30.36	7.62	26.63	47.49	74	-27.53	Pk
H	4874	37.59	30.36	7.62	26.63	48.94	74	-28.37	PK
V	7311	26.94	36.61	8.84	24.98	47.41	74	-26.15	Pk
H	7311	28.53	36.61	8.84	24.98	49	74	-25.67	PK
802.11b-2462MHz									
V	4924	37.45	30.43	7.94	26.63	49.19	74	-26.02	Pk
H	4924	39.68	30.43	7.94	26.63	51.42	74	-27.00	PK
V	7386	27.55	36.78	8.45	24.98	47.8	74	-25.79	Pk
H	7386	29.81	36.78	8.45	24.98	50.06	74	-27.17	PK

802.11b(Worst Case at Antenna Chain 1)

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11g-2412MHz									
V	4824	33.96	30.28	7.01	26.63	44.62	74	-29.8	Pk
H	4824	34.29	30.28	7.01	26.63	44.95	74	-30.65	PK
V	7236	30.14	36.59	8.91	24.98	50.66	74	-25.44	Pk
H	7236	31.08	36.59	8.91	24.98	51.6	74	-28	PK
802.11g-2437MHz									
V	4874	35.29	30.36	7.62	26.63	46.64	74	-28.53	Pk
H	4874	36.48	30.36	7.62	26.63	47.83	74	-29.44	PK
V	7311	28.14	36.61	8.84	24.98	48.61	74	-26.94	Pk
H	7311	29.73	36.61	8.84	24.98	50.2	74	-27.12	PK
802.11g-2462MHz									
V	4924	36.85	30.43	7.94	26.63	48.59	74	-26.79	Pk
H	4924	34.29	30.43	7.94	26.63	46.03	74	-29.08	PK
V	7386	25.52	36.78	8.45	24.98	45.77	74	-28.33	Pk
H	7386	26.19	36.78	8.45	24.98	46.44	74	-28.57	PK

802.11n HT20(Worst case at Combine with Antenna Chain 0 and Antenna Chain 1)

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11n20-2412MHz									
V	4824	32.85	30.28	7.01	26.63	43.51	74	-31.38	Pk
H	4824	34.33	30.28	7.01	26.63	44.99	74	-30.86	PK
V	7236	28.15	36.59	8.91	24.98	48.67	74	-25.89	Pk
H	7236	29.68	36.59	8.91	24.98	50.2	74	-27.16	PK
802.11n20-2437MHz									
V	4874	34.28	30.36	7.62	26.63	45.63	74	-28.37	Pk
H	4874	35.47	30.36	7.62	26.63	46.82	74	-27.18	PK
V	7311	27.64	36.61	8.84	24.98	48.11	74	-25.89	Pk
H	7311	29.54	36.61	8.84	24.98	50.01	74	-27.67	PK
802.11n20-2462MHz									
V	4924	34.15	30.43	7.94	26.63	45.89	74	-28.08	Pk
H	4924	36.28	30.43	7.94	26.63	48.02	74	-28.99	PK
V	7386	27.16	36.78	8.45	24.98	47.41	74	-27.9	Pk
H	7386	28.34	36.78	8.45	24.98	48.59	74	-25.41	PK

802.11n HT20(Worst case at Combine with Antenna Chain 0 and Antenna Chain 1)


Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11n40-2422MHz									
V	4844	30.12	30.18	7.06	26.63	40.73	74	-33.77	Pk
H	4844	32.22	30.18	7.06	26.63	42.83	74	-33.38	PK
V	7266	25.34	36.61	9.02	24.98	45.99	74	-29.17	Pk
H	7266	27.63	36.61	9.02	24.98	48.28	74	-28.11	PK
802.11n40-2437MHz									
V	4874	28.65	30.36	7.62	26.63	40	74	-32.5	Pk
H	4874	30.45	30.36	7.62	26.63	41.8	74	-32.97	PK
V	7311	24.68	36.61	8.84	24.98	45.15	74	-30.95	Pk
H	7311	26.69	36.61	8.84	24.98	47.16	74	-30.18	PK
802.11n40-2452MHz									
V	4904	31.22	30.31	8.06	26.63	42.96	74	-31	Pk
H	4904	33.45	30.31	8.06	26.63	45.19	74	-32.97	PK
V	7356	20.76	36.56	8.45	24.98	40.79	74	-32.11	Pk
H	7356	21.12	36.56	8.45	24.98	41.15	74	-30.69	PK

Note:

- 1). Measuring frequencies from 9 KHz - 10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9k~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
- 3). Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40

4.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2. and Average conducted output power, 9.2.3.1.

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The maximum Average conducted output power may be measured using a wideband RF power meter with a thermocouple detector or equivalent. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS


Type	Channel	Output power PK (dBm)	Output power PK (dBm)	Output power Total (dBm)	Limit (dBm)	Result
		ANT 1	ANT 2			
802.11b	01	11.45	11.54	/	30.00	Pass
	06	11.51	11.63	/		
	11	11.52	11.69	/		
802.11g	01	10.26	9.93	/	30.00	Pass
	06	10.11	10.34	/		
	11	9.86	9.97	/		
802.11n(HT20)	01	8.78	8.61	11.71	30.00	Pass
	06	8.81	8.58	11.71		
	11	8.82	8.66	11.75		
802.11n(HT40)	03	8.13	7.81	10.98	30.00	Pass
	06	8.09	8.07	11.09		
	09	7.91	7.85	10.89		

Type	Channel	Output power AV (dBm)	Output power AV (dBm)	Output power Total (dBm)	Limit (dBm)	Result
		ANT 1	ANT 2			
802.11b	01	8.65	8.68	/	30.00	Pass
	06	8.67	8.71	/		
	11	8.68	8.76	/		
802.11g	01	7.32	7.11	/	30.00	Pass
	06	7.21	7.41	/		
	11	7.02	7.13	/		
802.11n(HT20)	01	5.89	5.71	8.81	30.00	Pass
	06	5.96	5.68	8.83		
	11	5.98	5.74	8.87		
802.11n(HT40)	03	5.43	5.14	8.30	30.00	Pass
	06	5.32	5.27	8.31		
	09	5.21	5.16	8.20		


Note:

- 1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss;
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
- 4) The EUT used two monopole antenna for WIFI TX/RX,
the directional gain= $0.98+10\log 2=3.99\text{dbi}<6\text{ dbi}$


802.11b




802.11g



802.11n20




802.11n40



4.4. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 558074 D01 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \text{ RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

LIMIT


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


TEST RESULTS


Type	Channel	Power Spectral Density (dBm/3KHz)	Power Spectral Density (dBm/3KHz)	Power Spectral Density Total(dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-14.352	-13.699	/	8.00	Pass
	06	-13.642	-11.548	/		
	11	-13.471	-11.514	/		
802.11g	01	-17.314	-18.68	/	8.00	Pass
	06	-17.181	-15.054	/		
	11	-19.469	-18.018	/		
802.11n(HT20)	01	-17.505	-18.833	-15.1081	8.00	Pass
	06	-16.94	-18.267	-14.5427		
	11	-16.645	-18.92	-14.6249		
802.11n(HT40)	03	-20.778	-23.401	-18.8841	8.00	Pass
	06	-20.99	-20.933	-17.9511		
	09	-21.925	-22.377	-19.1348		


Note:

- 1). Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
- 2). Test results including cable loss;
- 3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
- 4.) Please refer to following plots;
- 5). The EUT used two monopole antenna for WIFI TX/RX, the directional gain= $0.98+10\log 2=3.99\text{dbi}<6 \text{ dbi}$
- 6). For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;
 $\text{Array gain} = 10 \log (N_{ant})$, where N_{ant} is the number of transmit antennas.










4.5. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS

Antenna 1

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	10.12	≥ 500	Pass
	06	10.12		
	11	10.13		
802.11g	01	16.56	≥ 500	Pass
	06	16.57		
	11	16.57		
802.11nHT20	01	17.76	≥ 500	Pass
	06	17.7		
	11	17.74		
802.11nHT40	03	36.51	≥ 500	Pass
	06	36.51		
	09	36.52		

Antenna 2

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	10.12	≥500	Pass
	06	10.12		
	11	10.12		
802.11g	01	16.55	≥500	Pass
	06	16.56		
	11	16.57		
802.11nHT20	01	17.76	≥500	Pass
	06	17.74		
	11	17.72		
802.11nHT40	03	36.51	≥500	Pass
	06	36.54		
	09	36.49		

Note:


- 1). Measured 6dB Bandwidth at difference data rate for each mode and recorded worst case for each mode.
- 2). Test results including cable loss;
- 3). Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;

Antenna 1

802.11b




802.11g




CH01

CH01



CH06

CH06




CH11

CH11


802.11n HT40



CH03



CH06



CH09

Antenna 2

802.11b




802.11g




CH01

CH01



CH06

CH06




CH11

CH11

802.11n HT20




802.11n HT40



CH01




CH03



CH06



CH06



CH11



CH09



4.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an internal generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test dures until all measured frequencies were complete.

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

TEST RESULTS

Remark: We tested at 802.11b/802.11g/802.11n HT20/802.11n HT40 mode at the antenna single transmitting mode and 802.11n HT20/802.11n HT40 at the MIMO mode, and recored the worst data at the antenna single transmitting mode.

4.6.1 For Radiated Bandedge Measurement**For Antenna 1**

IEEE 802.11b								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-51.526	0.98	0	44.684	Peak	74	-29.316	PASS
2310.000	-62.268	0.98	0	33.942	AV	54	-20.058	PASS
2390.000	-47.577	0.98	0	48.633	Peak	74	-25.367	PASS
2390.000	-59.253	0.98	0	36.957	AV	54	-17.043	PASS
2483.500	-46.721	0.98	0	49.489	Peak	74	-24.511	PASS
2483.500	-59.019	0.98	0	37.191	AV	54	-16.809	PASS
2500.000	-48.629	0.98	0	47.581	Peak	74	-26.419	PASS
2500.000	-60.919	0.98	0	35.291	AV	54	-18.709	PASS

IEEE 802.11g								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-51.936	0.98	0	44.274	Peak	74	-29.726	PASS
2310.000	-62.32	0.98	0	33.89	AV	54	-20.11	PASS
2390.000	-48.424	0.98	0	47.786	Peak	74	-26.214	PASS
2390.000	-59.828	0.98	0	36.382	AV	54	-17.618	PASS
2483.500	-47.481	0.98	0	48.729	Peak	74	-25.271	PASS
2483.500	-59.48	0.98	0	36.73	AV	54	-17.27	PASS
2500.000	-49.694	0.98	0	46.516	Peak	74	-27.484	PASS
2500.000	-61.071	0.98	0	35.139	AV	54	-18.861	PASS

IEEE 802.11 n HT20								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-50.599	0.98	0	45.611	Peak	74	-28.389	PASS
2310.000	-62.321	0.98	0	33.889	AV	54	-20.111	PASS
2390.000	-48.607	0.98	0	47.603	Peak	74	-26.397	PASS
2390.000	-59.692	0.98	0	36.518	AV	54	-17.482	PASS
2483.500	-47.226	0.98	0	48.984	Peak	74	-25.016	PASS
2483.500	-59.461	0.98	0	36.749	AV	54	-17.251	PASS
2500.000	-49.106	0.98	0	47.104	Peak	74	-26.896	PASS
2500.000	-61.12	0.98	0	35.09	AV	54	-18.91	PASS

IEEE 802.11n HT40								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-52.561	0.98	0	43.649	Peak	74	-30.351	PASS
2310.000	-62.374	0.98	0	33.836	AV	54	-20.164	PASS
2390.000	-47.409	0.98	0	48.801	Peak	74	-25.199	PASS
2390.000	-59.882	0.98	0	36.328	AV	54	-17.672	PASS
2483.500	-47.572	0.98	0	48.638	Peak	74	-25.362	PASS
2483.500	-59.384	0.98	0	36.826	AV	54	-17.174	PASS
2500.000	-50.08	0.98	0	46.13	Peak	74	-27.87	PASS
2500.000	-60.924	0.98	0	35.286	AV	54	-18.714	PASS

For Antenna 2

IEEE 802.11b								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-50.776	0.82	0	45.274	Peak	74	-28.726	PASS
2310.000	-62.24	0.82	0	33.81	AV	54	-20.19	PASS
2390.000	-47.554	0.82	0	48.496	Peak	74	-25.504	PASS
2390.000	-58.949	0.82	0	37.101	AV	54	-16.899	PASS
2483.500	-48.299	0.82	0	47.751	Peak	74	-26.249	PASS
2483.500	-59.183	0.82	0	36.867	AV	54	-17.133	PASS
2500.000	-49.977	0.82	0	46.073	Peak	74	-27.927	PASS
2500.000	-61.047	0.82	0	35.003	AV	54	-18.997	PASS

IEEE 802.11g								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-48.676	0.82	0	47.374	Peak	74	-26.626	PASS
2310.000	-62.312	0.82	0	33.738	AV	54	-20.262	PASS
2390.000	-48.25	0.82	0	47.8	Peak	74	-26.2	PASS
2390.000	-59.642	0.82	0	36.408	AV	54	-17.592	PASS
2483.500	-48.516	0.82	0	47.534	Peak	74	-26.466	PASS
2483.500	-59.37	0.82	0	36.68	AV	54	-17.32	PASS
2500.000	50.818	0.82	0	146.868	Peak	74	72.868	PASS
2500.000	-61.094	0.82	0	34.956	AV	54	-19.044	PASS

IEEE 802.11 n HT20								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-51.516	0.82	0	44.534	Peak	74	-29.466	PASS
2310.000	-62.396	0.82	0	33.654	AV	54	-20.346	PASS
2390.000	-48.428	0.82	0	47.622	Peak	74	-26.378	PASS
2390.000	-59.685	0.82	0	36.365	AV	54	-17.635	PASS
2483.500	-47.78	0.82	0	48.27	Peak	74	-25.73	PASS
2483.500	-59.307	0.82	0	36.743	AV	54	-17.257	PASS
2500.000	-51.074	0.82	0	44.976	Peak	74	-29.024	PASS
2500.000	-60.914	0.82	0	35.136	AV	54	-18.864	PASS

IEEE 802.11 n HT40								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
2310.000	-51.73	0.82	0	44.32	Peak	74	-29.68	PASS
2310.000	-62.275	0.82	0	33.775	AV	54	-20.225	PASS
2390.000	47.34	0.82	0	143.39	Peak	74	69.39	PASS
2390.000	-59.476	0.82	0	36.574	AV	54	-17.426	PASS
2483.500	-48.589	0.82	0	47.461	Peak	74	-26.539	PASS
2483.500	-59.581	0.82	0	36.469	AV	54	-17.531	PASS
2500.000	-49.696	0.82	0	46.354	Peak	74	-27.646	PASS
2500.000	-61.199	0.82	0	34.851	AV	54	-19.149	PASS

For Combined Antenna 1, Antenna 2

IEEE 802.11n HT20										
Frequency (MHz)	Conducted Power (dBm)			Directional Gain (dB)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
	Antenna 1	Antenna 2	Sum							
2310.000*	-50.599	-51.516	-48.023	3.99	0	51.117	Peak	74	-22.883	PASS
2310.000	-62.321	-62.396	-59.348	3.99	0	39.792	AV	54	-14.208	PASS
2390.000	-48.607	-48.428	-45.506	3.99	0	53.634	Peak	74	-20.366	PASS
2390.000	-59.692	-59.685	-56.678	3.99	0	42.462	AV	54	-11.538	PASS
2483.500*	-47.226	-47.78	-44.484	3.99	0	54.656	Peak	74	-19.344	PASS
2483.500	-59.461	-59.307	-56.373	3.99	0	42.767	AV	54	-11.233	PASS
2500.000	-49.106	-51.074	-46.969	3.99	0	52.171	Peak	74	-21.829	PASS
2500.000	-61.12	-60.914	-58.005	3.99	0	41.135	AV	54	-12.865	PASS

IEEE 802.11n HT40										
Frequency (MHz)	Conducted Power (dBm)			Directional Gain (dB)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Over limit dB	Verdict
	Antenna 1	Antenna 2	Sum							
2310.000*	-52.561	-51.73	-49.115	3.99	0	50.025	Peak	74	-23.975	PASS
2310.000	-62.374	-62.275	-59.314	3.99	0	39.826	AV	54	-14.174	PASS
2390.000	-47.409	47.34	47.340	3.99	0	146.480	Peak	74	72.480	PASS
2390.000	-59.882	-59.476	-56.664	3.99	0	42.476	AV	54	-11.524	PASS
2483.500*	-47.572	-48.589	-45.040	3.99	0	54.100	Peak	74	-19.900	PASS
2483.500	-59.384	-59.581	-56.471	3.99	0	42.669	AV	54	-11.331	PASS
2500.000	-50.08	-49.696	-46.873	3.99	0	52.267	Peak	74	-21.733	PASS
2500.000	-60.924	-61.199	-58.049	3.99	0	41.091	AV	54	-12.909	PASS

Remark:

1. Measured Band-edge measurements for radiated emissions at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. "---" means that the fundamental frequency not for 15.209 limits requirement.
5. No need measure Average values if Peak values meets Average limits;
6. * means maximum values of frequency band 2310 – 2390 MHz, 2483.5 – 2500 MHz;
7. For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;


$$\text{Array gain} = 10 \log(N_{\text{ant}})$$
, where N_{ant} is the number of transmit antennas.
8. $3.99 = 0.98 + 10 \cdot \log(2)$, $3.83 = 0.82 + 10 \cdot \log(2)$.
9. Covert Radiated E Level At 3m = Conducted average power + Directional Gain + $104.77 - 20 \cdot \log(3)$;
10. Please refer to following plots;

Band-edge measurements for radiated emissions
Antenna 1


IEEE 802.11b




IEEE 802.11g




Channel 1 / 2412 MHz – Peak




Channel 1 / 2412 MHz – Peak



Channel 1 / 2412 MHz – Average



Channel 1 / 2412 MHz – Average



Channel 11 / 2462 MHz – Peak

Channel 11 / 2462 MHz – Peak



Band-edge measurements for radiated emissions

Antenna 1


IEEE 802.11b




IEEE 802.11g

Channel 11 / 2462 MHz – Average
IEEE 802.11n HT20Channel 11 / 2462 MHz – Average
IEEE 802.11n HT40

Channel 1 / 2412 MHz – Peak



Channel 3 / 2422 MHz – Peak




Channel 1 / 2412 MHz – Average

Channel 3 / 2422 MHz – Average

Band-edge measurements for radiated emissions

Antenna 1


IEEE 802.11n HT20




IEEE 802.11n HT40



Channel 11 / 2462 MHz – Peak



Channel 9 / 2452 MHz – Peak




Channel 11 / 2462 MHz – Average


Channel 9 / 2452 MHz – Average

Band-edge measurements for radiated emissions
Antenna 2


IEEE 802.11b



IEEE 802.11g



Channel 1 / 2412 MHz – Peak




Channel 1 / 2412 MHz – Peak



Channel 1 / 2412 MHz – Average



Channel 1 / 2412 MHz – Average



Channel 11 / 2462 MHz – Peak


Channel 11 / 2462 MHz – Peak

Band-edge measurements for radiated emissions
Antenna 2


IEEE 802.11b




IEEE 802.11g




Channel 11 / 2462 MHz – Average
IEEE 802.11n HT20



Channel 11 / 2462 MHz – Average
IEEE 802.11n HT40



Channel 1 / 2412 MHz – Peak



Channel 3 / 2422 MHz – Peak



Channel 1 / 2412 MHz – Average

Channel 3 / 2422 MHz – Average