

	TEST REPOR	T				
FCC ID:	2AQ5C-HOTWS					
Test Report No::	TCT240508E043	(3)				
Date of issue::	May 15, 2024					
Testing laboratory:	SHENZHEN TONGCE TESTING	G LAB				
Testing location/ address:	2101 & 2201, Zhenchang Factor Subdistrict, Bao'an District, Sher People's Republic of China	•				
Applicant's name::	Hypercel Corporation					
Address:	28385 Constellation Rd., Valence States	cia, California 91355, Ur	ited			
Manufacturer's name:	Shenzhen Hypercel Technology	Co., Ltd				
Address:	Room 605, No.4 Building, Tongtai Times Center, No.6259 Bao'an Avenue, Bao'an District, Shenzhen City 518103, China					
Standard(s):	KDB 447498 D01 General RF E	xposure Guidance v06				
Product Name::	OPEN-EAR TRUE WIRELESS I	EARBUDS				
Trade Mark:	N/A					
Model/Type reference:	16032	(0)				
Rating(s)::	Rechargeable Li-ion Battery DC	3.7V				
Date of receipt of test item:	May 08, 2024	(C)				
Date (s) of performance of test:	May 08, 2024 ~ May 15, 2024					
Tested by (+signature):	Onnado YE	Onnado Kongce				
Check by (+signature):	Beryl ZHAO	Boyl 16 TCT	FING			
Approved by (+signature):	Tomsin	Tomsm 45				

### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.







# **Table of Contents**

1.1 1.2 2. Ge 2.1 2.2 3. Fa 3.1 3.2	. EUT desc . Model(s) eneral Info . Test envi . Descripti cilities au . Facilities	cription listormation ironment a ion of Sup nd Accre	and mode. port Units			
4. Te	st Kesult	s and Me	easureme	ent Data .	 (S)	 b



# 1. General Product Information

# 1.1. EUT description

Product Name:	OPEN-EAR TRUE WIRELESS EARBUDS	(61)
Model/Type reference:	16032	
Sample Number:	TCT240508E042-0101	
Operation Frequency:	2402MHz~2480MHz	
Modulation Type:	GFSK, π/4-DQPSK	
Antenna Type:	Chip Antenna	(C)
Antenna Gain:	1.95dBi	
Rating(s):	Rechargeable Li-ion Battery DC 3.7V	)

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. M	nrameter. lodel(s) l one.	list			



# 2. General Information

## 2.1. Test environment and mode

Item	Normal condition							
Temperature	+25°C							
Voltage	DC 3.7V							
Humidity	56%							
Atmospheric Pressure:	1008 mbar							
Test Mode:								
Transmitting mode:	Keep the EUT in continuous transmitting by select channel							

# 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment Model No		Serial No.	FCC ID	Trade Name	
1			1	1	

#### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.





# 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

**Designation Number: CN1205** 

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

## 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





# 4. Test Results and Measurement Data

According to KDB 447498 D01 General RF Exposure Guidance v06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 39	2.441	3.20	2.5±1	3.50	2.24	5	0.70	3.0

#### Result:

Base on the calculation value, No SAR measurement is required.



Page 6 of 6

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com