

## Maximum Permissive Exposure

1. Applicant : Imprint Co., Ltd.  
13F-1, No. 2, Jian 8th Rd., Zhonghe Dist., New Taipei City, Taiwan
2. Manufacturer : Imprint Co., Ltd.  
13F-1, No. 2, Jian 8th Rd., Zhonghe Dist., New Taipei City, Taiwan
3. Prepared By : Audix Technology Corporation.  
EMC Department  
No. 53-11, Dingfu, Linkou Dist.,  
New Taipei City 244, Taiwan  
Tel: (02) 2609-9301~2  
Fax: (02) 2609-9303
4. Product Name : PAZ VIVID+ 10W FAST WIRELESS CHARGING PAD
  - A) Standard : FCC CFR 47 §1.1310
  - B) Model No. : PZM0010
  - C) FCC ID : 2AQ5DPZM0010
  - D) Test Voltage : AC 120V/60Hz
5. Date of Test : 2019. 10. 30
6. Place of Test : **Audix Technology Corporation EMC Department**  
No. 53-11, Dingfu, Linkou Dist.,  
New Taipei City 244, Taiwan
7. Measurement Results : **PASSED**
- SIGNATURE :

  
\_\_\_\_\_  
Ben Cheng/Manager  
AUDIX Technology Corporation  
EMC Department  
Date: 2019. 12. 23



## 1. Measurement Equipment List

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
1.	Broadband Field Meter	NARDA	NBM-550	B-0959	2019.02.05	2 Years
2.	E-Field Probe	NARDA	EF0391	A-1034	2019.02.04	2 Years
3.	Exposure Level Tester	NARDA	ELT-400	M-0291	2019.02.04	2 Years
4.	B-Field Probe 100 cm <sup>2</sup>	NARDA	2300/90.10	M-0309	2019.02.04	2 Years

## 2. Test Result

**Imprint Co., Ltd.** declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on FCC recommendation.

Test Frequency	TX 134.9kHz	Test Mode	5W Charge with AC Adapter
----------------	-------------	-----------	---------------------------

Separation	Probe from EUT side	E-field strength (V/m)	H-field strength (A/m)
15cm	Left	0.790	0.157620
15cm	Right	0.750	0.153645
20cm	Top	0.810	0.156030
15cm	Front	0.840	0.144400
15cm	Back	0.880	0.150465
Limit		614	1.63

Test Frequency	TX 127.7kHz	Test Mode	7.5W Charge with AC Adapter
----------------	-------------	-----------	-----------------------------

Separation	Probe from EUT side	E-field strength (V/m)	H-field strength (A/m)
15cm	Left	0.850	0.156030
15cm	Right	0.830	0.152055
20cm	Top	0.790	0.150465
15cm	Front	0.560	0.148080
15cm	Back	0.810	0.152850
Limit		614	1.63

Test Frequency	TX 149.5kHz	Test Mode	10W Charge with AC Adapter
Separation	Probe from EUT side	E-field strength (V/m)	H-field strength (A/m)
15cm	Left	0.880	0.154440
15cm	Right	0.830	0.153645
20cm	Top	1.120	0.151260
15cm	Front	0.740	0.151260
15cm	Back	1.060	0.155235
Limit		614	1.63