

**FCC ID:2AQ5R-DB-AY-AP6275P**

**Maximum Permissible Exposure (MPE)**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)  | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposure</b>         |                               |                               |                                     |                          |
| 0.3-3.0  | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30   | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300   | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500  |                               |                               | f/300                               | 6                        |
| 1,500-100,000  |                               |                               | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34   | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30  | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300   | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500  |                               |                               | f/1500                              | 30                       |
| 1,500-100,000  |                               |                               | 1.0                                 | 30                       |

f = frequency in MHz \* = Plane-wave equivalent power density

**MPE Calculation Method**

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

**BT:**

Operation Frequency: 2402MHz~2480MHz  
 Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: External Antenna

BT antenna gain: 2.06 dBi ;

R=20cm

mW=10^(dBm/10)

| Channel Freq. (MHz) | modulation | conducted power | Tune-up power (dBm) | Max           |        | Antenna |         | Evaluation result (mW/cm <sup>2</sup> ) | Power density Limits (mW/cm <sup>2</sup> ) |
|---------------------|------------|-----------------|---------------------|---------------|--------|---------|---------|---|--|
|                     |            | (dBm)           |                     | tune-up power |        | Gain    |         |   |  |
|                     |            |                 |                     | (dBm)         | (mW)   | (dBi)   | Numeric |   |  |
| 2402                | GFSK       | 4.51            | 5±1                 | 6             | 3.981  | 2.06    | 1.61    | 0.0013                                  | 1  |
| 2441                |            | 5.43            | 5±1                 | 6             | 3.981  | 2.06    | 1.61    | 0.0013                                  | 1  |
| 2480                |            | 5.01            | 5±1                 | 6             | 3.981  | 2.06    | 1.61    | 0.0013                                  | 1  |
| 2402                | π/4-DQPSK  | 4.9             | 5.5±1               | 6.5           | 4.467  | 2.06    | 1.61    | 0.0014                                  | 1  |
| 2441                |            | 6.16            | 5.5±1               | 6.5           | 4.467  | 2.06    | 1.61    | 0.0014                                  | 1  |
| 2480                |            | 6.15            | 5.5±1               | 6.5           | 4.467  | 2.06    | 1.61    | 0.0014                                  | 1  |
| 2402                | 8-DPSK     | 5.41            | 6±1                 | 7             | 5.012  | 2.06    | 1.61    | 0.0016                                  | 1  |
| 2441                |            | 6.5             | 6±1                 | 7             | 5.012  | 2.06    | 1.61    | 0.0016                                  | 1  |
| 2480                |            | 6.57            | 6±1                 | 7             | 5.012  | 2.06    | 1.61    | 0.0016                                  | 1  |
| 2402                | BLE(1M)    | 8.83            | 9±1                 | 10            | 10.000 | 2.06    | 1.61    | 0.0032                                  | 1  |
| 2440                |            | 9.09            | 9±1                 | 10            | 10.000 | 2.06    | 1.61    | 0.0032                                  | 1  |
| 2480                |            | 8.49            | 9±1                 | 10            | 10.000 | 2.06    | 1.61    | 0.0032                                  | 1  |
| 2402                | BLE(2M)    | 9.08            | 9±1                 | 10            | 10.000 | 2.06    | 1.61    | 0.0032                                  | 1  |
| 2440                |            | 9.29            | 9±1                 | 10            | 10.000 | 2.06    | 1.61    | 0.0032                                  | 1  |
| 2480                |            | 8.73            | 9±1                 | 10            | 10.000 | 2.06    | 1.61    | 0.0032                                  | 1  |

**2.4G/5G WIFI:**

Operation Frequency: WIFI 802.11b/g/n/ax HT20: 2412-2462MHz,  
 WIFI 802.11n/ax HT40:2422-2452MHz  
 Power density limited: 1mW/ cm<sup>2</sup>

Operation Frequency: WIFI 802.11a/ac/n/ax(HT20): 5180-5240MHz;5260-5320MHz,5500-5700MHz,5745-5825MHz;WIFI 802.11ac/n/ax(HT40): 5190-5230MHz;5270-5310MHz,5510-5670MHz5755-5795MHz; WIFI 802.11ac80:5210-5210MHz;5290-5290MHz;5530-5610MHz;

5775-5775MHz

Power density limited: 1mW/cm

Antenna Type: External Antenna

2.4G WIFI antenna1 gain: 2.06dBi; WIFI antenna2 gain: 2.06dBi

5G WIFI antenna1 gain: 2.95dBi; WIFI antenna2 gain: 2.95dBi

R=20cm

mW=10^(dBm/10)

**WLAN2.4G SISO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|------------|
| Ant 1   | 16.02               | 2.95       | 18.97      | 78.89     | 20    | 0.015694                | 1                               | Pass       |
| Ant 2   | 15.58               | 2.95       | 18.53      | 71.29     | 20    | 0.014181                | 1                               |            |

**WLAN5.2G SISO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|------------|
| Ant 1   | 13.56               | 2.95       | 16.51      | 44.77     | 20    | 0.008907                | 1                               | Pass       |
| Ant 2   | 13.67               | 2.95       | 16.62      | 45.92     | 20    | 0.009135                | 1                               |            |

**WLAN5.3G SISO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|------------|
| Ant 1   | 13.45               | 2.95       | 16.4       | 43.65     | 20    | 0.008684                | 1                               | Pass       |
| Ant 2   | 13.46               | 2.95       | 16.41      | 43.75     | 20    | 0.008704                | 1                               |            |

**WLAN5.6G SISO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|------------|
| Ant 1   | 14.05               | 2.95       | 17         | 50.12     | 20    | 0.009971                | 1                               | Pass       |
| Ant 2   | 13.81               | 2.95       | 16.76      | 47.42     | 20    | 0.009435                | 1                               |            |

**WLAN5.8G SISO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|------------|
| Ant 1   | 13.63               | 2.95       | 16.58      | 45.50     | 20    | 0.009051                | 1                               | Pass       |
| Ant 2   | 13.52               | 2.95       | 16.47      | 44.36     | 20    | 0.008825                | 1                               |            |

**SIMULTANEOUS TRANSMISSIONS**

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE. To comply with the MPE, the fraction of the MPE in terms of E<sup>2</sup>, H<sup>2</sup> (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity. In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

**WLAN2.4G MIMO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Calculation result | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|--------------------|------------|
| Ant 1   | 16.02               | 2.95       | 18.97      | 78.89     | 20    | 0.015694                | 1                               | 0.055324           | Pass       |
| Ant 2   | 15.58               | 2.95       | 18.53      | 71.29     | 20    | 0.014181                | 1                               |                    |            |

**WLAN5.2G MIMO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Calculation result | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|--------------------|------------|
| Ant 1   | 13.56               | 2.95       | 16.51      | 44.77     | 20    | 0.008907                | 1                               | 0.033411           | Pass       |
| Ant 2   | 13.67               | 2.95       | 16.62      | 45.92     | 20    | 0.009135                | 1                               |                    |            |

**WLAN5.3G MIMO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Calculation result | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|--------------------|------------|
| Ant 1   | 13.45               | 2.95       | 16.4       | 43.65     | 20    | 0.008684                | 1                               | 0.032200           | Pass       |
| Ant 2   | 13.46               | 2.95       | 16.41      | 43.75     | 20    | 0.008704                | 1                               |                    |            |

**WLAN5.6G MIMO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Calculation result | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|--------------------|------------|
| Ant 1   | 14.05               | 2.95       | 17         | 50.12     | 20    | 0.009971                | 1                               | 0.035937           | Pass       |
| Ant 2   | 13.81               | 2.95       | 16.76      | 47.42     | 20    | 0.009435                | 1                               |                    |            |

**WLAN5.8G MIMO MODE**

| Antenna | Tune-up limit (dBm) | Gain (dBi) | EIRP (dBm) | EIRP (mW) | R(cm) | S (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) | Calculation result | Conclusion |
|---------|---------------------|------------|------------|-----------|-------|-------------------------|---------------------------------|--------------------|------------|
| Ant 1   | 13.63               | 2.95       | 16.58      | 45.50     | 20    | 0.009051                | 1                               | 0.033104           | Pass       |
| Ant 2   | 13.52               | 2.95       | 16.47      | 44.36     | 20    | 0.008825                | 1                               |                    |            |

This product does not support the requirements under multiple sources.

**Conclusion:**

The conclusion for MIMO mode should be  $0.055324 < 1$  for Max Power Density, Compliance the

**Signature:**

**Date:** 2023-04-24



**NAME AND TITLE** (Please print or type): alex li/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.